

# Iyer517

October 5, 2010

---

Iyer517	<i>exprSet instance Iyer517, time series on transcriptional response of fibroblasts to serum</i>
---------	--

---

## Description

an expression set for timed measurements of transcriptional response of fibroblasts to serum in presence or absence of cycloheximide

## Slots

**exprs:** Object of class matrix, value: 517 x 19 expression levels (normed to 1 at time 0)  
**se.exprs:** Object of class matrix, value: absent  
**description:** Object of class MIAME, value: string  
**annotation:** Object of class character, value: ""  
**notes:** Object of class character, value: ""  
**phenoData:** Object of class phenoData, value: data frame with info on timing  
**class:** Object of class character, value: 'exprSet'

## References

Iyer et al 1999 Science v283 83-87

## Examples

```
data(Iyer517)
show(Iyer517)
plot(apply(exprs(Iyer517)[1:100,1:13],2,mean),main="Cluster A",
      xlab="index in time seq",ylab="ratio to time 0",log="y")
```

---

IyerAnnotated      *Partly annotated version of Iyer517 data*

---

### Description

GenBank ids, LocusLink ids (where available) and GO tags (where available) for the 517 cDNAs in the dataset.

### Usage

```
data(IyerAnnotated); data(Iyer517GO)
```

### Format

**Iyer517GO**: An environment with keys given by the 'GB' identifiers of probes and values given by vectors of GO tags (named by evidence codes) obtained via locuslink mapping

**IyerAnnotated**: A data frame with 517 observations on the following 9 variables.

**Iclust** a factor with levels N A B ... – the cluster groups A-J of the Iyer paper, with N for those rows that were not clustered

**GB** a factor with levels AA001025 AA001722 ... accession numbers (often genbank) for probes

**seqno** a numeric vector indicating the order of the cDNA in the Iyer report on clustering. (Elements 2:101 formed cluster A, etc.)

**locusid** a numeric vector of locuslink ids, formed using AnnBuilder

**GO1** a character vector of GO tags (there were up to five based on the LL:GO mapping available March 2003 – these should be ignored in favor of the new Iyer517GO environment)

**GO2** a character vector

**GO3** a character vector

**GO4** a character vector

**GO5** a character vector

### Details

Annotating this dataset is a good exercise for AnnBuilder. Many of the probes seem to have no annotation.

### Source

<http://genome-www.stanford.edu/serum/data.html>

### References

Iyer et al, Science v283: 83-87 (1999)

### Examples

```
data(IyerAnnotated)
table(is.na(IyerAnnotated$GO1))
data(Iyer517GO)
get(ls(env=Iyer517GO)[1], env=Iyer517GO)
```

---

`get.dna2`

*query genbank for an EST accession id*

---

### **Description**

extends the `get.dna` function of E Paradis CRAN package "ape"

### **Usage**

```
get.dna2(access.nb)
```

### **Arguments**

`access.nb`      an EST accession id

### **Details**

queries ncbi

### **Value**

a vector of nucleotide codes

### **Note**

try `ape::get.dna` if this fails

### **Author(s)**

VJ Carey <stvjc@channing.harvard.edu>

### **See Also**

`ape::get.dna`

### **Examples**

```
if (interactive())
{
  data(IyerAnnotated)
  get.dna2(IyerAnnotated$GB[1])
}
```

# Index

## \*Topic **datasets**

IyerAnnotated, [2](#)

## \*Topic **methods**

Iyer517, [1](#)

## \*Topic **models**

get.dna2, [3](#)

get.dna2, [3](#)

Iyer517, [1](#)

Iyer517GO (*IyerAnnotated*), [2](#)

IyerAnnotated, [2](#)