

Package ‘CGHbase’

July 13, 2025

Type Package

Title CGHbase: Base functions and classes for arrayCGH data analysis.

Version 1.68.0

Date 2018-06-27

Author Sjoerd Vosse, Mark van de Wiel

Maintainer Mark van de Wiel <mark.vdwiel@vumc.nl>

Depends R (>= 2.10), methods, Biobase (>= 2.5.5), marray

Description Contains functions and classes that are needed by arrayCGH packages.

License GPL

Collate allGeneric.R classes.R private.R tools.R methods-cghRaw.R
methods-cghSeg.R methods-cghCall.R methods-cghRegions.R

biocViews Infrastructure, Microarray, CopyNumberVariation

URL <https://github.com/tgac-vumc/CGHbase>

BugReports <https://github.com/tgac-vumc/CGHbase/issues>

git_url <https://git.bioconductor.org/packages/CGHbase>

git_branch RELEASE_3_21

git_last_commit ae87494

git_last_commit_date 2025-04-15

Repository Bioconductor 3.21

Date/Publication 2025-07-13

Contents

CGHbase-package	2
avedist	3
cghCall	3
cghRaw	6
cghRegions	7

cghSeg	9
chromosomes	11
copynumber	12
frequencyPlot	13
frequencyPlotCalls	14
make_cghRaw	15
plot.cghRaw	16
probloss	16
regions	17
summaryPlot	18
Wilting	19
WiltingCalled	20
WiltingNorm	20
WiltingRaw	21
WiltingRegions	21
WiltingSeg	22
Index	23

CGHbase-package

CGHbase: Base functions and classes for arrayCGH data analysis.

Description

CGHbase: Base functions and classes for arrayCGH data analysis.

Details

Main infrastructural classes: [cghRaw](#), [cghSeg](#), [cghCall](#). Full help on methods and associated functions is available from within class help pages.

Attached data sets: [Wilting](#), [WiltingRaw](#), [WiltingNorm](#), [WiltingSeg](#), [WiltingCalled](#).

Author(s)

Sjoerd Vosse <sjoerdvos@yahoo.com>

avedist	<i>Retrieve regions information from cghRegions object.</i>
---------	---

Description

This function accesses the regions information stored in the featureData of an object derived from the [cghRegions-class](#).

Usage

```
avedist(object)
nclone(object)
```

Arguments

object	Object derived from class cghRegions
--------	--------------------------------------

Value

avedist returns a vector containing the Average L1-distance of clone signatures to the medoid signature; nclone returns a vector containing the number of clones that is included in each region;

Author(s)

Sjoerd Vosse

See Also

[cghRegions-class](#)

cghCall	<i>Class to contain and describe called array comparative genomic hybridization data.</i>
---------	---

Description

Container for aCGH data and experimental metadata. cghCall class is derived from [eSet](#), and requires the following matrices of equal dimension as assayData members:

- copynumber
- segmented
- calls
- probloss
- probnorm
- probgain

Furthermore, columns named Chromosome, Start, and End are required as featureData members, containing feature position information.

Extends

Directly extends class [eSet](#).

Creating Objects

```
new('cghCall', phenoData = [AnnotatedDataFrame], experimentData = [MIAME], annotation
= [character], copynumber = [matrix], segmented = [matrix], calls = [matrix], probloss
= [matrix], probnorm = [matrix], probgain = [matrix], featureData = [AnnotatedDataFrame],
...)
```

An object of class `cghCall` is generally obtained as output from [CGHcall](#).

Slots

Inherited from `eSet`:

assayData: Contains matrices with equal dimensions, and with column number equal to `nrow(phenoData)`.
 assayData must contain the following matrices

- copynumber
- segmented
- calls
- probloss
- probnorm
- probgain

with rows representing array probes and columns representing samples. Additional matrices of identical size (e.g., representing measurement errors) may also be included in `assayData`.

Class: [AssayData-class](#)

phenoData: See [eSet](#)

featureData: An [AnnotatedDataFrame](#) with columns Chromosome, Start, and End containing array element position data.

experimentData: See [eSet](#)

annotation: See [eSet](#)

Methods

Class-specific methods.

`copynumber(cghCall), copynumber(cghCall, matrix)<-` Access and set elements named copynumber in the `AssayData-class` slot.

`segmented(cghCall), segmented(cghCall, matrix)<-` Access and set elements named segmented in the `AssayData-class` slot.

`calls(cghCall), calls(cghCall, matrix)<-` Access and set elements named calls in the `AssayData-class` slot.

`probloss(cghCall), probloss(cghCall, matrix)<-` Access and set elements named probloss in the `AssayData-class` slot.

`probnorm(cghCall), probnorm(cghCall, matrix)<-` Access and set elements named probnorm in the `AssayData-class` slot.

`probgain(cghCall), probgain(cghCall, matrix) <-` Access and set elements named `probgain` in the `AssayData`-class slot.

`chromosomes, bstart, bpend` Access the chromosomal positions stored in `featureData`

plot Create a plot containing `log2ratios`, `segments` and call probabilities ordered by chromosomal position. EXTRA OPTIONS PLUS DEFAULTS: `dotres=10`. Every `dotres`-th `log2-ratio` is plotted. `dotres=1` plots all data. However, higher values save a lot of space and allow quicker browsing of the plots. `ylim=c(-5,5)`: limits of the y-axis. `gaincol='green'`; `losscol='red'`; `ampcol="darkgreen"`; `dlcol="darkred"`: Colors used for gain, loss (bars) and amplifications, double loss (tick marks). `build='GRCh37'`: build of human genome used for determining positions of centromeres

plot.summary Create a plot summarizing the call probabilities of all samples

frequencyPlotCalls Create a frequency plot summarizing the calls of all samples

See [eSet](#) for derived methods.

Author(s)

Sjoerd Vosse

See Also

[eSet-class](#), [cghRaw-class](#), [cghSeg-class](#)

Examples

```
# create an instance of cghCall
new("cghCall")

# create an instance of cghCall through \code{\link{ExpandCGHcall}}
## Not run:
data(Wilting)
rawcgh <- make_cghSeg(Wilting)
normalized <- normalize(rawcgh)
segmented <- segmentData(normalized)
perc.tumor <- rep(0.75, 3)
listcalled <- CGHcall(segmented, cellularity=perc.tumor)
called <- ExpandCGHcall(listcalled, segmented)

# plot the first sample. Default only every 10th log2-ratio is plotted (dotres=10). Adjust using dotres= option below
plot(called[,1])
# plot the first chromosome of the first sample
plot(called[chromosomes(called)==1,1])

# get the copynumber values of the third and fourth sample
log2ratios <- copynumber(called[,3:4])

# get the names of the samples
sampleNames(called)

# get the names of the array elements
```

```
featureNames(called)

## End(Not run)
```

cghRaw	<i>Class to contain and describe raw or normalized array comparative genomic hybridization data.</i>
--------	--

Description

Container for aCGH data and experimental metadata. cghRaw class is derived from [eSet](#), and requires a matrix named copynumber as assayData member. Furthermore, columns named Chromosome, Start, and End are required as featureData members, containing feature position information.

Extends

Directly extends class [eSet](#).

Creating Objects

```
new('cghRaw', phenoData = [AnnotatedDataFrame], experimentData = [MIAME], annotation = [character], copynumber = [matrix], featureData = [AnnotatedDataFrame], ...)
```

make_cghRaw is a function to convert a dataframe or textfile to an object of class cghRaw. The input should be either a dataframe or a tabseparated textfile (textfiles must contain a header). The first three columns should contain the name, chromosome and position in bp for each array target respectively. The chromosome and position column must contain numbers only. Following these is a column with log2 ratios for each of your samples. If the input type is a textfile, missing values should be represented as 'NA' or an empty field.

Slots

Inherited from eSet:

assayData: Contains matrices with equal dimensions, and with column number equal to nrow(phenoData). assayData must contain a matrix copynumber with rows represening array probes and columns representing samples. Additional matrices of identical size (e.g., representing measurement errors) may also be included in assayData. Class:[AssayData-class](#)

phenoData: See [eSet](#)

featureData: An [AnnotatedDataFrame](#) with columns Chromosome, Start, and End containing array element position data.

experimentData: See [eSet](#)

annotation: See [eSet](#)

Methods

Class-specific methods.

`copynumber(cghRaw)`, `copynumber(cghRaw,matrix)<-` Access and set elements named `copynumber` in the `AssayData-class` slot.

`chromosomes`, `bpstart`, `bpend` Access the chromosomal positions stored in `featureData`

plot Create a plot containing `log2ratios` ordered by chromosomal position

See [eSet](#) for derived methods. Annotation functionality is not yet supported.

Author(s)

Sjoerd Vosse

See Also

[eSet-class](#), [cghSeg-class](#), [cghCall-class](#)

Examples

```
# create an instance of cghRaw
new("cghRaw")

# create an instance of cghRaw from a dataframe
data(Wilting)
rawcgh <- make_cghRaw(Wilting)

# plot the first sample
plot(rawcgh[,1])
# first three chromosomes
plot(rawcgh[chromosomes(rawcgh)==1,1])

# get the copynumber values of the third and fourth sample
log2ratios <- copynumber(rawcgh[,3:4])

# get the names of the samples
sampleNames(rawcgh)

# get the names of the array elements
featureNames(rawcgh)
```

cghRegions

Class to contain and describe array comparative genomic hybridization regions data.

Description

Container for aCGH regions data and experimental metadata. `cghRegions` class is derived from `eSet`, and requires a matrix named `regions` as `assayData` member. Furthermore, columns named `Chromosome`, `Start`, `End`, `Nclone`, and `Avedist` are required as `featureData` members, containing region and position information.

Extends

Directly extends class `eSet`.

Creating Objects

```
new('cghRegions', phenoData = [AnnotatedDataFrame], experimentData = [MIAME], annotation
= [character], regions = [matrix], featureData = [AnnotatedDataFrame], ...)
```

An object of this class is generally obtained by running the function `CGHregions`.

Slots

Inherited from `eSet`:

assayData: Contains matrices with equal dimensions, and with column number equal to `nrow(phenoData)`. `assayData` must contain a matrix `regions` with rows representing regions and columns representing samples. Additional matrices of identical size (e.g., representing measurement errors) may also be included in `assayData`. Class: `AssayData`

phenoData: See `eSet`

featureData: An `AnnotatedDataFrame` with columns `Chromosome`, `Start`, `End`, `Nclone`, and `Avedist` containing region and position information.

experimentData: See `eSet`

annotation: See `eSet`

Methods

Class-specific methods.

`regions(cghRegions)`, `regions(cghRegions, matrix)` <- Access and set elements named `regions` in the `AssayData`-class slot.

`chromosomes`, `bpstart`, `bpend`, `nclone`, `avedist` Access the region and position information stored in `featureData`

plot.cghRegions Create a plot displaying chromosomes on the Y-axis and base pair position on the X-axis. A new region is displayed by a slight jump with respect to the previous region. Each region is displayed as a bi-colored segment, the lower and upper part of which correspond to the proportions `pl` and `pg` of samples with a loss (red) or gain (green), respectively. The color coding is displayed as well: 1: `pl (pg) < 10%`; 2: `10% = pl (pg) < 30%`; 3: `30% = pl (pg) < 50%`; 4: `pl (pg) = 50%`.

frequencyPlot Create a frequency plot

See `eSet` for derived methods. Annotation functionality is not yet supported.

Author(s)

Sjoerd Vosse

See Also[eSet](#), [cghRaw-class](#), [cghSeg-class](#), [cghCall-class](#)**Examples**

```
# create an instance of cghRegions
new("cghRegions")

# load an instance of cghRegions
data(WiltingRegions)

# plot all region data
plot(WiltingRegions)
# make a frequency plot
frequencyPlot(WiltingRegions)

# extract the region values
values <- regions(WiltingRegions)

# get the names of the samples
sampleNames(WiltingRegions)
```

cghSeg*Class to contain and describe segmented array comparative genomic hybridization data.*

Description

Container for aCGH data and experimental metadata. `cghSeg` class is derived from [eSet](#), and requires a matrix named `copynumber` as well as a matrix named `segmented` as `assayData` members of equal dimensions. Furthermore, columns named `Chromosome`, `Start`, and `End` are required as `featureData` members, containing feature position information.

Extends

Directly extends class [eSet](#).

Creating Objects

```
new('cghSeg', phenoData = [AnnotatedDataFrame], experimentData = [MIAME], annotation
= [character], copynumber = [matrix], segmented = [matrix], featureData = [AnnotatedDataFrame],
...)
```

An object of class `cghSeg` is generally obtained as output from [segmentData](#).

Slots

Inherited from `eSet`:

assayData: Contains matrices with equal dimensions, and with column number equal to `nrow(phenoData)`. `assayData` must contain matrices `copynumber` and `segmented` with rows representing array probes and columns representing samples. Additional matrices of identical size (e.g., representing measurement errors) may also be included in `assayData`. Class: [AssayData-class](#)

phenoData: See [eSet](#)

featureData: An [AnnotatedDataFrame](#) with columns `Chromosome`, `Start`, and `End` containing array element position data.

experimentData: See [eSet](#)

annotation: See [eSet](#)

Methods

Class-specific methods.

`copynumber(cghSeg)`, `copynumber(cghSeg, matrix)` <- Access and set elements named `copynumber` in the `AssayData-class` slot.

`segmented(cghSeg)`, `segmented(cghSeg, matrix)` <- Access and set elements named `segmented` in the `AssayData-class` slot.

`chromosomes`, `bpstart`, `bpend` Access the chromosomal positions stored in `featureData`

plot Create a plot containing `log2ratios` and `segments` ordered by chromosomal position. TWO EXTRA OPTIONS PLUS DEFAULTS: `dotres=10`. Every `dotres`-th `log2-ratio` is plotted. `dotres=1` plots all data. However, higher values save a lot of space and allow quicker browsing of the plots. `ylim=c(-2,5)`: limits of the y-axis

See [eSet](#) for derived methods.

Author(s)

Sjoerd Vosse

See Also

[eSet-class](#), [cghRaw-class](#), [cghCall-class](#)

Examples

```
# create an instance of cghSeg
new("cghSeg")

# create an instance of cghSeg through \code{segmentData}
## Not run:
data(Wilting)
rawcgh <- make_cghSeg(Wilting)
normalized <- normalize(rawcgh)
segmented <- segmentData(normalized)
```

```

# plot the first sample. Default only every 10th log2-ratio is plotted (dotres=10). Adjust using dotres= option be
plot(segmented[,1])
# first three chromosomes
plot(segmented[chromosomes(segmented)<=3,1])

# get the copynumber values of the third and fourth sample
log2ratios <- copynumber(segmented[,3:4])

# get the names of the samples
sampleNames(segmented)

# get the names of the array elements
featureNames(segmented)

## End(Not run)

```

chromosomes	<i>Retrieve feature position data from cgh objects.</i>
-------------	---

Description

These generic functions access the position data stored in the featureData of an object derived from the [cghRaw-class](#), [cghSeg-class](#) or [cghCall-class](#).

Usage

```

chromosomes(object)
bpstart(object)
bpend(object)

```

Arguments

object	Object derived from class cghRaw, cghSeg, or cghCall
--------	--

Value

chromosomes returns a vector of chromosome numbers; bpstart returns a vector of basepair start positions; bpend returns a vector of basepair end positions;

Author(s)

Sjoerd Vosse

See Also

[cghRaw-class](#), [cghSeg-class](#), [cghCall-class](#)

copynumber	<i>Retrieve copynumber data from cgh objects.</i>
------------	---

Description

These generic functions access the copynumber values of assay data stored in an object derived from the [cghRaw-class](#), [cghSeg-class](#) or [cghCall-class](#).

Usage

```
copynumber(object)
copynumber(object) <- value
segmented(object)
segmented(object) <- value
calls(object)
calls(object) <- value
```

Arguments

object	Object derived from class cghRaw, cghSeg, or cghCall
value	Matrix with rows representing features and columns samples.

Value

copynumber returns a matrix of copynumber values;

Author(s)

Sjoerd Vosse

See Also

[cghRaw-class](#), [cghSeg-class](#), [cghCall-class](#)

Examples

```
data(WiltingCalled)
log2ratios <- copynumber(WiltingCalled)
segments <- segmented(WiltingCalled)
calls <- calls(WiltingCalled)
```

frequencyPlot	<i>Visualization of aCGH regions.</i>
---------------	---------------------------------------

Description

This function creates a frequency plot for aCGH regions.

Usage

```
frequencyPlot(x, y, ...)
```

Arguments

x	An object of class <code>cghRegions</code> .
y	This argument is not used and should be missing.
...	Arguments plot.

Details

We find plotted on the x-axis the array probes sorted by chromosomal position. The vertical bars represent the frequency of gains and losses across your samples. The black bars represent gains, the gray bars represent losses.

Value

This function creates a plot.

Author(s)

Mark van de Wiel and Sjoerd Vosse

References

Mark A. van de Wiel and Wessel N. van Wieringen (2007). CGHregions: Dimension Reduction for Array CGH Data with Minimal Information Loss. *Cancer Informatics*, 2, 55-63.

Examples

```
## Not run:  
data(WiltingRegions)  
frequencyPlot(WiltingRegions)  
  
## End(Not run)
```

frequencyPlotCalls	<i>Visualization of aCGH profiles.</i>
--------------------	--

Description

This function creates a frequency plot for aCGH profiles.

Usage

```
frequencyPlotCalls(x,main='Frequency Plot', gaincol='blue', losscol='red', misscol=NA, build='GRCh37
```

Arguments

x	An object of class <code>cghCall</code> .
main	Title of plot
gaincol	Color to use for gains
losscol	Color to use for losses
misscol	Missings
build	Build of Humane Genome.Either GRCh37, GRCh36, GRCh35 or GRCh34
...	Arguments plot.

Details

We find plotted on the x-axis the array probes sorted by chromosomal position. The vertical bars represent the frequency of gains or losses.

Value

This function creates a plot.

Author(s)

Sjoerd Vosse & Mark van de Wiel

References

Mark A. van de Wiel, Kyung In Kim, Sjoerd J. Vosse, Wessel N. van Wieringen, Saskia M. Wilting and Bauke Ylstra. CGHcall: calling aberrations for array CGH tumor profiles. *Bioinformatics*, 23, 892-894.

Examples

```
## Not run:
data(Wilting)
rawcgh <- make_cghSeg(Wilting)
normalized <- normalize(rawcgh)
segmented <- segmentData(normalized)
called <- CGHcall(segmented,cellularity= rep(0.75, 3))
frequencyPlotCalls(called)

## End(Not run)
```

make_cghRaw

*Convert a dataframe or textfile to an object of class cghRaw.***Description**

This function converts a dataframe of appropriate format to an object of class `cghRaw`.

Usage

```
make_cghRaw(input)
```

Arguments

input	Either a dataframe or character string containing a filename. See details for the format.
-------	---

Details

The input should be either a dataframe or a tabseparated textfile (textfiles must contain a header). The first four columns should contain the name, chromosome and the start and end position in bp for each array target respectively. The chromosome and position column must contain numbers only. Following these is a column with log2 ratios for each of your samples. If the input type is a textfile, missing values should be represented as 'NA' or an empty field.

Value

This function returns an object of class `cghRaw-class`.

Author(s)

Sjoerd Vosse & Mark van de Wiel

Examples

```
data(Wilting)
## Convert to \code{\link{cghRaw}} object
cgh <- make_cghRaw(Wilting)
```

plot.cghRaw	<i>Plot aCGH data.</i>
-------------	------------------------

Description

Please see the class descriptions for more details on the plot functions.

Usage

```
## S3 method for class 'cghRaw'
plot(x, y, ...)
## S3 method for class 'cghSeg'
plot(x, y, ...)
## S3 method for class 'cghCall'
plot(x, y, ...)
## S3 method for class 'cghRegions'
plot(x, y, ...)
```

Arguments

x	An object of class cghRaw , cghSeg , cghCall , or cghSeg .
y	This argument is not used and should be missing.
...	Arguments plot.

Author(s)

Sjoerd Vosse

See Also

[cghRaw-class](#), [cghSeg-class](#), [cghCall-class](#), [cghRegions-class](#)

probbloss	<i>Retrieve call probabilities from a cghCall object.</i>
-----------	---

Description

These generic functions access the call probabilities from assay data stored in a object derived from the [cghCall-class](#).

Usage

```
probdloss(object)
probdloss(object) <- value
probdloss(object)
probdloss(object) <- value
probnorm(object)
probnorm(object) <- value
probgain(object)
probgain(object) <- value
probamp(object)
probamp(object) <- value
```

Arguments

object	Object derived from class <code>cghCall</code>
value	Matrix with rows representing features and columns samples.

Value

probdloss returns matrix of call probabilities;

Author(s)

Sjoerd Vosse

See Also

[cghCall-class](#)

regions

Retrieve regions data from cghRegions object.

Description

This function accesses the regions values of assay data stored in an object derived from the [cghRegions-class](#).

Usage

```
regions(object)
regions(object) <- value
```

Arguments

object	Object derived from class <code>cghRegions</code>
value	Matrix with rows representing features and columns samples.

Value

regions returns a matrix of regions values;

Author(s)

Sjoerd Vosse

See Also

[cghRegions-class](#)

summaryPlot

Visualization of aCGH profiles.

Description

This function creates a summary plot for aCGH profiles.

Usage

```
summaryPlot(x,main='Summary Plot', gaincol='blue', losscol='red', misscol=NA, build='GRCh37', ...)
```

Arguments

x	An object of class cghCall .
main	Title of plot
gaincol	Color to use for gains
losscol	Color to use for losses
misscol	Missings
build	Build of Humane Genome.Either GRCh37, GRCh36, GRCh35 or GRCh34
...	Arguments plot.

Details

We find plotted on the x-axis the array probes sorted by chromosomal position. The vertical bars represent the average probability that the positions they cover are gained (green bars) or lost (red bars). The green bars represent gains, the red bars represent losses.

Value

This function creates a plot.

Author(s)

Sjoerd Vosse & Mark van de Wiel

References

Mark A. van de Wiel, Kyung In Kim, Sjoerd J. Vosse, Wessel N. van Wieringen, Saskia M. Wilting and Bauke Ylstra. CGHcall: calling aberrations for array CGH tumor profiles. *Bioinformatics*, 23, 892-894.

Examples

```
## Not run:
data(Wilting)
rawcgh <- make_cghSeg(Wilting)
normalized <- normalize(rawcgh)
segmented <- segmentData(normalized)
called <- CGHcall(segmented,cellularity= rep(0.75, 3))
summaryPlot(called)

## End(Not run)
```

Wilting	<i>Cervical cancer arrayCGH data</i>
---------	--------------------------------------

Description

A dataframe containing 4709 rows and 8 columns with arrayCGH data.

Usage

Wilting

Format

A dataframe containing the following 8 columns:

Name The unique identifiers of array elements.

Chromosome Chromosome number of each array element.

Position Chromosomal position in bp of each array element.

AdCA10 Raw log2 ratios for cervical cancer sample AdCA10.

SCC27 Raw log2 ratios for cervical cancer sample SCC27.

SCC32 Raw log2 ratios for cervical cancer sample SCC32.

SCC36 Raw log2 ratios for cervical cancer sample SCC36.

SCC39 Raw log2 ratios for cervical cancer sample SCC39.

Source

Wilting, S.M., Snijders, P.J., Meijer, G.A., Ylstra, B., van den IJssel, P.R., Snijders, A.M., Albertson, D.G., Coffa, J., Schouten, J.P., van de Wiel, M.A., Meijer, C.J., & Steenbergen, R.D. (2006). Increased gene copy numbers at chromosome 20q are frequent in both squamous cell carcinomas and adenocarcinomas of the cervix. *Journal of Pathology*, 210, 258-259.

WiltingCalled

Cervical cancer arrayCGH data called with CGHcall

Description

Cervical cancer arrayCGH data called with [CGHcall](#) with default settings, containing 3552 features for 5 samples.

Usage

WiltingCalled

Format

An object of class [cghCall](#)

Source

Wilting, S.M., Snijders, P.J., Meijer, G.A., Ylstra, B., van den IJssel, P.R., Snijders, A.M., Albertson, D.G., Coffa, J., Schouten, J.P., van de Wiel, M.A., Meijer, C.J., & Steenbergen, R.D. (2006). Increased gene copy numbers at chromosome 20q are frequent in both squamous cell carcinomas and adenocarcinomas of the cervix. *Journal of Pathology*, 210, 258-259.

Mark A. van de Wiel, Kyung In Kim, Sjoerd J. Vosse, Wessel N. van Wieringen, Saskia M. Wilting and Bauke Ylstra. CGHcall: calling aberrations for array CGH tumor profiles. *Bioinformatics*, 23, 892-894.

WiltingNorm

Normalized log2 ratios from cervical cancer arrayCGH data.

Description

Normalized log2 ratios from cervical cancer arrayCGH data, containing 3552 features for 5 samples. These data have been normalized using the [normalize](#) function with default settings.

Usage

WiltingCalled

Format

An object of class [cghRaw](#).

Source

Wilting, S.M., Snijders, P.J., Meijer, G.A., Ylstra, B., van den IJssel, P.R., Snijders, A.M., Albertson, D.G., Coffa, J., Schouten, J.P., van de Wiel, M.A., Meijer, C.J., & Steenbergen, R.D. (2006). Increased gene copy numbers at chromosome 20q are frequent in both squamous cell carcinomas and adenocarcinomas of the cervix. *Journal of Pathology*, 210, 258-259.

WiltingRaw

Raw log2 ratios from cervical cancer arrayCGH data.

Description

Raw log2 ratios from cervical cancer arrayCGH data, containing 3552 features for 5 samples. These data have been preprocessed using [preprocess](#).

Usage

WiltingCalled

Format

An object of class [cghRaw](#).

Source

Wilting, S.M., Snijders, P.J., Meijer, G.A., Ylstra, B., van den IJssel, P.R., Snijders, A.M., Albertson, D.G., Coffa, J., Schouten, J.P., van de Wiel, M.A., Meijer, C.J., & Steenbergen, R.D. (2006). Increased gene copy numbers at chromosome 20q are frequent in both squamous cell carcinomas and adenocarcinomas of the cervix. *Journal of Pathology*, 210, 258-259.

WiltingRegions

Regions of cervical cancer arrayCGH data as defined by CGHregions

Description

Regions of cervical cancer arrayCGH data as defined by [CGHregions](#) with default settings, containing 90 regions over 5 samples.

Usage

WiltingRegions

Format

An object of class [cghRegions](#)

Source

Wilting, S.M., Snijders, P.J., Meijer, G.A., Ylstra, B., van den IJssel, P.R., Snijders, A.M., Albertson, D.G., Coffa, J., Schouten, J.P., van de Wiel, M.A., Meijer, C.J., & Steenbergen, R.D. (2006). Increased gene copy numbers at chromosome 20q are frequent in both squamous cell carcinomas and adenocarcinomas of the cervix. *Journal of Pathology*, 210, 258-259.

Mark A. van de Wiel and Wessel N. van Wieringen (2007). CGHregions: Dimension Reduction for Array CGH Data with Minimal Information Loss. *Cancer Informatics*, 2, 55-63.

 WiltingSeg

Segmented log2 ratios from cervical cancer arrayCGH data.

Description

Segmented log2 ratios from cervical cancer arrayCGH data, containing 3552 features for 5 samples. These data have been segmented using [segmentData](#) with default settings.

Usage

WiltingCalled

Format

An object of class [cghSeg](#).

Source

Wilting, S.M., Snijders, P.J., Meijer, G.A., Ylstra, B., van den IJssel, P.R., Snijders, A.M., Albertson, D.G., Coffa, J., Schouten, J.P., van de Wiel, M.A., Meijer, C.J., & Steenbergen, R.D. (2006). Increased gene copy numbers at chromosome 20q are frequent in both squamous cell carcinomas and adenocarcinomas of the cervix. *Journal of Pathology*, 210, 258-259.

Index

- * **classes**
 - cghCall, 3
 - cghRaw, 6
 - cghRegions, 7
 - cghSeg, 9
- * **datasets**
 - Wilting, 19
 - WiltingCalled, 20
 - WiltingNorm, 20
 - WiltingRaw, 21
 - WiltingRegions, 21
 - WiltingSeg, 22
- * **manip**
 - avedist, 3
 - chromosomes, 11
 - copynumber, 12
 - problobss, 16
 - regions, 17
- * **misc**
 - frequencyPlot, 13
 - frequencyPlotCalls, 14
 - make_cghRaw, 15
 - summaryPlot, 18
- * **package**
 - CGHbase-package, 2

AnnotatedDataFrame, 4, 6, 8, 10

AssayData, 8

avedist, 3

avedist, cghRegions-method (cghRegions), 7

bpend (chromosomes), 11

bpend, cghCall-method (cghCall), 3

bpend, cghRaw-method (cghRaw), 6

bpend, cghRegions-method (cghRegions), 7

bpend, cghSeg-method (cghSeg), 9

bpstart (chromosomes), 11

bpstart, cghCall-method (cghCall), 3

bpstart, cghRaw-method (cghRaw), 6

bpstart, cghRegions-method (cghRegions), 7

bpstart, cghSeg-method (cghSeg), 9

calls (copynumber), 12

calls, cghCall-method (cghCall), 3

calls<- (copynumber), 12

calls<-, cghCall, matrix-method (cghCall), 3

CGHbase (CGHbase-package), 2

CGHbase-package, 2

CGHcall, 4, 20

cghCall, 2, 3, 14, 16, 18, 20

cghCall-class (cghCall), 3

cghRaw, 2, 6, 16, 20, 21

cghRaw-class (cghRaw), 6

CGHregions, 8, 21

cghRegions, 7, 13, 21

cghRegions-class (cghRegions), 7

cghSeg, 2, 9, 16, 22

cghSeg-class (cghSeg), 9

chromosomes, 11

chromosomes, cghCall-method (cghCall), 3

chromosomes, cghRaw-method (cghRaw), 6

chromosomes, cghRegions-method (cghRegions), 7

chromosomes, cghSeg-method (cghSeg), 9

class: cghCall (cghCall), 3

class: cghRaw (cghRaw), 6

class: cghRegions (cghRegions), 7

class: cghSeg (cghSeg), 9

copynumber, 12

copynumber, cghCall-method (cghCall), 3

copynumber, cghRaw-method (cghRaw), 6

copynumber, cghSeg-method (cghSeg), 9

copynumber<- (copynumber), 12

copynumber<-, cghCall, matrix-method (cghCall), 3

copynumber<-, cghRaw, matrix-method (cghRaw), 6

copynumber<-, cghSeg, matrix-method
 (cghSeg), 9

eSet, 3–10

frequencyPlot, 13

frequencyPlot, cghRegions, missing-method
 (cghRegions), 7

frequencyPlotCalls, 14

frequencyPlotCalls, cghCall, missing-method
 (cghCall), 3

initialize, cghCall-method (cghCall), 3

initialize, cghRaw-method (cghRaw), 6

initialize, cghRegions-method
 (cghRegions), 7

initialize, cghSeg-method (cghSeg), 9

make_cghRaw, 15

nclone (avedist), 3

nclone, cghRegions-method (cghRegions), 7

normalize, 20

plot, cghCall, missing-method (cghCall), 3

plot, cghRaw, missing-method (cghRaw), 6

plot, cghSeg, missing-method (cghSeg), 9

plot.cghCall (plot.cghRaw), 16

plot.cghRaw, 16

plot.cghRegions (plot.cghRaw), 16

plot.cghRegions, cghRegions, missing-method
 (cghRegions), 7

plot.cghSeg (plot.cghRaw), 16

plot.summary, cghCall, missing-method
 (cghCall), 3

preprocess, 21

probamp (probdloss), 16

probamp, cghCall-method (cghCall), 3

probamp<- (probdloss), 16

probamp<-, cghCall, matrix-method
 (cghCall), 3

probdloss (probdloss), 16

probdloss, cghCall-method (cghCall), 3

probdloss<- (probdloss), 16

probdloss<-, cghCall, matrix-method
 (cghCall), 3

probgain (probdloss), 16

probgain, cghCall-method (cghCall), 3

probgain<- (probdloss), 16

probgain<-, cghCall, matrix-method
 (cghCall), 3

probloss, 16

probloss, cghCall-method (cghCall), 3

probloss<- (probloss), 16

probloss<-, cghCall, matrix-method
 (cghCall), 3

probnorm (probloss), 16

probnorm, cghCall-method (cghCall), 3

probnorm<- (probloss), 16

probnorm<-, cghCall, matrix-method
 (cghCall), 3

regions, 17

regions, cghRegions-method (cghRegions),
 7

regions<- (regions), 17

regions<-, cghRegions, matrix-method
 (cghRegions), 7

segmentData, 9, 22

segmented (copynumber), 12

segmented, cghCall-method (cghCall), 3

segmented, cghSeg-method (cghSeg), 9

segmented<- (copynumber), 12

segmented<-, cghCall, matrix-method
 (cghCall), 3

segmented<-, cghSeg, matrix-method
 (cghSeg), 9

summaryPlot, 18

Wilting, 2, 19

WiltingCalled, 2, 20

WiltingNorm, 2, 20

WiltingRaw, 2, 21

WiltingRegions, 21

WiltingSeg, 2, 22