

Package ‘TOP’

July 3, 2025

Title TOP Constructs Transferable Model Across Gene Expression Platforms

Version 1.9.0

Date 2022-11-09

Description TOP constructs a transferable model across gene expression platforms for prospective experiments. Such a transferable model can be trained to make predictions on independent validation data with an accuracy that is similar to a re-substituted model. The TOP procedure also has the flexibility to be adapted to suit the most common clinical response variables, including linear response, binomial and Cox PH models.

License GPL-3

URL <https://github.com/Harry25R/TOP>

BugReports <https://github.com/Harry25R/TOP/issues>

biocViews Software, Survival, GeneExpression

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Imports assertthat, caret, ClassifyR, directPA, doParallel, dplyr, ggnewscale, ggplot2, ggraph, ggrepel, ggthemes, glmnet, Hmisc, igraph, latex2exp, limma, magrittr, methods, plotly, pROC, purrr, reshape2, stats, stringr, survival, tibble, tidygraph, tidyr, statmod

Suggests knitr, rmarkdown, BiocStyle, Biobase, curatedOvarianData, ggbeeswarm, ggsci, survminer, tidyverse

VignetteBuilder knitr

LazyData false

git_url <https://git.bioconductor.org/packages/TOP>

git_branch devel

git_last_commit 237976c

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-07-02

Author Harry Robertson [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-9203-3894>>),
Nicholas Robertson [aut]

Maintainer Harry Robertson <harry.robertson@sydney.edu.au>

Contents

coefNetworkPlot	2
expit	3
filterFeatures	3
pairwise_col_diff	4
performance_TOP	5
predict_TOP	6
ROC_Plot	7
simplenetworkPlot	7
Surv_TOP_CI	8
TOP_coefPlot	9
TOP_data_binary	10
TOP_lambdaPlot	10
TOP_model	11
TOP_survival	12
TOP_survivalPrediction	14
Index	15

coefNetworkPlot	<i>coefNetworkPlot</i>
-----------------	------------------------

Description

coefNetworkPlot

Usage

```
coefNetworkPlot(TOP_model, nFeatures = 20, s = "lambda.min")
```

Arguments

- TOP_model A Transferable Omics Prediction model. The output from the TOP_model function.
- nFeatures The number of features that will be plotted. Default: 20
- s Lambda value for the lasso model. Default is "lambda.min"

Value

A coefNetwork plot

Examples

```
data(TOP_data_binary, package = "TOP")

x1 <- TOP_data_binary$x1
x2 <- TOP_data_binary$x2
x3 <- TOP_data_binary$x3
y1 <- TOP_data_binary$y1
y2 <- TOP_data_binary$y2
y3 <- TOP_data_binary$y3
```

```

set.seed(23)
x_list <- list(x1, x2)
y_list <- list(factor(y1), factor(y2))

model <- TOP_model(x_list, y_list)
coefNetworkPlot(model)
#' @import ggplot2

```

expit

*The expit function***Description**

The expit function

Usage

```
expit(x)
```

Arguments

x numeric

Value

The expit of x

Examples

```
curve(expit, from = -5, to = 5)
```

filterFeatures

*filterFeatures***Description**

A function that implements feature selection, using limma, from a list of data frames with corresponding labels.

Usage

```

filterFeatures(
  x_list,
  y_list,
  contrast = NULL,
  nFeatures = 50,
  combinationMethod = "OSP"
)

```

Arguments

<code>x_list</code>	A list of data frames, with columns corresponding to features and rows corresponding to observations.
<code>y_list</code>	A list of factor labels.
<code>contrast</code>	A character vector describing which order of levels to contrast in <code>y_list</code> ("disease - control"), Default: NULL
<code>nFeatures</code>	Number of features to return, Default: 50
<code>combinationMethod</code>	Which p-value combination method to use, Default: 'OSP' Options are 'Stouffer', 'OSP', 'Fisher', 'maxP'.

Details

`contrast` must be a character vector of length 1. If `contrast` is NULL, the first level of the first factor in `y_list` will be used as the reference level.

Value

A vector of feature names.

Examples

```
data(TOP_data_binary, package = "TOP")
x1 <- TOP_data_binary$x1
x2 <- TOP_data_binary$x2
x3 <- TOP_data_binary$x3

x_list <- list(x1, x2, x3)
y_list <- list(TOP_data_binary$y1, TOP_data_binary$y2, TOP_data_binary$y3)
y_list <- y_list <- lapply(y_list, function(x) {
  x <- factor(x, levels = c("1", "0"), labels = c("Yes", "No"))
})

filterFeatures(
  x_list, y_list,
  contrast = "Yes - No", nFeatures = 10, combinationMethod = "OSP"
)
```

<code>pairwise_col_diff</code>	<i>Compute pairwise difference between matrix columns</i>
--------------------------------	---

Description

Compute pairwise difference between matrix columns

Usage

```
pairwise_col_diff(x)
```

Arguments

x A data matrix of size n times p. Where rows are observations and columns are features.

Value

A matrix of size n times (p choose 2), where each column is the difference between two of the original columns.

Examples

```
n <- 1
p <- 4
x <- matrix(rep(seq_len(p), n), nrow = n, ncol = p, byrow = TRUE)
colnames(x) <- paste0("X", seq_len(p))
pairwise_col_diff(x)
```

performance_TOP

performance_TOP

Description

A function to calculate the external performance of the Tranferable Omics Prediction model.

Usage

```
performance_TOP(TOP_model, newx, newy, covariates = NULL, s = "lambda.min")
```

Arguments

TOP_model This is the output of the function TOP_model.

newx A matrix of the new data to be predicted. With the same number of feature columns as the original data.

newy A vector of the true labels that are being predicted. With the same number of samples as newx.

covariates A data.frame of the same covariates as the original TOP model, Default: NULL

s Lambda used in the lasso model, Default: 'lambda.min'

Value

A confusion matrix that displays the performance of the classifier.

Examples

```
data(TOP_data_binary, package = "TOP")
x1 <- TOP_data_binary$x1
x2 <- TOP_data_binary$x2

x_list <- list(x1,x2)
y_list <- list(TOP_data_binary$y1, TOP_data_binary$y2)
```

```

model <- TOP_model(x_list, y_list)

x3 <- TOP_data_binary$x3
y3 <- TOP_data_binary$y3

performance_TOP(model$models, newx = x3, newy = y3)

```

predict_TOP

Predict using the Trasferable Omics Prediction model.

Description

A prediction function for the Trasferable Omics Prediction model.

Usage

```
predict_TOP(TOP_model, newx, covariates = NULL, s = "lambda.min")
```

Arguments

TOP_model	The output from the TOP_model function.
newx	A matrix of the new data to be predicted. The columns should be features and the rows should be samples.
covariates	A data frame of the same covariates that were used in the TOP model, Default: NULL
s	Lambda value for the lasso model, Default: 'lambda.min'

Value

A vector of predictions for the new data.

Examples

```

data(TOP_data_binary, package = "TOP")

x1 <- TOP_data_binary$x1
x2 <- TOP_data_binary$x2
x3 <- TOP_data_binary$x3
y1 <- TOP_data_binary$y1
y2 <- TOP_data_binary$y2
y3 <- TOP_data_binary$y3

set.seed(23)
x_list <- list(x1, x2)
y_list <- list(factor(y1), factor(y2))

model <- TOP_model(x_list, y_list)
predictions <- predict_TOP(model$models, newx = x3)

```

ROC_Plot

*ROC_Plot***Description**

A function visualizes the performance of a classifier by plotting the Receiver Operating Characteristic (ROC) curve.

Usage

```
ROC_Plot(roc_list)
```

Arguments

`roc_list` A list of roc objects from the pROC package

Value

A ROC Plot

Examples

```
data(TOP_data_binary, package = "TOP")
x1 <- TOP_data_binary$x1
x2 <- TOP_data_binary$x2
x3 <- TOP_data_binary$x3
y1 <- TOP_data_binary$y1
y2 <- TOP_data_binary$y2
y3 <- TOP_data_binary$y3

set.seed(23)
x_list <- list(x1, x2)
y_list <- list(factor(y1), factor(y2))

model <- TOP_model(x_list, y_list)
pred <- predict_TOP(model$models, newx = x3)
roc <- pROC::roc(y3, pred)
ROC_Plot(list(roc))
```

simplenetworkPlot

*simplenetworkPlot***Description**

simplenetworkPlot

Usage

```
simplenetworkPlot(TOP_model, nFeatures = 50, s = "lambda.min")
```

Arguments

TOP_model	A Transferable Omics Prediction model. The output from the TOP_model function.
nFeatures	The number of features that will be plotted. Default: 20
s	Lambda value for the lasso model. Default is "lambda.min"

Value

A simple network plot

Examples

```
data(TOP_data_binary, package = "TOP")

x1 <- TOP_data_binary$x1
x2 <- TOP_data_binary$x2
x3 <- TOP_data_binary$x3
y1 <- TOP_data_binary$y1
y2 <- TOP_data_binary$y2
y3 <- TOP_data_binary$y3

set.seed(23)
x_list <- list(x1, x2)
y_list <- list(factor(y1), factor(y2))

model <- TOP_model(x_list, y_list)
simplenetworkPlot(model)
```

Surv_TOP_CI

Create a function to calculate the concordance index.

Description

FUNCTION_DESCRIPTION

Usage

```
Surv_TOP_CI(TOP_survival, newx, newy)
```

Arguments

TOP_survival	A TOP_survival model. See TOP_survival .
newx	A new data.frame to predict the survival time.
newy	A data.frame, where the first columns in each data frame is the time and the second column is the event status.

Value

An object of class concordance

Examples

```

data(TOP_data_binary, package = "TOP")
time <- rpois(300, c(600, 1000))
surv <- sample(c(0, 1), 300, replace = TRUE)
y <- data.frame(time, surv)

batch <- rep(paste0("y", 1:3), c(100, 100, 100))
y_list <- y |> split(batch)

x_list <- list(TOP_data_binary$x1, TOP_data_binary$x2, TOP_data_binary$x3)

surv_model <- TOP_survival(x_list[-3], y_list[-3], nFeatures = 10)
Surv_TOP_CI(surv_model, newx = x_list[[3]], newy = y_list[[3]])

```

TOP_coefPlot

*TOP_coefPlot***Description**

TOP_coefPlot

Usage

```
TOP_coefPlot(TOP_model, nFeatures = 20, s = "lambda.min")
```

Arguments

TOP_model	A Transferable Omics Prediction model. The output from the TOP_model function.
nFeatures	The number of features that will be plotted. Default: 20
s	Lambda value for the lasso model, Default: 'lambda.min'

Value

A TOP coeff plot

Examples

```

data(TOP_data_binary, package = "TOP")

x1 <- TOP_data_binary$x1
x2 <- TOP_data_binary$x2
x3 <- TOP_data_binary$x3
y1 <- TOP_data_binary$y1
y2 <- TOP_data_binary$y2
y3 <- TOP_data_binary$y3

set.seed(23)
x_list <- list(x1, x2)
y_list <- list(factor(y1), factor(y2))

model <- TOP_model(x_list, y_list)
TOP_coefPlot(model)

```

TOP_data_binary	<i>A simulated binary data</i>
-----------------	--------------------------------

Description

A simulated binary data

Usage

```
data("TOP_data_binary")
```

Format

A list with columns:

x1 A matrix of size 100x20, each column has mean 1 and sd 1

x2 A matrix of size 100x20, each column has mean 2 and sd 1

x3 A matrix of size 100x20, each column has mean 3 and sd 1

y1 A factor vector of 0's and 1's, created by beta and x1

y2 A factor vector of 0's and 1's, created by beta and x2

y3 A factor vector of 0's and 1's, created by beta and x3

beta A vector with first 10 entries drawn from random unif(-1, 1), otherwise 0's.

Value

The example data.

TOP_lambdaPlot	<i>TOP_lambdaPlot</i>
----------------	-----------------------

Description

TOP_lambdaPlot

Usage

```
TOP_lambdaPlot(  
  TOP_model,  
  nFeatures = 20,  
  s = "lambda.min",  
  interactive = FALSE,  
  label = FALSE  
)
```

Arguments

TOP_model	A Transferable Omics Prediction model. The output from the TOP_model function.
nFeatures	The number of features to plot, features are ranked beta's for lambda.min. Default: 20
s	Lambda value for the lasso model. Default is "lambda.min"
interactive	A boolean indicaitng whether the plot should be interactive. Defaults to FALSE .
label	A boolean indicating whether the features should be labeled on the plot. Defaults to FALSE .

Value

A TOP lambda plot

Examples

```
data(TOP_data_binary, package = "TOP")

x1 <- TOP_data_binary$x1
x2 <- TOP_data_binary$x2
x3 <- TOP_data_binary$x3
y1 <- TOP_data_binary$y1
y2 <- TOP_data_binary$y2
y3 <- TOP_data_binary$y3

set.seed(23)
x_list <- list(x1, x2)
y_list <- list(factor(y1), factor(y2))

model <- TOP_model(x_list, y_list)
TOP_lambdaPlot(model)
```

TOP_model	<i>TOP_model</i>
-----------	------------------

Description

The main function of the TOP package. This function returns a glmnet model .

Usage

```
TOP_model(
  x_list,
  y_list,
  covariates = NULL,
  dataset_weights = NULL,
  sample_weights = FALSE,
  optimiseExponent = FALSE,
  nCores = 1
)
```

Arguments

<code>x_list</code>	a list of data frames, each containing the data for a single batch or dataset. Columns should be features and rows should be observations.
<code>y_list</code>	a list of factors, each containing the labels for a single batch or dataset. The length of this list should be the same as the length of <code>x_list</code> .
<code>covariates</code>	a list of data frames with the covariates that should be included in the model, Default: NULL
<code>dataset_weights</code>	a list of data frames that refer to any grouping structure in the batches, Default: NULL
<code>sample_weights</code>	Should each batch be weighted equally? This is important in unequal sample sizes, Default: FALSE
<code>optimiseExponent</code>	Should the exponent used to modify the lasso weights be optimised using re-substitution?, Default: FALSE
<code>nCores</code>	A numeric specifying the number of cores used if the user wants to use parallelisation, Default: 1

Value

Returns a list with the following elements: `models`, which is a `glmnet` object and `features`, which is a list of the features used in each model.

Examples

```
data(TOP_data_binary, package = "TOP")

x1 <- TOP_data_binary$x1
x2 <- TOP_data_binary$x2
x3 <- TOP_data_binary$x3
y1 <- TOP_data_binary$y1
y2 <- TOP_data_binary$y2
y3 <- TOP_data_binary$y3

set.seed(23)
x_list <- list(x1, x2)
y_list <- list(factor(y1), factor(y2))

model <- TOP_model(x_list, y_list)
```

TOP_survival

TOP_survival

Description

FUNCTION_DESCRIPTION

Usage

```
TOP_survival(
  x_list,
  y_list,
  nFeatures = 50,
  dataset_weights = NULL,
  sample_weights = FALSE,
  nCores = 1
)
```

Arguments

<code>x_list</code>	A list of data frames, each containing the data for a single batch or dataset. Columns are features and rows are observations.
<code>y_list</code>	A list of data frames, where the first columns in each data frame is the time and the second column is the event status. The length of this list should be the same as the length of <code>x_list</code> .
<code>nFeatures</code>	Number of features to return, Default: 50
<code>dataset_weights</code>	a list of data frames that refer to any grouping structure in the batches, Default: NULL
<code>sample_weights</code>	Should each batch be weighted equally? This is important in unequal sample sizes, Default: FALSE
<code>nCores</code>	A numeric specifying the number of cores used if the user wants to use parallelisation, Default: 1

Details

DETAILS

Value

A cox net model

Examples

```
data(TOP_data_binary, package = "TOP")
time <- rpois(300, c(600, 1000))
surv <- sample(c(0, 1), 300, replace = TRUE)
y <- data.frame(time, surv)

batch <- rep(paste0("y", 1:3), c(100, 100, 100))
y_list <- y |> split(batch)

x_list <- list(TOP_data_binary$x1, TOP_data_binary$x2, TOP_data_binary$x3)

TOP_survival(x_list[-3], y_list[-3], nFeatures = 10)
```

TOP_survivalPrediction

TOP_survivalPrediction

Description

A prediction function for TOP_survival

Usage

```
TOP_survivalPrediction(TOP_survival, newx)
```

Arguments

TOP_survival A TOP_survival model. See [TOP_survival](#).
newx A new dataset to predict the survival time.

Value

A vector of predicted survival time.

Examples

```
data(TOP_data_binary, package = "TOP")
time <- rpois(300, c(600, 1000))
surv <- sample(c(0, 1), 300, replace = TRUE)
y <- data.frame(time, surv)

batch <- rep(paste0("y", 1:3), c(100, 100, 100))
y_list <- y |> split(batch)

x_list <- list(TOP_data_binary$x1, TOP_data_binary$x2, TOP_data_binary$x3)

surv_model <- TOP_survival(x_list[-3], y_list[-3], nFeatures = 10)
TOP_survivalPrediction(surv_model, newx = x_list[[3]])
```

Index

* **datasets**

TOP_data_binary, [10](#)

coefNetworkPlot, [2](#)

expit, [3](#)

filterFeatures, [3](#)

pairwise_col_diff, [4](#)

performance_TOP, [5](#)

predict_TOP, [6](#)

ROC_Plot, [7](#)

simplenetworkPlot, [7](#)

Surv_TOP_CI, [8](#)

TOP_coefPlot, [9](#)

TOP_data_binary, [10](#)

TOP_lambdaPlot, [10](#)

TOP_model, [11](#)

TOP_survival, [8](#), [12](#), [14](#)

TOP_survivalPrediction, [14](#)