

Package ‘omada’

July 2, 2025

Type Package

Title Machine learning tools for automated transcriptome clustering analysis

Version 1.11.0

Description Symptomatic heterogeneity in complex diseases reveals differences in molecular states that need to be investigated. However, selecting the numerous parameters of an exploratory clustering analysis in RNA profiling studies requires deep understanding of machine learning and extensive computational experimentation. Tools that assist with such decisions without prior field knowledge are nonexistent and further gene association analyses need to be performed independently. We have developed a suite of tools to automate these processes and make robust unsupervised clustering of transcriptomic data more accessible through automated machine learning based functions. The efficiency of each tool was tested with four datasets characterised by different expression signal strengths. Our toolkit’s decisions reflected the real number of stable partitions in datasets where the subgroups are discernible. Even in datasets with less clear biological distinctions, stable subgroups with different expression profiles and clinical associations were found.

Depends pdfCluster (>= 1.0-3), kernlab (>= 0.9-29), R (>= 4.2), fpc (>= 2.2-9), Rcpp (>= 1.0.7), diceR (>= 0.6.0), ggplot2 (>= 3.3.5), reshape (>= 0.8.8), genieclust (>= 1.1.3), clValid (>= 0.7), glmnet (>= 4.1.3), dplyr (>= 1.0.7), stats (>= 4.1.2), clValid (>= 0.7)

Suggests rmarkdown, knitr, testthat

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.1

VignetteBuilder knitr

biocViews Software, Clustering, RNASeq, GeneExpression

LazyData true

git_url <https://git.bioconductor.org/packages/omada>

git_branch devel

git_last_commit a4bccc1

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-07-01

Author Sokratis Kariotis [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-9993-6017>>)

Maintainer Sokratis Kariotis <sokratiskariotis@gmail.com>

Contents

clusteringMethodSelection	3
clusterVoting	3
feasibilityAnalysis	4
feasibilityAnalysisDataBased	5
featureSelection	5
get_agreement_scores	6
get_average_feature_k_stabilities	7
get_average_stabilities_per_k	7
get_average_stability	8
get_cluster_memberships_k	8
get_cluster_voting_k_votes	9
get_cluster_voting_memberships	9
get_cluster_voting_metric_votes	10
get_cluster_voting_scores	10
get_feature_selection_optimal_features	11
get_feature_selection_optimal_number_of_features	11
get_feature_selection_scores	12
get_generated_dataset	12
get_internal_metric_scores	13
get_max_stability	13
get_metric_votes_k	14
get_optimal_features	14
get_optimal_memberships	15
get_optimal_number_of_features	15
get_optimal_parameter_used	16
get_optimal_stability_score	16
get_partition_agreement_scores	17
get_sample_memberships	17
get_vote_frequencies_k	18
omada	18
optimalClustering	19
partitionAgreement	20
plot_average_stabilities	21
plot_cluster_voting	21
plot_feature_selection	22
plot_partition_agreement	22
plot_vote_frequencies	23
toy_genes	24
toy_gene_memberships	24

Index

clusteringMethodSelection

Method Selection through intra-method Consensus Partition Consistency

Description

Method Selection through intra-method Consensus Partition Consistency

Usage

```
clusteringMethodSelection(data, method.upper.k = 5, number.of.comparisons = 3)
```

Arguments

`data` A dataframe, where columns are features and rows are data points
`method.upper.k` The number of clusters, k, up to which the average agreements will be calculated
`number.of.comparisons` The number of comparisons to average over per k

Value

An object of class "methodSelection" containing a dataframe of partition agreement scores for a set of random parameters clustering runs across different methods and the corresponding plot

Examples

```
clusteringMethodSelection(toy_genes, method.upper.k = 3,  
number.of.comparisons = 2)
```

clusterVoting

Estimating number of clusters through internal exhaustive ensemble majority voting

Description

Estimating number of clusters through internal exhaustive ensemble majority voting

Usage

```
clusterVoting(data, min.k, max.k, algorithm)
```

Arguments

`data` A dataframe, where columns are features and rows are data points
`min.k` Minimum number of clusters for which we calculate stabilities
`max.k` Maximum number of clusters for which we calculate stabilities
`algorithm` The clustering algorithm to use for the multiple clustering runs to be measured

Value

An object of class "clusterVoting" containing a matrix with metric scores for every k and internal index, cluster memberships for every k, a dataframe with the k votes for every index, k vote frequencies and the frequency barplot of the k votes

Examples

```
clusterVoting(toy_genes, 4,14,"sc")
```

feasibilityAnalysis	<i>Simulating dataset and calculate stabilities over different number of clusters</i>
---------------------	---

Description

Simulating dataset and calculate stabilities over different number of clusters

Usage

```
feasibilityAnalysis(classes = 3, samples = 320, features = 400)
```

Arguments

classes	The number of classes of samples to be reflected in the simulated dataset. Also determines the ks to be considered (classes-2, classes+2)
samples	The number of samples in the simulated dataset
features	The number of features in the simulated dataset

Value

An object of class "feasibilityAnalysis" containing the average stabilities for all number of clusters(k), the average (over all k) and maximum stabilities observed and the generated dataset

Examples

```
feasibilityAnalysis(classes = 2, samples = 20, features = 30)
```

feasibilityAnalysisDataBased

Simulating dataset based on existing dataset's dimensions, mean and standard deviation

Description

Simulating dataset based on existing dataset's dimensions, mean and standard deviation

Usage

```
feasibilityAnalysisDataBased(data, classes = 3)
```

Arguments

data	The dataset to base the simulation extracting the number of samples, features and numeric
classes	The number of classes of samples to be reflected in the simulated dataset. Also determines the ks to be considered (classes-2, classes+2)

Value

An object of class "feasibilityAnalysis" containing the average stabilities for all numbers of clusters(k), the average (over all k) and maximum stabilities observed and the generated dataset

Examples

```
feasibilityAnalysisDataBased(data = toy_genes, classes = 2)
```

featureSelection

Predictor variable subsampling sets and bootstrapping stability set selection

Description

Predictor variable subsampling sets and bootstrapping stability set selection

Usage

```
featureSelection(data, min.k = 2, max.k = 4, step = 5)
```

Arguments

data	A dataframe, where columns are features and rows are data points
min.k	Minimum number of clusters for which we calculate stabilities
max.k	Maximum number of clusters for which we calculate stabilities
step	The number for additional features each feature set will contain

Value

An object of class "featureSelection" containing the dataframe of average bootstrap stabilities, where rows represent feature sets and columns number of clusters, the corresponding line plot, the number and the names of the selected features

Examples

```
featureSelection(toy_genes, min.k = 2, max.k = 4, step = 10)
```

get_agreement_scores	<i>Get a dataframe of partition agreement scores for a set of random parameters clustering runs across different methods</i>
----------------------	--

Description

Get a dataframe of partition agreement scores for a set of random parameters clustering runs across different methods

Usage

```
get_agreement_scores(object)
```

Arguments

object	An object of class "partitionAgreement"
--------	---

Value

A dataframe of partition agreement scores for a set of random parameters clustering runs across different methods

Examples

```
pa.object <- partitionAgreement(toy_genes, algorithm.1 = "spectral",
measure.1 = "rbfdot", algorithm.2 = "kmeans", measure.2 = "Lloyd",
number.of.clusters = 3)
get_agreement_scores(pa.object)
```

`get_average_feature_k_stabilities`*Get a dataframe of average bootstrap stabilities*

Description

Get a dataframe of average bootstrap stabilities

Usage

```
get_average_feature_k_stabilities(object)
```

Arguments

object An object of class "featureSelection"

Value

A dataframe of average bootstrap stabilities

Examples

```
fs.object <- featureSelection(toy_genes, min.k = 3, max.k = 4, step = 10)
get_average_feature_k_stabilities(fs.object)
```

`get_average_stabilities_per_k`*Get average stabilities for all numbers of clusters(k)*

Description

Get average stabilities for all numbers of clusters(k)

Usage

```
get_average_stabilities_per_k(object)
```

Arguments

object An object of class "feasibilityAnalysis"

Value

Average stabilities for all numbers of clusters(k)

Examples

```
fa.object <- feasibilityAnalysis(classes = 2, samples = 10, features = 15)
average.sts.k <- get_average_stabilities_per_k(fa.object)
```

`get_average_stability` *Get the average stability(over all k)*

Description

Get the average stability(over all k)

Usage

```
get_average_stability(object)
```

Arguments

`object` An object of class "feasibilityAnalysis"

Value

The average stability(over all k)

Examples

```
fa.object <- feasibilityAnalysis(classes = 2, samples = 10, features = 15)
average.st <- get_average_stability(fa.object)
```

`get_cluster_memberships_k`
Get cluster memberships for every k

Description

Get cluster memberships for every k

Usage

```
get_cluster_memberships_k(object)
```

Arguments

`object` An object of class "clusterVoting"

Value

Cluster memberships for every k

Examples

```
cv.object <- clusterVoting(toy_genes, 4,6,"sc")
get_cluster_memberships_k(cv.object)
```

```
get_cluster_voting_k_votes
```

Get k vote frequencies

Description

Get k vote frequencies

Usage

```
get_cluster_voting_k_votes(object)
```

Arguments

object An object of class "clusterAnalysis"

Value

Matrix with k vote frequencies

Examples

```
oa.object <- omada(toy_genes, method.upper.k = 4)
get_cluster_voting_k_votes(oa.object)
```

```
get_cluster_voting_memberships
```

Get cluster memberships for every k

Description

Get cluster memberships for every k

Usage

```
get_cluster_voting_memberships(object)
```

Arguments

object An object of class "clusterAnalysis"

Value

Cluster memberships for every k

Examples

```
oa.object <- omada(toy_genes, method.upper.k = 4)
get_cluster_voting_memberships(oa.object)
```

`get_cluster_voting_metric_votes`*Get a dataframe with the k votes for every index*

Description

Get a dataframe with the k votes for every index

Usage

```
get_cluster_voting_metric_votes(object)
```

Arguments

`object` An object of class "clusterAnalysis"

Value

Dataframe with the k votes for every index

Examples

```
oa.object <- omada(toy_genes, method.upper.k = 4)
get_cluster_voting_metric_votes(oa.object)
```

`get_cluster_voting_scores`*Get a matrix with metric scores for every k and internal index*

Description

Get a matrix with metric scores for every k and internal index

Usage

```
get_cluster_voting_scores(object)
```

Arguments

`object` An object of class "clusterAnalysis"

Value

A matrix with metric scores for every k and internal index

Examples

```
oa.object <- omada(toy_genes, method.upper.k = 4)
get_cluster_voting_scores(oa.object)
```

```
get_feature_selection_optimal_features
```

Get the optimal features

Description

Get the optimal features

Usage

```
get_feature_selection_optimal_features(object)
```

Arguments

object An object of class "clusterAnalysis"

Value

The list of optimal features

Examples

```
oa.object <- omada(toy_genes, method.upper.k = 4)
get_feature_selection_optimal_features(oa.object)
```

```
get_feature_selection_optimal_number_of_features
```

Get the optimal number of features

Description

Get the optimal number of features

Usage

```
get_feature_selection_optimal_number_of_features(object)
```

Arguments

object An object of class "clusterAnalysis"

Value

The optimal number of features

Examples

```
oa.object <- omada(toy_genes, method.upper.k = 6)
get_feature_selection_optimal_number_of_features(oa.object)
```

`get_feature_selection_scores`*Get a dataframe of average bootstrap stabilities*

Description

Get a dataframe of average bootstrap stabilities

Usage

```
get_feature_selection_scores(object)
```

Arguments

`object` An object of class "clusterAnalysis"

Value

A dataframe of average bootstrap stabilities

Examples

```
oa.object <- omada(toy_genes, method.upper.k = 6)
get_feature_selection_scores(oa.object)
```

`get_generated_dataset` *Get the simulated dataset*

Description

Get the simulated dataset

Usage

```
get_generated_dataset(object)
```

Arguments

`object` An object of class "feasibilityAnalysis"

Value

Simulated dataset

Examples

```
fa.object <- feasibilityAnalysis(classes = 4, samples = 50, features = 15)
generated.ds <- get_generated_dataset(fa.object)
```

`get_internal_metric_scores`*Get a matrix with metric scores for every k and internal index*

Description

Get a matrix with metric scores for every k and internal index

Usage

```
get_internal_metric_scores(object)
```

Arguments

object An object of class "clusterVoting"

Value

A matrix with metric scores for every k and internal index

Examples

```
cv.object <- clusterVoting(toy_genes, 4,6,"sc")
get_internal_metric_scores(cv.object)
```

`get_max_stability`*Get the maximum stability*

Description

Get the maximum stability

Usage

```
get_max_stability(object)
```

Arguments

object An object of class "feasibilityAnalysis"

Value

The maximum stability

Examples

```
fa.object <- feasibilityAnalysis(classes = 2, samples = 10, features = 15)
maximum.st <- get_max_stability(fa.object)
```

get_metric_votes_k	<i>Get a dataframe with the k votes for every index</i>
--------------------	---

Description

Get a dataframe with the k votes for every index

Usage

```
get_metric_votes_k(object)
```

Arguments

object	An object of class "clusterVoting"
--------	------------------------------------

Value

Dataframe with the k votes for every index

Examples

```
cv.object <- clusterVoting(toy_genes, 4,6,"sc")
get_metric_votes_k(cv.object)
```

get_optimal_features	<i>Get the optimal features</i>
----------------------	---------------------------------

Description

Get the optimal features

Usage

```
get_optimal_features(object)
```

Arguments

object	An object of class "featureSelection"
--------	---------------------------------------

Value

The list of optimal features

Examples

```
fs.object <- featureSelection(toy_genes, min.k = 3, max.k = 6, step = 10)
get_optimal_features(fs.object)
```

`get_optimal_memberships`*Get a dataframe with the memberships of the samples found in the input data*

Description

Get a dataframe with the memberships of the samples found in the input data

Usage

```
get_optimal_memberships(object)
```

Arguments

`object` An object of class "optimalClustering"

Value

A dataframe with the memberships of the samples found in the input data

Examples

```
oc.object <- optimalClustering(toy_genes, 4, "spectral")
get_optimal_memberships(oc.object)
```

`get_optimal_number_of_features`*Get the optimal number of features*

Description

Get the optimal number of features

Usage

```
get_optimal_number_of_features(object)
```

Arguments

`object` An object of class "featureSelection"

Value

The optimal number of features

Examples

```
fs.object <- featureSelection(toy_genes, min.k = 3, max.k = 6, step = 10)
get_optimal_number_of_features(fs.object)
```

`get_optimal_parameter_used`*Get the optimal parameter used*

Description

Get the optimal parameter used

Usage

```
get_optimal_parameter_used(object)
```

Arguments

`object` An object of class "optimalClustering"

Value

The optimal parameter used

Examples

```
oc.object <- optimalClustering(toy_genes, 4, "spectral")
get_optimal_parameter_used(oc.object)
```

`get_optimal_stability_score`*Get the optimal stability score*

Description

Get the optimal stability score

Usage

```
get_optimal_stability_score(object)
```

Arguments

`object` An object of class "optimalClustering"

Value

The optimal stability score

Examples

```
oc.object <- optimalClustering(toy_genes, 4, "spectral")
get_optimal_stability_score(oc.object)
```

`get_partition_agreement_scores`

Get a dataframe of partition agreement scores for a set of random parameters clustering runs across different methods

Description

Get a dataframe of partition agreement scores for a set of random parameters clustering runs across different methods

Get a dataframe of partition agreement scores

Usage

```
get_partition_agreement_scores(object)
```

```
get_partition_agreement_scores(object)
```

Arguments

object An object of class "clusterAnalysis"

Value

A dataframe of partition agreement scores for a set of random parameters clustering runs across different methods

A dataframe of partition agreement scores parameters clustering runs across different methods

Examples

```
ms.object <- clusteringMethodSelection(toy_genes, method.upper.k = 3,  
number.of.comparisons = 2)  
get_partition_agreement_scores(ms.object)  
oa.object <- omada(toy_genes, method.upper.k = 4)  
get_partition_agreement_scores(oa.object)
```

`get_sample_memberships`

Get a dataframe with the memberships of the samples found in the input data

Description

Get a dataframe with the memberships of the samples found in the input data

Usage

```
get_sample_memberships(object)
```

Arguments

object An object of class "clusterAnalysis"

Value

A dataframe with the memberships of the samples found in the input data

Examples

```
oa.object <- omada(toy_genes, method.upper.k = 4)
get_sample_memberships(oa.object)
```

get_vote_frequencies_k

Get k vote frequencies

Description

Get k vote frequencies

Usage

```
get_vote_frequencies_k(object)
```

Arguments

object An object of class "clusterVoting"

Value

Matrix with k vote frequencies

Examples

```
cv.object <- clusterVoting(toy_genes, 4,6,"sc")
get_vote_frequencies_k(cv.object)
```

omada

A wrapper function that utilizes all tools to produce the optimal sample memberships

Description

A wrapper function that utilizes all tools to produce the optimal sample memberships

Usage

```
omada(data, method.upper.k = 5)
```

Arguments

`data` A dataframe, where columns are features and rows are data points

`method.upper.k` The upper limit of clusters, k, to be considered. Must be more than 2

Value

An object of class "clusterAnalysis" containing `partition.agreement.scores`, `partition.agreement.plot`, `feature.selection.scores`, `feature.selection.plot`, `feature.selection.optimal.features`, `feature.selection.optimal.number.of.features`, `cluster.voting.scores`, `cluster.voting.cluster.memberships`, `cluster.voting.metric.votes`,

Examples

```
omada(toy_genes, method.upper.k = 3)
```

optimalClustering	<i>Clustering with the optimal parameters estimated by these tools</i>
-------------------	--

Description

Clustering with the optimal parameters estimated by these tools

Usage

```
optimalClustering(data, clusters, algorithm)
```

Arguments

`data` A dataframe, where columns are features and rows are data points

`clusters` Number of clusters to be generated by this clustering

`algorithm` The clustering algorithm to be used

Value

An object of class "optimalClustering" containing a dataframe with the memberships of the samples found in the input data, the optimal stability score and parameter used

Examples

```
optimalClustering(toy_genes, 2, "kmeans")
```

partitionAgreement	<i>Partition Agreement calculation between two clustering runs</i>
--------------------	--

Description

Calculate the agreement (0,1) between two partitioning generated by two clustering runs using the adjust Rand Index. We can use three clustering algorithms (spectral, kmeans and hierarchical) along with the following parameters for each:

Usage

```
partitionAgreement(
  data,
  algorithm.1 = "hierarchical",
  measure.1 = "canberra",
  hier.agгло.algorithm.1 = "average",
  algorithm.2 = "hierarchical",
  measure.2 = "manhattan",
  hier.agгло.algorithm.2 = "average",
  number.of.clusters = 5
)
```

Arguments

data	A dataframe, where columns are features and rows are data points
algorithm.1	Second algorithm to be used (spectral/kmeans/hierarchical)
measure.1	Concerns the first algorithm to be used and represents a kernel for Spectral/kmeans or a distance measure for hierarchical clustering
hier.agгло.algorithm.1	Concerns the first algorithm to be used and represents the agglomerative method for hierarchical clustering (not used in spectral/kmeans clustering)
algorithm.2	First algorithm to be used (spectral/kmeans/hierarchical)
measure.2	Concerns the second algorithm to be used and represents a kernel for Spectral/kmeans or a distance measure for hierarchical clustering
hier.agгло.algorithm.2	Concerns the second algorithm to be used and represents the agglomerative method for hierarchical clustering (not used in spectral/kmeans clustering)
number.of.clusters	The upper limit of clusters to form starting from 2

Details

Spectral kernels: rbfdot, polydot, vanilladot, tanhdot, laplacedot, besseldot, anovadot, splinedot

K-means kernels: "Hartigan-Wong", Lloyd, Forgy, MacQueen

Hierarchical Agglomeration methods: average, ward.D, ward.D2, single, complete, mcquitty, median, centroid

Distance measures: euclidean, manhattan, canberra, minkowski, maximum

Value

An object of class "partitionAgreement" containing agreements (Rand Indexes) from 1 cluster (ARI=0) up to the number of clusters requested

Examples

```
partitionAgreement(toy_genes, algorithm.1 = "hierarchical",
  measure.1 = "canberra", hier.agglo.algorithm.1 = "average",
  algorithm.2 = "hierarchical", measure.2 = "manhattan",
  hier.agglo.algorithm.2 = "average", number.of.clusters = 3)

partitionAgreement(toy_genes, algorithm.1 = "spectral", measure.1 = "rbfdot",
  algorithm.2 = "kmeans", measure.2 = "Lloyd", number.of.clusters = 5)
```

plot_average_stabilities

Plot the average bootstrap stabilities

Description

Plot the average bootstrap stabilities

Usage

```
plot_average_stabilities(object)
```

Arguments

object An object of class "featureSelection"

Value

Line plot of average bootstrap stabilities

Examples

```
fs.object <- featureSelection(toy_genes, min.k = 3, max.k = 6, step = 10)
plot_average_stabilities(fs.object)
```

plot_cluster_voting

Plot k vote frequencies

Description

Plot k vote frequencies

Usage

```
plot_cluster_voting(object)
```

Arguments

object An object of class "clusterAnalysis"

Value

Plot k vote frequencies

Examples

```
oa.object <- omada(toy_genes, method.upper.k = 3)
plot_cluster_voting(oa.object)
```

plot_feature_selection

Plot the average bootstrap stabilities

Description

Plot the average bootstrap stabilities

Usage

```
plot_feature_selection(object)
```

Arguments

object An object of class "clusterAnalysis"

Value

Line plot of average bootstrap stabilities

Examples

```
oa.object <- omada(toy_genes, method.upper.k = 4)
plot_feature_selection(oa.object)
```

plot_partition_agreement

Plot of partition agreement scores

Description

Plot of partition agreement scores

Plot of partition agreement scores

Usage

```
plot_partition_agreement(object)
```

```
plot_partition_agreement(object)
```

Arguments

object An object of class "clusterAnalysis"

Value

Plot of partition agreement scores

Plot of partition agreement scores

Examples

```
ms.object <- clusteringMethodSelection(toy_genes, method.upper.k = 3,
number.of.comparisons = 2)
plot_partition_agreement(ms.object)
oa.object <- omada(toy_genes, method.upper.k = 4)
plot_partition_agreement(oa.object)
```

plot_vote_frequencies *Plot k vote frequencies*

Description

Plot k vote frequencies

Usage

```
plot_vote_frequencies(object)
```

Arguments

object An object of class "clusterVoting"

Value

Plot k vote frequencies

Examples

```
cv.object <- clusterVoting(toy_genes, 4,6,"sc")
plot_vote_frequencies(cv.object)
```

toy_genes	<i>Toy gene data for package examples</i>
-----------	---

Description

Columns are genes and rows are samples

Usage

```
data(toy_genes)
```

Format

An object of class `"cross"`; see `[qtl::read.cross()]`.

Source

nope

References

nothing

Examples

```
data(toy_genes)
```

toy_gene_memberships	<i>Cluster memberships for toy gene data for package examples</i>
----------------------	---

Description

Column "id" represents genes and column "memberships" represents their respective clusters. Rows are samples

Usage

```
data(toy_gene_memberships)
```

Format

An object of class `"cross"`; see `[qtl::read.cross()]`.

Source

nope

References

nothing

toy_gene_memberships

25

Examples

```
data(toy_gene_memberships)
```

Index

- * **datasets**
 - toy_gene_memberships, [24](#)
 - toy_genes, [24](#)
- clusteringMethodSelection, [3](#)
- clusterVoting, [3](#)
- feasibilityAnalysis, [4](#)
- feasibilityAnalysisDataBased, [5](#)
- featureSelection, [5](#)
- get_agreement_scores, [6](#)
- get_average_feature_k_stabilities, [7](#)
- get_average_stabilities_per_k, [7](#)
- get_average_stability, [8](#)
- get_cluster_memberships_k, [8](#)
- get_cluster_voting_k_votes, [9](#)
- get_cluster_voting_memberships, [9](#)
- get_cluster_voting_metric_votes, [10](#)
- get_cluster_voting_scores, [10](#)
- get_feature_selection_optimal_features,
[11](#)
- get_feature_selection_optimal_number_of_features,
[11](#)
- get_feature_selection_scores, [12](#)
- get_generated_dataset, [12](#)
- get_internal_metric_scores, [13](#)
- get_max_stability, [13](#)
- get_metric_votes_k, [14](#)
- get_optimal_features, [14](#)
- get_optimal_memberships, [15](#)
- get_optimal_number_of_features, [15](#)
- get_optimal_parameter_used, [16](#)
- get_optimal_stability_score, [16](#)
- get_partition_agreement_scores, [17](#)
- get_sample_memberships, [17](#)
- get_vote_frequencies_k, [18](#)
- omada, [18](#)
- optimalClustering, [19](#)
- partitionAgreement, [20](#)
- plot_average_stabilities, [21](#)
- plot_cluster_voting, [21](#)
- plot_feature_selection, [22](#)
- plot_partition_agreement, [22](#)
- plot_vote_frequencies, [23](#)
- toy_gene_memberships, [24](#)
- toy_genes, [24](#)