

# Package ‘BioMVCClass’

June 29, 2025

**Title** Model-View-Controller (MVC) Classes That Use Biobase

**Version** 1.76.0

**Author** Elizabeth Whalen

**Description** Creates classes used in model-view-controller (MVC) design

**Depends** R (>= 2.1.0), methods, MVCClass, Biobase, graph, Rgraphviz

**Maintainer** Elizabeth Whalen <ewhalen@hsph.harvard.edu>

**License** LGPL

**biocViews** Visualization, Infrastructure, GraphAndNetwork

**git\_url** <https://git.bioconductor.org/packages/BioMVCClass>

**git\_branch** RELEASE\_3\_21

**git\_last\_commit** 3435d53

**git\_last\_commit\_date** 2025-04-15

**Repository** Bioconductor 3.21

**Date/Publication** 2025-06-29

## Contents

exprModel-class . . . . .	2
graphModel-class . . . . .	3
graphView-class . . . . .	4
GSE-class . . . . .	5
gseModel-class . . . . .	6
heatmapView-class . . . . .	7
<b>Index</b>	<b>8</b>

---

 exprModel-class

---

 Class "exprModel": A class to represent an ExpressionSet model
 

---

### Description

exprModel is a class to represent an ExpressionSet model. This class inherits from the virtual class, gModel. An object of exprModel is responsible for storing and updating the data.

### Objects from the Class

Objects can be created by calls of the form `new("exprModel", ...)`. The initialize method for this class will be created in other packages that use this package (for example, the initialize method will be created in the iSNetwork package).

### Slots

**modelData:** the model data, which is an ExpressionSet

**linkData:** a list of functions that link this model to its parent and child models (if it has any)

**virtualData:** the data that is needed by the views of this object

**modelName:** the name of this model

**modelVar:** a list of variables that refer to the modelData (for instance this may be t-test values that were calculated from the modelData)

### Extends

Class "gModel", directly.

### Methods

No methods defined with class "exprModel" in the signature. The methods for this class will be created in other packages that use this package like iSNetwork.

### Author(s)

Elizabeth Whalen

### See Also

[graphModel-class](#)

---

graphModel-class	<i>Class "graphModel": A class to represent a graph model</i>
------------------	---

---

### Description

graphModel is a class to represent a graph model. This class inherits from the virtual class, gModel. An object of graphModel is responsible for storing and updating the data.

### Objects from the Class

Objects can be created by calls of the form `new("graphModel", ...)`. The initialize method for this class will be created in other packages that use this package (for example, the initialize method will be created in the iSNetwork package).

### Slots

**modelData:** the model data, which is a graph object

**linkData:** a list of functions that link this model to its parent and child models (if it has any)

**virtualData:** data that is needed by views of this model

**modelName:** the name of this model

**modelVar:** a list of variables that refer to the modelData (for instance this may be t-test values that were calculated from the modelData)

### Extends

Class "gModel", directly.

### Methods

No methods defined with class "graphModel" in the signature. The methods for this class will be created in other packages that use this package like iSNetwork.

### Author(s)

Elizabeth Whalen

### See Also

[exprModel-class](#)

---

graphView-class

---

Class "graphView": A class to represent a graph view

---

## Description

graphView is a class to represent a view that is a graph. graphView inherits from the class, plotView, which inherits from the virtual class, genView.

## Objects from the Class

Objects can be created by calls of the form `new("graphView", ...)`. The initialize method for this class will be created in other packages that use this package (for example, the initialize method will be created in the iSNetwork package).

## Slots

**plotDevice:** the plot device number

**plotPar:** the parameter list for the plot, see `par()`

**drArea:** an object of class "GtkDrawingArea"

**dataName:** a character string describing what data are shown in the view

**win:** an object of class "GtkWindow" that holds the view

**winNum:** a number that tells what number view this is (for example, the first view created will have `winNum=1`)

**grLayout:** the Ragraph object, which represents the layout for the graph plot

## Extends

Class "plotView", directly. Class "genView", by class "plotView".

## Methods

No methods defined with class "graphView" in the signature.

## Author(s)

Elizabeth Whalen

---

GSE-class*Class "GSE": A class to represent gene set enrichment data*

---

**Description**

GSE is a class to represent gene set enrichment data and will be used in the `modelData` slot in the `gseModel` object. This class will store all of the information that pertains to performing gene set enrichment.

**Objects from the Class**

Objects can be created by calls of the form `new("GSE", ...)`.

**Slots**

**incidMat**: the incidence matrix that shows the relationship between the genes and the gene sets

**gTestStat**: the test statistic for the genes relationship with the phenotype

**gsTestStat**: the test statistic for the gene set

**expData**: the experimental data (here it will be of class `ExpressionSet`)

**descr**: a description of the gene set being studied

**Methods**

**incidMat<-** Sets the `incidMat` slot

**incidMat** Returns the `incidMat` slot

**gTestStat<-** Sets the `gTestStat` slot

**gTestStat** Returns the `gTestStat` slot

**gsTestStat<-** Sets the `gsTestStat` slot

**gsTestStat** Returns the `gsTestStat` slot

**expData<-** Sets the `expData` slot

**expData** Returns the `expData` slot

**descr<-** Sets the `descr` slot

**descr** Returns the `descr` slot

**Author(s)**

Elizabeth Whalen

**See Also**

[gseModel-class](#)

---

gseModel-class	<i>Class "gseModel": A class to represent a GSE model</i>
----------------	---

---

### Description

gseModel is a class to represent a gene set enrichment (GSE) model. This class inherits from the virtual class, gModel.

### Objects from the Class

Objects can be created by calls of the form `new("gseModel", ...)`. The initialize method for this class will be created in other packages that use this package (for example, the initialize method will be created in the iSNetwork package).

### Slots

**modelData:** the model data, which is an object of GSE

**linkData:** a list of functions that link this model to its parent and child models (if it has any)

**virtualData:** the data that is needed by the views of this object

**modelName:** the name of this model

**modelVar:** a list of variables that refer to the modelData (for instance this may be t-test values that were calculated from the modelData)

### Extends

Class "gModel", directly.

### Methods

No methods defined with class "gseModel" in the signature. The methods for this class will be created in other packages that use this package like iSNetwork.

### Author(s)

Elizabeth Whalen

### See Also

[GSE-class](#), [graphModel-class](#), [exprModel-class](#)

---

heatmapView-class	Class "heatmapView": A class to represent a heatmap view
-------------------	--

---

### Description

heatmapView is a class to represent a view that is a heatmap. heatmapView inherits from the class, plotView, which inherits from the virtual class, genView.

### Objects from the Class

Objects can be created by calls of the form `new("heatmapView", ...)`. The initialize method for this class will be created in other packages that use this package (for example, the initialize method will be created in the iSNetwork package).

### Slots

**ordering:** a list of information returned from the heatmap function  
**plotDevice:** the plot device number  
**plotPar:** the parameter list for the plot, see `par()`  
**drArea:** an object of class "GtkDrawingArea"  
**dataName:** a character string describing what data are shown in the view  
**win:** an object of class "GtkWindow" that holds the view  
**winNum:** a number that tells what number view this is (for example, the first view created will have `winNum=1`)  
**rNames:** the names of the rows to be included in the heatmap (this allows the original data to be subset in the view)

### Extends

Class "plotView", directly. Class "genView", by class "plotView".

### Methods

**ordering<-** Sets the ordering slot  
**ordering** Returns the ordering slot  
**rNames<-** Sets the rNames slot  
**rNames** Returns the rNames slot

### Author(s)

Elizabeth Whalen

# Index

## \* classes

- exprModel-class, 2
- graphModel-class, 3
- graphView-class, 4
- GSE-class, 5
- gseModel-class, 6
- heatmapView-class, 7

descr (GSE-class), 5

descr, GSE-method (GSE-class), 5

descr<- (GSE-class), 5

descr<-, GSE-method (GSE-class), 5

expData (GSE-class), 5

expData, GSE-method (GSE-class), 5

expData<- (GSE-class), 5

expData<-, GSE-method (GSE-class), 5

exprModel (exprModel-class), 2

exprModel-class, 2

graphModel (graphModel-class), 3

graphModel-class, 3

graphView (graphView-class), 4

graphView-class, 4

grLayout (graphView-class), 4

grLayout, graphView-method (graphView-class), 4

grLayout<- (graphView-class), 4

grLayout<-, graphView-method (graphView-class), 4

GSE (GSE-class), 5

GSE-class, 5

gseModel (gseModel-class), 6

gseModel-class, 6

gsTestStat (GSE-class), 5

gsTestStat, GSE-method (GSE-class), 5

gsTestStat<- (GSE-class), 5

gsTestStat<-, GSE-method (GSE-class), 5

gTestStat (GSE-class), 5

gTestStat, GSE-method (GSE-class), 5

gTestStat<- (GSE-class), 5

gTestStat<-, GSE-method (GSE-class), 5

heatmapView (heatmapView-class), 7

heatmapView-class, 7

incidMat (GSE-class), 5

incidMat, GSE-method (GSE-class), 5

incidMat<- (GSE-class), 5

incidMat<-, GSE-method (GSE-class), 5

ordering (heatmapView-class), 7

ordering, heatmapView-method (heatmapView-class), 7

ordering<- (heatmapView-class), 7

ordering<-, heatmapView-method (heatmapView-class), 7

rNames (heatmapView-class), 7

rNames, heatmapView-method (heatmapView-class), 7

rNames<- (heatmapView-class), 7

rNames<-, heatmapView-method (heatmapView-class), 7