

# Package ‘mcount’

October 13, 2022

**Type** Package

**Title** Marginalized Count Regression Models

**Version** 1.0.0

**Author** Zhengyang Zhou [aut, cre]

Dateng Li [aut]

David Huh [aut]

Eun-Young Mun [aut]

**Depends** R (>= 3.6)

**Maintainer** Zhengyang Zhou <zhengyang.zhou@unthsc.edu>

**Description** Implementation of marginalized models for zero-inflated count data. This package provides a tool to implement an estimation algorithm for the marginalized count models, which directly makes inference on the effect of each covariate on the marginal mean of the outcome. The method involves the marginalized zero-inflated Poisson model described in Long et al. (2014) <[doi:10.1002/sim.6293](https://doi.org/10.1002/sim.6293)>.

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**Imports** bbmle, stats

**NeedsCompilation** no

**RoxygenNote** 7.1.2

**Repository** CRAN

**Date/Publication** 2022-03-11 10:30:05 UTC

## R topics documented:

dat.pfi . . . . .	2
mzip . . . . .	2

**Index**

4

---

`dat.pfi`*Example Data*

---

### Description

A data set from White et al. (2008), which is also described in Mun et al. (2015, 2022)

### Usage

```
data(dat.pfi)
```

### Format

The data fram contains 194 rows and 5 columns:

**m0** the number of standard alcohol drinks consumed at baseline

**int\_PF** 1: received personalized feedback interventions (PFI); 0: did not receive PFI

**year\_new** 1: first-year college student; 0: otherwise

**race\_new** 1: white; 0: non-white

**y** the number of standard alcohol drinks consumed at post-intervention; the response variable

### References

Mun, E.-Y., Zhou, Z., Huh, D., Tan, L., Li, D., Tanner-Smith, E. E., Walters, S. T., & Larimer, M.E. (2022). Brief alcohol interventions are effective through six months: Findings from marginalized zero-inflated Poisson and negative binomial models in a two-step IPD meta-analysis. *Prevention Science*. (under review)

Mun, E. Y., De La Torre, J., Atkins, D. C., White, H. R., Ray, A. E., Kim, S. Y., ... & The Project INTEGRATE Team. (2015). Project INTEGRATE: An integrative study of brief alcohol interventions for college students. *Psychology of Addictive Behaviors*, 29(1), 34-48.

White, H. R., Mun, E.-Y., & Morgan, T. J. (2008). Do brief personalized feedback interventions work for mandated students or is it just getting caught that works? *Psychology of Addictive Behaviors*, 22 (1), 107–116. <https://doi.org/10.1037/0893-164X.22.1.107>.

---

`mzip`*Estimating marginalized zero-inflated Poisson model*

---

### Description

Function to estimate a marginalized zero-inflated Poisson model

## Usage

```
mzip(formula, data)
```

## Arguments

formula	an object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted. A typical formula has the form <code>response ~ terms</code> where <code>response</code> is the count response vector and <code>terms</code> is a series of terms that predict <code>response</code> . For example, <code>formula = y ~ x1 + x2 + x3</code> . Do not write <code>intercept</code> in the <code>formula</code> ; <code>intercept</code> will be automatically added in model fitting.
data	a data frame containing variables in the model.

## Details

Function returns an object of class "`mle2`" from **bbmle** R package. Apply `summary` function to the resulting object from the function to obtain more estimation information.

## Value

Suffix `_zero` corresponds to the parameters associated with the structural zero rate part of a model.

Suffix `_mean` corresponds to the parameters associated with the overall mean, which evaluate the effects of covariates on the overall mean.

## References

Long, D. L., Preisser, J. S., Herring, A. H., & Golin, C. E. (2014). A marginalized zero-inflated Poisson regression model with overall exposure effects. *Statistics in Medicine*, 33(29), 5151-5165.

## Examples

```
head(dat.pfi)

#Fit a marginalized zero-inflated Poisson model
res = mzip(formula = y ~ m0 + int_PF + year_new + race_new, data = dat.pfi)

#Obtain estimation results
bbmle::summary(res)
```

# Index

\* **datasets**

  dat.pfi, [2](#)

  dat.pfi, [2](#)

  mzip, [2](#)