

Package ‘packageDiff’

October 14, 2022

Title Compare R Package Differences

Version 0.1

Date 2019-12-31

Description It provides utility functions for investigating changes within R packages. The `pkgInfo()` function extracts package information such as exported and non-exported functions as well as their arguments. The `pkgDiff()` function compares this information for two versions of a package and creates a diff file viewable in a browser.

Imports `diffr, htmlwidgets`

License GPL (>= 2)

Depends R (>= 2.10)

URL <https://github.com/couthcommander/packageDiff>

Encoding UTF-8

RoxygenNote 6.1.1

NeedsCompilation no

Author Cole Beck [aut, cre] (<<https://orcid.org/0000-0002-6849-6255>>)

Maintainer Cole Beck <cole.beck@vumc.org>

Repository CRAN

Date/Publication 2020-01-16 11:30:02 UTC

R topics documented:

packageDiff-package	2
pkgDiff	3
pkgInfo	3
print.pkgInfo	4
unzipPackage	5

Index

6

packageDiff-package *Package Diff*

Description

It provides utility functions for investigating changes within R packages. The `pkgInfo` function extracts package information such as exported and non-exported functions as well as their arguments. The `pkgDiff` function compares this information for two versions of a package and creates a diff file viewable in a browser.

Details

This package is experimental. Please submit bugs to <https://github.com/couthcommander/packageDiff>.

Author(s)

Cole Beck <cole.beck@vumc.org>

Maintainer: Cole Beck <cole.beck@vumc.org>

See Also

Useful links:

- <https://github.com/couthcommander/packageDiff>

Examples

```
tar1 <- system.file("examples", "yaml_2.1.18.tar.gz", package = "packageDiff")
tar2 <- system.file("examples", "yaml_2.1.19.tar.gz", package = "packageDiff")
a <- pkgInfo(tar1)
b <- pkgInfo(tar2)
pkgDiff(a, b)

a <- pkgInfo('https://cran.r-project.org/src/contrib/Archive/yaml/yaml_2.1.18.tar.gz')
b <- pkgInfo('https://cran.r-project.org/src/contrib/Archive/yaml/yaml_2.1.19.tar.gz')
pkgDiff(a, b)
```

pkgDiff*Package Diff*

Description

This function compares version changes within packages.

Usage

```
pkgDiff(a, b, doc = TRUE, width = 80)
```

Arguments

- | | |
|-------|---------------------------------------|
| a | First package, a ‘pkgInfo’ object. |
| b | Second package, a ‘pkgInfo’ object. |
| doc | Include documentation in diff output. |
| width | Output width. |

Details

Generate diffs between package information.

Value

‘diffr’ object is open in browser

Examples

```
tar1 <- system.file("examples", "yaml_2.1.18.tar.gz", package = "packageDiff")
tar2 <- system.file("examples", "yaml_2.1.19.tar.gz", package = "packageDiff")
a <- pkgInfo(tar1)
b <- pkgInfo(tar2)
pkgDiff(a, b)
```

pkgInfo*Extract Package Information*

Description

This function extracts information from an R package.

Usage

```
pkgInfo(pkg, leaveRemains = FALSE)
```

Arguments

- pkg** The compressed (tar.gz) build file of an R package.
leaveRemains Keep decompressed package in temp directory.

Details

Generate package information from its build file.

Value

- | | |
|-------------------|--|
| Package | Package name |
| Version | Version number |
| Imports | Imported packages |
| Suggests | Suggested packages |
| ImportedFunctions | Functions imported from other packages |
| ExportedFunctions | Functions exported from package |
| AllFunctions | All defined functions |
| FormalArgs | Function arguments |
| Data | Dimension information on data sets |
| documentation | Full package documentation |

Examples

```
tarfile <- system.file("examples", "acepack_1.3-3.3.tar.gz", package = "packageDiff")
info <- pkgInfo(tarfile)

url <- 'https://cran.r-project.org/src/contrib/Archive/acepack/acepack_1.3-3.3.tar.gz'
info <- pkgInfo(url)
```

print.pkgInfo *Print Package Information*

Description

Print method for ‘packageInfo’ class.

Usage

```
## S3 method for class 'pkgInfo'
print(x, doc = FALSE, ...)
```

Arguments

- x A packageInfo object.
- doc Include documentation in output.
- ... Additional parameters, unused at this time.

Details

Print its argument and return it invisibly.

Examples

```
tarfile <- system.file("examples", "acepack_1.3-3.3.tar.gz", package = "packageDiff")
pkgInfo(tarfile)

url <- 'https://cran.r-project.org/src/contrib/Archive/acepack/acepack_1.3-3.3.tar.gz'
info <- pkgInfo(url)
print(info)
```

unzipPackage*Extract R Package*

Description

Untar an R package into a temp directory.

Usage

```
unzipPackage(x)
```

Arguments

- x The compressed (tar.gz) build file of an R package, either local or URL.

Value

List of files extracted.

Examples

```
tarfile <- system.file("examples", "acepack_1.3-3.3.tar.gz", package = "packageDiff")
info <- unzipPackage(tarfile)
```

Index

packageDiff (packageDiff-package), [2](#)

packageDiff-package, [2](#)

pkgDiff, [3](#)

pkgInfo, [3](#)

print.pkgInfo, [4](#)

unzipPackage, [5](#)