

Package ‘toastui’

April 3, 2025

Title Interactive Tables, Calendars and Charts for the Web

Version 0.4.0

Description Create interactive tables, calendars, charts and markdown WYSIWYG editor with 'TOAST UI' <<https://ui.toast.com/>> libraries to integrate in 'shiny' applications or 'rmarkdown' 'HTML' documents.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Depends R (>= 2.10)

Imports utils, htmlwidgets, htmltools, magrittr, phosphoricons, rlang, shiny (>= 1.1.0), shinyWidgets

Suggests apexcharter, bslib, knitr, rmarkdown, scales, tinytest

VignetteBuilder knitr

RoxygenNote 7.3.2

URL <https://dreamrs.github.io/toastui/>

BugReports <https://github.com/dreamRs/toastui/issues>

NeedsCompilation no

Author Victor Perrier [aut, cre, cph],
Fanny Meyer [aut],
NHN FE Development Lab [cph] (tui-grid, tui-calendar, tui-chart
libraries)

Maintainer Victor Perrier <victor.perrier@dreamrs.fr>

Repository CRAN

Date/Publication 2025-04-03 08:10:02 UTC

Contents

caes	3
cal-demo-data	4

calendar	4
calendar-proxy-navigate	6
calendar-proxy-schedule	8
calendar-shiny	10
calendar_properties	12
calendar_proxy	13
cal_events	14
cal_month_options	16
cal_props	17
cal_proxy_clear	18
cal_proxy_clear_selection	19
cal_proxy_options	20
cal_proxy_toggle	21
cal_proxy_view	23
cal_schedules	24
cal_template	25
cal_theme	26
cal_timezone	27
cal_week_options	29
chart	30
chart-shiny	32
chart_labs	33
chart_options	34
countries	34
datagrid	35
datagrid-shiny	38
datagrid-theme	39
datagrid_proxy	44
editor	45
editor-proxy-show-hide	46
editor-shiny	48
editor_proxy	49
editor_proxy_change_preview	50
editor_proxy_insert	52
grid-cell-style	53
grid-editor	56
grid-header	59
grid_click	61
grid_colorbar	62
grid_columns	64
grid_columns_opts	66
grid_col_button	67
grid_col_checkbox	69
grid_editor_date	71
grid_filters	73
grid_format	74
grid_proxy_add_row	76
grid_proxy_delete_row	77

grid_row_merge	79
grid_selection_cell	80
grid_selection_row	81
grid_sparkline	83
grid_style_column	84
grid_style_row	85
grid_summary	87
guess_colwidths_options	88
met_paris	89
navigation_options	89
ps3_games	91
rolling_stones_50	91
rolling_stones_500	92
schedules_properties	93
set_grid_lang	93
toastui	95
toastui-exports	95
validateOpts	96

Index**98**

caes	<i>Construct aesthetic mappings</i>
------	-------------------------------------

Description

Low-level version of `ggplot2::aes`.

Usage

```
caes(x, y, ...)
```

Arguments

`x, y, ...` List of name-value pairs in the form `aesthetic = variable`.

Value

a list of quosure.

Examples

```
caes(x = month, y = value)
caes(x = month, y = value, fill = city)
```

`cal-demo-data`*Calendar demo data***Description**

Create calendar demo data for schedules and properties

Usage

```
cal_demo_data(view = c("month", "week", "day"))

cal_demo_props()
```

Arguments

`view` Calendar view for which to use the data.

Value

a `data.frame`.

Examples

```
# Monthly schedule
cal_demo_data("month")

#' # Weekly schedule
cal_demo_data("week")
```

`calendar`*Create an interactive calendar***Description**

Build interactive calendar with the JavaScript tui-calendar library.

Usage

```
calendar(
  data = NULL,
  view = c("month", "week", "day"),
  defaultDate = NULL,
  useDetailPopup = TRUE,
  useCreationPopup = FALSE,
  isReadOnly = TRUE,
  navigation = FALSE,
```

```
navOpts = navigation_options(),
...,
width = NULL,
height = NULL,
elementId = NULL
)
```

Arguments

data	A <code>data.frame</code> with schedules data, see cal_demo_data() .
view	Default view of calendar. The default value is 'week', other possible values are 'month' and 'day'.
defaultDate	Default date for displaying calendar.
useDetailPopup	Logical. Display a pop-up on click with detailed informations about schedules.
useCreationPopup	Logical. Allow user to create schedules with a pop-up.
isReadOnly	Calendar is read-only mode and a user can't create and modify any schedule. The default value is true.
navigation	Add navigation buttons to go to previous or next period, or return to 'today'.
navOpts	Options to customize buttons (only if <code>navigation = TRUE</code>), see navigation_options() .
...	Additional arguments passed to JavaScript method.
width, height	A numeric input in pixels.
elementId	Use an explicit element ID for the widget.

Value

A calendar htmlwidget.

Note

`taskView` and `scheduleView` arguments have been moved to [cal_week_options\(\)](#).

See Also

[calendarOutput\(\) / renderCalendar\(\)](#) for usage in Shiny applications.

Examples

```
# Default: monthly view
calendar()

# Weekly view
calendar(view = "week")

# Or only day:
calendar(view = "day")
```

```

# Add navigation buttons
calendar(navigation = TRUE)

# Add schedules data
ex_data <- cal_demo_data()
calendar(ex_data)

# By default detail popup is activated
# you can click on a schedule to view detail
calendar(useDetailPopup = TRUE) %>%
  cal_schedules(
    title = "My schedule",
    body = "Some detail about it",
    start = format(Sys.Date(), "%Y-%m-03"),
    end = format(Sys.Date(), "%Y-%m-04"),
    category = "allday"
  )

# to disable it use useDetailPopup = FALSE

# You can use HTML tags inside it:
library(htmltools)
calendar(useDetailPopup = TRUE) %>%
  cal_schedules(
    title = "My schedule",
    body = doRenderTags(tags$div(
      tags$h3("Title for my schedule"),
      tags$p(
        "You can write", tags$em("custom"), tags$b("HTML"),
        "in a popup !"
      ),
      tags$p(
        style = "color: firebrick;",
        "For example write in red !"
      ),
      tags$ul(
        tags$li("Or make a bullet list!"),
        tags$li("With another item"),
        tags$li("And one more")
      )
    )),
    start = format(Sys.Date(), "%Y-%m-03"),
    end = format(Sys.Date(), "%Y-%m-04"),
    category = "allday"
  )

```

Description

Those functions allow to navigate in the calendar from the server in a Shiny application.

Usage

```
cal_proxy_next(proxy)
cal_proxy_prev(proxy)
cal_proxy_today(proxy)
cal_proxy_date(proxy, date)
```

Arguments

proxy	A calendar_proxy() htmlwidget object.
date	A specific date to navigate to.

Value

A calendar_proxy object.

See Also

Other calendar proxy methods: [cal_proxy_clear\(\)](#), [cal_proxy_clear_selection\(\)](#), [cal_proxy_options\(\)](#), [cal_proxy_toggle\(\)](#), [cal_proxy_view\(\)](#), [calendar-proxy-schedule](#), [calendar_proxy\(\)](#)

Examples

```
library(shiny)
library(toastui)

ui <- fluidPage(
  tags$h2("Navigate in calendar with actionButtons"),
  actionButton(
    inputId = "prev_date",
    label = "Previous",
    icon = icon("chevron-left")
  ),
  actionButton(
    inputId = "next_date",
    label = "Next",
    icon = icon("chevron-right")
  ),
  actionButton(
    inputId = "today",
    label = "Today"
  ),
  fluidRow(
    column(
      width = 9,
```

```

        calendarOutput(outputId = "my_calendar")
    ),
    column(
        width = 3,
        verbatimTextOutput("result")
    )
)
)

server <- function(input, output, session) {

    output$my_calendar <- renderCalendar({
        calendar()
    })

    output$result <- renderPrint({
        input$my_calendar_dates
    })

    observeEvent(input$prev_date, cal_proxy_prev("my_calendar"))
    observeEvent(input$next_date, cal_proxy_next("my_calendar"))
    observeEvent(input$today, cal_proxy_today("my_calendar"))

}

if (interactive())
    shinyApp(ui, server)

```

calendar-proxy-schedule*Create / Update / Delete schedule(s) with Proxy***Description**

These functions allow to create new schedule(s), update existing ones and delete schedule in a calendar within the server in a Shiny application.

Usage

```

cal_proxy_add(proxy, value)

cal_proxy_delete(proxy, value)

cal_proxy_update(proxy, value)

```

Arguments

proxy	A calendar_proxy() htmlwidget object.
value	A list with schedules data.

Value

A calendar_proxy object.

Note

Those functions are intended to be used with corresponding input value:

- `input$outputId$add`: triggered when a schedule is added on calendar via creation popup.
- `input$outputId$update`: triggered when an existing schedule is edited.
- `input$outputId$deleted`: triggered when a schedule is deleted.

See Also

Other calendar proxy methods: [cal_proxy_clear\(\)](#), [cal_proxy_clear_selection\(\)](#), [cal_proxy_options\(\)](#), [cal_proxy_toggle\(\)](#), [cal_proxy_view\(\)](#), [calendar-proxy-navigate](#), [calendar_proxy\(\)](#)

Examples

```
library(shiny)
library(toastui)

ui <- fluidPage(
  tags$h2("Add, Update and Delete schedule interactively"),

  tags$p(
    "Click on the calendar to create a new schedule",
    "then you will be able to edit or delete it."
  ),

  calendarOutput("my_calendar")
)

server <- function(input, output) {

  output$my_calendar <- renderCalendar({
    cal <- calendar(
      defaultDate = Sys.Date(),
      navigation = TRUE,
      isReadOnly = FALSE,
      useCreationPopup = TRUE
    )
  })

  observeEvent(input$my_calendar_add, {
    str(input$my_calendar_add)
    cal_proxy_add("my_calendar", input$my_calendar_add)
  })

  observeEvent(input$my_calendar_update, {
    str(input$my_calendar_update)
    cal_proxy_update("my_calendar", input$my_calendar_update)
  })
}
```

```

observeEvent(input$my_calendar_delete, {
  str(input$my_calendar_delete)
  cal_proxy_delete("my_calendar", input$my_calendar_delete)
})

if (interactive())
  shinyApp(ui = ui, server = server)

```

calendar-shiny *Shiny bindings for calendar()*

Description

Output and render functions for using [calendar\(\)](#) within Shiny applications and interactive Rmd documents.

Usage

```

calendarOutput(outputId, width = "100%", height = "600px")

renderCalendar(expr, env = parent.frame(), quoted = FALSE)

```

Arguments

<code>outputId</code>	Output variable to read from.
<code>width, height</code>	Must be a valid CSS unit (like 100%, 400px, auto) or a number, which will be coerced to a string and have px appended.
<code>expr</code>	An expression that generates a calendar
<code>env</code>	The environment in which to evaluate <code>expr</code> .
<code>quoted</code>	Is <code>expr</code> a quoted expression (with <code>quote()</code>)? This is useful if you want to save an expression in a variable.

Value

Output element that can be included in UI. Render function to create output in server.

Special inputs

The following `input` values will be accessible in the server:

- `input$outputId_add` : contain data about schedule added via the creation popup. Javascript event: `beforeCreateSchedule`.
- `input$outputId_schedules` : contain data about last schedule added. Javascript event: `afterRenderSchedule`.
- `input$outputId_click` : contain data about schedule user click on. Javascript event: `clickSchedule`.

- **input\$outputId_delete** : contain data about schedule deleted by user via creation popup.
Javascript event: beforeDeleteSchedule.
- **input\$outputId_update** : contain data about schedule updated by user via creation popup.
Javascript event: beforeUpdateSchedule.
- **input\$outputId_dates** : start and end date represented in the calendar.

To use them you need to replace outputId by the id you've used to create the calendar. If you use one of the above javascript event in `cal_events()`, the input won't be accessible.

Examples

```
library(shiny)
library(toastui)

ui <- fluidPage(
  tags$h2("calendar shiny example"),
  fluidRow(
    column(
      width = 8,
      calendarOutput("my_calendar")
    ),
    column(
      width = 4,
      tags$b("Dates:"), 
      verbatimTextOutput("dates"),
      tags$b("Clicked schedule:"), 
      verbatimTextOutput("click")
    )
  )
)

server <- function(input, output, session) {

  output$my_calendar <- renderCalendar({
    calendar(cal_demo_data(), navigation = TRUE) %>%
    cal_props(
      list(
        id = 1,
        name = "PERSO",
        color = "white",
        bgColor = "firebrick",
        borderColor = "firebrick"
      ),
      list(
        id = 2,
        name = "WORK",
        color = "white",
        bgColor = "forestgreen",
        borderColor = "forestgreen"
      )
    )
  })
}
```

```

output$dates <- renderPrint({
  input$my_calendar_dates
})

output$click <- renderPrint({
  input$my_calendar_click
})

}

if (interactive())
  shinyApp(ui, server)

```

`calendar_properties` *Calendar properties*

Description

This dataset contains properties that can be used to set calendars properties in `cal_props()`.

Usage

`calendar_properties`

Format

A `data.frame` with 6 rows and 3 variables:

Name Name of property

Type Type

Description Description

Source

Toast UI documentation (<https://nhn.github.io/tui.calendar/latest/CalendarInfo/>)

calendar_proxy	<i>Proxy for calendar htmlwidget</i>
----------------	--------------------------------------

Description

Proxy for calendar htmlwidget

Usage

```
calendar_proxy(shinyId, session = shiny::getDefaultReactiveDomain())
```

Arguments

- | | |
|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| shinyId | single-element character vector indicating the output ID of the chart to modify
(if invoked from a Shiny module, the namespace will be added automatically). |
| session | the Shiny session object to which the chart belongs; usually the default value
will suffice. |

Value

A calendar_proxy object.

See Also

Other calendar proxy methods: [cal_proxy_clear\(\)](#), [cal_proxy_clear_selection\(\)](#), [cal_proxy_options\(\)](#), [cal_proxy_toggle\(\)](#), [cal_proxy_view\(\)](#), [calendar-proxy-navigate](#), [calendar-proxy-schedule](#)

Examples

```
## Not run:  
  
# Consider having created a calendar widget with  
calendarOutput("my_calendar") # UI  
output$my_calendar <- renderCalendar({}) # Server  
  
# Then you can call proxy methods in observer:  
  
# set calendar proxy then call a cal_proxy_* function  
calendar_proxy("my_calendar") %>%  
  cal_proxy_today()  
  
# or directly  
cal_proxy_today("my_calendar")  
  
## End(Not run)
```

cal_events*Calendar custom JavaScript events*

Description

Currently only works in Shiny applications.

Usage

```
cal_events(
  cal,
  afterRenderSchedule = NULL,
  beforeCreateSchedule = NULL,
  beforeDeleteSchedule = NULL,
  beforeUpdateSchedule = NULL,
  clickDayname = NULL,
  clickMorecalendar = NULL,
  clickSchedule = NULL,
  clickTimezonesCollapseBtncalendar = NULL,
  selectDateTime = NULL
)
```

Arguments

cal	A calendar htmlwidget object.
afterRenderSchedule	Fire this event by every single schedule after rendering whole calendar.
beforeCreateSchedule	Fire this event when select time period in daily, weekly, monthly.
beforeDeleteSchedule	Fire this event when delete a schedule.
beforeUpdateSchedule	Fire this event when drag a schedule to change time in daily, weekly, monthly.
clickDayname	Fire this event when click a day name in weekly.
clickMorecalendar	Fire this event when click a schedule.
clickSchedule	Fire this event when click a schedule.
clickTimezonesCollapseBtncalendar	Fire this event by clicking timezones collapse button.
selectDateTime	Occurs when dragging and dropping a specific date or time then dropping.

Value

A calendar htmlwidget object.

Note

All arguments must be JavaScript function wrapped in `htmlwidgets::JS()`.

Examples

```
library(shiny)
library(toastui)

calendarProps <- data.frame(
  id = paste0("cal_", 1:3),
  name = c("TODO", "Meetings", "Tasks"),
  color = c("#FFF", "#FFF", "#000"),
  backgroundColor = c("#E41A1C", "#377EB8", "#4DAF4A"),
  borderColor = c("#a90000", "#005288", "#0a7f1c")
)

n <- 20
date_start <- sample(
  seq(from = as.POSIXct(Sys.Date()-14), by = "1 hour", length.out = 24*7*4),
  n, TRUE
)
date_end <- date_start + sample(1:25, n, TRUE) * 3600
schedules <- data.frame(
  id = paste0("event_", 1:n),
  calendarId = paste0("cal_", sample(1:3, n, TRUE)),
  title = LETTERS[1:n],
  body = paste("Body schedule", letters[1:n]),
  start = format(date_start, format = "%Y-%m-%d %H:00:00"),
  end = format(date_end, format = "%Y-%m-%d %H:00:00"),
  category = sample(c("allday", "time", "task"), n, TRUE),
  stringsAsFactors = FALSE
)

ui <- fluidPage(
  tags$h2("Custom click event"),
  fluidRow(
    column(
      width = 8,
      calendarOutput(outputId = "cal")
    ),
    column(
      width = 4,
      verbatimTextOutput(outputId = "res_click")
    )
  )
)

server <- function(input, output, session) {
  output$cal <- renderCalendar({
    calendar(useDetailPopup = FALSE) %>%
      cal_props(calendarProps) %>%

```

```

  cal_schedules(schedules) %>%
  cal_events(
    clickSchedule = JS("function(event) {Shiny.setInputValue('click', event)}")
  )
})

output$res_click <- renderPrint(input$click)

}

if (interactive())
shinyApp(ui, server)

```

cal_month_options *Calendar Month Options*

Description

Options for monthly view.

Usage

```

cal_month_options(
  cal,
  startDayOfWeek = NULL,
  daynames = NULL,
  narrowWeekend = NULL,
  visibleWeeksCount = NULL,
  isAlways6Week = NULL,
  workweek = NULL,
  visibleEventCount = NULL,
  ...
)

```

Arguments

<code>cal</code>	A calendar() object.
<code>startDayOfWeek</code>	Numeric. The start day of week.
<code>daynames</code>	Vector. The day names in monthly. Default values are 'Sun', 'Mon', 'Tue', 'Wed', 'Thu', 'Fri', 'Sat'
<code>narrowWeekend</code>	Logical. Make weekend column narrow(1/2 width).
<code>visibleWeeksCount</code>	Numeric. The visible week count in monthly(0 or null are same with 6).
<code>isAlways6Week</code>	Logical. Always show 6 weeks. If false, show 5 weeks or 6 weeks based on the month.
<code>workweek</code>	Logical. Show only 5 days except for weekend.

```
visibleEventCount  
    Numeric. The visible schedule count in monthly grid.  
...  
    Additional options.
```

Value

A calendar htmlwidget.

Note

Online JavaScript documentation: <https://github.com/nhn/tui.calendar/blob/main/docs/en/apis/options.md#month>

Examples

```
# Change option for monthly view  
calendar(view = "month") %>%  
  cal_month_options(  
    startDayOfWeek = 1,  
    daynames = c("Dim", "Lun", "Mar", "Mer", "Jeu", "Ven", "Sam"),  
    narrowWeekend = TRUE  
)
```

cal_props

Calendar properties

Description

Define calendar properties for grouping schedules under common theme.

Usage

```
cal_props(cal, ...)
```

Arguments

cal	A <code>calendar()</code> object.
...	Either named arguments to use as calendar properties or a <code>data.frame</code> with rows as calendars and columns as properties. See https://nhn.github.io/tui.calendar/latest/CalendarInfo/ for options.

Value

A calendar htmlwidget.

Examples

```
library(toastui)

# Define theme for schedules
calendar(cal_demo_data()[, -c(9, 10, 11)]) %>%
  cal_props(
    list(
      id = "1",
      name = "PERSO",
      color = "lightblue",
      backgroundColor = "purple",
      borderColor = "magenta"
    ),
    list(
      id = "2",
      name = "WORK",
      color = "red",
      backgroundColor = "yellow",
      borderColor = "orange"
    )
  )
```

cal_proxy_clear *Clear calendar with Proxy*

Description

This function allow to delete all schedules and clear view.

Usage

```
cal_proxy_clear(proxy)
```

Arguments

proxy A [calendar_proxy\(\)](#) htmlwidget object.

Value

A `calendar_proxy` object.

See Also

Other calendar proxy methods: [cal_proxy_clear_selection\(\)](#), [cal_proxy_options\(\)](#), [cal_proxy_toggle\(\)](#), [cal_proxy_view\(\)](#), [calendar-proxy-navigate](#), [calendar-proxy-schedule](#), [calendar_proxy\(\)](#)

Examples

```
library(shiny)
library(toastui)

ui <- fluidPage(
  tags$h2("Clear all schedules"),
  actionButton("clear", "Clear all", class = "btn-block btn-danger"),
  calendarOutput("my_calendar")
)

server <- function(input, output, session) {

  output$my_calendar <- renderCalendar({
    calendar(cal_demo_data(), navigation = FALSE)
  })

  observeEvent(input$clear, cal_proxy_clear("my_calendar"))
}

if (interactive())
  shinyApp(ui, server)
```

cal_proxy_clear_selection

Clear selection from calendar with Proxy

Description

Removes all date/time selection elements currently displayed in the calendar.

Usage

```
cal_proxy_clear_selection(proxy)
```

Arguments

proxy A [calendar_proxy\(\)](#) htmlwidget object.

Value

A calendar_proxy object.

See Also

Other calendar proxy methods: [cal_proxy_clear\(\)](#), [cal_proxy_options\(\)](#), [cal_proxy_toggle\(\)](#), [cal_proxy_view\(\)](#), [calendar-proxy-navigate](#), [calendar-proxy-schedule](#), [calendar_proxy\(\)](#)

`cal_proxy_options` *Set calendar's options with Proxy*

Description

This function allow to set options for a calendar.

Usage

```
cal_proxy_options(proxy, ...)
```

Arguments

<code>proxy</code>	A calendar_proxy() htmlwidget object.
<code>...</code>	Options for the calendar, you can use arguments from calendar() , cal_month_options() (under the form <code>month = list(...)</code>), cal_week_options() (under the form <code>week = list(...)</code>)

Value

A `calendar_proxy` object.

See Also

Other calendar proxy methods: [cal_proxy_clear\(\)](#), [cal_proxy_clear_selection\(\)](#), [cal_proxy_toggle\(\)](#), [cal_proxy_view\(\)](#), [calendar-proxy-navigate](#), [calendar-proxy-schedule](#), [calendar_proxy\(\)](#)

Examples

```
library(shiny)
library(toastui)

ui <- fluidPage(
  fluidRow(
    column(
      width = 4,
      checkboxInput(
        inputId = "narrowWeekend",
        label = "narrowWeekend ?",
        value = FALSE
      ),
      checkboxInput(
        inputId = "workweek",
        label = "workweek ?",
        value = FALSE
      )
    ),
    column(
      width = 8,
```

```

        calendarOutput("mycal")
    )
)
)

server <- function(input, output, session) {

  output$mycal <- renderCalendar({
    calendar(cal_demo_data(), view = "month")
  })

  observeEvent(input$narrowWeekend, {
    cal_proxy_options("mycal", month = list(narrowWeekend = input$narrowWeekend))
  })

  observeEvent(input$workweek, {
    cal_proxy_options("mycal", month = list(workweek = input$workweek))
  })
}

if (interactive())
  shinyApp(ui, server)

```

cal_proxy_toggle *Toggle schedules visibility with Proxy*

Description

This function allow to show or hide schedules based on their calendar's ID.

Usage

```
cal_proxy_toggle(proxy, calendarId, toHide = TRUE)
```

Arguments

proxy	A calendar_proxy() htmlwidget object.
calendarId	One or several calendar IDs to toggle.
toHide	Logical, show or hide schedules with provided calendar IDs.

Value

A [calendar_proxy](#) object.

See Also

Other calendar proxy methods: [cal_proxy_clear\(\)](#), [cal_proxy_clear_selection\(\)](#), [cal_proxy_options\(\)](#), [cal_proxy_view\(\)](#), [calendar-proxy-navigate](#), [calendar-proxy-schedule](#), [calendar_proxy\(\)](#)

Examples

```

library(shiny)
library(toastui)

ui <- fluidPage(
  fluidRow(
    column(
      width = 2,
      tags$h4("Checkbox logic :"),
      checkboxGroupInput(
        inputId = "calendarId",
        label = "Calendars to show:",
        choices = list(
          "Perso" = "1",
          "Work" = "2",
          "Courses" = "3"
        ),
        selected = 1:3
      ),
      tags$h4("Button logic :"),
      actionButton("cal_1", "Perso", class= "btn-block"),
      actionButton("cal_2", "Work", class= "btn-block"),
      actionButton("cal_3", "Courses", class= "btn-block")
    ),
    column(
      width = 10,
      tags$h2("Show / Hide schedules by calendarId"),
      calendarOutput(outputId = "cal"),
      uiOutput("ui")
    )
  )
)

server <- function(input, output, session) {

  output$cal <- renderCalendar({
    calendar(view = "month", taskView = TRUE, useDetailPopup = FALSE) %>%
      cal_props(cal_demo_props()) %>%
      cal_schedules(cal_demo_data())
  })

  # With checkbox
  observeEvent(input$calendarId, {
    cal_proxy_toggle("cal", input$calendarId, toHide = TRUE)
    cal_proxy_toggle("cal", setdiff(1:3, input$calendarId), toHide = FALSE)
  }, ignoreInit = TRUE, ignoreNULL = FALSE)

  # With buttons
  observeEvent(input$cal_1, {
    cal_proxy_toggle("cal", "1", toHide = input$cal_1 %% 2 == 1)
  }, ignoreInit = TRUE)
  observeEvent(input$cal_2, {

```

```

    cal_proxy_toggle("cal", "2", toHide = input$cal_2 %% 2 == 1)
}, ignoreInit = TRUE)
observeEvent(input$cal_3, {
  cal_proxy_toggle("cal", "3", toHide = input$cal_3 %% 2 == 1)
}, ignoreInit = TRUE)

}

if (interactive())
shinyApp(ui, server)

```

cal_proxy_view*Change calendar view with Proxy***Description**

This function allow to change the calendar view from the server in a Shiny application.

Usage

```
cal_proxy_view(proxy, view)
```

Arguments

proxy	A calendar_proxy() htmlwidget object.
view	The new view for the calendar: "day", "week" or "month".

Value

A [calendar_proxy](#) object.

See Also

Other calendar proxy methods: [cal_proxy_clear\(\)](#), [cal_proxy_clear_selection\(\)](#), [cal_proxy_options\(\)](#), [cal_proxy_toggle\(\)](#), [calendar-proxy-navigate](#), [calendar-proxy-schedule](#), [calendar_proxy\(\)](#)

Examples

```

library(shiny)

ui <- fluidPage(
  tags$h2("Change calendar view"),
  radioButtons(
    inputId = "view",
    label = "Change view:",
    choices = c("day", "week", "month"),
    inline = TRUE
),

```

```

    calendarOutput(outputId = "my_calendar")
  )

server <- function(input, output, session) {

  output$my_calendar <- renderCalendar({
    calendar(view = "day", scheduleView = "allday") %>%
      cal_schedules(
        title = "Today planning",
        start = Sys.Date(),
        end = Sys.Date(),
        category = "allday"
      )
  })
}

observeEvent(
  input$view,
  cal_proxy_view("my_calendar", input$view),
  ignoreInit = TRUE
)

}

if (interactive())
  shinyApp(ui, server)

```

cal_schedules *Add schedules to calendar*

Description

Add schedules to calendar

Usage

```
cal_schedules(cal, ...)
```

Arguments

- cal A calendar htmlwidget.
- ... Either named arguments to use as schedule properties or a data.frame with rows as schedules and columns as properties. See <https://nhn.github.io/tui.calendar/latest/EventObject/> for options.

Value

A calendar htmlwidget.

Examples

```
# Add schedule data from a data.frame
ex_data <- cal_demo_data()
calendar() %>%
  cal_schedules(ex_data)

# Or add item by item
calendar() %>%
  cal_schedules(
    title = "R - introduction",
    body = "What is R?",
    start = format(Sys.Date(), "%Y-%m-03 08:00:00"),
    end = format(Sys.Date(), "%Y-%m-03 12:00:00"),
    category = "time"
  ) %>%
  cal_schedules(
    title = "R - visualisation",
    body = "With ggplot2",
    start = format(Sys.Date(), "%Y-%m-05 08:00:00"),
    end = format(Sys.Date(), "%Y-%m-05 12:00:00"),
    category = "time"
  ) %>%
  cal_schedules(
    title = "Build first package",
    body = "Build first package",
    start = format(Sys.Date(), "%Y-%m-12"),
    end = format(Sys.Date(), "%Y-%m-18"),
    category = "allday"
  ) %>%
  cal_schedules(
    title = "Lunch",
    body = "With friends",
    start = format(Sys.Date(), "%Y-%m-15 12:00:00"),
    end = format(Sys.Date(), "%Y-%m-15 14:00:00"),
    category = "time"
  )
)
```

cal_template

Set template for a calendar

Description

Template JS functions to support customer renderer

Usage

```
cal_template(
```

```

    cal,
    milestoneTitle = NULL,
    taskTitle = NULL,
    alldayTitle = NULL,
    ...
)

```

Arguments

<code>cal</code>	A <code>calendar()</code> object.
<code>milestoneTitle</code>	The milestone title (at left column) template function.
<code>taskTitle</code>	The task title (at left column) template function.
<code>alldayTitle</code>	The allday title (at left column) template function.
<code>...</code>	Additionals arguments, see online documentation.

Value

A `calendar` htmlwidget object.

Note

Online JavaScript documentation: <https://github.com/nhn/tui.calendar/blob/main/docs/en/apis/template.md>. All arguments must be JavaScript function with `htmlwidgets::JS()`.

Examples

```

calendar(view = "week", taskView = TRUE) %>%
  cal_template(
    milestoneTitle = "TODO",
    taskTitle = "Assignment",
    alldayTitle = "Full-time"
  )

```

cal_theme

Calendar theme options

Description

Full configuration for theme. "common" prefix is for entire calendar. "common" properties can be overridden by "week", "month". "week" prefix is for weekly and daily view. "month" prefix is for monthly view.

Usage

```
cal_theme(cal, ..., .list = NULL)
```

Arguments

cal	A <code>calendar()</code> object.
...	Named arguments to customize appearance with CSS. See online documentation for full list of options.
.list	Alternative to ... for using a list.

Value

A calendar htmlwidget object.

Note

Online JavaScript documentation: <https://github.com/nhn/tui.calendar/blob/main/docs/en/apis/theme.md>

Examples

```
calendar(view = "month") %>%
  cal_theme(
    common.border = "2px solid #E5E9F0",
    month.dayname.borderLeft = "2px solid #E5E9F0",
    common.backgroundColor = "#2E3440",
    common.holiday.color = "#88C0D0",
    common.saturday.color = "#88C0D0",
    common.dayname.color = "#ECEFF4",
    common.today.color = "#333"
  )
```

cal_timezone

Calendar Timezone

Description

Set a custom time zone. You can add secondary timezone in the weekly/daily view.

Usage

```
cal_timezone(
  cal,
  timezoneName = NULL,
  displayLabel = NULL,
  tooltip = NULL,
  extra_zones = NULL,
  offsetCalculator = NULL
)
```

Arguments

<code>cal</code>	A <code>calendar()</code> object.
<code>timezoneName</code>	timezone name (time zone names of the IANA time zone database, such as 'Asia/Seoul', 'America/New_York'). Basically, it will calculate the offset using 'Intl.DateTimeFormat' with the value of the this property entered.
<code>displayLabel</code>	The display label of your timezone at weekly/daily view(e.g. 'GMT+09:00')
<code>tooltip</code>	The tooltip(e.g. 'Seoul')
<code>extra_zones</code>	A list with additional timezones to be shown in left timegrid of weekly/daily view.
<code>offsetCalculator</code>	Javascript function. If you define the 'offsetCalculator' property, the offset calculation is done with this function.

Value

A calendar htmlwidget.

Note

Online JavaScript documentation: <https://github.com/nhn/tui.calendar/blob/main/docs/en/apis/options.md#timezone>

Examples

```
library(toastui)
calendar(view = "week", defaultDate = "2021-06-18") %>%
  cal_schedules(
    title = "My schedule",
    start = "2021-06-18T10:00:00",
    end = "2021-06-18T17:00:00",
    category = "time"
  ) %>%
  # Set primary timezone and add secondary timezone
  cal_timezone(
    timezoneName = "Europe/Paris",
    displayLabel = "GMT+02:00",
    tooltip = "Paris",
    extra_zones = list(
      list(
        timezoneName = "Asia/Seoul",
        displayLabel = "GMT+09:00",
        tooltip = "Seoul"
      )
    )
  )
```

<code>cal_week_options</code>	<i>Calendar Week Options</i>
-------------------------------	------------------------------

Description

Options for daily, weekly view.

Usage

```
cal_week_options(
  cal,
  startDayOfWeek = NULL,
  daynames = NULL,
  narrowWeekend = NULL,
  workweek = NULL,
  showNowIndicator = NULL,
  showTimezoneCollapseButton = NULL,
  timezonesCollapsed = NULL,
  hourStart = NULL,
  hourEnd = NULL,
  eventView = TRUE,
  taskView = FALSE,
  collapseDuplicateEvents = NULL,
  ...
)
```

Arguments

<code>cal</code>	A <code>calendar()</code> object.
<code>startDayOfWeek</code>	Numeric. The start day of week.
<code>daynames</code>	Vector. The day names in weekly and daily. Default values are 'Sun', 'Mon', 'Tue', 'Wed', 'Thu', 'Fri', 'Sat'.
<code>narrowWeekend</code>	Logical. Make weekend column narrow(1/2 width).
<code>workweek</code>	Logical. Show only 5 days except for weekend.
<code>showNowIndicator</code>	Display or not the current time indicator in the weekly/daily view.
<code>showTimezoneCollapseButton</code>	Logical. Show a collapse button to close multiple timezones
<code>timezonesCollapsed</code>	Logical. An initial multiple timezones collapsed state.
<code>hourStart</code>	Numeric. Can limit of render hour start.
<code>hourEnd</code>	Numeric. Can limit of render hour end.
<code>eventView</code>	Show the all day and time grid in weekly, daily view. The default value is TRUE. If the value is a vector, it can be "allday", "time".

taskView Show the milestone and task in weekly, daily view. The default value is FALSE.
 If the value is a vector, it can be "milestone", "task".

collapseDuplicateEvents Collapse duplicate events in the daily/weekly view.

... Additional options.

Value

A calendar htmlwidget.

Note

Online JavaScript documentation: <https://github.com/nhn/tui.calendar/blob/main/docs/en/apis/options.md#week>

Examples

```
# Change option for weekly view
calendar(view = "week") %>%
  cal_week_options(
    startDayOfWeek = 1,
    daynames = c("Dim", "Lun", "Mar", "Mer", "Jeu", "Ven", "Sam"),
    narrowWeekend = TRUE
  )
```

Description

Interactive charts

Usage

```
chart(
  data = list(),
  mapping = NULL,
  type = c("column", "bar", "area", "line", "scatter", "bubble", "boxPlot", "heatmap",
          "treemap", "radialBar", "pie", "gauge"),
  ...,
  options = list(),
  height = NULL,
  width = NULL,
  elementId = NULL
)
```

Arguments

data	A <code>data.frame</code> if used with <code>mapping</code> otherwise a configuration list.
mapping	Default list of aesthetic mappings to use for chart if <code>data</code> is a <code>data.frame</code> .
type	Type of chart.
...	Optional arguments (currently not used).
options	A list of options for the chart.
height, width	Height and width for the chart.
elementId	An optional id.

Value

A chart `htmlwidget`.

See Also

[chartOutput\(\)](#) / [renderChart\(\)](#) for usage in Shiny applications.

Examples

```
library(toastui)

# Some data
mydata <- data.frame(
  month = month.name,
  value = sample(1:100, 12)
)

# Chart using mapping
chart(mydata, caes(x = month, y = value), type = "bar")

# Otherwise:
chart(
  data = list(
    categories = mydata$month,
    series = list(
      list(
        name = "Value",
        data = mydata$value
      )
    )
  ),
  options = list(
    chart = list(title = "My title"),
    legend = list(visible = FALSE)
  ),
  type = "column"
)
```

chart-shiny*Shiny bindings for chart()*

Description

Output and render functions for using [chart\(\)](#) within Shiny applications and interactive Rmd documents.

Usage

```
chartOutput(outputId, width = "100%", height = "400px")
```

```
renderChart(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

outputId	Output variable to read from.
width, height	Must be a valid CSS unit (like 100%, 400px, auto) or a number, which will be coerced to a string and have px appended.
expr	An expression that generates a calendar
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

Value

Output element that can be included in UI. Render function to create output in server.

Examples

```
library(toastui)
library(shiny)

ui <- fluidPage(
  fluidRow(
    column(
      width = 8, offset = 2,
      tags$h2("Chart example"),
      selectInput("var", "Variable:", names(dimnames(Titanic))),
      chartOutput("mychart1"),
      chartOutput("mychart2")
    )
  )
)

server <- function(input, output, session) {
  output$mychart1 <- renderChart({
```

```
Titanic %>%
  as.data.frame() %>%
  aggregate(as.formula(paste("Freq", input$var, sep = "~")), data = ., FUN = sum) %>%
  chart(caes(x = !as.symbol(input$var), y = Freq), type = "column")
})

output$mychart2 <- renderChart({
  req(input$var != "Survived")
  Titanic %>%
    as.data.frame() %>%
    aggregate(as.formula(paste("Freq ~ Survived", input$var, sep = "+")), data = ., FUN = sum) %>%
    chart(caes(x = !as.symbol(input$var), y = Freq, fill = Survived), type = "column")
})
}

if (interactive())
  shinyApp(ui, server)
```

chart_labs*Chart labs*

Description

Chart labs

Usage

```
chart_labs(.chart, title = NULL, x = NULL, y = NULL)
```

Arguments

.chart	A chart htmlwidget.
title	Text for main title.
x	Text for x-axis title.
y	Text for y-axis title.

Value

A chart htmlwidget.

Examples

```
chart(mtcars, caes(x = mpg, y = wt), type = "scatter") %>%
  chart_labs(
    title = "Main title",
    x = "X axis",
    y = "Y axis"
  )
```

`chart_options` *Chart options*

Description

Chart options

Usage

```
chart_options(.chart, ...)
```

Arguments

- .chart A chart htmlwidget.
- ... Named list of options, options depends on chart's type, see common options [here](#).

Value

A chart htmlwidget.

Examples

```
chart(mtcars, caes(x = mpg, y = wt), type = "scatter") %>%
  chart_options(
    chart = list(title = "A scatter chart")
  )
```

`countries` *Information on population, region, area size, infant mortality and more.*

Description

Data about countries of the world.

Usage

```
countries
```

Format

A `data.frame` with 227 rows and 20 variables:

```
Country    a character vector  
Region     a character vector  
Population  a numeric vector  
‘Area (sq. mi.)’ a numeric vector  
‘Pop. Density (per sq. mi.)’ a numeric vector  
‘Coastline (coast/area ratio)’ a numeric vector  
‘Net migration’ a numeric vector  
‘Infant mortality (per 1000 births)’ a numeric vector  
‘GDP ($ per capita)’ a numeric vector  
‘Literacy (%)’ a numeric vector  
‘Phones (per 1000)’ a numeric vector  
‘Arable (%)’ a numeric vector  
‘Crops (%)’ a numeric vector  
‘Other (%)’ a numeric vector  
Climate    a numeric vector  
Birthrate   a numeric vector  
Deathrate   a numeric vector  
Agriculture a numeric vector  
Industry    a numeric vector  
Service     a numeric vector
```

Source

fernandol on Kaggle (<https://www.kaggle.com/datasets/fernandol/countries-of-the-world/>)

Description

Create interactive tables : sortable, filterable, editable with the JavaScript library **tui-grid**.

Usage

```
datagrid(
  data = list(),
  ...,
  sortable = TRUE,
  pagination = NULL,
  filters = FALSE,
  colnames = NULL,
  colwidths = "fit",
  align = "auto",
  theme = c("clean", "striped", "default"),
  draggable = FALSE,
  data_as_input = FALSE,
  contextmenu = FALSE,
  datepicker_locale = NULL,
  guess_colwidths_opts = guess_colwidths_options(),
  width = NULL,
  height = NULL,
  elementId = NULL
)
```

Arguments

<code>data</code>	A <code>data.frame</code> or something convertible in <code>data.frame</code> .
<code>...</code>	Arguments passed to the Grid JavaScript method .
<code>sortable</code>	Logical, allow to sort columns.
<code>pagination</code>	Number of rows per page to display, default to <code>NULL</code> (no pagination).
<code>filters</code>	Logical, allow to filter columns.
<code>colnames</code>	Alternative colnames to be displayed in the header.
<code>colwidths</code>	Width for the columns, can be <code>"auto"</code> (width is determined by column's content) or a single or numeric vector to set the width in pixel. Use <code>NULL</code> to disable and use default behavior.
<code>align</code>	Alignment for columns content: <code>"auto"</code> (numeric and date on right, other on left), <code>"right"</code> , <code>"center"</code> or <code>"left"</code> . Use <code>NULL</code> to ignore.
<code>theme</code>	Predefined theme to be used.
<code>draggable</code>	Whether to enable to drag the row for changing the order of rows.
<code>data_as_input</code>	Should the data be available in an input <code>input\$<ID>_data</code> server-side?
<code>contextmenu</code>	Display or not a context menu when using right click in the grid. Can also be a list of custom options, see tui-grid documentation for examples.
<code>datepicker_locale</code>	Custome locale texts for datepicker editor, see example in grid_editor_date() .
<code>guess_colwidths_opts</code>	Options when <code>colwidths = "guess"</code> , see guess_colwidths_options() .
<code>width, height</code>	Width and height of the table in a CSS unit or a numeric.
<code>elementId</code>	Use an explicit element ID for the widget.

Value

A datagrid htmlwidget.

See Also

[datagridOutput\(\)](#) / [renderDatagrid\(\)](#) for usage in Shiny applications.

Examples

```
library(toastui)

# default usage
datagrid(rolling_stones_50)

# Column's width alternatives (default is "fit")
datagrid(rolling_stones_50, colwidths = "guess")
datagrid(rolling_stones_50, colwidths = "auto")
datagrid(rolling_stones_50, colwidths = NULL)

# disable sorting
datagrid(rolling_stones_50, sortable = FALSE)

# enable default filtering
datagrid(rolling_stones_50, filters = TRUE)

# enable pagination (10 rows per page)
datagrid(rolling_stones_50, pagination = 10)

# Themes
datagrid(rolling_stones_50, theme = "striped")
datagrid(rolling_stones_50, theme = "default")

# Empty table
datagrid(list())

# Empty columns
datagrid(data.frame(
  variable_1 = character(0),
  variable_2 = character(0)
))

# Specify colnames
datagrid(
  data = data.frame(
    variable_1 = sample(1:50, 12),
    variable_2 = month.name
  ),
  colnames = c("Number", "Month of the year")
)
```

datagrid-shiny*Shiny bindings for `datagrid()`*

Description

Output and render functions for using `datagrid()` within Shiny applications and interactive Rmd documents.

Usage

```
datagridOutput(outputId, width = "100%", height = "400px")

renderDatagrid(expr, env = parent.frame(), quoted = FALSE)

renderDatagrid2(expr, env = parent.frame(), quoted = FALSE)

datagridOutput2(outputId, width = "100%", height = "auto")
```

Arguments

<code>outputId</code>	Output variable to read from.
<code>width, height</code>	Must be a valid CSS unit (like 100%, 400px, auto) or a number, which will be coerced to a string and have px appended.
<code>expr</code>	An expression that generates a calendar
<code>env</code>	The environment in which to evaluate <code>expr</code> .
<code>quoted</code>	Is <code>expr</code> a quoted expression (with <code>quote()</code>)? This is useful if you want to save an expression in a variable.

Value

Output element that can be included in UI. Render function to create output in server.

Special inputs

The following `input` values will be accessible in the server:

- `input$outputId_data` : contain the data displayed in grid, only available when `datagrid(data_as_input = TRUE)` or when using `grid_editor()`
- `input$outputId_data_filtered` : contain the filtered data displayed in grid, only available when `datagrid(data_as_input = TRUE)` or when using `grid_editor()`
- `input$outputId_validation` : contain results of validation rules applied to data, only available when using validation argument in `grid_editor()`

These other inputs can be defined using other functions:

- *row selection*: giving row selected with checkboxes or radio buttons in `inputId` defined in `grid_selection_row()`

- *cell selection*: giving cell selected with mouse in `inputId` defined in `grid_selection_cell()`
- *cell clicked*: giving row index and column name of cell clicked in `inputId` defined in `grid_click()`

Examples

```
library(shiny)
library(toastui)

ui <- fluidPage(
  tags$h2("datagrid shiny example"),
  tabsetPanel(
    tabPanel(
      title = "Fixed height",
      datagridOutput("default"),
      tags$b("CHECK HEIGHT")
    ),
    tabPanel(
      title = "Full height",
      datagridOutput("fullheight", height = "auto"),
      tags$b("CHECK HEIGHT")
    ),
    tabPanel(
      title = "Pagination",
      datagridOutput("pagination", height = "auto"),
      tags$b("CHECK HEIGHT")
    )
  )
)

server <- function(input, output, session) {

  output$default <- renderDatagrid({
    datagrid(rolling_stones_500)
  })

  output$fullheight <- renderDatagrid({
    datagrid(rolling_stones_500, bodyHeight = "auto")
  })

  output$pagination <- renderDatagrid({
    datagrid(rolling_stones_500, pagination = 15)
  })

}

if (interactive())
  shinyApp(ui, server)
```

Description

Properties to customize grid theme, see full list here : <https://nhn.github.io/tui.grid/latest/Grid/>.

Usage

```
set_grid_theme(  
    selection.background = NULL,  
    selection.border = NULL,  
    scrollbar.border = NULL,  
    scrollbar.background = NULL,  
    scrollbar.emptySpace = NULL,  
    scrollbar.thumb = NULL,  
    scrollbar.active = NULL,  
    outline.border = NULL,  
    outline.showVerticalBorder = NULL,  
    frozenBorder.border = NULL,  
    area.header.border = NULL,  
    area.header.background = NULL,  
    area.body.background = NULL,  
    area.summary.border = NULL,  
    area.summary.background = NULL,  
    row.even.background = NULL,  
    row.even.text = NULL,  
    row.odd.background = NULL,  
    row.odd.text = NULL,  
    row.dummy.background = NULL,  
    row.hover.background = NULL,  
    cell.normal.background = NULL,  
    cell.normal.border = NULL,  
    cell.normal.text = NULL,  
    cell.normal.showVerticalBorder = NULL,  
    cell.normal.showHorizontalBorder = NULL,  
    cell.header.background = NULL,  
    cell.header.border = NULL,  
    cell.header.text = NULL,  
    cell.header.showVerticalBorder = NULL,  
    cell.header.showHorizontalBorder = NULL,  
    cell.rowHeader.background = NULL,  
    cell.rowHeader.border = NULL,  
    cell.rowHeader.text = NULL,  
    cell.rowHeader.showVerticalBorder = NULL,  
    cell.rowHeader.showHorizontalBorder = NULL,  
    cell.summary.background = NULL,  
    cell.summary.border = NULL,  
    cell.summary.text = NULL,  
    cell.summary.showVerticalBorder = NULL,  
    cell.summary.showHorizontalBorder = NULL,
```

```
    cell.selectedHeader.background = NULL,
    cell.selectedRowHeader.background = NULL,
    cell.focused.border = NULL,
    cell.focused.background = NULL,
    cell.focusedInactive.border = NULL,
    cell.required.background = NULL,
    cell.required.text = NULL,
    cell.editable.background = NULL,
    cell.editable.text = NULL,
    cell.disabled.background = NULL,
    cell.disabled.text = NULL,
    cell.invalid.background = NULL,
    cell.invalid.text = NULL
)
reset_grid_theme()
```

Arguments

selection.background	Background color of a selection layer.
selection.border	Border color of a selection layer.
scrollbar.border	Border color of scrollbars.
scrollbar.background	Background color of scrollbars.
scrollbar.emptySpace	Color of extra spaces except scrollbar.
scrollbar.thumb	Color of thumbs in scrollbars.
scrollbar.active	Color of arrows(for IE) or thumb:hover(for other browsers) in scrollbars.
outline.border	Color of the table outline.
outline.showVerticalBorder	Whether vertical outlines of the table are visible.
frozenBorder.border	Border color of a frozen border.
area.header.border	Border color of the header area in the table.
area.header.background	Background color of the header area in the table.
area.body.background	Background color of the body area in the table.
area.summary.border	Border color of the summary area in the table.

```
area.summary.background
    Background color of the summary area in the table.
row.even.background
    background color of even row.
row.even.text  text color of even row.
row.odd.background
    background color of cells in odd row.
row.odd.text   text color of odd row.
row.dummy.background
    background color of dummy row.
row.hover.background
    background color of hovered row.
cell.normal.background
    Background color of normal cells.
cell.normal.border
    Border color of normal cells.
cell.normal.text
    Text color of normal cells.
cell.normal.showVerticalBorder
    Whether vertical borders of normal cells are visible.
cell.normal.showHorizontalBorder
    Whether horizontal borders of normal cells are visible.
cell.header.background
    Background color of header cells.
cell.header.border
    border color of header cells.
cell.header.text
    text color of header cells.
cell.header.showVerticalBorder
    Whether vertical borders of header cells are visible.
cell.header.showHorizontalBorder
    Whether horizontal borders of header cells are visible.
cell.rowHeader.background
    Background color of row's header cells.
cell.rowHeader.border
    border color of row's header cells.
cell.rowHeader.text
    text color of row's header cells.
cell.rowHeader.showVerticalBorder
    Whether vertical borders of row's header cells are visible.
cell.rowHeader.showHorizontalBorder
    Whether horizontal borders of row's header cells are visible.
cell.summary.background
    Background color of cells in the summary area.
cell.summary.border
    border color of cells in the summary area.
```

```
cell.summary.text
    text color of cells in the summary area.
cell.summary.showVerticalBorder
    Whether vertical borders of cells in the summary area are visible.
cell.summary.showHorizontalBorder
    Whether horizontal borders of cells in the summary area are visible.
cell.selectedHeader.background
    background color of selected header cells.
cell.selectedRowHeader.background
    background color of selected row's head cells.
cell.focused.border
    border color of a focused cell.
cell.focused.background
    background color of a focused cell.
cell.focusedInactive.border
    border color of a inactive focus cell.
cell.required.background
    background color of required cells.
cell.required.text
    text color of required cells.
cell.editable.background
    background color of the editable cells.
cell.editable.text
    text color of the selected editable cells.
cell.disabled.background
    background color of disabled cells.
cell.disabled.text
    text color of disabled cells.
cell.invalid.background
    background color of invalid cells.
cell.invalid.text
    text color of invalid cells.
```

Value

No return value.

Examples

```
library(toastui)

# Default is "clean" theme
datagrid(rolling_stones_50)

# others builtins themes
datagrid(rolling_stones_50, theme = "striped")
datagrid(rolling_stones_50, theme = "default")
```

```
# Set global theme options
set_grid_theme(
  row.even.background = "#ddeb7",
  cell.normal.border = "#9bc2e6",
  cell.normal.showVerticalBorder = TRUE,
  cell.normal.showHorizontalBorder = TRUE,
  cell.header.background = "#5b9bd5",
  cell.header.text = "#FFF",
  cell.selectedHeader.background = "#013ADF",
  cell.focused.border = "#013ADF"
)
datagrid(rolling_stones_50)

# Remove theme
reset_grid_theme()
```

datagrid_proxy	<i>Proxy for datagrid htmlwidget</i>
----------------	--------------------------------------

Description

Proxy for datagrid htmlwidget

Usage

```
datagrid_proxy(shinyId, session = shiny::getDefaultReactiveDomain())
```

Arguments

shinyId	single-element character vector indicating the output ID of the chart to modify (if invoked from a Shiny module, the namespace will be added automatically).
session	the Shiny session object to which the chart belongs; usually the default value will suffice.

Value

A `datagrid_proxy` object.

See Also

Other datagrid proxy methods: [grid_proxy_add_row\(\)](#), [grid_proxy_delete_row\(\)](#)

Examples

```
## Not run:

# Consider having created adatagrid widget with
datagridOutput("my_grid") # UI
output$my_grid <- renderDatagrid({}) # Server

# Then you can call proxy methods in observer:

# set datagrid proxy then call a cal_proxy_* function
datagrid_proxy("my_grid") %>%
  datagrid_proxy_addrow(mydata)

# or directly
datagrid_proxy_addrow("my_grid", mydata)

## End(Not run)
```

editor

Create an interactive editor

Description

Create an interactive editor

Usage

```
editor(
  ...,
  getMarkdownOnChange = TRUE,
  getHTMLOnChange = TRUE,
  width = NULL,
  height = NULL,
  elementId = NULL
)
```

Arguments

... Options for the editor, see examples or [online reference](#).
getMarkdownOnChange, getHTMLOnChange
Get editor's content in Shiny application through an input value : `input$<outputId>_(markdown|html)`.
height, width Height and width for the chart.
elementId An optional id.

Value

An editor htmlwidget.

Examples

```
# Default is markdown editor with tab to switch to preview
editor()
# equivalent to
editor(previewStyle = "tab")
# Show preview side by side
editor(previewStyle = "vertical")

# Default edit type is markdown
editor(initialEditType = "markdown")
# Change to wysiwyg and remove switch mode option
editor(initialEditType = "wysiwyg", hideModeSwitch = TRUE)

# i18n : change language
editor(language = "fr")
editor(language = "ar")
# see https://github.com/nhn/tui.editor/blob/master/docs/en/i18n.md for other supported languages
```

editor-proxy-show-hide

Show/hide an editor

Description

Show/hide an editor

Usage

```
editor_proxy_show(proxy)
editor_proxy_hide(proxy)
```

Arguments

proxy A `editor_proxy()` htmlwidget object.

Value

A `editor_proxy` object.

See Also

Other editor proxy methods: `editor_proxy()`, `editor_proxy_change_preview()`, `editor_proxy_insert()`

Examples

```
library(shiny)
library(toastui)

ui <- fluidPage(
  tags$h2("Use editor's proxy"),
  fluidRow(
    column(
      width = 4,
      radioButtons(
        inputId = "changePreviewStyle",
        label = "change preview style",
        choices = c("tab", "vertical")
      ),
      checkboxInput(
        inputId = "showhide",
        label = "Show/hide editor",
        value = TRUE
      ),
     textInput(
        inputId = "text",
        label = "Text to insert:",
        width = "100%"
      ),
      actionButton("insert", "Insert text")
    ),
    column(
      width = 8,
      editorOutput("my_editor")
    )
  )
)

server <- function(input, output, session) {

  output$my_editor <- renderEditor({
    editor()
  })

  observeEvent(input$changePreviewStyle, {
    editor_proxy_change_preview("my_editor", input$changePreviewStyle)
  }, ignoreInit = TRUE)

  observeEvent(input$showhide, {
    if (input$showhide) {
      editor_proxy_show("my_editor")
    } else {
      editor_proxy_hide("my_editor")
    }
  }, ignoreInit = TRUE)

  observeEvent(input$insert, {
```

```

    editor_proxy_insert("my_editor", text = input$text)
  })
}

if (interactive())
  shinyApp(ui, server)

```

editor-shiny

Shiny bindings for editor()

Description

Output and render functions for using [editor\(\)](#) within Shiny applications and interactive Rmd documents.

Usage

```

editorOutput(outputId, width = "100%", height = "600px")

renderEditor(expr, env = parent.frame(), quoted = FALSE)

```

Arguments

outputId	Output variable to read from.
width, height	Must be a valid CSS unit (like 100%, 400px, auto) or a number, which will be coerced to a string and have px appended.
expr	An expression that generates a calendar
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

Value

Output element that can be included in UI. Render function to create output in server.

Examples

```

library(shiny)
library(toastui)

ui <- fluidPage(
  tags$h2("editor shiny example"),
  tabsetPanel(
    tabPanel(
      title = "Default",
      editorOutput("default"),
      tags$b("CHECK HEIGHT")
    )
  )
)

```

```
),
tabPanel(
  title = "WYSIWYG",
  editorOutput("wysiwyg"),
  tags$b("CHECK HEIGHT")
),
tabPanel(
  title = "Vertical",
  editorOutput("vertical"),
  tags$b("CHECK HEIGHT")
)
)
)

server <- function(input, output, session) {

  output$default <- renderEditor({
    editor(minHeight = "400px")
  })

  output$wysiwyg <- renderEditor({
    editor(initialEditType = "wysiwyg", hideModeSwitch = TRUE)
  })

  output$vertical <- renderEditor({
    editor(previewStyle = "vertical")
  })

}

if (interactive())
  shinyApp(ui, server)
```

editor_proxy

Proxy for editor htmlwidget

Description

Proxy for editor htmlwidget

Usage

```
editor_proxy(shinyId, session = shiny::getDefaultReactiveDomain())
```

Arguments

shinyId	single-element character vector indicating the output ID of the chart to modify (if invoked from a Shiny module, the namespace will be added automatically).
session	the Shiny session object to which the chart belongs; usually the default value will suffice.

Value

A `editor_proxy` object.

See Also

Other editor proxy methods: `editor-proxy-show-hide`, `editor_proxy_change_preview()`, `editor_proxy_insert()`

Examples

```
## Not run:

# Consider having created a editor widget with
editorOutput("my_editor") # UI
output$my_editor <- renderEditor({}) # Server

# Then you can call proxy methods in observer:

# set editor proxy then call a cal_proxy_* function
editor_proxy("my_editor") %>%
  cal_proxy_today()

# or directly
cal_proxy_today("my_editor")

## End(Not run)
```

editor_proxy_change_preview

Change editor's preview style

Description

Change editor's preview style

Usage

```
editor_proxy_change_preview(proxy, style = c("tab", "vertical"))
```

Arguments

proxy	A <code>editor_proxy()</code> or outputId of the editor
style	Style for the editor : 'tab' or 'vertical'.

Value

A `editor_proxy` object.

See Also

Other editor proxy methods: [editor-proxy-show-hide](#), [editor_proxy\(\)](#), [editor_proxy_insert\(\)](#)

Examples

```
library(shiny)
library(toastui)

ui <- fluidPage(
  tags$h2("Use editor's proxy"),
  fluidRow(
    column(
      width = 4,
      radioButtons(
        inputId = "changePreviewStyle",
        label = "change preview style",
        choices = c("tab", "vertical")
      ),
      checkboxInput(
        inputId = "showhide",
        label = "Show/hide editor",
        value = TRUE
      ),
      textInput(
        inputId = "text",
        label = "Text to insert:",
        width = "100%"
      ),
      actionButton("insert", "Insert text")
    ),
    column(
      width = 8,
      editorOutput("my_editor")
    )
  )
)

server <- function(input, output, session) {

  output$my_editor <- renderEditor({
    editor()
  })

  observeEvent(input$changePreviewStyle, {
    editor_proxy_change_preview("my_editor", input$changePreviewStyle)
  }, ignoreInit = TRUE)

  observeEvent(input$showhide, {
    if (input$showhide) {
      editor_proxy_show("my_editor")
    } else {
      editor_proxy_hide("my_editor")
    }
  })
}
```

```

        }
    }, ignoreInit = TRUE)

observeEvent(input$insert, {
  editor_proxy_insert("my_editor", text = input$text)
})

if (interactive())
  shinyApp(ui, server)

```

`editor_proxy_insert` *Insert text in an editor*

Description

Insert text in an editor

Usage

```
editor_proxy_insert(proxy, text)
```

Arguments

proxy	A <code>editor_proxy()</code> or <code>outputId</code> of the editor
text	Text to insert.

Value

A `editor_proxy` object.

See Also

Other editor proxy methods: `editor-proxy-show-hide`, `editor_proxy()`, `editor_proxy_change_preview()`

Examples

```

library(shiny)
library(toastui)

ui <- fluidPage(
  tags$h2("Use editor's proxy"),
  fluidRow(
    column(
      width = 4,
      radioButtons(
        inputId = "changePreviewStyle",
        label = "change preview style",

```

```
choices = c("tab", "vertical")
),
checkboxInput(
  inputId = "showhide",
  label = "Show/hide editor",
  value = TRUE
),
textInput(
  inputId = "text",
  label = "Text to insert:",
  width = "100%"
),
actionButton("insert", "Insert text")
),
column(
  width = 8,
  editorOutput("my_editor")
)
)
)
)

server <- function(input, output, session) {

  output$my_editor <- renderEditor({
    editor()
  })

  observeEvent(input$changePreviewStyle, {
    editor_proxy_change_preview("my_editor", input$changePreviewStyle)
  }, ignoreInit = TRUE)

  observeEvent(input$showhide, {
    if (input$showhide) {
      editor_proxy_show("my_editor")
    } else {
      editor_proxy_hide("my_editor")
    }
  }, ignoreInit = TRUE)

  observeEvent(input$insert, {
    editor_proxy_insert("my_editor", text = input$text)
  })
}

if (interactive())
  shinyApp(ui, server)
```

Description

Customize cell(s) appearance with CSS according to an expression in the data used in the grid.

Usage

```
grid_style_cell(
  grid,
  expr,
  column,
  background = NULL,
  color = NULL,
  fontWeight = NULL,
  ...,
  class = NULL,
  cssProperties = NULL
)

grid_style_cells(
  grid,
  fun,
  columns,
  background = NULL,
  color = NULL,
  ...,
  class = NULL,
  cssProperties = NULL
)
```

Arguments

<code>grid</code>	A grid created with datagrid() .
<code>expr</code>	An expression giving position of row. Must return a logical vector.
<code>column</code>	Name of column (variable name) where to apply style.
<code>background</code>	Background color.
<code>color</code>	Text color.
<code>fontWeight</code>	Font weight, you can use "bold" for example.
<code>...</code>	Other CSS properties.
<code>class</code>	CSS class to apply to the row.
<code>cssProperties</code>	Alternative to specify CSS properties with a named list.
<code>fun</code>	Function to apply to <code>columns</code> to identify rows to style.
<code>columns</code>	Columns names to use with <code>fun</code> .

Value

A datagrid htmlwidget.

Examples

```
library(toastui)

datagrid(mtcars) %>%
  grid_style_cell(
    mpg > 19,
    column = "mpg",
    background = "#F781BE",
    fontWeight = "bold"
  )

datagrid(mtcars) %>%
  grid_style_cell(
    vs == 0,
    column = "vs",
    background = "#E41A1C80",
    color = "#FFF"
  ) %>%
  grid_style_cell(
    vs == 1,
    column = "vs",
    background = "#377EB880"
  )

# Use rlang to use character
library(rlang)
my_var <- "disp"
datagrid(mtcars) %>%
  grid_style_cell(
    !isym(my_var) > 180,
    column = "disp",
    background = "#F781BE"
  )

# Style multiple columns

cor_longley <- as.data.frame(cor(longley))
cor_longley$Var <- row.names(cor_longley)
vars <- c("GNP.deflator", "GNP",
         "Unemployed", "Armed.Forces",
         "Population", "Year", "Employed")
datagrid(cor_longley[, c("Var", vars)]) %>%
  grid_style_cells(
    fun = ~ . > 0.9,
    columns = vars,
    background = "#053061",
    color = "#FFF"
```

```
) %>%
grid_style_cells(
  fun = ~ . > 0 & . <= 0.9,
  columns = vars,
  background = "#539dc8",
  color = "#FFF"
) %>%
grid_style_cells(
  fun = ~ . < 0,
  columns = vars,
  background = "#b51f2e",
  color = "#FFF"
)
```

grid-editor*Grid editor for columns***Description**

Allow to edit content of columns with different inputs, then retrieve value server-side in shiny application with `input$<outputId>_data`.

Usage

```
grid_editor(
  grid,
  column,
  type = c("text", "number", "checkbox", "select", "radio", "password"),
  choices = NULL,
  validation = validateOpts(),
  useListItemText = FALSE
)

grid_editor_opts(
  grid,
  editingEvent = c("dblclick", "click"),
  actionBarId = NULL,
  session = shiny::getDefaultReactiveDomain()
)
```

Arguments

<code>grid</code>	A table created with datagrid() .
<code>column</code>	Column for which to activate the editable content.
<code>type</code>	Type of editor: "text", "number", "checkbox", "select", "radio" or "password".
<code>choices</code>	Vector of choices, required for "checkbox", "select" and "radio" type.
<code>validation</code>	Rules to validate content edited, see validateOpts() .

useListItemText	If choices contains special characters (spaces, punctuation, ...) set this option to TRUE, you'll have to encode data in column to numeric as character (e.g. "1", "2", ...).
editingEvent	If set to "click", editable cell in the view-mode will be changed to edit-mode by a single click.
actionButtonId	Use an actionButton inputId to send edited data to the server only when this button is clicked. This allows not to send all the changes made by the user to the server.
session	Shiny session.

Value

A datagrid htmlwidget.

See Also

[grid_editor_date](#) for a date picker.

Examples

```
library(toastui)
library(shiny)

ui <- fluidPage(
  tags$h2("Edit grid demo"),
  fluidRow(
    column(
      width = 6,
      tags$p(
        "Each time you modify the grid, data is send to server"
      ),
      datagridOutput("grid1"),
      verbatimTextOutput("edited1")
    ),
    column(
      width = 6,
      tags$p(
        "Modify the grid, then click button to send data to server"
      ),
      datagridOutput("grid2"),
      actionButton(
        inputId = "update2",
        label = "Update edited data",
        class = "btn-block"
      ),
      verbatimTextOutput("edited2")
    )
  )
)
```

```

server <- function(input, output, session) {

  # Use same grid twice
  editdata <- data.frame(
    character = month.name,
    select = month.name,
    checkbox = month.abb,
    radio = month.name
  )
  editgrid <- datagrid(editdata) %>%
    grid_editor(
      column = "character",
      type = "text"
    ) %>%
    grid_editor(
      column = "select",
      type = "select",
      choices = month.name
    ) %>%
    grid_editor(
      column = "checkbox",
      type = "checkbox",
      choices = month.abb
    ) %>%
    grid_editor(
      column = "radio",
      type = "radio",
      choices = month.name
    )

  output$grid1 <- renderDatagrid({
    editgrid
  })

  output$edited1 <- renderPrint({
    input$grid1_data
  })

  output$grid2 <- renderDatagrid({
    editgrid %>%
      grid_editor_opts(
        actionBarId = "update2"
      )
  })

  output$edited2 <- renderPrint({
    input$grid2_data
  })

}

if (interactive())
  shinyApp(ui, server)

```

grid-header	<i>Header options</i>
-------------	-----------------------

Description

Properties to modify grid's header, like creating grouped header.

Usage

```
grid_header(  
  grid,  
  complexColumns = NULL,  
  columns = NULL,  
  align = NULL,  
  valign = NULL,  
  height = NULL  
)  
  
grid_complex_header(grid, ..., height = 80)
```

Arguments

grid	A table created with datagrid() .
complexColumns	list. This option creates new parent headers of the multiple columns which includes the headers of specified columns, and sets up the hierarchy.
columns	list. Options for column's header.
align	Horizontal alignment of the header content. Available values are 'left', 'center', 'right'.
valign	Vertical alignment of the row header content. Available values are 'top', 'middle', 'bottom'.
height	Numeric. The height of the header area.
...	Named arguments to merge columns under a common header, e.g. newcol = c("col1", "col2").

Value

A datagrid htmlwidget.

Examples

```
library(toastui)  
  
datagrid(rolling_stones_50) %>%  
  grid_header(  
    align = "left",  
    height = "150px"
```

```
)  
  
# Create columns groups  
datagrid(iris) %>%  
  grid_complex_header(  
    "Sepal" = c("Sepal.Length", "Sepal.Width"),  
    "Petal" = c("Petal.Length", "Petal.Width")  
)  
  
# or use the full form to use more options  
datagrid(iris) %>%  
  grid_columns(  
    columns = c("Petal.Length", "Petal.Width"),  
    header = c("Length", "Width")  
) %>%  
  grid_header(  
    complexColumns = list(  
      list(  
        header = "Sepal",  
        name = "Sepal",  
        hideChildHeaders = TRUE,  
        resizable = TRUE,  
        childNames = c("Sepal.Length", "Sepal.Width")  
      ),  
      list(  
        header = "Petal",  
        name = "Petal",  
        childNames = c("Petal.Length", "Petal.Width")  
      )  
    ),  
    height = 80,  
    valign = "middle"  
)  
  
# Custom HTML in header  
# (not that sorting is incompatible with)  
library(htmltools)  
datagrid(mtcars) %>%  
  grid_columns(  
    columns = "mpg",  
    minWidth = 120,  
    header = tags$div(  
      tags$b("Miles/(US) gallon"),  
      tags$br(),  
      tags$i("numeric")  
    )  
) %>%  
  grid_header(  
    columns = list(  
      list(  
        header = "Miles/(US) gallon",  
        width = 120  
      )  
    )  
  )
```

```
    name = "mpg",
    align = "left",
    renderer = JS("DatagridColumnHeaderHTML")
)
)
)
```

grid_click*Click event (in shiny)*

Description

Click event (in shiny)

Usage

```
grid_click(grid, inputId)
```

Arguments

grid	A table created with datagrid() .
inputId	The <code>input</code> slot that will be used to access the value.

Value

A `datagrid` htmlwidget.

Examples

```
if (interactive()) {
  library(shiny)
  library(toastui)

  ui <- fluidPage(
    tags$h2("datagrid click"),
    datagridOutput("grid"),
    verbatimTextOutput("res")
  )

  server <- function(input, output, session) {

    df <- data.frame(
      index = 1:12,
      month = month.name,
      letters = letters[1:12]
    )

    output$grid <- renderDatagrid({
```

```

datagrid(df) %>%
  grid_click(
    inputId = "click"
  )
})

output$res <- renderPrint({
  input$click
})
}

shinyApp(ui, server)
}

```

grid_colorbar*Style cells with a color bar***Description**

Style cells with a color bar

Usage

```

grid_colorbar(
  grid,
  column,
  bar_bg = "#5E81AC",
  color = "#ECEFF4",
  background = "#ECEFF4",
  from = NULL,
  prefix = NULL,
  suffix = NULL,
  label_outside = FALSE,
  label_width = "20px",
  border_radius = "0px",
  height = "16px",
  align = c("left", "center", "right")
)

```

Arguments

<code>grid</code>	A grid created with datagrid() .
<code>column</code>	The name of the column where to create a color bar.
<code>bar_bg</code>	Background color of the color bar.
<code>color</code>	Color of the text.
<code>background</code>	Background of the cell.
<code>from</code>	Range of values of the variable to represent as a color bar.

prefix, suffix	String to put in front of or after the value.
label_outside	Show label outside of the color bar.
label_width	Width of label in case it's displayed outside the color bar.
border_radius	Border radius of color bar.
height	Height in pixel of color bar.
align	Alignment of label if it is displayed inside the color bar.

Value

A datagrid htmlwidget.

Examples

```
library(toastui)

dat <- rolling_stones_50[, "Artist", drop = FALSE]
dat$percentage <- sample(1:100, size = 50, replace = TRUE)
dat$numeric <- sample(1:1500, size = 50, replace = TRUE)

datagrid(dat) %>%
  grid_colorbar(
    column = "percentage"
  )

datagrid(dat) %>%
  grid_colorbar(
    column = "percentage",
    label_outside = TRUE
  )

# More options
datagrid(dat) %>%
  grid_colorbar(
    column = "percentage",
    from = c(0, 100),
    suffix = "%"
  ) %>%
  grid_colorbar(
    column = "numeric",
    bar_bg = "#BF616A",
    from = c(0, 1500),
    prefix = "$",
    height = "20px"
  )

data.frame(
  rn = rownames(mtcars),
  mpg = mtcars$mpg,
  check.names = FALSE
) %>%
```

```
datagrid(colnames = c("Automobile", "Miles/(US) gallon")) %>%
  grid_colorbar(
    column = "mpg",
    bar_bg = ifelse(mtcars$mpg > mean(mtcars$mpg), "#5cb85c", "#BF616A"),
    label_outside = TRUE,
    label_width = "25px"
  )
```

grid_columns*Set columns options***Description**

Set options for one or several specific column.

Usage

```
grid_columns(
  grid,
  columns,
  header = NULL,
  ellipsis = NULL,
  align = NULL,
  valign = NULL,
  className = NULL,
  width = NULL,
  minWidth = NULL,
  hidden = NULL,
  resizable = NULL,
  defaultValue = NULL,
  formatter = NULL,
  escapeHTML = NULL,
  ignored = NULL,
  sortable = NULL,
  sortingType = NULL,
  onBeforeChange = NULL,
  onAfterChange = NULL,
  whiteSpace = NULL,
  ...
)
```

Arguments

grid	A grid created with datagrid() .
columns	Name(s) of column in the data used in datagrid() .
header	The header of the column to be shown on the header.

<code>ellipsis</code>	If set to true, ellipsis will be used for overflowing content.
<code>align</code>	Horizontal alignment of the column content. Available values are 'left', 'center', 'right'.
<code>vAlign</code>	Vertical alignment of the column content. Available values are 'top', 'middle', 'bottom'.
<code>className</code>	The name of the class to be used for all cells of the column.
<code>width</code>	The width of the column. The unit is pixel. If this value isn't set, the column's width is automatically resized.
<code>minWidth</code>	The minimum width of the column. The unit is pixel.
<code>hidden</code>	If set to true, the column will not be shown.
<code>resizable</code>	If set to false, the width of the column will not be changed.
<code>defaultValue</code>	The default value to be shown when the column doesn't have a value.
<code>formatter</code>	The function that formats the value of the cell. The return value of the function will be shown as the value of the cell. If set to 'listItemText', the value will be shown the text.
<code>escapeHTML</code>	If set to true, the value of the cell will be encoded as HTML entities.
<code>ignored</code>	If set to true, the value of the column will be ignored when setting up the list of modified rows.
<code>sortable</code>	If set to true, sort button will be shown on the right side of the column header, which executes the sort action when clicked.
<code>sortingType</code>	If set to 'desc', will execute descending sort initially when sort button is clicked. Default to 'asc'.
<code>onBeforeChange</code>	The function that will be called before changing the value of the cell. If stop() method in event object is called, the changing will be canceled.
<code>onAfterChange</code>	The function that will be called after changing the value of the cell.
<code>whiteSpace</code>	If set to 'normal', the text line is broken by fitting to the column's width. If set to 'pre', spaces are preserved and the text is broken by new line characters. If set to 'pre-wrap', spaces are preserved, the text line is broken by fitting to the column's width and new line characters. If set to 'pre-line', spaces are merged, the text line is broken by fitting to the column's width and new line characters.
<code>...</code>	Additional parameters.

Value

A datagrid htmlwidget.

Note

Documentation come from <https://nhn.github.io/tui.grid/latest/Grid/>.

Examples

```
library(toastui)

# New header label
datagrid(mtcars[, 1:5]) %>%
  grid_columns(columns = "mpg", header = "Miles/(US) gallon")

# Align content to right & resize
datagrid(mtcars[, 1:5]) %>%
  grid_columns(
    columns = "mpg",
    align = "left",
    resizable = TRUE
  ) %>%
  grid_columns(
    columns = "cyl",
    align = "left",
    resizable = TRUE
  )

# Hide a column
datagrid(mtcars[, 1:5]) %>%
  grid_columns(
    columns = "mpg",
    hidden = TRUE
  )

# Set options for 2 columns
datagrid(mtcars[, 1:5]) %>%
  grid_columns(
    columns = c("mpg", "cyl"),
    header = c("Miles/(US) gallon", "Number of cylinders")
  )
```

grid_columns_opts *Set global columns options*

Description

Set options for all columns.

Usage

```
grid_columns_opts(
  grid,
  minWidth = NULL,
```

```
    resizable = NULL,  
    frozenCount = NULL,  
    frozenBorderWidth = NULL  
)
```

Arguments

grid	A table created with datagrid() .
minWidth	Minimum width of each columns.
resizable	If set to true, resize-handles of each columns will be shown.
frozenCount	The number of frozen columns.
frozenBorderWidth	The value of frozen border width. When the frozen columns are created by "frozenCount" option, the frozen border width set.

Value

A datagrid htmlwidget.

Examples

```
library(toastui)  
  
# Set minimal width for columns  
datagrid(countries) %>%  
  grid_columns_opts(  
    minWidth = 140  
)  
  
# Freeze two first columns  
datagrid(countries) %>%  
  grid_columns_opts(  
    minWidth = 140,  
    frozenCount = 2,  
    frozenBorderWidth = 5  
)
```

grid_col_button	<i>Display buttons in grid's column</i>
-----------------	-----------------------------------------

Description

Display buttons in grid's column

Usage

```
grid_col_button(
  grid,
  column,
  inputId,
  label = NULL,
  icon = NULL,
  status = "default",
  btn_width = "100%",
  ...
)
```

Arguments

<code>grid</code>	A table created with datagrid() .
<code>column</code>	The name of the column where to create buttons.
<code>inputId</code>	The <code>input</code> slot that will be used to access the value.
<code>label</code>	Label to display on button, if <code>NULL</code> use column's content.
<code>icon</code>	Icon to display in button.
<code>status</code>	Bootstrap status (color) of the button: default, primary, success, info, warning, danger, ... A class prefixed by <code>btn-</code> will be added to the button.
<code>btn_width</code>	Button's width.
<code>...</code>	Further arguments passed to grid_columns() .

Value

A `datagrid` htmlwidget.

Examples

```
library(toastui)
library(shiny)

ui <- fluidPage(
  tags$h2("Buttons in grid"),
  datagridOutput("grid"),
  verbatimTextOutput("clicks")
)

server <- function(input, output, session) {

  dat <- data.frame(
    variable = paste(1:26, LETTERS, sep = " - "),
    button1 = 1:26,
    button2 = letters,
    button3 = LETTERS
  )
}
```

```

output$grid <- renderDatagrid({
  datagrid(dat) %>%
    grid_col_button(
      column = "button1",
      inputId = "button1"
    ) %>%
    grid_col_button(
      column = "button2",
      inputId = "button2",
      align = "center",
      btn_width = "50%",
      status = "primary"
    ) %>%
    grid_col_button(
      column = "button3",
      inputId = "button3",
      label = "Remove",
      icon = icon("trash"),
      status = "danger"
    )
  })
}

output$clicks <- renderPrint({
  cat(
    "Button 1: ", input$button1,
    "\nButton 2: ", input$button2,
    "\nButton 3: ", input$button3,
    "\n"
  )
})

if (interactive())
  shinyApp(ui, server)

```

grid_col_checkbox *Display checkboxes in grid's column*

Description

Display checkboxes in grid's column

Usage

```

grid_col_checkbox(
  grid,
  column,
  class = "form-check d-flex justify-content-center my-1",
  ...
)

```

Arguments

<code>grid</code>	A table created with datagrid() .
<code>column</code>	The name of the column where to create buttons.
<code>class</code>	CSS classes to add to checkbox container.
<code>...</code>	Further arguments passed to grid_columns() .

Value

A datagrid htmlwidget.

Examples

```
library(toastui)
library(shiny)
library(bslib)

ui <- fluidPage(
  theme = bslib::bs_theme(version = 5L),
  tags$h2("Checkbox column grid demo"),
  fluidRow(
    column(
      width = 8,
      datagridOutput("grid"),
      verbatimTextOutput("edited")
    )
  )
)

server <- function(input, output, session) {

  output$grid <- renderDatagrid({
    data.frame(
      month = month.name,
      checkboxes = sample(c(TRUE, FALSE), 12, replace = TRUE),
      switches = sample(c(TRUE, FALSE), 12, replace = TRUE)
    ) %>%
      datagrid(data_as_input = TRUE) %>%
      grid_col_checkbox(column = "checkboxes") %>%
      grid_col_checkbox(
        column = "switches",
        # !\ will only works with bslib::bs_theme(version = 5L)
        class = "form-check form-switch d-flex justify-content-center my-1"
      )
  })

  output$edited <- renderPrint({
    input$grid_data # outputId + "_data"
  })
}
```

```
if (interactive())
  shinyApp(ui, server)
```

grid_editor_date *Grid editor for date/time columns*

Description

Allow to edit content of columns with a calendar and time picker, then retrieve value server-side in shiny application with `input$<outputId>_data`.

Usage

```
grid_editor_date(
  grid,
  column,
  format = "yyyy-MM-dd",
  type = c("date", "month", "year"),
  timepicker = c("none", "tab", "normal"),
  weekStartDay = NULL,
  language = NULL
)
```

Arguments

grid	A table created with datagrid() .
column	Column for which to activate the date picker.
format	Date format, default is "yyyy-MM-dd".
type	Type of selection: date, month or year.
timepicker	Add a timepicker.
weekStartDay	Start of the week : 'Sun' (default), 'Mon', ..., 'Sat'
language	Either "en" or "ko" the builtin language, or "custom" to use texts defined in <code>datagrid(datepicker_locale = list(...))</code> , see example.

Value

A datagrid htmlwidget.

See Also

[grid_editor](#) for normal inputs.

Examples

```

library(toastui)

dat <- data.frame(
  date = Sys.Date() + 1:10,
  date_locale = format(Sys.Date() + 1:10, format = "%d/%m/%Y"),
  month = format(Sys.Date() + 1:10, format = "%Y-%m"),
  year = format(Sys.Date() + 1:10, format = "%Y"),
  time1 = Sys.time() + 1:10,
  time2 = Sys.time() + 1:10
)

datagrid(
  data = dat,
  datepicker_locale = list(
    titles = list(
      DD = c(
        "Dimanche", "Lundi", "Mardi",
        "Mercredi", "Jeudi", "Vendredi", "Samedi"
      ),
      D = c("Dim", "Lun", "Mar", "Mer", "Jeu", "Ven", "Sam"),
      MMMM = c(
        "Janvier", "F\u00e9vrier", "Mars",
        "Avril", "Mai", "Juin", "Juillet",
        "Ao\u00f9ft", "Septembre", "Octobre",
        "Novembre", "D\u00e9cembre"
      ),
      MMM = c(
        "Jan", "F\u00e9v", "Mar", "Avr",
        "Mai", "Juin", "Juil", "Aou",
        "Sept", "Oct", "Nov", "D\u00e9c"
      )
    ),
    titleFormat = "MMM yyyy",
    todayFormat = "DD dd MMMM yyyy",
    date = "Date",
    time = "Heure"
  )
) %>%
  grid_editor_date(
    column = "date"
  )%>%
  grid_editor_date(
    column = "date_locale",
    format = "dd/MM/yyyy",
    language = "custom",
    weekStartDay = "Mon"
  ) %>%
  grid_editor_date(
    column = "month",
    type = "month",
  )

```

```
  format = "yyyy-MM"
) %>%
grid_editor_date(
  column = "year",
  type = "year",
  format = "yyyy"
) %>%
grid_editor_date(
  column = "time1",
  timepicker = "tab",
  format = "yyyy-MM-dd HH:mm"
) %>%
grid_editor_date(
  column = "time2",
  timepicker = "normal",
  format = "yyyy-MM-dd HH:mm"
)
```

grid_filters*Set filters options*

Description

Set filters options

Usage

```
grid_filters(
  grid,
  columns,
  showApplyBtn = NULL,
  showClearBtn = NULL,
  operator = NULL,
  format = "yyyy-MM-dd",
  type = "auto"
)
```

Arguments

grid	A table created with datagrid() .
columns	Name(s) of column in the data used in datagrid() .
showApplyBtn	Apply filters only when button is pressed.
showClearBtn	Reset the filter that has already been applied.
operator	Multi-option filter, the operator used against multiple rules : "OR" or "AND".
format	Date format.
type	Type of filter : "auto", "text", "number", "date" or "select".

Value

A datagrid htmlwidget.

Examples

```
library(toastui)

data <- data.frame(
  number = 1:12,
  month.abb = month.abb,
  month.name = month.name,
  date = Sys.Date() + 0:11,
  stringsAsFactors = FALSE
)

datagrid(data) %>%
  grid_filters(
    columns = "month.abb",
    showApplyBtn = TRUE,
    showClearBtn = TRUE,
    type = "text"
  ) %>%
  grid_filters(
    columns = "month.name",
    type = "select"
  ) %>%
  grid_filters(columns = "date") %>%
  grid_filters(columns = "number")

# Filter all variables
datagrid(rolling_stones_500) %>%
  grid_filters(columns = names(rolling_stones_500))
# or
datagrid(rolling_stones_500, filters = TRUE)
```

grid_format

Format column content

Description

Format column content

Usage

```
grid_format(grid, column, formatter)
```

Arguments

grid	A table created with datagrid() .
column	Name of the column to format.
formatter	Either an R function or a JavaScript function wrapped in JS() .

Value

A datagrid htmlwidget.

Examples

```
library(toastui)
library(scales)

# Create some data
data <- data.frame(
  col_num = rnorm(12),
  col_currency = sample(1:1e6, 12, TRUE),
  col_percentage = sample(1:100, 12, TRUE) / 100,
  col_date = sample(Sys.Date() + 0:364, 12),
  col_time = Sys.time() + sample.int(86400 * 365, 12),
  col_logical = sample(c(TRUE, FALSE), 12, TRUE),
  stringsAsFactors = FALSE
)

# Use R functions
datagrid(data, colwidths = "fit") %>%
  grid_format(
    "col_percentage", label_percent(accuracy = 1)
  ) %>%
  grid_format(
    "col_currency", label_dollar(prefix = "$", big.mark = ",")
  ) %>%
  grid_format(
    "col_num", label_number(accuracy = 0.01)
  ) %>%
  grid_format(
    "col_date", label_date(format = "%d/%m/%Y")
  ) %>%
  grid_format(
    "col_time", label_date(format = "%d/%m/%Y %H:%M")
  ) %%%
  grid_format(
    "col_logical", function(value) {
      lapply(
        X = value,
        FUN = function(x) {
          if (x)
            shiny::icon("check")
          else
        }
      )
    }
  )
}
```

```

        shiny::icon("times")
    }
)
}
)

# Use a JavaScript function
datagrid(data) %>%
  grid_format(
    column = "col_percentage",
    formatter = JS("function(obj) {return (obj.value*100).toFixed(0) + '%';}")
  )

```

grid_proxy_add_row *Add rows to an existent datagrid*

Description

Add rows to an existent datagrid

Usage

```
grid_proxy_add_row(proxy, data)
```

Arguments

proxy	A datagrid_proxy() or outputId of the grid.
data	data.frame to append in the grid.

Value

A datagrid_proxy object.

See Also

Other datagrid proxy methods: [datagrid_proxy\(\)](#), [grid_proxy_delete_row\(\)](#)

Examples

```

library(shiny)
library(toastui)

ui <- fluidPage(
  tags$h2("Append row to grid"),
  datagridOutput("grid"),

```

```

actionButton(
  inputId = "add",
  label = "Add row",
  class = "btn-block"
)
)

server <- function(input, output, session) {

  dat <- data.frame(
    character = month.name,
    select = month.name,
    checkbox = month.abb,
    radio = month.name,
    password = month.name
  )

  output$grid <- renderDatagrid({
    datagrid(rolling_stones_50[1, ])
  })

  value <- reactiveVal(1)
  observeEvent(input$add, {
    row <- value() + 1
    grid_proxy_add_row(
      proxy = "grid",
      data = rolling_stones_50[row, ]
    )
    value(row)
  })
}

if (interactive())
  shinyApp(ui, server)

```

`grid_proxy_delete_row` *Delete row in an existent grid*

Description

Delete row in an existent grid

Usage

```
grid_proxy_delete_row(proxy, rowKey)
```

Arguments

`proxy`

A `datagrid_proxy()` or `outputId` of the grid.

`rowKey`

Row key of the row to delete, you can find the `rowKey` value in `input$<outputId>_data`.

Value

A datagrid_proxy object.

See Also

Otherdatagrid proxy methods: [datagrid_proxy\(\)](#), [grid_proxy_add_row\(\)](#)

Examples

```
library(toastui)
library(shiny)

ui <- fluidPage(
  tags$h2("Delete row in grid via proxy"),
  fluidRow(
    column(
      width = 6,
      datagridOutput("grid"),
      verbatimTextOutput("clicks")
    ),
    column(
      width = 6,
      verbatimTextOutput("output_data")
    )
  )
)

server <- function(input, output, session) {

  dat <- data.frame(
    index = 1:26,
    letter = sample(letters),
    remove = 1:26
  )

  output$grid <- renderDatagrid({
    datagrid(dat, data_as_input = TRUE) %>%
      grid_columns("remove", width = 120) %>%
      grid_col_button(
        column = "remove",
        inputId = "remove_row",
        label = "Remove",
        icon = icon("trash"),
        status = "danger",
        btn_width = "115px",
        align = "left"
      )
  })

  output$clicks <- renderPrint({
    cat(
      "Removed: ", input$remove_row,
```

```

        "\n"
    )
})

observeEvent(input$remove_row, {
  data <- input$grid_data
  rowKey <- data$rowKey[data$remove == input$remove_row]
  grid_proxy_delete_row("grid", rowKey)
})

output$output_data <- renderPrint({
  input$grid_data
})

}

if (interactive())
  shinyApp(ui, server)

```

`grid_row_merge` *Merge rows*

Description

Merge rows

Usage

```
grid_row_merge(grid, columns)
```

Arguments

<code>grid</code>	A grid created with datagrid() .
<code>columns</code>	column(s) in which merge consecutive rows.

Value

A `datagrid` htmlwidget.

Examples

```

library(toastui)

datagrid(mtcars[order(mtcars$cyl), 1:5]) %>%
  grid_row_merge(columns = "cyl")

datagrid(mtcars[, 1:8]) %>%
  grid_row_merge(columns = "cyl") %>%
  grid_row_merge(columns = "vs")

```

`grid_selection_cell` *Cell selection (in shiny)*

Description

Cell selection (in shiny)

Usage

```
grid_selection_cell(grid, inputId, selectionUnit = c("cell", "row"))
```

Arguments

<code>grid</code>	A table created with datagrid() .
<code>inputId</code>	The <code>input</code> slot that will be used to access the value.
<code>selectionUnit</code>	The unit of selection on <code>grid</code> .

Value

A `datagrid` htmlwidget.

Examples

```
if (interactive()) {
  library(shiny)
  library(toastui)

  ui <- fluidPage(
    tags$h2("datagrid cell selection"),
    datagridOutput("grid_1"),
    verbatimTextOutput("result_1"),
    datagridOutput("grid_2"),
    verbatimTextOutput("result_2")
  )

  server <- function(input, output, session) {

    df <- data.frame(
      index = 1:12,
      month = month.name,
      letters = letters[1:12]
    )

    output$grid_1 <- renderDatagrid({
      datagrid(df) %>%

```

```
grid_selection_cell(  
  inputId = "cells"  
)  
)  
output$result_1 <- renderPrint({  
  input$cells  
)  
  
output$grid_2 <- renderDatagrid({  
  datagrid(df) %>%  
  grid_selection_cell(  
    inputId = "rows",  
    selectionUnit = "row"  
)  
)  
output$result_2 <- renderPrint({  
  input$rows  
)  
}  
  
shinyApp(ui, server)  
}
```

grid_selection_row *Row selection (in shiny)*

Description

Row selection (in shiny)

Usage

```
grid_selection_row(  
  grid,  
  inputId,  
  type = c("checkbox", "radio"),  
  return = c("data", "index"),  
  width = NULL  
)
```

Arguments

grid	A table created with datagrid() .
inputId	The input slot that will be used to access the value.
type	Type of selection: "checkbox" (multiple rows) or "radio" (unique row).
return	Value that will be accessible via <code>input</code> : a <code>data.frame</code> with selected row(s) or just the index of selected row(s).
width	Width of the column.

Value

A datagrid htmlwidget.

Examples

```
library(shiny)
library(toastui)

ui <- fluidPage(
  tags$h2("datagrid row selection"),
  fluidRow(
    column(
      width = 6,
      datagridOutput("grid_checkbox"),
      verbatimTextOutput("res_checkbox")
    ),
    column(
      width = 6,
      datagridOutput("grid_radio"),
      verbatimTextOutput("res_radio")
    )
  )
)

server <- function(input, output, session) {

  df <- data.frame(
    index = 1:12,
    month = month.name,
    letters = letters[1:12]
  )

  output$grid_checkbox <- renderDatagrid({
    datagrid(df) %>%
      grid_selection_row(
        inputId = "sel_check",
        type = "checkbox"
      )
  })

  output$res_checkbox <- renderPrint({
    input$sel_check
  })

  output$grid_radio <- renderDatagrid({
    datagrid(df) %>%
      grid_selection_row(
        inputId = "sel_radio",
        type = "radio"
      )
  })
}
```

```
output$res_radio <- renderPrint({  
  input$sel_radio  
})  
  
}  
  
if (interactive())  
  shinyApp(ui, server)
```

grid_sparkline *Render HTMLwidgets in Grid*

Description

Create small charts in a column.

Usage

```
grid_sparkline(grid, column, renderer, height = "40px", styles = NULL)
```

Arguments

grid	A grid created with datagrid() .
column	Column data are stored and where to render widgets.
renderer	A function that will create an HTMLwidget.
height	Height of the row (applies to all table).
styles	A list of CSS parameters to apply to the cells where widgets are rendered.

Value

A datagrid htmlwidget.

Examples

```
library(toastui)  
library(apexcharter)  
  
# Create some fake data  
spark <- data.frame(  
  month = month.name,  
  stringsAsFactors = FALSE  
)  
# Create a list-columns with data.frames  
# from which to create charts  
spark$data <- lapply(  
  X = seq_len(12),  
  FUN = function(x) {  
    data.frame(x = 1:10, y = sample(1:30, 10, TRUE))
```

```

        }
    )

# Create the grid
datagrid(spark) %>%
  grid_columns(
    columns = "month", width = 150
  ) %>%
  grid_sparkline(
    column = "data",
    renderer = function(data) { # this function will render a chart
      apex(data, aes(x, y), type = "area") %>%
        ax_chart(sparkline = list(enabled = TRUE))
    }
  )

# You can also use package highcharter for example
# by using the following renderer:
# renderer = function(data) {
#   hchart(data, type = "area", hcaes(x, y)) %>%
#     hc_add_theme(hc_theme_sparkline())
# }
```

grid_style_column *Set column style*

Description

Apply styles to a column according to CSS properties declared by expression based on data passed to grid..

Usage

```
grid_style_column(
  grid,
  column,
  background = NULL,
  color = NULL,
  fontWeight = NULL,
  ...
)
```

Arguments

grid	A grid created with datagrid() .
column	Name of column (variable name) where to apply style.
background	Background color.
color	Text color.

```
fontWeight      Font weight, you can use "bold" for example.  
...             Other CSS properties.
```

Value

A datagrid htmlwidget.

Examples

```
library(toastui)  
library(scales)  
  
datagrid(mtcars) %>%  
  grid_style_column(  
    column = "mpg",  
    background = col_numeric("Blues", domain = NULL)(mpg),  
    fontWeight = "bold",  
    color = ifelse(mpg > 25, "white", "black")  
  )  
  
datagrid(mtcars) %>%  
  grid_style_column(  
    column = "mpg",  
    background = col_numeric("Blues", domain = NULL)(mpg),  
    fontWeight = "bold",  
    color = ifelse(mpg > 25, "white", "black")  
  ) %>%  
  grid_style_column(  
    column = "cyl",  
    background = col_bin("Blues", domain = NULL)(cyl),  
    fontStyle = "italic"  
  )
```

grid_style_row *Set grid row style*

Description

Apply styles to an entire row identified by an expression.

Usage

```
grid_style_row(  
  grid,  
  expr,  
  background = NULL,  
  color = NULL,  
  fontWeight = NULL,  
  ...,
```

```
    class = NULL,
    cssProperties = NULL
)
```

Arguments

<code>grid</code>	A grid created with datagrid() .
<code>expr</code>	An expression giving position of row. Must return a logical vector.
<code>background</code>	Background color.
<code>color</code>	Text color.
<code>fontWeight</code>	Font weight, you can use "bold" for example.
<code>...</code>	Other CSS properties.
<code>class</code>	CSS class to apply to the row.
<code>cssProperties</code>	Alternative to specify CSS properties with a named list.

Value

A datagrid htmlwidget.

Examples

```
library(toastui)

datagrid(mtcars) %>%
  grid_style_row(
    mpg > 19,
    background = "#F781BE"
  )

datagrid(mtcars) %>%
  grid_style_row(
    vs == 0,
    background = "#E41A1C80",
    color = "#FFF"
  ) %>%
  grid_style_row(
    vs == 1,
    background = "#377EB880"
  )

# Use rlang to use character
library(rlang)
my_var <- "disp"
datagrid(mtcars) %>%
  grid_style_row(
    !isym(my_var) > 180,
    background = "#F781BE"
  )
```

grid_summary	<i>Add summary area to grid</i>
--------------	---------------------------------

Description

Add summary area to grid

Usage

```
grid_summary(  
  grid,  
  columns,  
  stat = c("sum", "min", "max", "avg"),  
  digits = 0,  
  label = NULL,  
  sep = "<br>",  
  position = c("bottom", "top"),  
  height = 40,  
  js_function = NULL  
)
```

Arguments

grid	A table created with datagrid() .
columns	Name of column (variable name) for which to add a summary.
stat	Statistic to display: "sum", "min", "max" or "avg". Can be several values.
digits	Number of digits to display.
label	Label to display next to statistic.
sep	Separator between several statistics.
position	The position of the summary area: "bottom" or "top".
height	The height of the summary area.
js_function	JavaScript function to compute the statistic you want. Function should have one argument, it will be the values of the column. If used, stat, digits, label and sep will be ignored.

Value

A datagrid htmlwidget.

Examples

```
library(toastui)

# Add a line with sum of column
datagrid(ps3_games[, c(1, 5, 6, 7, 8)], colwidths = "guess") %>%
  grid_summary(
    column = "NA_Sales",
    stat = "sum"
  )

# Do that for several columns
datagrid(ps3_games[, c(1, 5, 6, 7, 8)], colwidths = "guess") %>%
  grid_summary(
    column = c("NA_Sales", "EU_Sales", "JP_Sales", "Other_Sales"),
    stat = "sum",
    label = "Total: "
  )
```

guess_colwidths_options

Options for guessing columns widths

Description

Options for guessing columns widths

Usage

```
guess_colwidths_options(min_width = 70, max_width = 400, mul = 1, add = 0)
```

Arguments

<code>min_width</code>	Minimal width.
<code>max_width</code>	Maximal width.
<code>mul</code>	Multiplicative constant.
<code>add</code>	Additive constant

Value

a list of options to use in [datagrid\(\)](#).

Examples

```
datagrid(rolling_stones_50, colwidths = "guess")
datagrid(
  rolling_stones_50,
  colwidths = "guess",
  guess_colwidths_opts= guess_colwidths_options(mul = 2)
)
```

`met_paris`

Meteorological for Le Bourget Station

Description

This dataset contains temperature and relative humidity for year 2020.

Usage

`met_paris`

Format

A `data.frame` with 12 rows and 3 variables:

month Month of the year

temp List column containing `data.frame` with 2 column "date and"temp"

rh List column containing `data.frame` with 2 column "date and"rh"

Source

Data collected with package `stationaRy` from NOAA

`navigation_options`

Options for buttons displayed above calendar

Description

Options for buttons displayed above calendar

Usage

```
navigation_options(  
  today_label = "Today",  
  prev_label = ph("caret-left"),  
  next_label = ph("caret-right"),  
  class = "btn-bordered btn-sm btn-primary",  
  bg = NULL,  
  color = NULL,  
  fmt_date = "YYYY-MM-DD",  
  sep_date = " ~ ")
```

Arguments

<code>today_label</code>	Text to display on today button.
<code>prev_label</code>	Text to display on prev button.
<code>next_label</code>	Text to display on next button.
<code>class</code>	Class to add to buttons.
<code>bg, color</code>	Background and text colors.
<code>fmt_date</code>	Format for the date displayed next to the buttons, use dayjs library (see https://day.js.org/docs/en/display/format)
<code>sep_date</code>	Separator to use between start date and end date.

Value

a list.

Note

Buttons are generated with the following CSS library : <http://bttn.surge.sh/>, where you can find available options for `class` argument.

Examples

```
# Use another button style
calendar(
  navigation = TRUE,
  navOpts = navigation_options(
    class = "bttn-stretch bttn-sm bttn-warning"
  )
)

# Custom colors (background and text)
calendar(
  navigation = TRUE,
  navOpts = navigation_options(bg = "#FE2E2E", color = "#FFF")
)

# both
calendar(
  navigation = TRUE,
  navOpts = navigation_options(
    bg = "#04B431", color = "#FFF",
    class = "bttn-float bttn-md"
  )
)

# Change date format and separator
calendar(
  navigation = TRUE,
  navOpts = navigation_options(
    fmt_date = "DD/MM/YYYY",
  )
)
```

```
    sep_date = " - "
)
)
```

ps3_games

Top 20 PS3 games

Description

This dataset contains 20 PS3 video games with sales.

Usage

```
ps3_games
```

Format

A `data.frame` with 20 rows and 8 variables:

Name Name of the game

Year Year of the game's release

Genre Genre of the game

Publisher Publisher of the game

NA_Sales Sales in North America (in millions)

EU_Sales Sales in Europe (in millions)

JP_Sales Sales in Japan (in millions)

Other_Sales Sales in the rest of the world (in millions)

Source

GregorySmith on Kaggle (<https://www.kaggle.com/datasets/gregorut/videogamesales/>)

rolling_stones_50

Rolling Stone's 50 Greatest Albums of All Time

Description

Data about Rolling Stone magazine's (2012) top 50 albums of all time list.

Usage

```
rolling_stones_50
```

Format

A `data.frame` with 50 rows and 6 variables:

Number Position on the list

Year Year of release

Album Album name

Artist Artist name

Genre Genre name

Subgenre Subgenre name

Source

Gibs on Kaggle (<https://www.kaggle.com/datasets/notgibs/500-greatest-albums-of-all-time-rolling-stone/>)

`rolling_stones_500`

Rolling Stone's 500 Greatest Albums of All Time

Description

Data about Rolling Stone magazine's (2012) top 500 albums of all time list.

Usage

`rolling_stones_500`

Format

A `data.frame` with 500 rows and 6 variables:

Number Position on the list

Year Year of release

Album Album name

Artist Artist name

Genre Genre name

Subgenre Subgenre name

Source

Gibs on Kaggle (<https://www.kaggle.com/datasets/notgibs/500-greatest-albums-of-all-time-rolling-stone/>)

schedules_properties *Schedules properties*

Description

This dataset contains properties that can be used to create schedules in [calendar\(\)](#).

Usage

```
schedules_properties
```

Format

A `data.frame` with 26 rows and 3 variables:

Name Name of property

Type Type

Description Description

Source

Toast UI documentation (<https://nhn.github.io/tui.calendar/latest/EventObject/>)

set_grid_lang *Set grid language options*

Description

Set grid language options

Usage

```
set_grid_lang(  
  display.noData = "No data",  
  display.loadingData = "Loading data...",  
  display.resizeHandleGuide = "You can change the width... [truncated]",  
  filter.contains = "Contains",  
  filter.eq = "Equals",  
  filter.ne = "Not equals",  
  filter.start = "Starts with",  
  filter.end = "Ends with",  
  filter.after = "After",  
  filter.afterEq = "After or Equal",  
  filter.before = "Before",  
  filter.beforeEq = "Before or Equal",
```

```

filter.apply = "Apply",
filter.clear = "Clear",
filter.selectAll = "Select All"
)

```

Arguments

display.noData, display.loadingData, display.resizeHandleGuide	Display language options.
filter.contains, filter.eq, filter.ne, filter.start, filter.end,	
filter.after, filter.afterEq, filter.before, filter.beforeEq,	
filter.apply, filter.clear, filter.selectAll	Filter language options.

Value

No return value.

Examples

```

library(toastui)

# Change text displayed when no data in grid
set_grid_lang(display.noData = "Pas de donn\u00e9es")
datagrid(data.frame())

# change text for filters
set_grid_lang(
  # Text
  filter.contains = "Contient",
  filter.eq = "Egal \u00e0",
  filter.ne = "Diff\u00e9rent de",
  filter.start = "Commence par",
  filter.end = "Fini par",
  # Date
  filter.after = "Apr\u00e8s",
  filter.afterEq = "Apr\u00e8s ou \u00e9gal \u00e0",
  filter.before = "Avant",
  filter.beforeEq = "Avant ou \u00e9gal \u00e0",
  # Buttons
  filter.apply = "Appliquer",
  filter.clear = "Supprimer",
  # Select
  filter.selectAll = "Tout s\u00e9lectionner"
)

datagrid(rolling_stones_50) %>%
  grid_filters(
    columns = "Artist",
    type = "text",
    showApplyBtn = TRUE,
    showClearBtn = TRUE
  )

```

```
) %>%  
grid_filters(  
  columns = "Genre",  
  type = "select"  
) %>%  
grid_filters(  
  columns = "Year",  
  type = "date"  
)
```

toastui

HTMLwidget interface to the R href="https://ui.toast.com/TOASTUI javascript libraries.

Description

Create interactive tables, calendars and charts with one package.

Tables

Interactive and editable tables with **tui-grid**, see [datagrid\(\)](#).

Calendars

Interactive and editable calendars with **tui-calendar**, see [calendar](#).

Charts

Interactive charts with **tui-chart**, see [chart](#).

Author(s)

Victor Perrier (@dreamRs_fr)

See Also

Useful links:

- <https://dreamrs.github.io/toastui/>
- Report bugs at <https://github.com/dreamRs/toastui/issues>

toastui-exports

toastui exported operators and S3 methods

Description

The following functions are imported and then re-exported from the toastui package to avoid listing the magrittr as Depends of toastui

<code>validateOpts</code>	<i>Validation options</i>
---------------------------	---------------------------

Description

Validate columns' content with rules, useful when content is editable.

Usage

```
validateOpts(
  required = NULL,
  type = NULL,
  min = NULL,
  max = NULL,
  regExp = NULL,
  unique = NULL,
  jsfun = NULL
)
```

Arguments

<code>required</code>	If set to TRUE, the data of the column will be checked to be not empty.
<code>type</code>	Type of data, can be "string" or "number".
<code>min</code>	For numeric values, the minimum acceptable value.
<code>max</code>	For numeric values, the maximum acceptable value.
<code>regExp</code>	A regular expression to validate content.
<code>unique</code>	If set to TRUE, check the uniqueness on the data of the column.
<code>jsfun</code>	A JS function to validate content.

Value

A datagrid htmlwidget.
a list of options to use in [grid_editor\(\)](#).

Examples

```
library(shiny)

ui <- fluidPage(
  tags$h2("Validation rules"),
  datagridOutput("grid"),
  verbatimTextOutput("validation")
)

server <- function(input, output, session) {
```

```
output$grid <- renderDatagrid({  
  validate <- data.frame(  
    col_text = c("a", "b", "a", NA, "c"),  
    col_number = sample(1:10, 5),  
    col_mail = c("victor@mail.com", "victor", NA, "victor@mail", "victor.fr")  
  )  
  
  datagrid(validate) %>%  
    grid_editor(  
      "col_text", type = "text",  
      validation = validateOpts(required = TRUE, unique = TRUE)  
    ) %>%  
    grid_editor(  
      "col_number", type = "number",  
      validation = validateOpts(min = 0, max = 5)  
    ) %>%  
    grid_editor(  
      "col_mail", type = "text",  
      validation = validateOpts(  
        regExp = "^(a-zA-Z0-9_\\-\\.]+@[a-zA-Z0-9_\\-\\.]+\\.(a-zA-Z){2,5})$"  
      )  
    )  
  })  
  
  output$validation <- renderPrint({  
    input$grid_validation  
  })  
}  
  
if (interactive())  
  shinyApp(ui, server)
```

Index

- * **calendar proxy methods**
 - cal_proxy_clear, 18
 - cal_proxy_clear_selection, 19
 - cal_proxy_options, 20
 - cal_proxy_toggle, 21
 - cal_proxy_view, 23
 - calendar-proxy-navigate, 6
 - calendar-proxy-schedule, 8
 - calendar_proxy, 13
- * **datagrid proxy methods**
 - datagrid_proxy, 44
 - grid_proxy_add_row, 76
 - grid_proxy_delete_row, 77
- * **datasets**
 - calendar_properties, 12
 - countries, 34
 - met_paris, 89
 - ps3_games, 91
 - rolling_stones_50, 91
 - rolling_stones_500, 92
 - schedules_properties, 93
- * **editor proxy methods**
 - editor-proxy-show-hide, 46
 - editor_proxy, 49
 - editor_proxy_change_preview, 50
 - editor_proxy_insert, 52
- %>% (toastui-exports), 95
- caes, 3
- cal-demo-data, 4
- cal_demo_data (cal-demo-data), 4
- cal_demo_data(), 5
- cal_demo_props (cal-demo-data), 4
- cal_events, 14
- cal_events(), 11
- cal_month_options, 16
- cal_month_options(), 20
- cal_props, 17
- cal_props(), 12
- cal_proxy_add
 - (calendar-proxy-schedule), 8
- cal_proxy_clear, 7, 9, 13, 18, 19–21, 23
- cal_proxy_clear_selection, 7, 9, 13, 18, 19, 20, 21, 23
- cal_proxy_date
 - (calendar-proxy-navigate), 6
- cal_proxy_delete
 - (calendar-proxy-schedule), 8
- cal_proxy_next
 - (calendar-proxy-navigate), 6
- cal_proxy_options, 7, 9, 13, 18, 19, 20, 21, 23
- cal_proxy_prev
 - (calendar-proxy-navigate), 6
- cal_proxy_today
 - (calendar-proxy-navigate), 6
- cal_proxy_toggle, 7, 9, 13, 18–20, 21, 23
- cal_proxy_update
 - (calendar-proxy-schedule), 8
- cal_proxy_view, 7, 9, 13, 18–21, 23
- cal_schedules, 24
- cal_template, 25
- cal_theme, 26
- cal_timezone, 27
- cal_week_options, 29
- cal_week_options(), 5, 20
- calendar, 4, 95
- calendar(), 10, 16, 17, 20, 26–29, 93
- calendar-proxy-navigate, 6
- calendar-proxy-schedule, 8
- calendar-shiny, 10
- calendar_properties, 12
- calendar_proxy, 7, 9, 13, 18–21, 23
- calendar_proxy(), 7, 8, 18–21, 23
- calendarOutput (calendar-shiny), 10
- calendarOutput(), 5
- chart, 30, 95
- chart(), 32

chart-shiny, 32
chart_labs, 33
chart_options, 34
chartOutput (chart-shiny), 32
chartOutput(), 31
countries, 34

datagrid, 35
datagrid(), 38, 54, 56, 59, 61, 62, 64, 67, 68, 70, 71, 73, 75, 79–81, 83, 84, 86–88, 95
datagrid-shiny, 38
datagrid-theme, 39
datagrid_proxy, 44, 76, 78
datagrid_proxy(), 76, 77
datagridOutput (datagrid-shiny), 38
datagridOutput(), 37
datagridOutput2 (datagrid-shiny), 38

editor, 45
editor(), 48
editor-proxy-show-hide, 46
editor-shiny, 48
editor_proxy, 46, 49, 51, 52
editor_proxy(), 46, 50, 52
editor_proxy_change_preview, 46, 50, 50, 52
editor_proxy_hide
 (editor-proxy-show-hide), 46
editor_proxy_insert, 46, 50, 51, 52
editor_proxy_show
 (editor-proxy-show-hide), 46
editorOutput (editor-shiny), 48

grid-cell-style, 53
grid-editor, 56
grid-header, 59
grid_click, 61
grid_click(), 39
grid_col_button, 67
grid_col_checkbox, 69
grid_colorbar, 62
grid_columns, 64
grid_columns(), 68, 70
grid_columns_opts, 66
grid_complex_header (grid-header), 59
grid_editor, 71
grid_editor (grid-editor), 56
grid_editor(), 38, 96

grid_editor_date, 57, 71
grid_editor_date(), 36
grid_editor_opts (grid-editor), 56
grid_filters, 73
grid_format, 74
grid_header (grid-header), 59
grid_proxy_add_row, 44, 76, 78
grid_proxy_delete_row, 44, 76, 77
grid_row_merge, 79
grid_selection_cell, 80
grid_selection_cell(), 39
grid_selection_row, 81
grid_selection_row(), 38
grid_sparkline, 83
grid_style_cell (grid-cell-style), 53
grid_style_cells (grid-cell-style), 53
grid_style_column, 84
grid_style_row, 85
grid_summary, 87
guess_colwidths_options, 88
guess_colwidths_options(), 36

htmlwidgets::JS(), 15, 26

JS(toastui-exports), 95
JS(), 75

met_paris, 89

navigation_options, 89
navigation_options(), 5

ps3_games, 91

renderCalendar (calendar-shiny), 10
renderCalendar(), 5
renderChart (chart-shiny), 32
renderChart(), 31
renderDatagrid (datagrid-shiny), 38
renderDatagrid(), 37
renderDatagrid2 (datagrid-shiny), 38
renderEditor (editor-shiny), 48
reset_grid_theme (datagrid-theme), 39
rolling_stones_50, 91
rolling_stones_500, 92

schedules_properties, 93
set_grid_lang, 93
set_grid_theme (datagrid-theme), 39

[toastui](#), [95](#)
[toastui-exports](#), [95](#)
[toastui-package \(toastui\)](#), [95](#)

[validateOpts](#), [96](#)
[validateOpts\(\)](#), [56](#)