

Annotation

Martin Morgan
Fred Hutchinson Cancer Research Center

19-21 January, 2011

Annotation Resources – Genes and Genomes

AnnotationDbi

- ▶ Chip, 'org', GO, KEGG, homology
- ▶ Curated from NCBI, GO, other sources for each *Bioconductor* release.
- ▶ SQL 'under the hood'

biomaRt

- ▶ Large online annotation collection
- ▶ Curated by OICR / EMBL-EBI

BSgenome

- ▶ Genome sequences – try `available.genomes`

AnnotationDbi

Demo

Demo

Work Flow: Sequence Analysis

Prior to analysis


- ▶ Biological experimental design – treatments, replication, etc.
- ▶ Sequencing preparation – library preparation, manufacturer protocol, etc.

Analysis

1. Pre-processing (sequencing, alignment, quality assessment)
2. Count, e.g., reads per transcript – ChIP-seq; RNA-seq; novel transcript identification; microbiome; ...
3. Differential representation / ChIP-seq / SNP / ...
4. Annotation
5. ...

<http://bioconductor.org/workflows> for common analyses.

Bridge PCR



Bentley et al., 2008, Nature 456: 53-9

Bioconductor entry points

- ▶ Quality assessment.
- ▶ Preliminary read processing, e.g., demultiplexing, remediation
- ▶ Specialized alignment, e.g., `matchPDict` in *Biostrings*.
- ▶ 'Upstream' domain-specific work flows, e.g., ChIP-seq peak calling (*chipseq*), RNA-seq reads per transcript (*GenomicRanges* / *IRanges* / ...)
- ▶ Statistical analysis of designed experiments, e.g., *edgeR*, *DESeq*
- ▶ Specialized analysis, e.g., microbiome sequence processing and ecological analysis (*vegan*, *ape*, ...)

Representing Sequence Information

DNAStringSet

- ▶ Collections of DNA sequences, e.g., microarray probes, Illumina reads
- ▶ Quality scores

GRanges

- ▶ Genome coordinates – reference sequence name, start and end coordinates, strand; e.g., aligned reads
- ▶ *GRangesList* – hierarchical structure, e.g., exons within transcripts

Additional classes: *AlignedRead*, *GappedAlignment*, ...

DNAStrngSet

Demo

GRanges

Demo

AlignedRead and *GappedAlignment*

Demo

Sequence Annotations

- ▶ Existing infrastructure for gene-level annotation

GenomicFeatures

- ▶ Idea: retrieve annotations from common sources, e.g., UCSC genome browser 'known genes' track; save as a local data base.
- ▶ Query for regions of interest, e.g., exons per transcript

GenomicFeatures

Demo

Lab activity

Goal: Explore sequences and their annotation

1. Data input and exploration
2. Gapped alignments
3. Transcript annotations
4. Counting reads aligned to regions
5. (Differential representation)
6. Annotation to biological function

Example Data

Nagalakshmi et al., 2008. The transcriptional landscape of the yeast genome defined by RNA sequencing, *Science* 320: 1344–1349 [?].

- ▶ Original ‘RNA-seq’ experiment
- ▶ Two different primers to generate DNA from poly(A) RNA:
 - RH Random hexamer
 - dT oligo(dT)
- ▶ Biological and technical replicates
- ▶ Illumina GAI – relatively small number (<5 million / lane) of short (33bp) reads; poor trailing base quality.