

Package ‘pearson7’

October 14, 2022

Version 1.0-3

Date 2020-05-07

Title Maximum Likelihood Inference for the Pearson VII Distribution
with Shape Parameter 3/2

Author John Hughes

Maintainer John Hughes <drjphughesjr@gmail.com>

Description Supports maximum likelihood inference for the Pearson VII distribution with shape parameter 3/2 and free location and scale parameters. This distribution is relevant when estimating the velocity of processive motor proteins with random detachment.

License GPL (>= 2)

Collate 'pearson7.R' 'zzz.R'

RoxigenNote 5.0.1

NeedsCompilation no

Repository CRAN

Date/Publication 2020-05-08 09:30:03 UTC

R topics documented:

dpearson7	2
pearson7.fit	3
pearson7.objective	4
ppearson7	5
qpearson7	6
rpearson7	7
summary.pearson7	8

Index

9

dpearson7	<i>Evaluate the density for the Pearson VII distribution with shape parameter 3/2.</i>
-----------	--

Description

Evaluate the density for the Pearson VII distribution with shape parameter 3/2.

Usage

```
dpearson7(x, mu = 0, sigma = 1, log = FALSE)
```

Arguments

x	vector of quantiles.
mu	vector of means.
sigma	vector of scales.
log	logical; if TRUE, probabilities p are given as log(p).

Details

If `mu` is not specified, it assumes the default value of 0. If `sigma` is not specified, it assumes the default value of 1.

The Pearson VII distribution with location μ , scale σ , and shape 3/2 has density

$$f(x) = 1/(2\sigma)[1 + \{(x - \mu)/\sigma\}^2]^{-3/2}.$$

Value

the density.

References

Hughes, J., Shastry, S., Hancock, W. O., and Fricks, J. (2013) Estimating velocity for processive motor proteins with random detachment. *Journal of Agricultural, Biological, and Environmental Statistics*, in press.

Pearson, K. (1916) Mathematical contributions to the theory of evolution. xix. second supplement to a memoir on skew variation. *Philosophical Transactions of the Royal Society of London. Series A, Containing Papers of a Mathematical or Physical Character*, **216**, 429–457.

See Also

[ppearson7](#), [qpearson7](#), [rpearson7](#)

Examples

```
curve(dpearson7(x), -5, 5, lwd = 2, n = 500, ylab = "f(x)")
curve(dnorm(x), lwd = 2, lty = 2, n = 500, add = TRUE)
```

pearson7.fit

Find the MLE for a sample from the Pearson VII distribution with shape parameter 3/2.

Description

Find the MLE for a sample from the Pearson VII distribution with shape parameter 3/2.

Usage

```
pearson7.fit(y, mu0 = median(y), sigma0 = sqrt(3) * median(abs(y -
median(y))), tol = 1e-08)
```

Arguments

y	a vector of observations.
mu0	an initial value for μ .
sigma0	an initial value for σ .
tol	the convergence tolerance.

Details

This function uses a Newton-Raphson algorithm to find the MLE. The starting values for μ and σ are the sample median and $\sqrt{3}$ times the sample MAD, respectively. See the reference for details.

Value

`pearson7.fit` returns an object of class “pearson7”, which is a list containing the following components.

theta.hat	the estimates of μ and σ .
hessian	the Hessian matrix evaluated at <code>theta.hat</code> .
iterations	the number of iterations required to attain convergence.
value	the value of the log likelihood at <code>theta.hat</code> .

References

Hughes, J., Shastry, S., Hancock, W. O., and Fricks, J. (2013) Estimating velocity for processive motor proteins with random detachment. *Journal of Agricultural, Biological, and Environmental Statistics*, in press.

See Also[pearson7.objective](#)**Examples**

```
y = rpearson7(100, 100, 10)
fit = pearson7.fit(y)
fit
summary(fit)
```

pearson7.objective *Compute the negative log likelihood for a sample.*

Description

Compute the negative log likelihood for a sample.

Usage

```
pearson7.objective(params, y)
```

Arguments

params	a vector of parameter values.
y	a vector of observations.

Details

This function computes the negative log likelihood for (μ, σ) given a sample. This function can be optimized using [optim](#), but it is better to use [pearson7.fit](#).

Value

the negative log likelihood.

See Also[dpearson7](#), [pearson7.fit](#)

ppearson7	<i>Evaluate the distribution function for the Pearson VII distribution with shape parameter 3/2.</i>
------------------	--

Description

Evaluate the distribution function for the Pearson VII distribution with shape parameter 3/2.

Usage

```
ppearson7(q, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
```

Arguments

q	vector of quantiles.
mu	vector of means.
sigma	vector of scales.
lower.tail	logical; if TRUE (default), probabilities are $P(X \leq x)$, otherwise $P(X > x)$.
log.p	logical; if TRUE, probabilities p are given as log(p).

Details

If **mu** is not specified, it assumes the default value of 0. If **sigma** is not specified, it assumes the default value of 1.

The Pearson VII distribution with location μ , scale σ , and shape 3/2 has cdf

$$F(x) = \{1 + (x - \mu)/\sqrt{\sigma^2 + (x - \mu)^2}\}/2.$$

Value

the probability.

References

Hughes, J., Shastry, S., Hancock, W. O., and Fricks, J. (2013) Estimating velocity for processive motor proteins with random detachment. *Journal of Agricultural, Biological, and Environmental Statistics*, in press.

See Also

[dpearson7](#), [qpearson7](#), [rpearson7](#)

Examples

```
curve(ppearson7(x), 0, 5, lwd = 2, ylim = c(0.8, 1), ylab = "F(x)")
curve(pnorm(x), lwd = 2, lty = 2, add = TRUE)
```

qpearson7 Evaluate the quantile function for the Pearson VII distribution with shape parameter 3/2.

Description

Evaluate the quantile function for the Pearson VII distribution with shape parameter 3/2.

Usage

```
qpearson7(p, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
```

Arguments

p	vector of probabilities.
mu	vector of means.
sigma	vector of scales.
lower.tail	logical; if TRUE (default), probabilities are $P(X \leq x)$, otherwise $P(X > x)$.
log.p	logical; if TRUE, probabilities p are given as log(p).

Details

If **mu** is not specified, it assumes the default value of 0. If **sigma** is not specified, it assumes the default value of 1.

The Pearson VII distribution with location μ , scale σ , and shape 3/2 has quantile function

$$F^{-1}(x) = \mu + (\sigma/2)(2x - 1)/\sqrt{x(1-x)}.$$

Value

the quantile.

References

Hughes, J., Shastry, S., Hancock, W. O., and Fricks, J. (2013) Estimating velocity for processive motor proteins with random detachment. *Journal of Agricultural, Biological, and Environmental Statistics*, in press.

See Also

[dpearson7](#), [ppearson7](#), [rpearson7](#)

Examples

```
curve(qpearson7(x), 0, 1, lwd = 2, ylab = expression(F^{-1}(x)))
curve(qnorm(x), lwd = 2, lty = 2, n = 500, add = TRUE)
```

rpearson7

Generate random deviates from a Pearson VII distribution with shape parameter 3/2.

Description

Generate random deviates from a Pearson VII distribution with shape parameter 3/2.

Usage

```
rpearson7(n, mu = 0, sigma = 1)
```

Arguments

n	number of observations.
mu	vector of means.
sigma	vector of scales.

Details

If `mu` is not specified, it assumes the default value of 0. If `sigma` is not specified, it assumes the default value of 1.

Value

random deviates.

References

Hughes, J., Shastry, S., Hancock, W. O., and Fricks, J. (2013) Estimating velocity for processive motor proteins with random detachment. *Journal of Agricultural, Biological, and Environmental Statistics*, in press.

Devroye, L. (1986) *Non-Uniform Random Variate Generation*. New York: Springer-Verlag.

See Also

[dpearson7](#), [ppearson7](#), [qpearson7](#)

Examples

```
y = rpearson7(1000)
hist(y, prob = TRUE, breaks = 100, col = "gray")
curve(dpearson7(x), lwd = 2, col = "blue", add = TRUE)
```

summary.pearson7 *Print a summary of a Pearson VII fit.*

Description

Print a summary of a Pearson VII fit.

Usage

```
## S3 method for class 'pearson7'  
summary(object, alpha = 0.05, digits = 4, ...)
```

Arguments

- | | |
|---------------------|---|
| <code>object</code> | an object of class “pearson7”, the result of a call to pearson7.fit . |
| <code>alpha</code> | the significance level used to compute the confidence intervals. The default is 0.05. |
| <code>digits</code> | the number of significant digits to display. The default is 4. |
| <code>...</code> | additional arguments. |

Details

This function displays (1) a table of estimates, (2) the value of the log likelihood, and (3) the number of Newton-Raphson iterations. Each row of the table of estimates shows the parameter estimate and the approximate $(1 - \alpha)100\%$ confidence interval for the parameter.

See Also

[pearson7.fit](#)

Index

dpearson7, 2, 4–7
optim, 4
pearson7.fit, 3, 4, 8
pearson7.objective, 4, 4
ppearson7, 2, 5, 6, 7
qpearson7, 2, 5, 6, 7
rpearson7, 2, 5, 6, 7
summary.pearson7, 8