

Package ‘tidygee’

October 14, 2022

Title 'tidyverse' Methods for 'Earth Engine'

Version 0.1.0

Description Provides 'tidyverse' methods for wrangling and analyzing 'Earth Engine' <<https://earthengine.google.com/>> data. These methods help the user with filtering, joining and summarising 'Earth Engine' image collections.

License MIT + file LICENSE

URL <https://github.com/r-tidy-remote-sensing/tidygee>

BugReports <https://github.com/r-tidy-remote-sensing/tidygee/issues/>

Depends R (>= 4.1)

Imports assertthat, crayon, dplyr, glue, lubridate, purrr, readr, reticulate (>= 1.24), rgee, rlang, sf, stringr, tidyverse

Suggests knitr, rmarkdown, tibble, testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.2

NeedsCompilation no

Author Zack Arno [aut, cre, cph],
Josh Erickson [aut, cph]

Maintainer Zack Arno <zackarno@gmail.com>

Repository CRAN

Date/Publication 2022-09-15 08:00:02 UTC

R topics documented:

add_date_to_bandname	2
as_ee	3
as_tidye	3

bgd_msna	4
bind_ics	5
clip	6
create_tidyee	7
ee_composite	8
ee_extract_tidy	8
ee_month_composite	10
ee_month_filter	11
ee_year_composite	11
ee_year_filter	12
ee_year_month_composite	12
ee_year_month_filter	13
filter	14
filter_bounds	15
group_by	16
group_split	17
inner_join	18
mutate	18
print.tidyee	19
select	19
set_idx	20
slice	21
summarise	22
ungroup	23

Index**24**

add_date_to_bandname add_date_to_band_name

Description

append date to band name

Usage

```
add_date_to_bandname(x)
```

Arguments

x	ee\$ImageCollection or ee\$Image
---	----------------------------------

Value

a date to band name in x.

<code>as_ee</code>	<i>as_ee tidyee to ee\$ImageCollection or ee\$Image</i>
--------------------	---

Description

`as_ee` tidyee to ee\$ImageCollection or ee\$Image

Usage

```
as_ee(x)
```

Arguments

<code>x</code>	tidyee
----------------	--------

Value

ee\$ImageCollection or ee\$Image

Examples

```
## Not run:
library(rgee)
library(tidyee)

modis_ic <- ee$ImageCollection("MODIS/006/MOD13Q1")

# create tidyee class
modis_ic_tidy <- as_tidyee(modis_ic)
# convert back to origina ee$ImageCollection class
modis_ic_tidy |>
  as_ee()

## End(Not run)
```

<code>as_tidyee</code>	<i>as_tidyee</i>
------------------------	------------------

Description

The function returns a list containing the original object (Image/ImageCollection)as well as a "virtual data.frame (vrt)" which is a data.frame holding key properties of the ee\$Image/ee\$ImageCollection. The returned list has been assigned a new class "tidyee".

Usage

```
as_tidyee(x, time_end = FALSE)
```

Arguments

x	ee\$Image or ee\$ImageCollection
time_end	logical include time_end ("system:time_end") in vrt (default=F)

Value

tidyee class object which contains a list with two components ("x","vrt")

Examples

```
## Not run:
library(tidyrgee)
library(rgee)
ee_Initialize()
modis_ic <- ee$ImageCollection("MODIS/006/MOD13Q1")
modis_ic_tidy <- as_tidyee(modis_ic)

## End(Not run)
```

bgd_msna

*A subset of question responses from the 2019 Host Community MSNA
in Bangladesh*

Description

Data frame of responses with anonymized coordinates

Usage

`bgd_msna`

Format

A data frame with 1374 rows and 15 variables:

- _uuid** unique identifier
- informed_consent** informed consent
- survey_date** date of survey
- end_survey** date of end of survey
- electricity_grid** question about electricity grid
- solar_light** question about solar light
- illness_HH_count** repeat group calculation on # hh members with illness in past x days
- cooking_fuel/collected_firewood** select multiple response - did HH collect firewood for cooking fuel

income_source/agricultural_production_sale income source question - ariculture
agricultural_land question on agricultural land
employment_source/agricultural_casual employment source - ag
employment_source/non_agricultural_casual employment source - non-ag
employment_source/fishing employment source - fishing
_gps_reading_longitude longitude - jittered/anonymized
_gps_reading_latitude latitude - jittered/anonymized ...

Value

data frame

bind_ics *bind ImageCollections*

Description

bind ImageCollections

Usage

bind_ics(x)

Arguments

x list of tidyee objects

Value

tidyee object containing single image collection and vrt

Examples

```
## Not run:  
library(tidyrgee)  
library(rgee)  
ee_Initialize()  
modis_ic <- ee$ImageCollection("MODIS/006/MOD13Q1")  
modis_ic_tidy <- as_tidyee(modis_ic)  
modis_tidy_list <- modis_tidy |>  
group_split(month)  
modis_tidy_list |>  
bind_ics()  
  
## End(Not run)
```

clip*clip flexible wrapper for rgee::ee\$Image\$clip()***Description**

allows clipping of tidyee,ee\$Imagecollection, or ee\$Image classes. Also allows objects to be clipped to sf object in addition to ee\$FeatureCollections/ee\$Feature

Usage

```
clip(x, y, return_tidyee = TRUE)
```

Arguments

x	object to be clipped (tidyee, ee\$ImageCollection, ee\$Image)
y	geometry object to clip to (sf, ee\$Feature,ee\$FeatureCollections)
return_tidyee	logical return tidyee class (default = TRUE) object or ee\$ImageCollection. Faster performance if F

Value

x as tidyee or ee\$Image/ee\$ImageCollection depending on return_tidyee argument.

Examples

```
## Not run:
library(tidyrgee)
library(tidyverse)
library(rgee)
rgee::ee_Initialize()

# create geometry and convert to sf
coord_tibble <- tibble::tribble(
  ~X,           ~Y,
  92.2303683692011, 20.9126490153521,
  92.2311567217866, 20.9127410439304,
  92.2287527311594, 20.9124072954926,
  92.2289221219251, 20.9197352745068,
  92.238724724534, 20.9081803233546
)
sf_ob <- sf::st_as_sf(coord_tibble, coords=c("X", "Y"), crs=4326)

roi <- ee$Geometry$Polygon(list(
  c(-114.275, 45.891),
  c(-108.275, 45.868),
  c(-108.240, 48.868),
  c(-114.240, 48.891)
))
```

```

# load landsat
ls = ee$ImageCollection("LANDSAT/LC08/C01/T1_SR")

# create tidyee class
ls_tidy <- as_tidyee(ls)

# filter_bounds on sf object
# return tidyee object
ls_tidy |>
  filter_bounds(y = roi,return_tidyee = FALSE) |>
  clip(roi,return_tidyee = FALSE)

# pretty instant with return_tidyee=FALSE
ls_clipped_roi_ic <- ls_tidy |>
  filter_bounds(y = roi,return_tidyee = FALSE) |>
  clip(roi,return_tidyee = FALSE)

# takes more time with return_tidyee=T, but you get the vrt
ls_clipped_roi_tidyee <- ls_tidy |>
  filter_bounds(y = roi,return_tidyee = FALSE) |>
  clip(roi,return_tidyee = TRUE)

# demonstrating on sf object
ls_clipped_sf_ob_ic <- ls_tidy |>
  filter_bounds(y = sf_ob,return_tidyee = FALSE) |>
  clip(roi,return_tidyee = FALSE)

ls_clipped_sf_ob_tidyee <- ls_tidy |>
  filter_bounds(y = roi,return_tidyee = FALSE) |>
  clip(roi,return_tidyee = TRUE)

## End(Not run)

```

create_tidyee*create_tidyee***Description**

helper function to assign new tidyee when running `as_tidyee`

Usage

```
create_tidyee(x, vrt)
```

Arguments

x	ee\$ImageCollection
vrt	virtual table

Value

tidyee class list object

`ee_composite`

ee_composite

Description

`ee_composite`

Usage

```
ee_composite(x, ...)
## S3 method for class 'tidyee'
ee_composite(x, stat, ...)
```

Arguments

- `x` tidyee object containing ee\$ImageCollection
- `...` other arguments
- `stat` A character indicating what to reduce the ImageCollection by, e.g. 'median' (default), 'mean', 'max', 'min', 'sum', 'sd', 'first'.

Value

tidyee class containing ee\$Image where all images within ee\$ImageCollection have been aggregated based on pixel-level stats

`ee_extract_tidy`

ee_extract_tidy

Description

`ee_extract_tidy`

Usage

```
ee_extract_tidy(
  x,
  y,
  stat = "mean",
  scale,
  via = "getInfo",
  container = "rgee_backup",
  sf = TRUE,
  lazy = FALSE,
  quiet = FALSE,
  ...
)
```

Arguments

x	tidyee, ee\$Image, or ee\$ImageCollection
y	sf or ee\$feature or ee\$FeatureCollection
stat	zonal stat ("mean", "median", "min", "max" etc)
scale	A nominal scale in meters of the Image projection to work in. By default 1000.
via	Character. Method to export the image. Three method are implemented: "getInfo", "drive", "gcs".
container	Character. Name of the folder ('drive') or bucket ('gcs') to be exported into (ignore if via is not defined as "drive" or "gcs").
sf	Logical. Should return an sf object?
lazy	Logical. If TRUE, a future::sequential object is created to evaluate the task in the future. Ignore if via is set as "getInfo". See details.
quiet	Logical. Suppress info message.
...	additional parameters

Value

data.frame in long format with point estimates for each time-step and y feature based on statistic provided

See Also

[ee_extract](#) for information about ee_extract on ee\$ImageCollections and ee\$Images

Examples

```
## Not run:
library(rgee)
library(tidyrgee)
ee_Initialize()
modis_ic <- ee$ImageCollection("MODIS/006/MOD13Q1")
```

```

point_sample_buffered <- tidyrggee::bgd_msna |>
  sample_n(3) |>
  sf::st_as_sf(coords=c("_gps_reading_longitude",
                        "_gps_reading_latitude"), crs=4326) |>
  sf::st_transform(crs=32646) |>
  sf::st_buffer(dist = 500) |>
  dplyr::select(`_uuid`)
modis_ic_tidy <- as_tidyee(modis_ic)
modis_monthly_baseline_mean <- modis_ic_tidy |>
  select("NDVI") |>
  filter(year %in% 2000:2015) |>
  group_by(month) |>
  summarise(stat="mean")

ndvi_monthly_mean_at_pt<- modis_monthly_baseline_mean |>
  ee_extract(y = point_sample_buffered,
             fun="mean",
             scale = 500)

## End(Not run)

```

ee_month_composite *Pixel-level composite by month*

Description

Pixel-level composite by month

Usage

```

ee_month_composite(x, ...)

## S3 method for class 'ee.imagecollection.ImageCollection'
ee_month_composite(x, stat, months, ...)

## S3 method for class 'tidyee'
ee_month_composite(x, stat, ...)

```

Arguments

x	An earth engine ImageCollection or tidyee class.
...	extra args to pass on
stat	A character indicating what to reduce the ImageCollection by, e.g. 'median' (default), 'mean', 'max', 'min', 'sum', 'sd', 'first'.
months	A vector of months, e.g. c(1, 12).

Value

tidyee class containing ee\$Image or ee\$ImageCollection with pixels aggregated by month

`ee_month_filter` *ee_month_filter*

Description

`ee_month_filter`

Usage

```
ee_month_filter(imageCol, month, ...)
```

Arguments

<code>imageCol</code>	<code>ee\$ImageCollection</code>
<code>month</code>	numeric vector containing month values (1-12)
<code>...</code>	other arguments

Value

`ee$ImageCollection` or `ee$Image` filtered by month

`ee_year_composite` *Pixel level composite by year*

Description

Pixel level composite by year

Usage

```
ee_year_composite(x, ...)

## S3 method for class 'ee.imagecollection.ImageCollection'
ee_year_composite(x, stat, year, ...)

## S3 method for class 'tidyee'
ee_year_composite(x, stat, ...)
```

Arguments

<code>x</code>	An earth engine ImageCollection or tidyee class.
<code>...</code>	other arguments
<code>stat</code>	A character indicating what to reduce the ImageCollection by, e.g. 'median' (default), 'mean', 'max', 'min', 'sum', 'sd', 'first'.
<code>year</code>	numeric vector containing years (i.e c(2001,2002,2003))

Value

tidyee class containing ee\$Image or ee\$ImageCollection with pixels aggregated by year

<code>ee_year_filter</code>	<i>ee_year_filter</i>
-----------------------------	-----------------------

Description

`ee_year_filter`

Usage

```
ee_year_filter(imageCol, year, ...)
```

Arguments

<code>imageCol</code>	ee\$ImageCollection
<code>year</code>	numeric vector containing years (i.e c(2001,2002,2003))
<code>...</code>	other arguments

Value

ee\$ImageCollection or ee\$Image filtered by year

<code>ee_year_month_composite</code>	<i>Pixel-level composite by year and month</i>
--------------------------------------	--

Description

Pixel-level composite by year and month

Usage

```
ee_year_month_composite(x, ...)

## S3 method for class 'ee.imagecollection.ImageCollection'
ee_year_month_composite(x, stat, startDate, endDate, months, ...)

## S3 method for class 'tidyee'
ee_year_month_composite(x, stat, ...)
```

Arguments

x	An earth engine ImageCollection or tidyee class.
...	args to pass on.
stat	A character indicating what to reduce the ImageCollection by, e.g. 'median' (default), 'mean', 'max', 'min', 'sum', 'sd', 'first'.
startDate	character format date, e.g. "2018-10-23".
endDate	character format date, e.g. "2018-10-23".
months	numeric vector, e.g. c(1,12).

Value

tidyee class containing ee\$Image or ee\$ImageCollection with pixels aggregated by year and month

ee_year_month_filter *ee_year_month_filter*

Description

ee_year_month_filter

Usage

```
ee_year_month_filter(imageCol, year, month, ...)
```

Arguments

imageCol	ee\$ImageCollection
year	numeric vector contain years to filter
month	numeric vector contain months to filter
...	other arguments

Value

ee\$ImageCollection or ee\$Image filtered by year & month

<code>filter</code>	<i>filter ee\$ImageCollections or tidyee objects that contain imageCollections</i>
---------------------	--

Description

`filter ee$ImageCollections or tidyee objects that contain imageCollections`

Arguments

- .data ImageCollection or tidyee class object
- ... other arguments

Value

filtered image or imageCollection form filtered imageCollection

See Also

[filter](#) for information about filter on normal data tables.

Examples

```
## Not run:

library(rgee)
library(tidyrgee)
ee_Initialize()
l8 = ee$ImageCollection('LANDSAT/LC08/C01/T1_SR')
l8 |>
  filter(date>"2016-01-01",date<"2016-03-04")

# example with tidyee ckass
modis_ic <- ee$ImageCollection("MODIS/006/MOD13Q1")
modis_ic_tidy <- as_tidyee(modis_ic)

# filter by month
modis_march_april <- modis_ic_tidy |>
  filter(month %in% c(3,4))

## End(Not run)
```

<code>filter_bounds</code>	<i>filter_bounds a wrapper for rgee::ee\$ImageCollection\$filterBounds</i>
----------------------------	--

Description

`filter_bounds` a wrapper for `rgee::ee$ImageCollection$filterBounds`

Usage

```
filter_bounds(x, y, use_tidyee_index = FALSE, return_tidyee = TRUE)
```

Arguments

x	tidyee object containing ee\$ImageCollection or ee\$ImageCollection
y	feature to filter bounds by (sf, ee\$FeatureCollection, ee\$Feature, ee\$Geometry)
use_tidyee_index	filter on tidyee_index (default = F) or system_index (by default)
return_tidyee	logical return tidyee class (default = TRUE) object or ee\$ImageCollection. Faster performance if set to FALSE

Value

tidyee class or ee\$ImageCollection class object with scenes filtered to bounding box of y geometry

Examples

```
## Not run:

library(tidyrgee)
library(tidyverse)
library(rgee)
rgee::ee_Initialize()

# create geometry and convert to sf
coord_tibble <- tibble::tribble(
  ~X, ~Y,
  92.2303683692011, 20.9126490153521,
  92.2311567217866, 20.9127410439304,
  92.2287527311594, 20.9124072954926,
  92.2289221219251, 20.9197352745068,
  92.238724724534, 20.9081803233546
)
sf_ob <- sf::st_as_sf(coord_tibble, coords=c("X", "Y"), crs=4326)

# load landsat
ls = ee$ImageCollection("LANDSAT/LC08/C01/T1_SR")

#create tidyee class
```

```

ls_tidy <- as_tidyee(ls)

# filter_bounds on sf object
# return tidyee object
ls_tidy |>
  filter_bounds(sf_ob)
# return ee$ImageCollection
ls_tidy |>
  filter_bounds(sf_ob,return_tidyee = FALSE)

# filter_bounds on ee$Geometry object
# return tidyee object
ee_geom_ob <- sf_ob |> rgee::ee_as_sf()
ls_tidy |>
  filter_bounds(ee_geom_ob)

## End(Not run)

```

group_by

Group an imageCollection or tidyee object with Imagecollections by a parameter

Description

Group an imageCollection or tidyee object with Imagecollections by a parameter

Arguments

- .data ee\$ImageCollection or tidyee object
- ... group_by variables
- .add When FALSE, the default, group_by() will override existing groups. To add to the existing groups, use .add = TRUE.
This argument was previously called add, but that prevented creating a new grouping variable called add, and conflicts with our naming conventions.
- .drop Drop groups formed by factor levels that don't appear in the data? The default is TRUE except when .data has been previously grouped with .drop = FALSE. See [group_by_drop_default\(\)](#) for details.

Value

ee\$ImageCollection with grouped_vars attribute

See Also

[group_by](#) for information about group_by on normal data tables.

Examples

```
## Not run:
library(tidyrgee)
ee_Initialize()
modis_ic <- ee$ImageCollection("MODIS/006/MOD13Q1")
modis_ic |>
  filter(date>="2016-01-01",date<="2019-12-31") |>
  group_by(year)

## End(Not run)
```

group_split

filter ee\$ImageCollections or tidyee objects that contain imageCollections

Description

filter ee\$ImageCollections or tidyee objects that contain imageCollections

Arguments

- .tbl ImageCollection or tidyee class object
- ... other arguments
- return_tidyee logical return tidyee object(default =T), if FALSE - only return ee\$ImageCollection

Value

filtered image or imageCollection form filtered imageCollection

See Also

[group_split](#) for information about filter on normal data tables.

Examples

```
## Not run:
library(rgee)
library(tidyrgee)
ee_Initialize()
l8 = ee$ImageCollection('LANDSAT/LC08/C01/T1_SR')
l8 |>
  filter(date>"2016-01-01",date<"2016-03-04")

# example with tidyee ckass
modis_ic <- ee$ImageCollection("MODIS/006/MOD13Q1")
modis_ic_tidy <- as_tidyee(modis_ic)
```

```
# filter by month
modis_march_april <- modis_ic_tidy |>
filter(month %in% c(3,4))

## End(Not run)
```

inner_join

inner_join bands from different image/ImageCollections based on shared property

Description

`inner_join` bands from different image/ImageCollections based on shared property

Arguments

- | | |
|-------------------|--|
| <code>x, y</code> | A pair of tidyee objects containing ee\$ImageCollections |
| <code>by</code> | A character vector of variables to join by. |

Value

An object of the same type as `x`. The output has the following properties: Same number of images as `x` Total number of bands equal the number of bands in `x` plus the number of bands in `y`

See Also

[inner_join](#) for information about `inner_join` on normal data tables.

mutate

mutate columns into tidyee vrt which can later be used to modify tidyee ImageCollection

Description

`mutate` columns into tidyee `vrt` which can later be used to modify tidyee `ImageCollection`

Arguments

- | | |
|--------------------|--|
| <code>.data</code> | tidyee class object (list of ee_ob, vrt) |
| <code>...</code> | mutate arguments |

Value

return tidyee class object with `vrt` data.frame mutated.

See Also

[mutate](#) for information about mutate on normal data tables.

Examples

```
## Not run:  
library(tidyrgee)  
library(rgee)  
ee_Initialize()  
modis_ic <- ee$ImageCollection("MODIS/006/MOD13Q1")  
modis_ic_tidy <- as_tidyee(modis_ic)  
  
## End(Not run)
```

print.tidyee

print tidyee

Description

print tidyee

Usage

```
## S3 method for class 'tidyee'  
print(x, ...)
```

Arguments

x	tidyee object
...	additional arguments

Value

printed tidyee object

select

Select bands from ee\$Image or ee\$ImageCollection

Description

Select bands from ee\$Image or ee\$ImageCollection

Arguments

.data	tidyee class object containing ee\$ImageCollection or ee\$Image
...	one or more quoted or unquoted expressions separated by commas.

Value

tidyee class object with specified (...) bands selected

See Also

[select](#) for information about select on normal data tables.

Examples

```
## Not run:
library(tidyrgee)
ee_Initialize()
modis_ic <- ee$ImageCollection("MODIS/006/MOD13Q1")
modis_ic_tidy <- as_tidyee(modis_ic)

# select NDVI band
modis_ndvi <- modis_ic_tidy |>
  select("NDVI")

# select NDVI band, but change band to new name
modis_ndvi_renamed <- modis_ic_tidy |>
  select(ndvi_new= "NDVI")

## End(Not run)
```

*set_idx**set_idx***Description**

`set_idx`

Usage

```
set_idx(x, idx_name = "tidyee_index")
```

Arguments

<code>x</code>	tidyee or ee\$ImageCollection class object
<code>idx_name</code>	name for index to create (default = "tidyee_index")

Value

tidyee or ee\$ImageCollection class object with new index containing sequential 0-based indexing

Examples

```
## Not run:
library(rgee)
library(tidyrggee)
ee_Initialize()
modis_link <- "MODIS/006/MOD13Q1"
modisIC <- ee$ImageCollection(modis_link)
modis_ndvi_tidy <- as_tidyee(modisIC) |>
  select("NDVI")
modis_ndvi_tidy |>

## End(Not run)
```

slice

slice ee\$ImageCollections or tidyee objects that contain imageCollections

Description

slice ee\$ImageCollections or tidyee objects that contain imageCollections

Arguments

.data	ImageCollection or tidyee class object
...	other arguments

Value

sliced/filtered image or imageCollection form filtered imageCollection

See Also

[slice](#) for information about slice on normal data tables.

Examples

```
## Not run:
library(rgee)
library(tidyrggee)
ee_Initialize()
l8 = ee$ImageCollection('LANDSAT/LC08/C01/T1_SR')
l8 |>
  filter(date>"2016-01-01",date<"2016-03-04")

# example with tidyee ckass
modis_ic <- ee$ImageCollection("MODIS/006/MOD13Q1")
```

```

modis_ic_tidy <- as_tidyee(modis_ic)

# filter by month
modis_march_april <- modis_ic_tidy |>
  filter(month %in% c(3,4))

## End(Not run)

```

summarise

Summary pixel-level stats for ee\$ImageCollection or tidyrggee objects with ImageCollections

Description

Summary pixel-level stats for ee\$ImageCollection or tidyrggee objects with ImageCollections

Usage

```

## S3 method for class 'ee.imagecollection.ImageCollection'
summarise(.data, stat, ...)

## S3 method for class 'tidyee'
summarise(.data, stat, ..., join_bands = TRUE)

```

Arguments

.data	ee\$Image or ee\$ImageCollection
stat	character stat/function to apply
...	other arguments
join_bands	logical (default= TRUE) if multiple stats selected should bands be joined?

Value

ee\$Image or ee\$ImageCollection where pixels are summarised by group_by and stat
 ee\$Image or ee\$ImageCollection where pixels are summarised by group_by and stat
 ee\$Image or ee\$ImageCollection where pixels are summarised by group_by and stat

See Also

[summarise](#) for information about summarise on normal data tables.

Examples

```
## Not run:  
library(tidyrggee)  
library(rgee)  
ee_Initialize()  
modis_ic <- ee$ImageCollection("MODIS/006/MOD13Q1")  
modis_ic |>  
  filter(date>="2016-01-01",date<="2019-12-31") |>  
  group_by(year) |>  
  summarise(stat="max")  
  
## End(Not run)
```

ungroup

ungroup

Description

`ungroup`

Arguments

x	tidyee object
...	ungroup args

Value

tidyee class object with vrt ungrouped.

See Also

[ungroup](#) for information about `ungroup` on normal data tables.

Index

* **datasets**
 bgd_msna, 4

 add_date_to_bandname, 2
 as_ee, 3
 as_tidyee, 3

 bgd_msna, 4
 bind_ics, 5

 clip, 6
 create_tidyee, 7

 ee_composite, 8
 ee_extract, 9
 ee_extract_tidy, 8
 ee_month_composite, 10
 ee_month_filter, 11
 ee_year_composite, 11
 ee_year_filter, 12
 ee_year_month_composite, 12
 ee_year_month_filter, 13

 filter, 14, 14
 filter_bounds, 15

 group_by, 16, 16
 group_by_drop_default(), 16
 group_split, 17, 17

 inner_join, 18, 18

 mutate, 18, 19

 print.tidyee, 19

 select, 19, 20
 set_idx, 20
 slice, 21, 21
 summarise, 22, 22

 ungroup, 23, 23