Package ‘torch’

June 23, 2025

Type Package

Title Tensors and Neural Networks with 'GPU' Acceleration

Version 0.15.0

Description Provides functionality to define and train neural networks similar to 'PyTorch' by Paszke et al (2019) <doi:10.48550/arXiv.1912.01703> but written entirely in R using the 'libtorch' library. Also supports low-level tensor operations and 'GPU' acceleration.

License MIT + file LICENSE

URL https://torch.mlverse.org/docs, https://github.com/mlverse/torch

BugReports https://github.com/mlverse/torch/issues

Encoding UTF-8

SystemRequirements LibTorch (https://pytorch.org/); Only x86_64 platforms are currently supported except for ARM system running macOS.

Config/build/copy-method copy

LinkingTo Rcpp

Imports Rcpp, R6, withr, rlang (>= 1.0.0), methods, utils, stats, bit64, magrittr, tools, coro (>= 1.0.2), callr, cli (>= 3.0.0), glue, desc, safetensors (>= 0.1.1), jsonlite, scales

RoxygenNote 7.3.2

Suggests testthat (>= 3.0.0), covr, knitr (>= 1.36), rmarkdown, palmerpenguins, mvtnorm, numDeriv, katex

VignetteBuilder knitr

Collate 'R7.R' 'RcppExports.R' 'autocast.R' 'tensor.R' 'autograd.R' 'backends.R' 'call_torch_function.R' 'codegen-utils.R' 'compare.R' 'compat-purrr.R' 'compilation_unit.R' 'conditions.R' 'contrib.R' 'creation-ops.R' 'cuda.R' 'device.R' 'dimname_list.R' 'utils.R' 'distributions-constraints.R' 'distributions-utils.R' 'distributions-exp-family.R' 'distributions.R' 'distributions-bernoulli.R' 'distributions-categorical.R' 'distributions-gamma.R'

'distributions-chi2.R' 'distributions-mixture_same_family.R'
'distributions-multivariate_normal.R' 'distributions-normal.R'
'distributions-poisson.R' 'dtype.R' 'gen-method.R'
'gen-namespace-docs.R' 'gen-namespace-examples.R'
'gen-namespace.R' 'generator.R' 'help.R' 'utils-data.R'
'optim.R' 'optim-adam.R' 'optim-sgd.R' 'optim-rmsprop.R'
'optim-adagrad.R' 'optim-adamw.R' 'ignite.R' 'indexing.R'
'install.R' 'ivalue.R' 'jit-compile.R' 'jit-execute.R'
'jit-ops.R' 'lantern_load.R' 'lantern_sync.R' 'layout.R'
'linalg.R' 'memory_format.R' 'nn.R' 'nn-activation.R'
'nn-batchnorm.R' 'nn-conv.R' 'nn-distance.R' 'nn-dropout.R'
'nn-flatten.R' 'nn-init.R' 'nn-linear.R' 'nn-loss.R'
'nn-normalization.R' 'nn-pooling.R' 'nn-rnn.R' 'nn-sparse.R'
'nn-transformer.R' 'nn-upsampling.R' 'nn-utils-clip-grad.R'
'nn-utils-rnn.R' 'nn-utils-weight-norm.R' 'nn-utils.R'
'nn_adaptive.R' 'nnf-activation.R' 'nnf-batchnorm.R'
'nnf-conv.R' 'nnf-distance.R' 'nnf-dropout.R' 'nnf-embedding.R'
'nnf-fold.R' 'nnf-instancenorm.R' 'nnf-linear.R' 'nnf-loss.R'
'nnf-normalization.R' 'nnf-padding.R' 'nnf-pixelshuffle.R'
'nnf-pooling.R' 'nnf-upsampling.R' 'nnf-vision.R' 'operators.R'
'optim-adadelta.R' 'optim-asgd.R' 'optim-lbfgs.R'
'optim-lr_scheduler.R' 'optim-rprop.R' 'positron.R' 'package.R'
'qscheme.R' 'quantization.R' 'reduction.R' 'save.R' 'scalar.R'
'script_module.R' 'stack.R' 'storage.R' 'threads.R' 'trace.R'
'translate.R' 'type-info.R' 'utils-data-collate.R'
'utils-data-dataloader.R' 'utils-data-enum.R'
'utils-data-fetcher.R' 'utils-data-sampler.R' 'utils-pipe.R'
'variable_list.R' 'with-indices.R' 'wrapers.R'

NeedsCompilation yes

Author Daniel Falbel [aut, cre, cph],
Javier Luraschi [aut],
Dmitriy Selivanov [ctb],
Athos Damiani [ctb],
Christophe Regouby [ctb],
Krzysztof Joachimiak [ctb],
Hamada S. Badr [ctb],
Sebastian Fischer [ctb],
Maximilian Pichler [ctb],
RStudio [cph]

Maintainer Daniel Falbel <daniel@rstudio.com>

Repository CRAN

Date/Publication 2025-06-23 20:30:02 UTC

Contents

as_array 17

AutogradContext . . . 18
autograd_backward . . . 20
autograd_function . . . 21
autograd_grad . . . 22
autograd_set_grad_mode . . . 23
backends_cudnn_is_available . . . 23
backends_cudnn_version . . . 24
backends_mkldnn_is_available . . . 24
backends_mkl_is_available . . . 24
backends_mps_is_available . . . 25
backends_openmp_is_available . . . 25
broadcast_all . . . 26
clone_module . . . 26
Constraint . . . 27
contrib_sort_vertices . . . 28
cuda_amp_grad_scaler . . . 29
cuda_current_device . . . 29
cuda_device_count . . . 30
cuda_dump_memory_snapshot . . . 30
cuda_empty_cache . . . 31
cuda_get_device_capability . . . 31
cuda_is_available . . . 31
cuda_memory_snapshot . . . 32
cuda_memory_stats . . . 32
cuda_record_memory_history . . . 34
cuda_runtime_version . . . 35
cuda_synchronize . . . 35
dataloader . . . 36
dataloader_make_iter . . . 38
dataloader_next . . . 38
dataset . . . 38
dataset_subset . . . 40
Distribution . . . 40
distr_bernoulli . . . 43
distr_categorical . . . 44
distr_chi2 . . . 45
distr_gamma . . . 46
distr_mixture_same_family . . . 46
distr_multivariate_normal . . . 47
distr_normal . . . 48
distr_poisson . . . 49
enumerate . . . 50
enumerate.dataloader . . . 50
get_install_libs_url . . . 51
install_torch . . . 52
is_dataloader . . . 53
is_nn_buffer . . . 53
is_nn_module . . . 54

is_nn_parameter . . . 54
is_optimizer . . . 54
is_torch_device . . . 55
is_torch_dtype . . . 55
is_torch_layout . . . 55
is_torch_memory_format . . . 56
is_torch_qscheme . . . 56
is_undefined_tensor . . . 56
iterable_dataset . . . 57
jit_compile . . . 58
jit_load . . . 58
jit_ops . . . 59
jit_save . . . 60
jit_save_for_mobile . . . 60
jit_scalar . . . 61
jit_serialize . . . 61
jit_trace . . . 62
jit_trace_module . . . 63
jit_tuple . . . 64
jit_unserialize . . . 65
linalg_cholesky . . . 65
linalg_cholesky_ex . . . 66
linalg_cond . . . 67
linalg_det . . . 69
linalg_eig . . . 70
linalg_eigh . . . 71
linalg_eigvals . . . 73
linalg_eigvalsh . . . 74
linalg_householder_product . . . 75
linalg_inv . . . 76
linalg_inv_ex . . . 77
linalg_lstsq . . . 78
linalg_matrix_norm . . . 80
linalg_matrix_power . . . 82
linalg_matrix_rank . . . 83
linalg_multi_dot . . . 84
linalg_norm . . . 85
linalg_pinv . . . 87
linalg_qr . . . 88
linalg_slogdet . . . 89
linalg_solve . . . 90
linalg_solve_triangular . . . 91
linalg_svd . . . 92
linalg_svdvals . . . 94
linalg_tensorinv . . . 95
linalg_tensorsolve . . . 96
linalg_vector_norm . . . 97
load_state_dict . . . 99

local_autocast . . . 99
local_device . . . 101
lr_cosine_annealing . . . 102
lr_lambda . . . 102
lr_multiplicative . . . 103
lr_one_cycle . . . 104
lr_reduce_on_plateau . . . 106
lr_scheduler . . . 108
lr_step . . . 108
nnf_adaptive_avg_pool1d . . . 109
nnf_adaptive_avg_pool2d . . . 109
nnf_adaptive_avg_pool3d . . . 110
nnf_adaptive_max_pool1d . . . 110
nnf_adaptive_max_pool2d . . . 111
nnf_adaptive_max_pool3d . . . 111
nnf_affine_grid . . . 112
nnf_alpha_dropout . . . 112
nnf_area_under_min_fpr_fnr . . . 113
nnf_avg_pool1d . . . 113
nnf_avg_pool2d . . . 114
nnf_avg_pool3d . . . 115
nnf_batch_norm . . . 116
nnf_bilinear . . . 116
nnf_binary_cross_entropy . . . 117
nnf_binary_cross_entropy_with_logits . . . 118
nnf_celu . . . 118
nnf_contrib_sparsemax . . . 119
nnf_conv1d . . . 119
nnf_conv2d . . . 120
nnf_conv3d . . . 121
nnf_conv_tbc . . . 121
nnf_conv_transpose1d . . . 122
nnf_conv_transpose2d . . . 123
nnf_conv_transpose3d . . . 124
nnf_cosine_embedding_loss . . . 125
nnf_cosine_similarity . . . 125
nnf_cross_entropy . . . 126
nnf_ctc_loss . . . 127
nnf_dropout . . . 128
nnf_dropout2d . . . 128
nnf_dropout3d . . . 129
nnf_elu . . . 129
nnf_embedding . . . 130
nnf_embedding_bag . . . 131
nnf_fold . . . 132
nnf_fractional_max_pool2d . . . 133
nnf_fractional_max_pool3d . . . 134
nnf_gelu . . . 135

nnf_glu . . . 135
nnf_grid_sample . . . 136
nnf_group_norm . . . 137
nnf_gumbel_softmax . . . 138
nnf_hardshrink . . . 138
nnf_hardsigmoid . . . 139
nnf_hardswish . . . 139
nnf_hardtanh . . . 140
nnf_hinge_embedding_loss . . . 140
nnf_instance_norm . . . 141
nnf_interpolate . . . 141
nnf_kl_div . . . 143
nnf_l1_loss . . . 143
nnf_layer_norm . . . 144
nnf_leaky_relu . . . 144
nnf_linear . . . 145
nnf_local_response_norm . . . 145
nnf_logsigmoid . . . 146
nnf_log_softmax . . . 146
nnf_lp_pool1d . . . 147
nnf_lp_pool2d . . . 147
nnf_margin_ranking_loss . . . 148
nnf_max_pool1d . . . 148
nnf_max_pool2d . . . 149
nnf_max_pool3d . . . 150
nnf_max_unpool1d . . . 150
nnf_max_unpool2d . . . 151
nnf_max_unpool3d . . . 152
nnf_mse_loss . . . 152
nnf_multilabel_margin_loss . . . 153
nnf_multilabel_soft_margin_loss . . . 153
nnf_multi_head_attention_forward . . . 154
nnf_multi_margin_loss . . . 156
nnf_nll_loss . . . 157
nnf_normalize . . . 158
nnf_one_hot . . . 158
nnf_pad . . . 159
nnf_pairwise_distance . . . 160
nnf_pdist . . . 160
nnf_pixel_shuffle . . . 161
nnf_poisson_nll_loss . . . 161
nnf_prelu . . . 162
nnf_relu . . . 162
nnf_relu6 . . . 163
nnf_rrelu . . . 163
nnf_selu . . . 164
nnf_sigmoid . . . 164
nnf_silu . . . 165

nnf_smooth_l1_loss . . . 165
nnf_softmax . . . 166
nnf_softmin . . . 166
nnf_softplus . . . 167
nnf_softshrink . . . 168
nnf_softsign . . . 168
nnf_soft_margin_loss . . . 169
nnf_tanhshrink . . . 169
nnf_threshold . . . 170
nnf_triplet_margin_loss . . . 170
nnf_triplet_margin_with_distance_loss . . . 171
nnf_unfold . . . 172
nn_adaptive_avg_pool1d . . . 173
nn_adaptive_avg_pool2d . . . 173
nn_adaptive_avg_pool3d . . . 174
nn_adaptive_log_softmax_with_loss . . . 175
nn_adaptive_max_pool1d . . . 177
nn_adaptive_max_pool2d . . . 177
nn_adaptive_max_pool3d . . . 178
nn_aum_loss . . . 179
nn_avg_pool1d . . . 180
nn_avg_pool2d . . . 181
nn_avg_pool3d . . . 182
nn_batch_norm1d . . . 184
nn_batch_norm2d . . . 185
nn_batch_norm3d . . . 187
nn_bce_loss . . . 188
nn_bce_with_logits_loss . . . 190
nn_bilinear . . . 191
nn_buffer . . . 192
nn_celu . . . 193
nn_contrib_sparsemax . . . 194
nn_conv1d . . . 194
nn_conv2d . . . 196
nn_conv3d . . . 199
nn_conv_transpose1d . . . 201
nn_conv_transpose2d . . . 203
nn_conv_transpose3d . . . 206
nn_cosine_embedding_loss . . . 209
nn_cross_entropy_loss . . . 209
nn_ctc_loss . . . 211
nn_dropout . . . 213
nn_dropout2d . . . 214
nn_dropout3d . . . 215
nn_elu . . . 216
nn_embedding . . . 216
nn_embedding_bag . . . 218
nn_flatten . . . 219

nn_fractional_max_pool2d . . . 220
nn_fractional_max_pool3d . . . 221
nn_gelu . . . 222
nn_glu . . . 223
nn_group_norm . . . 223
nn_gru . . . 225
nn_hardshrink . . . 227
nn_hardsigmoid . . . 227
nn_hardswish . . . 228
nn_hardtanh . . . 229
nn_hinge_embedding_loss . . . 230
nn_identity . . . 231
nn_init_calculate_gain . . . 231
nn_init_constant_ . . . 232
nn_init_dirac_ . . . 232
nn_init_eye_ . . . 233
nn_init_kaiming_normal_ . . . 233
nn_init_kaiming_uniform_ . . . 234
nn_init_normal_ . . . 235
nn_init_ones_ . . . 236
nn_init_orthogonal_ . . . 236
nn_init_sparse_ . . . 237
nn_init_trunc_normal_ . . . 237
nn_init_uniform_ . . . 238
nn_init_xavier_normal_ . . . 239
nn_init_xavier_uniform_ . . . 239
nn_init_zeros_ . . . 240
nn_kl_div_loss . . . 240
nn_l1_loss . . . 241
nn_layer_norm . . . 242
nn_leaky_relu . . . 244
nn_linear . . . 245
nn_log_sigmoid . . . 246
nn_log_softmax . . . 246
nn_lp_pool1d . . . 247
nn_lp_pool2d . . . 248
nn_lstm . . . 250
nn_margin_ranking_loss . . . 252
nn_max_pool1d . . . 253
nn_max_pool2d . . . 254
nn_max_pool3d . . . 255
nn_max_unpool1d . . . 257
nn_max_unpool2d . . . 258
nn_max_unpool3d . . . 259
nn_module . . . 260
nn_module_dict . . . 262
nn_module_list . . . 263
nn_mse_loss . . . 264

nn_multihead_attention . . . 265
nn_multilabel_margin_loss . . . 267
nn_multilabel_soft_margin_loss . . . 268
nn_multi_margin_loss . . . 269
nn_nll_loss . . . 270
nn_pairwise_distance . . . 271
nn_parameter . . . 272
nn_poisson_nll_loss . . . 273
nn_prelu . . . 274
nn_prune_head . . . 275
nn_relu . . . 276
nn_relu6 . . . 276
nn_rnn . . . 277
nn_rrelu . . . 279
nn_selu . . . 280
nn_sequential . . . 281
nn_sigmoid . . . 282
nn_silu . . . 282
nn_smooth_l1_loss . . . 283
nn_softmax . . . 284
nn_softmax2d . . . 285
nn_softmin . . . 285
nn_softplus . . . 286
nn_softshrink . . . 287
nn_softsign . . . 288
nn_soft_margin_loss . . . 288
nn_tanh . . . 289
nn_tanhshrink . . . 290
nn_threshold . . . 290
nn_transformer_encoder . . . 291
nn_transformer_encoder_layer . . . 292
nn_triplet_margin_loss . . . 293
nn_triplet_margin_with_distance_loss . . . 295
nn_unflatten . . . 297
nn_upsample . . . 298
nn_utils_clip_grad_norm_ . . . 299
nn_utils_clip_grad_value_ . . . 299
nn_utils_rnn_pack_padded_sequence . . . 300
nn_utils_rnn_pack_sequence . . . 301
nn_utils_rnn_pad_packed_sequence . . . 302
nn_utils_rnn_pad_sequence . . . 303
nn_utils_weight_norm . . . 304
optimizer . . . 306
OptimizerIgnite . . . 308
optimizer_ignite . . . 310
optim_adadelta . . . 310
optim_adagrad . . . 312
optim_adam . . . 313

optim_adamw . . . 314
optim_asgd . . . 315
optim_ignite_adagrad . . . 316
optim_ignite_adam . . . 317
optim_ignite_adamw . . . 318
optim_ignite_rmsprop . . . 319
optim_ignite_sgd . . . 320
optim_lbfgs . . . 321
optim_required . . . 322
optim_rmsprop . . . 323
optim_rprop . . . 324
optim_sgd . . . 325
sampler . . . 326
tensor_dataset . . . 327
threads . . . 327
torch_abs . . . 328
torch_absolute . . . 328
torch_acos . . . 329
torch_acosh . . . 329
torch_adaptive_avg_pool1d . . . 330
torch_add . . . 331
torch_addbmm . . . 332
torch_addcdiv . . . 333
torch_addcmul . . . 334
torch_addmm . . . 335
torch_addmv . . . 336
torch_addr . . . 337
torch_allclose . . . 338
torch_amax . . . 339
torch_amin . . . 340
torch_angle . . . 341
torch_arange . . . 341
torch_arccos . . . 343
torch_arccosh . . . 343
torch_arcsin . . . 344
torch_arcsinh . . . 344
torch_arctan . . . 345
torch_arctanh . . . 345
torch_argmax . . . 346
torch_argmin . . . 347
torch_argsort . . . 348
torch_asin . . . 348
torch_asinh . . . 349
torch_as_strided . . . 350
torch_atan . . . 351
torch_atan2 . . . 351
torch_atanh . . . 352
torch_atleast_1d . . . 353

torch_atleast_2d . . . 354
torch_atleast_3d . . . 354
torch_avg_pool1d . . . 355
torch_baddbmm . . . 356
torch_bartlett_window . . . 357
torch_bernoulli . . . 358
torch_bincount . . . 359
torch_bitwise_and . . . 360
torch_bitwise_not . . . 360
torch_bitwise_or . . . 361
torch_bitwise_xor . . . 361
torch_blackman_window . . . 362
torch_block_diag . . . 363
torch_bmm . . . 363
torch_broadcast_tensors . . . 364
torch_bucketize . . . 365
torch_can_cast . . . 366
torch_cartesian_prod . . . 366
torch_cat . . . 367
torch_cdist . . . 368
torch_ceil . . . 368
torch_celu . . . 369
torch_celu_ . . . 370
torch_chain_matmul . . . 370
torch_channel_shuffle . . . 371
torch_cholesky . . . 372
torch_cholesky_inverse . . . 373
torch_cholesky_solve . . . 374
torch_chunk . . . 375
torch_clamp . . . 375
torch_clip . . . 376
torch_clone . . . 377
torch_combinations . . . 378
torch_complex . . . 378
torch_conj . . . 379
torch_conv1d . . . 380
torch_conv2d . . . 381
torch_conv3d . . . 382
torch_conv_tbc . . . 383
torch_conv_transpose1d . . . 383
torch_conv_transpose2d . . . 384
torch_conv_transpose3d . . . 386
torch_cos . . . 387
torch_cosh . . . 388
torch_cosine_similarity . . . 388
torch_count_nonzero . . . 389
torch_cross . . . 390
torch_cummax . . . 391

torch_cummin . . . 391
torch_cumprod . . . 392
torch_cumsum . . . 393
torch_deg2rad . . . 394
torch_dequantize . . . 394
torch_det . . . 395
torch_device . . . 396
torch_diag . . . 396
torch_diagflat . . . 397
torch_diagonal . . . 398
torch_diag_embed . . . 399
torch_diff . . . 400
torch_digamma . . . 401
torch_dist . . . 401
torch_div . . . 402
torch_divide . . . 403
torch_dot . . . 404
torch_dstack . . . 405
torch_dtype . . . 406
torch_eig . . . 407
torch_einsum . . . 407
torch_empty . . . 409
torch_empty_like . . . 410
torch_empty_strided . . . 411
torch_eq . . . 412
torch_equal . . . 413
torch_erf . . . 413
torch_erfc . . . 414
torch_erfinv . . . 415
torch_exp . . . 415
torch_exp2 . . . 416
torch_expm1 . . . 417
torch_eye . . . 417
torch_fft_fft . . . 418
torch_fft_fftfreq . . . 419
torch_fft_ifft . . . 420
torch_fft_irfft . . . 421
torch_fft_rfft . . . 422
torch_finfo . . . 423
torch_fix . . . 423
torch_flatten . . . 424
torch_flip . . . 424
torch_fliplr . . . 425
torch_flipud . . . 426
torch_floor . . . 427
torch_floor_divide . . . 427
torch_fmod . . . 428
torch_frac . . . 429

torch_full . . . 429
torch_full_like . . . 430
torch_gather . . . 431
torch_gcd . . . 432
torch_ge . . . 433
torch_generator . . . 434
torch_geqrf . . . 434
torch_ger . . . 435
torch_get_rng_state . . . 436
torch_greater . . . 436
torch_greater_equal . . . 437
torch_gt . . . 437
torch_hamming_window . . . 438
torch_hann_window . . . 439
torch_heaviside . . . 440
torch_histc . . . 441
torch_hstack . . . 442
torch_hypot . . . 442
torch_i0 . . . 443
torch_iinfo . . . 444
torch_imag . . . 444
torch_index . . . 445
torch_index_put . . . 445
torch_index_put_ . . . 446
torch_index_select . . . 446
torch_install_path . . . 447
torch_inverse . . . 447
torch_isclose . . . 448
torch_isfinite . . . 449
torch_isinf . . . 450
torch_isnan . . . 450
torch_isneginf . . . 451
torch_isposinf . . . 451
torch_isreal . . . 452
torch_istft . . . 453
torch_is_complex . . . 454
torch_is_floating_point . . . 455
torch_is_installed . . . 455
torch_is_nonzero . . . 456
torch_kaiser_window . . . 456
torch_kron . . . 458
torch_kthvalue . . . 458
torch_layout . . . 459
torch_lcm . . . 459
torch_le . . . 460
torch_lerp . . . 461
torch_less . . . 462
torch_less_equal . . . 462

torch_lgamma . . . 463
torch_linspace . . . 463
torch_load . . . 464
torch_log . . . 465
torch_log10 . . . 465
torch_log1p . . . 466
torch_log2 . . . 467
torch_logaddexp . . . 468
torch_logaddexp2 . . . 468
torch_logcumsumexp . . . 469
torch_logdet . . . 470
torch_logical_and . . . 471
torch_logical_not . . . 471
torch_logical_or . . . 472
torch_logical_xor . . . 473
torch_logit . . . 473
torch_logspace . . . 474
torch_logsumexp . . . 475
torch_lstsq . . . 476
torch_lt . . . 477
torch_lu . . . 478
torch_lu_solve . . . 478
torch_lu_unpack . . . 479
torch_manual_seed . . . 480
torch_masked_select . . . 481
torch_matmul . . . 482
torch_matrix_exp . . . 483
torch_matrix_power . . . 484
torch_matrix_rank . . . 485
torch_max . . . 485
torch_maximum . . . 487
torch_mean . . . 487
torch_median . . . 488
torch_memory_format . . . 489
torch_meshgrid . . . 490
torch_min . . . 490
torch_minimum . . . 492
torch_mm . . . 493
torch_mode . . . 493
torch_movedim . . . 494
torch_mul . . . 495
torch_multinomial . . . 496
torch_multiply . . . 497
torch_mv . . . 498
torch_mvlgamma . . . 498
torch_nanquantile . . . 499
torch_nansum . . . 500
torch_narrow . . . 501

torch_ne . . . 502
torch_neg . . . 503
torch_negative . . . 503
torch_nextafter . . . 504
torch_nonzero . . . 504
torch_norm . . . 505
torch_normal . . . 506
torch_not_equal . . . 508
torch_ones . . . 508
torch_ones_like . . . 509
torch_orgqr . . . 510
torch_ormqr . . . 511
torch_outer . . . 511
torch_pdist . . . 512
torch_pinverse . . . 513
torch_pixel_shuffle . . . 514
torch_poisson . . . 514
torch_polar . . . 515
torch_polygamma . . . 516
torch_pow . . . 517
torch_prod . . . 518
torch_promote_types . . . 519
torch_qr . . . 520
torch_qscheme . . . 521
torch_quantile . . . 521
torch_quantize_per_channel . . . 522
torch_quantize_per_tensor . . . 523
torch_rad2deg . . . 524
torch_rand . . . 524
torch_randint . . . 525
torch_randint_like . . . 526
torch_randn . . . 527
torch_randn_like . . . 529
torch_randperm . . . 530
torch_rand_like . . . 531
torch_range . . . 532
torch_real . . . 533
torch_reciprocal . . . 534
torch_reduction . . . 534
torch_relu . . . 535
torch_relu_ . . . 535
torch_remainder . . . 536
torch_renorm . . . 536
torch_repeat_interleave . . . 537
torch_reshape . . . 538
torch_result_type . . . 539
torch_roll . . . 540
torch_rot90 . . . 540

torch_round . . . 541
torch_rrelu_ . . . 542
torch_rsqrt . . . 543
torch_save . . . 543
torch_scalar_tensor . . . 544
torch_searchsorted . . . 545
torch_selu . . . 546
torch_selu_ . . . 546
torch_serialize . . . 547
torch_set_default_dtype . . . 547
torch_sgn . . . 548
torch_sigmoid . . . 548
torch_sign . . . 549
torch_signbit . . . 550
torch_sin . . . 550
torch_sinh . . . 551
torch_slogdet . . . 552
torch_sort . . . 553
torch_sparse_coo_tensor . . . 553
torch_split . . . 555
torch_sqrt . . . 556
torch_square . . . 556
torch_squeeze . . . 557
torch_stack . . . 558
torch_std . . . 558
torch_std_mean . . . 559
torch_stft . . . 560
torch_sub . . . 563
torch_subtract . . . 563
torch_sum . . . 564
torch_svd . . . 565
torch_t . . . 566
torch_take . . . 567
torch_take_along_dim . . . 568
torch_tan . . . 569
torch_tanh . . . 569
torch_tensor . . . 570
torch_tensordot . . . 571
torch_tensor_from_buffer . . . 571
torch_threshold_ . . . 572
torch_topk . . . 573
torch_trace . . . 574
torch_transpose . . . 574
torch_trapz . . . 575
torch_triangular_solve . . . 576
torch_tril . . . 577
torch_tril_indices . . . 578
torch_triu . . . 579

torch_triu_indices 580
torch_true_divide 582
torch_trunc 582
torch_unbind 583
torch_unique_consecutive 584
torch_unsafe_chunk 585
torch_unsafe_split 585
torch_unsqueeze 586
torch_vander 587
torch_var 587
torch_var_mean 588
torch_vdot 589
torch_view_as_complex 590
torch_view_as_real 591
torch_vstack 592
torch_where 592
torch_zeros 593
torch_zeros_like 594
with_detect_anomaly 596
with_enable_grad 597
with_no_grad 598

Index **599**

`as_array` *Converts to array*

Description

Converts to array

Usage

```
as_array(x)
```

Arguments

x	object to be converted into an array

`AutogradContext` *Class representing the context.*

Description

Class representing the context.

Class representing the context.

Public fields

`ptr` (Dev related) pointer to the context c++ object.

Active bindings

`needs_input_grad` boolean listing arguments of `forward` and whether they require_grad.

`saved_variables` list of objects that were saved for backward via `save_for_backward`.

Methods

Public methods:

- `AutogradContext$new()`
- `AutogradContext$save_for_backward()`
- `AutogradContext$mark_non_differentiable()`
- `AutogradContext$mark_dirty()`
- `AutogradContext$clone()`

Method `new()`**:** (Dev related) Initializes the context. Not user related.

Usage:

```
AutogradContext$new(
  ptr,
  env,
  argument_names = NULL,
  argument_needs_grad = NULL
)
```

Arguments:

`ptr` pointer to the c++ object

`env` environment that encloses both forward and backward

`argument_names` names of forward arguments

`argument_needs_grad` whether each argument in forward needs grad.

Method `save_for_backward()`**:** Saves given objects for a future call to backward().

This should be called at most once, and only from inside the `forward()` method.

Later, saved objects can be accessed through the `saved_variables` attribute. Before returning them to the user, a check is made to ensure they weren't used in any in-place operation that modified their content.

Arguments can also be any kind of R object.

Usage:

```
AutogradContext$save_for_backward(...)
```

Arguments:

`...` any kind of R object that will be saved for the backward pass. It's common to pass named arguments.

Method `mark_non_differentiable()`**:** Marks outputs as non-differentiable.

This should be called at most once, only from inside the `forward()` method, and all arguments should be outputs.

This will mark outputs as not requiring gradients, increasing the efficiency of backward computation. You still need to accept a gradient for each output in `backward()`, but it's always going to be a zero tensor with the same shape as the shape of a corresponding output.

This is used e.g. for indices returned from a max Function.

Usage:

```
AutogradContext$mark_non_differentiable(...)
```

Arguments:

`...` non-differentiable outputs.

Method `mark_dirty()`**:** Marks given tensors as modified in an in-place operation.

This should be called at most once, only from inside the `forward()` method, and all arguments should be inputs.

Every tensor that's been modified in-place in a call to `forward()` should be given to this function, to ensure correctness of our checks. It doesn't matter whether the function is called before or after modification.

Usage:

```
AutogradContext$mark_dirty(...)
```

Arguments:

`...` tensors that are modified in-place.

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
AutogradContext$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

autograd_backward *Computes the sum of gradients of given tensors w.r.t. graph leaves.*

Description

The graph is differentiated using the chain rule. If any of tensors are non-scalar (i.e. their data has more than one element) and require gradient, then the Jacobian-vector product would be computed, in this case the function additionally requires specifying `grad_tensors`. It should be a sequence of matching length, that contains the "vector" in the Jacobian-vector product, usually the gradient of the differentiated function w.r.t. corresponding tensors (None is an acceptable value for all tensors that don't need gradient tensors).

Usage

```
autograd_backward(
  tensors,
  grad_tensors = NULL,
  retain_graph = create_graph,
  create_graph = FALSE
)
```

Arguments

`tensors`	(list of Tensor) – Tensors of which the derivative will be computed.
`grad_tensors`	(list of (Tensor or `NULL`)) - The "vector" in the Jacobian-vector product, usually gradients w value would be acceptable for all grad_tensors, then this argument is optional.
`retain_graph`	(bool, optional) – If `FALSE`, the graph used to compute the grad will be freed. Note that in nearly all cases setting this option to `TRUE` is not needed and often can be worked around in a much more efficient way. Defaults to the value of `create_graph`.
`create_graph`	(bool, optional) – If `TRUE`, graph of the derivative will be constructed, allowing to compute higher order derivative products. Defaults to `FALSE`.

Details

This function accumulates gradients in the leaves - you might need to zero them before calling it.

Examples

```
if (torch_is_installed()) {
x <- torch_tensor(1, requires_grad = TRUE)
y <- 2 * x

a <- torch_tensor(1, requires_grad = TRUE)
b <- 3 * a

autograd_backward(list(y, b))
}
```

autograd_function *Records operation history and defines formulas for differentiating ops.*

Description

Every operation performed on Tensor's creates a new function object, that performs the computation, and records that it happened. The history is retained in the form of a DAG of functions, with edges denoting data dependencies (input <- output). Then, when backward is called, the graph is processed in the topological ordering, by calling `backward()` methods of each Function object, and passing returned gradients on to next Function's.

Usage

```
autograd_function(forward, backward)
```

Arguments

`forward`	Performs the operation. It must accept a context `ctx` as the first argument, followed by any number of arguments (tensors or other types). The context can be used to store tensors that can be then retrieved during the backward pass. See AutogradContext for more information about context methods.
`backward`	Defines a formula for differentiating the operation. It must accept a context `ctx` as the first argument, followed by as many outputs ad `forward()` returned (as a `list()`). The names of the arguments don't matter and they are passed in the order in which they were returned by `forward()`. The function should return a named list, where each argument is the gradient w.r.t the given output, and each element in the returned list should be the gradient w.r.t. the corresponding input. The context can be used to retrieve tensors saved during the forward pass. It also has an attribute `ctx$needs_input_grad` as a named list of booleans representing whether each input needs gradient. E.g., `backward()` will have `ctx$needs_input_grad$input = TRUE` if the `input` argument to `forward()` needs gradient computated w.r.t. the output. See AutogradContext for more information about context methods.

Examples

```
if (torch_is_installed()) {

exp2 <- autograd_function(
  forward = function(ctx, i) {
    result <- i$exp()
    ctx$save_for_backward(result = result)
    result
  },
  backward = function(ctx, grad_output) {
    list(i = grad_output * ctx$saved_variable$result)
  }
)
}
```

autograd_grad *Computes and returns the sum of gradients of outputs w.r.t. the inputs.*

Description

grad_outputs should be a list of length matching output containing the "vector" in Jacobian-vector product, usually the pre-computed gradients w.r.t. each of the outputs. If an output doesn't require_grad, then the gradient can be None).

Usage

```
autograd_grad(
  outputs,
  inputs,
  grad_outputs = NULL,
  retain_graph = create_graph,
  create_graph = FALSE,
  allow_unused = FALSE
)
```

Arguments

outputs	(sequence of Tensor) – outputs of the differentiated function.
inputs	(sequence of Tensor) – Inputs w.r.t. which the gradient will be returned (and not accumulated into .grad).
grad_outputs	(sequence of Tensor) – The "vector" in the Jacobian-vector product. Usually gradients w.r.t. each output. None values can be specified for scalar Tensors or ones that don't require grad. If a None value would be acceptable for all grad_tensors, then this argument is optional. Default: None.
retain_graph	(bool, optional) – If FALSE, the graph used to compute the grad will be freed. Note that in nearly all cases setting this option to TRUE is not needed and often can be worked around in a much more efficient way. Defaults to the value of create_graph.
create_graph	(bool, optional) – If TRUE, graph of the derivative will be constructed, allowing to compute h
allow_unused	(bool, optional) – If FALSE, specifying inputs that were not used when computing outputs (and therefore their grad is always zero) is an error. Defaults to FALSE

Details

If only_inputs is TRUE, the function will only return a list of gradients w.r.t the specified inputs. If it's FALSE, then gradient w.r.t. all remaining leaves will still be computed, and will be accumulated into their .grad attribute.

Examples

```
if (torch_is_installed()) {
w <- torch_tensor(0.5, requires_grad = TRUE)
b <- torch_tensor(0.9, requires_grad = TRUE)
x <- torch_tensor(runif(100))
y <- 2 * x + 1
loss <- (y - (w * x + b))^2
loss <- loss$mean()

o <- autograd_grad(loss, list(w, b))
o
}
```

---

autograd_set_grad_mode

Set grad mode

Description

Sets or disables gradient history.

Usage

```
autograd_set_grad_mode(enabled)
```

Arguments

enabled	bool wether to enable or disable the gradient recording.

---

backends_cudnn_is_available

CuDNN is available

Description

CuDNN is available

Usage

```
backends_cudnn_is_available()
```

backends_cudnn_version

CuDNN version

Description

CuDNN version

Usage

```
backends_cudnn_version()
```

backends_mkldnn_is_available

MKLDNN is available

Description

MKLDNN is available

Usage

```
backends_mkldnn_is_available()
```

Value

Returns whether LibTorch is built with MKL-DNN support.

backends_mkl_is_available

MKL is available

Description

MKL is available

Usage

```
backends_mkl_is_available()
```

Value

Returns whether LibTorch is built with MKL support.

backends_mps_is_available

MPS is available

Description

MPS is available

Usage

```
backends_mps_is_available()
```

Value

Returns whether LibTorch is built with MPS support.

backends_openmp_is_available

OpenMP is available

Description

OpenMP is available

Usage

```
backends_openmp_is_available()
```

Value

Returns whether LibTorch is built with OpenMP support.

broadcast_all — *Given a list of values (possibly containing numbers), returns a list where each value is broadcasted based on the following rules:*

Description

Raises value_error: if any of the values is not a `numeric` instance, a `torch.*Tensor` instance, or an instance implementing **torch_function** TODO: add has_torch_function((v,)) See: https://github.com/pytorch/pytorch/blob/m

Usage

```
broadcast_all(values)
```

Arguments

`values` List of:

- `torch.*Tensor` instances are broadcasted as per `_broadcasting-semantics`.
- `numeric` instances (scalars) are upcast to tensors having the same size and type as the first tensor passed to `values`. If all the values are scalars, then they are upcasted to scalar Tensors. values (list of `numeric`, `torch.*Tensor` or objects implementing **torch_function**)

clone_module — *Clone a torch module.*

Description

Clones a module.

Usage

```
clone_module(module, deep = FALSE, ..., replace_values = TRUE)
```

Arguments

`module` (`nn_module`)
The module to clone

`deep` (`logical(1)`)
Whether to create a deep clone.

`...` (any)
Additional parameters, currently unused.

`replace_values` (`logical(1)`)
Whether to replace parameters and buffers with the cloned values.

Examples

```
if (torch_is_installed()) {
clone_module(nn_linear(1, 1), deep = TRUE)
# is the same as
nn_linear(1, 1)$clone(deep = TRUE)
}
```

`Constraint` *Abstract base class for constraints.*

Description

Abstract base class for constraints.

Abstract base class for constraints.

Details

A constraint object represents a region over which a variable is valid, e.g. within which a variable can be optimized.

Methods

Public methods:

- `Constraint$check()`
- `Constraint$print()`
- `Constraint$clone()`

Method `check()`**:** Returns a byte tensor of `sample_shape` + `batch_shape` indicating whether each event in value satisfies this constraint.

Usage:

```
Constraint$check(value)
```

Arguments:

`value` each event in value will be checked.

Method `print()`**:** Define the print method for constraints,

Usage:

```
Constraint$print()
```

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
Constraint$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

contrib_sort_vertices *Contrib sort vertices*

Description

Based on the implementation from Rotated_IoU

Usage

```
contrib_sort_vertices(vertices, mask, num_valid)
```

Arguments

vertices	A Tensor with the vertices.
mask	A tensors containing the masks.
num_valid	A integer tensors.

Details

All tensors should be on a CUDA device so this function can be used.

Note

This function does not make part of the official torch API.

Examples

```
if (torch_is_installed()) {
if (cuda_is_available()) {
  v <- torch_randn(8, 1024, 24, 2)$cuda()
  mean <- torch_mean(v, dim = 2, keepdim = TRUE)
  v <- v - mean
  m <- (torch_rand(8, 1024, 24) > 0.8)$cuda()
  nv <- torch_sum(m$to(dtype = torch_int()), dim = -1)$to(dtype = torch_int())$cuda()
  result <- contrib_sort_vertices(v, m, nv)
}
}
```

cuda_amp_grad_scaler *Creates a gradient scaler*

Description

A gradient scaler instance is used to perform dynamic gradient scaling to avoid gradient underflow when training with mixed precision.

Usage

```
cuda_amp_grad_scaler(
  init_scale = 2^16,
  growth_factor = 2,
  backoff_factor = 0.5,
  growth_interval = 2000,
  enabled = TRUE
)
```

Arguments

`init_scale`	a numeric value indicating the initial scale factor.
`growth_factor`	a numeric value indicating the growth factor.
`backoff_factor`	a numeric value indicating the backoff factor.
`growth_interval`	a numeric value indicating the growth interval.
`enabled`	a logical value indicating whether the gradient scaler should be enabled.

Value

A gradient scaler object.

cuda_current_device *Returns the index of a currently selected device.*

Description

Returns the index of a currently selected device.

Usage

```
cuda_current_device()
```

cuda_device_count *Returns the number of GPUs available.*

Description

Returns the number of GPUs available.

Usage

```
cuda_device_count()
```

cuda_dump_memory_snapshot *Save CUDA Memory State Snapshot to File*

Description

Calls `cuda_memory_snapshot()` and saves the resulting binary snapshot to a specified file using `writeBin`. The resulting file can be visualized using the interactive snapshot viewer available at pytorch.org/memory_viz.

Usage

```
cuda_dump_memory_snapshot(filepath)
```

Arguments

`filepath`	Character; the path to the file where the snapshot will be saved.

Value

None; snapshot is saved directly to the file.

Examples

```
if (torch_is_installed()) {
## Not run:
cuda_dump_memory_snapshot("snapshot.bin")

## End(Not run)
}
```

cuda_empty_cache *Empty cache*

Description

Releases all unoccupied cached memory currently held by the caching allocator so that those can be used in other GPU application and visible in `nvidia-smi`.

Usage

```
cuda_empty_cache()
```

Note

`cuda_empty_cache()` doesn't increase the amount of GPU memory available for torch. However, it may help reduce fragmentation of GPU memory in certain cases. See Memory management article for more details about GPU memory management.

cuda_get_device_capability *Returns the major and minor CUDA capability of* `device`

Description

Returns the major and minor CUDA capability of `device`

Usage

```
cuda_get_device_capability(device = cuda_current_device())
```

Arguments

`device`	Integer value of the CUDA device to return capabilities of.

cuda_is_available *Returns a bool indicating if CUDA is currently available.*

Description

Returns a bool indicating if CUDA is currently available.

Usage

```
cuda_is_available()
```

cuda_memory_snapshot *Capture CUDA Memory State Snapshot*

Description

Saves a snapshot of the CUDA memory state at the time it was called. The resulting binary output is in pickle format and can be visualized using the interactive snapshot viewer available at pytorch.org/memory_viz.

Usage

```
cuda_memory_snapshot()
```

Value

Raw binary data representing the snapshot in pickle format.

Examples

```
if (torch_is_installed()) {
## Not run:
snapshot <- cuda_memory_snapshot()

## End(Not run)
}
```

cuda_memory_stats *Returns a dictionary of CUDA memory allocator statistics for a given device.*

Description

The return value of this function is a dictionary of statistics, each of which is a non-negative integer.

Usage

```
cuda_memory_stats(device = cuda_current_device())

cuda_memory_summary(device = cuda_current_device())
```

Arguments

device	Integer value of the CUDA device to return capabilities of.

Core statistics

- "allocated.{all,large_pool,small_pool}.{current,peak,allocated,freed}": number of allocation requests received by the memory allocator.
- "allocated_bytes.{all,large_pool,small_pool}.{current,peak,allocated,freed}": amount of allocated memory.
- "segment.{all,large_pool,small_pool}.{current,peak,allocated,freed}": number of reserved segments from cudaMalloc().
- "reserved_bytes.{all,large_pool,small_pool}.{current,peak,allocated,freed}": amount of reserved memory.
- "active.{all,large_pool,small_pool}.{current,peak,allocated,freed}": number of active memory blocks.
- "active_bytes.{all,large_pool,small_pool}.{current,peak,allocated,freed}": amount of active memory.
- "inactive_split.{all,large_pool,small_pool}.{current,peak,allocated,freed}": number of inactive, non-releasable memory blocks.
- "inactive_split_bytes.{all,large_pool,small_pool}.{current,peak,allocated,freed}": amount of inactive, non-releasable memory.

For these core statistics, values are broken down as follows.

Pool type:

- all: combined statistics across all memory pools.
- large_pool: statistics for the large allocation pool (as of October 2019, for size >= 1MB allocations).
- small_pool: statistics for the small allocation pool (as of October 2019, for size < 1MB allocations).

Metric type:

- current: current value of this metric.
- peak: maximum value of this metric.
- allocated: historical total increase in this metric.
- freed: historical total decrease in this metric.

Additional metrics

- "num_alloc_retries": number of failed cudaMalloc calls that result in a cache flush and retry.
- "num_ooms": number of out-of-memory errors thrown.

cuda_record_memory_history

Enable Recording of Memory Allocation Stack Traces

Description

Enables recording of stack traces associated with memory allocations, allowing users to identify the source of memory allocation in CUDA snapshots.

Usage

```
cuda_record_memory_history(
  enabled,
  context = "all",
  stacks = "all",
  max_entries = 1
)
```

Arguments

`enabled`	Character or `NULL`. Controls memory history recording. Options: `NULL` Disable recording of memory history. `"state"` Record currently allocated memory information. `"all"` Record the history of all allocation and free events (default).
`context`	Character or `NULL`. Controls traceback recording. Options: `NULL` Do not record any tracebacks. `"state"` Record tracebacks for currently allocated memory. `"alloc"` Record tracebacks for allocation events. `"all"` Record tracebacks for both allocation and free events (default).
`stacks`	Character. Defines the stack trace frames to include. Options: `"all"` Include all frames (default).
`max_entries`	Integer. The maximum number of allocation/free events to retain.

Details

Alongside tracking stack traces for each current allocation and free event, this function can also keep a historical log of all allocation and free events.

Use `cuda_memory_snapshot()` to retrieve recorded information. Visualization can be performed using pytorch.org/memory_viz.

Value

None; function invoked for side effects.

Examples

```
if (torch_is_installed()) {
## Not run:
cuda_record_memory_history(enabled = 'all', context = 'all', stacks = 'all', max_entries = 10000)

## End(Not run)
}
```

`cuda_runtime_version` *Returns the CUDA runtime version*

Description

Returns the CUDA runtime version

Usage

```
cuda_runtime_version()
```

`cuda_synchronize` *Waits for all kernels in all streams on a CUDA device to complete.*

Description

Waits for all kernels in all streams on a CUDA device to complete.

Usage

```
cuda_synchronize(device = NULL)
```

Arguments

`device`	device for which to synchronize. It uses the current device given by `cuda_current_device()` if no device is specified.

`dataloader` *Data loader. Combines a dataset and a sampler, and provides single- or multi-process iterators over the dataset.*

Description

Data loader. Combines a dataset and a sampler, and provides single- or multi-process iterators over the dataset.

Usage

```
dataloader(
  dataset,
  batch_size = 1,
  shuffle = FALSE,
  sampler = NULL,
  batch_sampler = NULL,
  num_workers = 0,
  collate_fn = NULL,
  pin_memory = FALSE,
  drop_last = FALSE,
  timeout = -1,
  worker_init_fn = NULL,
  worker_globals = NULL,
  worker_packages = NULL
)
```

Arguments

`dataset`	(Dataset): dataset from which to load the data.
`batch_size`	(int, optional): how many samples per batch to load (default: `1`).
`shuffle`	(bool, optional): set to `TRUE` to have the data reshuffled at every epoch (default: `FALSE`).
`sampler`	(Sampler, optional): defines the strategy to draw samples from the dataset. If specified, `shuffle` must be False. Custom samplers can be created with `sampler()`.
`batch_sampler`	(Sampler, optional): like sampler, but returns a batch of indices at a time. Mutually exclusive with `batch_size`, `shuffle`, `sampler`, and `drop_last`. Custom samplers can be created with `sampler()`.
`num_workers`	(int, optional): how many subprocesses to use for data loading. 0 means that the data will be loaded in the main process. (default: `0`)
`collate_fn`	(callable, optional): merges a list of samples to form a mini-batch.
`pin_memory`	(bool, optional): If `TRUE`, the data loader will copy tensors into CUDA pinned memory before returning them. If your data elements are a custom type, or your `collate_fn` returns a batch that is a custom type see the example below.

`drop_last` (bool, optional): set to `TRUE` to drop the last incomplete batch, if the dataset size is not divisible by the batch size. If `FALSE` and the size of dataset is not divisible by the batch size, then the last batch will be smaller. (default: `FALSE`)

`timeout` (numeric, optional): if positive, the timeout value for collecting a batch from workers. -1 means no timeout. (default: `-1`)

`worker_init_fn` (callable, optional): If not `NULL`, this will be called on each worker subprocess with the worker id (an int in `[1, num_workers]`) as input, after seeding and before data loading. (default: `NULL`)

`worker_globals` (list or character vector, optional) only used when `num_workers > 0`. If a character vector, then objects with those names are copied from the global environment to the workers. If a named list, then this list is copied and attached to the worker global environment. Notice that the objects are copied only once at the worker initialization.

`worker_packages` (character vector, optional) Only used if `num_workers > 0` optional character vector naming packages that should be loaded in each worker.

Parallel data loading

When using `num_workers > 0` data loading will happen in parallel for each worker. Note that batches are taken in parallel and not observations.

The worker initialization process happens in the following order:

- `num_workers` R sessions are initialized.

Then in each worker we perform the following actions:

- the `torch` library is loaded.
- a random seed is set both using `set.seed()` and using `torch_manual_seed`.
- packages passed to the `worker_packages` argument are loaded.
- objects passed trough the `worker_globals` parameters are copied into the global environment.
- the `worker_init` function is ran with an `id` argument.
- the dataset fetcher is copied to the worker.

See Also

`dataset()`, `sampler()`

dataloader_make_iter *Creates an iterator from a DataLoader*

Description

Creates an iterator from a DataLoader

Usage

```
dataloader_make_iter(dataloader)
```

Arguments

dataloader	a dataloader object.

dataloader_next *Get the next element of a dataloader iterator*

Description

Get the next element of a dataloader iterator

Usage

```
dataloader_next(iter, completed = NULL)
```

Arguments

iter	a DataLoader iter created with dataloader_make_iter.
completed	the returned value when the iterator is exhausted.

dataset *Helper function to create an function that generates R6 instances of class* `dataset`

Description

All datasets that represent a map from keys to data samples should subclass this class. All subclasses should overwrite the `.getitem()` method, which supports fetching a data sample for a given key. Subclasses could also optionally overwrite `.length()`, which is expected to return the size of the dataset (e.g. number of samples) used by many sampler implementations and the default options of `dataloader()`.

Usage

```
dataset(
  name = NULL,
  inherit = Dataset,
  ...,
  private = NULL,
  active = NULL,
  parent_env = parent.frame()
)
```

Arguments

name	a name for the dataset. It it's also used as the class for it.
inherit	you can optionally inherit from a dataset when creating a new dataset.
...	public methods for the dataset class
private	passed to R6::R6Class().
active	passed to R6::R6Class().
parent_env	An environment to use as the parent of newly-created objects.

Value

The output is a function f with class dataset_generator. Calling f() creates a new instance of the R6 class dataset. The R6 class is stored in the enclosing environment of f and can also be accessed through fs attribute Dataset.

Get a batch of observations

By default datasets are iterated by returning each observation/item individually. Often it's possible to have an optimized implementation to take a batch of observations (eg, subsetting a tensor by multiple indexes at once is faster than subsetting once for each index), in this case you can implement a .getbatch method that will be used instead of .getitem when getting a batch of observations within the dataloader. .getbatch must work for batches of size larger or equal to 1 and care must be taken so it doesn't drop the batch dimension when it's queried with a length 1 batch index - for instance by using drop=FALSE. .getitem() is expected to not include the batch dimension as it's added by the datalaoder. For more on this see the the vignette("loading-data").

Note

dataloader() by default constructs a index sampler that yields integral indices. To make it work with a map-style dataset with non-integral indices/keys, a custom sampler must be provided.

dataset_subset *Dataset Subset*

Description

Subset of a dataset at specified indices.

Usage

```
dataset_subset(dataset, indices)
```

Arguments

dataset	(Dataset): The whole Dataset
indices	(sequence): Indices in the whole set selected for subset

Distribution *Generic R6 class representing distributions*

Description

Distribution is the abstract base class for probability distributions. Note: in Python, adding torch.Size objects works as concatenation Try for example: torch.Size((2, 1)) + torch.Size((1,))

Public fields

`.validate_args` whether to validate arguments

`has_rsample` whether has an rsample

`has_enumerate_support` whether has enumerate support

Active bindings

`batch_shape` Returns the shape over which parameters are batched.

`event_shape` Returns the shape of a single sample (without batching). Returns a dictionary from argument names to `torch_Constraint` objects that should be satisfied by each argument of this distribution. Args that are not tensors need not appear in this dict.

`support` Returns a `torch_Constraint` object representing this distribution's support.

`mean` Returns the mean on of the distribution

`variance` Returns the variance of the distribution

`stddev` Returns the standard deviation of the distribution TODO: consider different message

Methods

Public methods:

- Distribution$new()
- Distribution$expand()
- Distribution$sample()
- Distribution$rsample()
- Distribution$log_prob()
- Distribution$cdf()
- Distribution$icdf()
- Distribution$enumerate_support()
- Distribution$entropy()
- Distribution$perplexity()
- Distribution$.extended_shape()
- Distribution$.validate_sample()
- Distribution$print()
- Distribution$clone()

Method `new()`**:** Initializes a distribution class.

Usage:

```
Distribution$new(batch_shape = NULL, event_shape = NULL, validate_args = NULL)
```

Arguments:

`batch_shape` the shape over which parameters are batched.

`event_shape` the shape of a single sample (without batching).

`validate_args` whether to validate the arguments or not. Validation can be time consuming so you might want to disable it.

Method `expand()`**:** Returns a new distribution instance (or populates an existing instance provided by a derived class) with batch dimensions expanded to batch_shape. This method calls expand on the distribution's parameters. As such, this does not allocate new memory for the expanded distribution instance. Additionally, this does not repeat any args checking or parameter broadcasting in `initialize`, when an instance is first created.

Usage:

```
Distribution$expand(batch_shape, .instance = NULL)
```

Arguments:

`batch_shape` the desired expanded size.

`.instance` new instance provided by subclasses that need to override `expand`.

Method `sample()`**:** Generates a `sample_shape` shaped sample or `sample_shape` shaped batch of samples if the distribution parameters are batched.

Usage:

```
Distribution$sample(sample_shape = NULL)
```

Arguments:

`sample_shape` the shape you want to sample.

Method `rsample()`**:** Generates a sample_shape shaped reparameterized sample or sample_shape shaped batch of reparameterized samples if the distribution parameters are batched.

Usage:

```
Distribution$rsample(sample_shape = NULL)
```

Arguments:

`sample_shape` the shape you want to sample.

Method `log_prob()`**:** Returns the log of the probability density/mass function evaluated at `value`.

Usage:

```
Distribution$log_prob(value)
```

Arguments:

`value` values to evaluate the density on.

Method `cdf()`**:** Returns the cumulative density/mass function evaluated at `value`.

Usage:

```
Distribution$cdf(value)
```

Arguments:

`value` values to evaluate the density on.

Method `icdf()`**:** Returns the inverse cumulative density/mass function evaluated at `value`.

@description Returns tensor containing all values supported by a discrete distribution. The result will enumerate over dimension 0, so the shape of the result will be `(cardinality,) + batch_shape + event_shape (wher` = ()for `univariate distributions)`. `Note that this enumerates over all batched tensors in lock-steplist(c(0` 0), c(1, 1), ...). `With` expand=FALSE, `enumeration happens along dim 0, but with the remaining batch dimensio` c(1), ...)‘.

Usage:

```
Distribution$icdf(value)
```

Arguments:

`value` values to evaluate the density on.

Method `enumerate_support()`**:**

Usage:

```
Distribution$enumerate_support(expand = TRUE)
```

Arguments:

`expand` (bool): whether to expand the support over the batch dims to match the distribution's `batch_shape`.

Returns: Tensor iterating over dimension 0.

Method `entropy()`**:** Returns entropy of distribution, batched over batch_shape.

Usage:

```
Distribution$entropy()
```

Returns: Tensor of shape batch_shape.

Method `perplexity()`**:** Returns perplexity of distribution, batched over batch_shape.

Usage:

```
Distribution$perplexity()
```

Returns: Tensor of shape batch_shape.

Method `.extended_shape()`**:** Returns the size of the sample returned by the distribution, given a `sample_shape`. Note, that the batch and event shapes of a distribution instance are fixed at the time of construction. If this is empty, the returned shape is upcast to (1,).

Usage:

```
Distribution$.extended_shape(sample_shape = NULL)
```

Arguments:

`sample_shape` (torch_Size): the size of the sample to be drawn.

Method `.validate_sample()`**:** Argument validation for distribution methods such as `log_prob`, `cdf` and `icdf`. The rightmost dimensions of a value to be scored via these methods must agree with the distribution's batch and event shapes.

Usage:

```
Distribution$.validate_sample(value)
```

Arguments:

`value` (Tensor): the tensor whose log probability is to be computed by the `log_prob` method.

Method `print()`**:** Prints the distribution instance.

Usage:

```
Distribution$print()
```

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
Distribution$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

`distr_bernoulli` *Creates a Bernoulli distribution parameterized by* `probs` *or* `logits` *(but not both). Samples are binary (0 or 1). They take the value* `1` *with probability* `p` *and* `0` *with probability* `1 - p`.

Description

Creates a Bernoulli distribution parameterized by `probs` or `logits` (but not both). Samples are binary (0 or 1). They take the value `1` with probability `p` and `0` with probability `1 - p`.

Usage

```
distr_bernoulli(probs = NULL, logits = NULL, validate_args = NULL)
```

Arguments

probs	(numeric or torch_tensor): the probability of sampling 1
logits	(numeric or torch_tensor): the log-odds of sampling 1
validate_args	whether to validate arguments or not.

See Also

Distribution for details on the available methods.

Other distributions: distr_chi2(), distr_gamma(), distr_multivariate_normal(), distr_normal(), distr_poisson()

Examples

```
if (torch_is_installed()) {
m <- distr_bernoulli(0.3)
m$sample() # 30% chance 1; 70% chance 0
}
```

---

distr_categorical — *Creates a categorical distribution parameterized by either* probs *or* logits *(but not both).*

Description

Creates a categorical distribution parameterized by either probs or logits (but not both).

Usage

```
distr_categorical(probs = NULL, logits = NULL, validate_args = NULL)
```

Arguments

probs	(Tensor): event probabilities
logits	(Tensor): event log probabilities (unnormalized)
validate_args	Additional arguments

Note

It is equivalent to the distribution that torch_multinomial() samples from.

Samples are integers from $\{0, \ldots, K-1\}$ where K is probs$size(-1).

If probs is 1-dimensional with length-K, each element is the relative probability of sampling the class at that index.

If probs is N-dimensional, the first N-1 dimensions are treated as a batch of relative probability vectors.

The probs argument must be non-negative, finite and have a non-zero sum, and it will be normalized to sum to 1 along the last dimension. attr:probs will return this normalized value. The logits argument will be interpreted as unnormalized log probabilities and can therefore be any real number. It will likewise be normalized so that the resulting probabilities sum to 1 along the last dimension. attr:logits will return this normalized value.

See also: torch_multinomial()

Examples

```
if (torch_is_installed()) {
m <- distr_categorical(torch_tensor(c(0.25, 0.25, 0.25, 0.25)))
m$sample() # equal probability of 1,2,3,4
}
```

---

distr_chi2 *Creates a Chi2 distribution parameterized by shape parameter* df. *This is exactly equivalent to* distr_gamma(alpha=0.5*df, beta=0.5)

Description

Creates a Chi2 distribution parameterized by shape parameter df. This is exactly equivalent to distr_gamma(alpha=0.5*df, beta=0.5)

Usage

```
distr_chi2(df, validate_args = NULL)
```

Arguments

df	(float or torch_tensor): shape parameter of the distribution
validate_args	whether to validate arguments or not.

See Also

Distribution for details on the available methods.

Other distributions: distr_bernoulli(), distr_gamma(), distr_multivariate_normal(), distr_normal(), distr_poisson()

Examples

```
if (torch_is_installed()) {
m <- distr_chi2(torch_tensor(1.0))
m$sample() # Chi2 distributed with shape df=1
torch_tensor(0.1046)
}
```

distr_gamma *Creates a Gamma distribution parameterized by shape* `concentration` *and* `rate`.

Description

Creates a Gamma distribution parameterized by shape `concentration` and `rate`.

Usage

```
distr_gamma(concentration, rate, validate_args = NULL)
```

Arguments

`concentration`	(float or Tensor): shape parameter of the distribution (often referred to as alpha)
`rate`	(float or Tensor): rate = 1 / scale of the distribution (often referred to as beta)
`validate_args`	whether to validate arguments or not.

See Also

Distribution for details on the available methods.

Other distributions: `distr_bernoulli()`, `distr_chi2()`, `distr_multivariate_normal()`, `distr_normal()`, `distr_poisson()`

Examples

```
if (torch_is_installed()) {
m <- distr_gamma(torch_tensor(1.0), torch_tensor(1.0))
m$sample() # Gamma distributed with concentration=1 and rate=1
}
```

distr_mixture_same_family *Mixture of components in the same family*

Description

The `MixtureSameFamily` distribution implements a (batch of) mixture distribution where all component are from different parameterizations of the same distribution type. It is parameterized by a `Categorical` selecting distribution" (over `k` component) and a component distribution, i.e., a `Distribution` with a rightmost batch shape (equal to `[k]`) which indexes each (batch of) component.

Usage

```
distr_mixture_same_family(
  mixture_distribution,
  component_distribution,
  validate_args = NULL
)
```

Arguments

`mixture_distribution`
: `torch_distributions.Categorical`-like instance. Manages the probability of selecting component. The number of categories must match the rightmost batch dimension of the `component_distribution`. Must have either scalar `batch_shape` or `batch_shape` matching `component_distribution.batch_shape[:-1]`

`component_distribution`
: `torch_distributions.Distribution`-like instance. Right-most batch dimension indexes component.

`validate_args` Additional arguments

Examples

```
if (torch_is_installed()) {
# Construct Gaussian Mixture Model in 1D consisting of 5 equally
# weighted normal distributions
mix <- distr_categorical(torch_ones(5))
comp <- distr_normal(torch_randn(5), torch_rand(5))
gmm <- distr_mixture_same_family(mix, comp)
}
```

---

distr_multivariate_normal

Gaussian distribution

Description

Creates a multivariate normal (also called Gaussian) distribution parameterized by a mean vector and a covariance matrix.

Usage

```
distr_multivariate_normal(
  loc,
  covariance_matrix = NULL,
  precision_matrix = NULL,
  scale_tril = NULL,
  validate_args = NULL
)
```

Arguments

`loc`	(Tensor): mean of the distribution
`covariance_matrix`	(Tensor): positive-definite covariance matrix
`precision_matrix`	(Tensor): positive-definite precision matrix
`scale_tril`	(Tensor): lower-triangular factor of covariance, with positive-valued diagonal
`validate_args`	Bool wether to validate the arguments or not.

Details

The multivariate normal distribution can be parameterized either in terms of a positive definite covariance matrix $\mathbf{\Sigma}$ or a positive definite precision matrix $\mathbf{\Sigma}^{-1}$ or a lower-triangular matrix $\mathbf{L}$ with positive-valued diagonal entries, such that $\mathbf{\Sigma} = \mathbf{L}\mathbf{L}^\top$. This triangular matrix can be obtained via e.g. Cholesky decomposition of the covariance.

Note

Only one of `covariance_matrix` or `precision_matrix` or `scale_tril` can be specified. Using `scale_tril` will be more efficient: all computations internally are based on `scale_tril`. If `covariance_matrix` or `precision_matrix` is passed instead, it is only used to compute the corresponding lower triangular matrices using a Cholesky decomposition.

See Also

Distribution for details on the available methods.

Other distributions: `distr_bernoulli()`, `distr_chi2()`, `distr_gamma()`, `distr_normal()`, `distr_poisson()`

Examples

```
if (torch_is_installed()) {
m <- distr_multivariate_normal(torch_zeros(2), torch_eye(2))
m$sample() # normally distributed with mean=`[0,0]` and covariance_matrix=`I`
}
```

`distr_normal` *Creates a normal (also called Gaussian) distribution parameterized by* `loc` *and* `scale`.

Description

Creates a normal (also called Gaussian) distribution parameterized by `loc` and `scale`.

Usage

```
distr_normal(loc, scale, validate_args = NULL)
```

Arguments

loc	(float or Tensor): mean of the distribution (often referred to as mu)
scale	(float or Tensor): standard deviation of the distribution (often referred to as sigma)
validate_args	Additional arguments

Value

Object of torch_Normal class

See Also

Distribution for details on the available methods.

Other distributions: distr_bernoulli(), distr_chi2(), distr_gamma(), distr_multivariate_normal(), distr_poisson()

Examples

```
if (torch_is_installed()) {
m <- distr_normal(loc = 0, scale = 1)
m$sample() # normally distributed with loc=0 and scale=1
}
```

---

distr_poisson *Creates a Poisson distribution parameterized by* rate*, the rate parameter.*

Description

Samples are nonnegative integers, with a pmf given by

$$\text{rate}^k \frac{e^{-\text{rate}}}{k!}$$

Usage

```
distr_poisson(rate, validate_args = NULL)
```

Arguments

rate	(numeric, torch_tensor): the rate parameter
validate_args	whether to validate arguments or not.

See Also

Distribution for details on the available methods.

Other distributions: distr_bernoulli(), distr_chi2(), distr_gamma(), distr_multivariate_normal(), distr_normal()

Examples

```
if (torch_is_installed()) {
m <- distr_poisson(torch_tensor(4))
m$sample()
}
```

---

enumerate *Enumerate an iterator*

Description

Enumerate an iterator

Usage

```
enumerate(x, ...)
```

Arguments

x	the generator to enumerate.
...	passed to specific methods.

---

enumerate.dataloader *Enumerate an iterator*

Description

Enumerate an iterator

Usage

```
## S3 method for class 'dataloader'
enumerate(x, max_len = 1e+06, ...)
```

Arguments

x	the generator to enumerate.
max_len	maximum number of iterations.
...	passed to specific methods.

get_install_libs_url *Install Torch from files*

Description

List the Torch and Lantern libraries URLs to download as local files in order to proceed with `install_torch_from_file()`.

Installs Torch and its dependencies from files.

Usage

```
get_install_libs_url(version = NA, type = NA)

install_torch_from_file(version = NA, type = NA, libtorch, liblantern, ...)
```

Arguments

`version`	Not used
`type`	Not used. This function is deprecated.
`libtorch`	The installation archive file to use for Torch. Shall be a `"file://"` URL scheme.
`liblantern`	The installation archive file to use for Lantern. Shall be a `"file://"` URL scheme.
`...`	other parameters to be passed to `"install_torch()"`

Details

When `"install_torch()"` initiated download is not possible, but installation archive files are present on local filesystem, `"install_torch_from_file()"` can be used as a workaround to installation issue. `"libtorch"` is the archive containing all torch modules, and `"liblantern"` is the C interface to libtorch that is used for the R package. Both are highly dependent, and should be checked through `"get_install_libs_url()"`

Examples

```
if (torch_is_installed()) {
## Not run:
# on a linux CPU platform
get_install_libs_url()
# then after making both files available into /tmp/
Sys.setenv(TORCH_URL="/tmp/libtorch-v1.13.1.zip")
Sys.setenv(LANTERN_URL="/tmp/lantern-0.9.1.9001+cpu+arm64-Darwin.zip")
torch::install_torch()

## End(Not run)
}
```

install_torch *Install Torch*

Description

Installs Torch and its dependencies.

Usage

```
install_torch(reinstall = FALSE, ..., .inform_restart = TRUE)
```

Arguments

reinstall	Re-install Torch even if its already installed?
...	Currently unused.
.inform_restart	if TRUE and running in an interactive() session, after installation it will print a message to inform the user that the session must be restarted for torch to work correctly.

Details

This function is mainly controlled by environment variables that can be used to override the defaults:

- TORCH_HOME: the installation path. By default dependencies are installed within the package directory. Eg what's given by system.file(package="torch").
- TORCH_URL: A URL, path to a ZIP file or a directory containing a LibTorch version. Files will be installed/copied to the TORCH_HOME directory.
- LANTERN_URL: Same as TORCH_URL but for the Lantern library.
- TORCH_INSTALL_DEBUG: Setting it to 1, shows debug log messages during installation.
- PRECXX11ABI: Setting it to 1 will will trigger the installation of a Pre-cxx11 ABI installation of LibTorch. This can be useful in environments with older versions of GLIBC like CentOS7 and older Debian/Ubuntu versions.
- LANTERN_BASE_URL: The base URL for lantern files. This allows passing a directory where lantern binaries are located. The filename is then constructed as usual.
- TORCH_COMMIT_SHA: torch repository commit sha to be used when querying lantern uploads. Set it to 'none' to avoid looking for build for that commit and use the latest build for the branch.
- CUDA: We try to automatically detect the CUDA version installed in your system, but you might want to manually set it here. You can also disable CUDA installation by setting it to 'cpu'.
- TORCH_R_VERSION: The R torch version. It's unlikely that you need to change it, but it can be useful if you don't have the R package installed, but want to install the dependencies.

The TORCH_INSTALL environment variable can be set to 0 to prevent auto-installing torch and TORCH_LOAD set to 0 to avoid loading dependencies automatically. These environment variables are meant for advanced use cases and troubleshooting only. When timeout error occurs during library archive download, or length of downloaded files differ from reported length, an increase of the timeout value should help.

---

is_dataloader *Checks if the object is a dataloader*

Description

Checks if the object is a dataloader

Usage

```
is_dataloader(x)
```

Arguments

x	object to check

---

is_nn_buffer *Checks if the object is a nn_buffer*

Description

Checks if the object is a nn_buffer

Usage

```
is_nn_buffer(x)
```

Arguments

x	object to check

is_nn_module *Checks if the object is an nn_module*

Description

Checks if the object is an nn_module

Usage

```
is_nn_module(x)
```

Arguments

x	object to check

is_nn_parameter *Checks if an object is a nn_parameter*

Description

Checks if an object is a nn_parameter

Usage

```
is_nn_parameter(x)
```

Arguments

x	the object to check

is_optimizer *Checks if the object is a torch optimizer*

Description

Checks if the object is a torch optimizer

Usage

```
is_optimizer(x)
```

Arguments

x	object to check

is_torch_device *Checks if object is a device*

Description

Checks if object is a device

Usage

```
is_torch_device(x)
```

Arguments

x	object to check

is_torch_dtype *Check if object is a torch data type*

Description

Check if object is a torch data type

Usage

```
is_torch_dtype(x)
```

Arguments

x	object to check.

is_torch_layout *Check if an object is a torch layout.*

Description

Check if an object is a torch layout.

Usage

```
is_torch_layout(x)
```

Arguments

x	object to check

is_torch_memory_format *Check if an object is a memory format*

Description

Check if an object is a memory format

Usage

```
is_torch_memory_format(x)
```

Arguments

x	object to check

is_torch_qscheme *Checks if an object is a QScheme*

Description

Checks if an object is a QScheme

Usage

```
is_torch_qscheme(x)
```

Arguments

x	object to check

is_undefined_tensor *Checks if a tensor is undefined*

Description

Checks if a tensor is undefined

Usage

```
is_undefined_tensor(x)
```

Arguments

x	tensor to check

iterable_dataset *Creates an iterable dataset*

Description

Creates an iterable dataset

Usage

```
iterable_dataset(
  name,
  inherit = IterableDataset,
  ...,
  private = NULL,
  active = NULL,
  parent_env = parent.frame()
)
```

Arguments

name	a name for the dataset. It it's also used as the class for it.
inherit	you can optionally inherit from a dataset when creating a new dataset.
...	public methods for the dataset class
private	passed to `R6::R6Class()`.
active	passed to `R6::R6Class()`.
parent_env	An environment to use as the parent of newly-created objects.

Examples

```
if (torch_is_installed()) {
ids <- iterable_dataset(
  name = "hello",
  initialize = function(n = 5) {
    self$n <- n
    self$i <- 0
  },
  .iter = function() {
    i <- 0
    function() {
      i <<- i + 1
      if (i > self$n) {
        coro::exhausted()
      } else {
        i
      }
    }
  }
```

```
)
coro::collect(ids()$.iter())
}
```

`jit_compile` *Compile TorchScript code into a graph*

Description

See the TorchScript language reference for documentation on how to write TorchScript code.

Usage

```
jit_compile(source)
```

Arguments

`source`	valid TorchScript source code.

Examples

```
if (torch_is_installed()) {
comp <- jit_compile("
def fn (x):
  return torch.abs(x)

def foo (x):
  return torch.sum(x)

")

comp$fn(torch_tensor(-1))
comp$foo(torch_randn(10))
}
```

`jit_load` *Loads a* `script_function` *or* `script_module` *previously saved with* `jit_save`

Description

Loads a `script_function` or `script_module` previously saved with `jit_save`

Usage

```
jit_load(path, ...)
```

Arguments

path	a path to a `script_function` or `script_module` serialized with `jit_save()`.
...	currently unused.

`jit_ops` *Enable idiomatic access to JIT operators from R.*

Description

Call JIT operators directly from R, keeping the familiar argument types and argument order. Note, however, that:

- all arguments are required (no defaults)
- axis numbering (as well as position numbers overall) starts from 0
- scalars have to be wrapped in `jit_scalar()`

Usage

```
jit_ops
```

Format

An object of class `torch_ops` of length 0.

Examples

```
if (torch_is_installed()) {
t1 <- torch::torch_rand(4, 5)
t2 <- torch::torch_ones(5, 4)
# same as torch::torch_matmul(t1, t2)
jit_ops$aten$matmul(t1, t2)

# same as torch_split(torch::torch_arange(0, 3), 2, 1)
jit_ops$aten$split(torch::torch_arange(0, 3), torch::jit_scalar(2L), torch::jit_scalar(0L))

}
```

jit_save — *Saves a* `script_function` *to a path*

Description

Saves a `script_function` to a path

Usage

```
jit_save(obj, path, ...)
```

Arguments

`obj`	An `script_function` to save
`path`	The path to save the serialized function.
`...`	currently unused

Examples

```
if (torch_is_installed()) {
fn <- function(x) {
  torch_relu(x)
}

input <- torch_tensor(c(-1, 0, 1))
tr_fn <- jit_trace(fn, input)

tmp <- tempfile("tst", fileext = "pt")
jit_save(tr_fn, tmp)
}
```

jit_save_for_mobile — *Saves a* `script_function` *or* `script_module` *in bytecode form, to be loaded on a mobile device*

Description

Saves a `script_function` or `script_module` in bytecode form, to be loaded on a mobile device

Usage

```
jit_save_for_mobile(obj, path, ...)
```

Arguments

obj	An script_function or script_module to save
path	The path to save the serialized function.
...	currently unused

Examples

```
if (torch_is_installed()) {
fn <- function(x) {
  torch_relu(x)
}

input <- torch_tensor(c(-1, 0, 1))
tr_fn <- jit_trace(fn, input)

tmp <- tempfile("tst", fileext = "pt")
jit_save_for_mobile(tr_fn, tmp)
}
```

---

jit_scalar *Adds the 'jit_scalar' class to the input*

Description

Allows disambiguating length 1 vectors from scalars when passing them to the jit.

Usage

```
jit_scalar(x)
```

Arguments

x	a length 1 R vector.

---

jit_serialize *Serialize a Script Module*

Description

Serializes a script module and returns it as a raw vector. You can read the object again using jit_unserialize.

Usage

```
jit_serialize(obj)
```

Arguments

obj	(script_module) Model to be serialized.

Value

raw()

Examples

```
if (torch_is_installed()) {
model <- jit_trace(nn_linear(1, 1), torch_randn(1))
serialized <- jit_serialize(model)
}
```

---

jit_trace *Trace a function and return an executable* script_function.

Description

Using jit_trace, you can turn an existing R function into a TorchScript script_function. You must provide example inputs, and we run the function, recording the operations performed on all the tensors.

Usage

```
jit_trace(func, ..., strict = TRUE, respect_mode = TRUE)
```

Arguments

func	An R function that will be run with example_inputs. func arguments and return values must be tensors or (possibly nested) lists that contain tensors. Can also be a nn_module(), in such case jit_trace_module() is used to trace that module.
...	example inputs that will be passed to the function while tracing. The resulting trace can be run with inputs of different types and shapes assuming the traced operations support those types and shapes. example_inputs may also be a single Tensor in which case it is automatically wrapped in a list. Note that ... **can not** be named, and the order is respected.
strict	run the tracer in a strict mode or not (default: TRUE). Only turn this off when you want the tracer to record your mutable container types (currently list/dict) and you are sure that the container you are using in your problem is a constant structure and does not get used as control flow (if, for) conditions.
respect_mode	(logical(1)) Whether both modes ('train' or 'eval') should be traced. If TRUE (default), the underlying C++ ScriptModule will have two methods trainforward() and evalforward(). The $forward() method of the R torch module will then select either based on the mode. If FALSE, only the current mode of the module will be jitted and hence only one forward() method exists.

Details

The resulting recording of a standalone function produces a `script_function`.

Value

An `script_function` if `func` is a function and `script_module` if `func` is a `nn_module()`.

Warning

Tracing only correctly records functions and modules which are not data dependent (e.g., do not have conditionals on data in tensors) and do not have any untracked external dependencies (e.g., perform input/output or access global variables). Tracing only records operations done when the given function is run on the given tensors. Therefore, the returned `script_function` will always run the same traced graph on any input. This has some important implications when your module is expected to run different sets of operations, depending on the input and/or the module state. For example,

- Tracing will not record any control-flow like if-statements or loops. When this control-flow is constant across your module, this is fine and it often inlines the control-flow decisions. But sometimes the control-flow is actually part of the model itself. For instance, a recurrent network is a loop over the (possibly dynamic) length of an input sequence.
- In the returned `script_function`, operations that have different behaviors in training and eval modes will always behave as if it is in the mode it was in during tracing, no matter which mode the `script_function` is in.

In cases like these, tracing would not be appropriate and scripting is a better choice. If you trace such models, you may silently get incorrect results on subsequent invocations of the model. The tracer will try to emit warnings when doing something that may cause an incorrect trace to be produced. For scripting, see `jit_compile`.

Examples

```
if (torch_is_installed()) {
fn <- function(x) {
  torch_relu(x)
}
input <- torch_tensor(c(-1, 0, 1))
tr_fn <- jit_trace(fn, input)
tr_fn(input)
}
```

---

jit_trace_module *Trace a module*

Description

Trace a module and return an executable ScriptModule that will be optimized using just-in-time compilation. When a module is passed to `jit_trace()`, only the forward method is run and traced. With `jit_trace_module()`, you can specify a named list of method names to example inputs to trace (see the inputs) argument below.

Usage

```
jit_trace_module(mod, ..., strict = TRUE, respect_mode = TRUE)
```

Arguments

mod	A torch nn_module() containing methods whose names are specified in inputs. The given methods will be compiled as a part of a single ScriptModule.
...	A named list containing sample inputs indexed by method names in mod. The inputs will be passed to methods whose names correspond to inputs keys while tracing. list('forward'=example_forward_input, 'method2'=example_method2_input).
strict	run the tracer in a strict mode or not (default: TRUE). Only turn this off when you want the tracer to record your mutable container types (currently list/dict) and you are sure that the container you are using in your problem is a constant structure and does not get used as control flow (if, for) conditions.
respect_mode	(logical(1)) Whether both modes ('train' or 'eval') should be traced. If TRUE (default), the underlying C++ ScriptModule will have two methods trainforward() and evalforward(). The $forward() method of the R torch module will then select either based on the mode. If FALSE, only the current mode of the module will be jitted and hence only one forward() method exists.

Details

See jit_trace for more information on tracing.

Examples

```
if (torch_is_installed()) {
linear <- nn_linear(10, 1)
tr_linear <- jit_trace_module(linear, forward = list(torch_randn(10, 10)))

x <- torch_randn(10, 10)
torch_allclose(linear(x), tr_linear(x))
}
```

---

jit_tuple *Adds the 'jit_tuple' class to the input*

Description

Allows specifying that an output or input must be considered a jit tuple and instead of a list or dictionary when tracing.

Usage

```
jit_tuple(x)
```

Arguments

x	the list object that will be converted to a tuple.

---

jit_unserialize *Unserialize a Script Module*

Description

Unserializes a script module from a raw vector (generated with `jit_serialize`‘).

Usage

```
jit_unserialize(obj)
```

Arguments

obj	(raw) Serialized model.

Value

`script_module` model <- jit_trace(nn_linear(1, 1), torch_randn(1)) serialized <- jit_serialize(model) model2 <- jit_unserialize(serialized)

---

linalg_cholesky *Computes the Cholesky decomposition of a complex Hermitian or real symmetric positive-definite matrix.*

Description

Letting . be . or . , the **Cholesky decomposition** of a complex Hermitian or real symmetric positive-definite matrix . is defined as

Usage

```
linalg_cholesky(A)
```

Arguments

A	(Tensor): tensor of shape `(*, n, n)` where `*` is zero or more batch dimensions consisting of symmetric or Hermitian positive-definite matrices.

Details

Equation not displayed. Install 'katex' then re-install 'torch'.

where . is a lower triangular matrix and . is the conjugate transpose when . is complex, and the transpose when . is real-valued.

Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if `A` is a batch of matrices then the output has the same batch dimensions.

See Also

- `linalg_cholesky_ex()` for a version of this operation that skips the (slow) error checking by default and instead returns the debug information. This makes it a faster way to check if a matrix is positive-definite. `linalg_eigh()` for a different decomposition of a Hermitian matrix. The eigenvalue decomposition gives more information about the matrix but it slower to compute than the Cholesky decomposition.

Other linalg: `linalg_cholesky_ex()`, `linalg_det()`, `linalg_eig()`, `linalg_eigh()`, `linalg_eigvals()`, `linalg_eigvalsh()`, `linalg_householder_product()`, `linalg_inv()`, `linalg_inv_ex()`, `linalg_lstsq()`, `linalg_matrix_norm()`, `linalg_matrix_power()`, `linalg_matrix_rank()`, `linalg_multi_dot()`, `linalg_norm()`, `linalg_pinv()`, `linalg_qr()`, `linalg_slogdet()`, `linalg_solve()`, `linalg_solve_triangular()`, `linalg_svd()`, `linalg_svdvals()`, `linalg_tensorinv()`, `linalg_tensorsolve()`, `linalg_vector_norm()`

Examples

```
if (torch_is_installed()) {
a <- torch_eye(10)
linalg_cholesky(a)
}
```

`linalg_cholesky_ex` *Computes the Cholesky decomposition of a complex Hermitian or real symmetric positive-definite matrix.*

Description

This function skips the (slow) error checking and error message construction of `linalg_cholesky()`, instead directly returning the LAPACK error codes as part of a named tuple `(L, info)`. This makes this function a faster way to check if a matrix is positive-definite, and it provides an opportunity to handle decomposition errors more gracefully or performantly than `linalg_cholesky()` does. Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if `A` is a batch of matrices then the output has the same batch dimensions. If `A` is not a Hermitian positive-definite matrix, or if it's a batch of matrices and one or more of them is not a Hermitian positive-definite matrix, then `info` stores a positive integer for the corresponding matrix. The positive integer indicates the order of the leading minor that is not positive-definite, and the decomposition could not be completed. `info` filled with zeros indicates that the decomposition was successful. If `check_errors=TRUE` and `info` contains positive integers, then a RuntimeError is thrown.

Usage

```
linalg_cholesky_ex(A, check_errors = FALSE)
```

Arguments

A	(Tensor): the Hermitian n \times n matrix or the batch of such matrices of size (*, n, n) where * is one or more batch dimensions.
check_errors	(bool, optional): controls whether to check the content of infos. Default: FALSE.

Note

If A is on a CUDA device, this function may synchronize that device with the CPU.

This function is "experimental" and it may change in a future PyTorch release.

See Also

linalg_cholesky() is a NumPy compatible variant that always checks for errors.

Other linalg: linalg_cholesky(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
A <- torch_randn(2, 2)
out <- linalg_cholesky_ex(A)
out
}
```

---

linalg_cond — *Computes the condition number of a matrix with respect to a matrix norm.*

Description

Letting . be . or . , the **condition number** . of a matrix . is defined as

Usage

```
linalg_cond(A, p = NULL)
```

Arguments

A	(Tensor): tensor of shape `(*, m, n)` where `*` is zero or more batch dimensions for `p` in `(2, -2)`, and of shape `(*, n, n)` where every matrix is invertible for `p` in `('fro', 'nuc', inf, -inf, 1, -1)`.
p	(int, inf, -inf, 'fro', 'nuc', optional): the type of the matrix norm to use in the computations (see above). Default: `NULL`

Details

Equation not displayed. Install 'katex' then re-install 'torch'.

The condition number of `A` measures the numerical stability of the linear system `AX = B` with respect to a matrix norm.

Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if `A` is a batch of matrices then the output has the same batch dimensions.

`p` defines the matrix norm that is computed. See the table in 'Details' to find the supported norms.

For `p` is one of `('fro', 'nuc', inf, -inf, 1, -1)`, this function uses `linalg_norm()` and `linalg_inv()`.

As such, in this case, the matrix (or every matrix in the batch) `A` has to be square and invertible.

For `p` in `(2, -2)`, this function can be computed in terms of the singular values .

Equation not displayed. Install 'katex' then re-install 'torch'.

In these cases, it is computed using `linalg_svd()`. For these norms, the matrix (or every matrix in the batch) `A` may have any shape.

p	matrix norm
`NULL`	2-norm (largest singular value)
`'fro'`	Frobenius norm
`'nuc'`	nuclear norm
`Inf`	`max(sum(abs(x), dim=2))`
`-Inf`	`min(sum(abs(x), dim=2))`
`1`	`max(sum(abs(x), dim=1))`
`-1`	`min(sum(abs(x), dim=1))`
`2`	largest singular value
`-2`	smallest singular value

Value

A real-valued tensor, even when `A` is complex.

Note

When inputs are on a CUDA device, this function synchronizes that device with the CPU if if `p` is one of `('fro', 'nuc', inf, -inf, 1, -1)`.

Examples

```
if (torch_is_installed()) {
a <- torch_tensor(rbind(c(1., 0, -1), c(0, 1, 0), c(1, 0, 1)))
linalg_cond(a)
linalg_cond(a, "fro")
}
```

`linalg_det` *Computes the determinant of a square matrix.*

Description

Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if `A` is a batch of matrices then the output has the same batch dimensions.

Usage

```
linalg_det(A)
```

Arguments

`A`	(Tensor): tensor of shape `(*, n, n)` where `*` is zero or more batch dimensions.

See Also

Other linalg: `linalg_cholesky()`, `linalg_cholesky_ex()`, `linalg_eig()`, `linalg_eigh()`, `linalg_eigvals()`, `linalg_eigvalsh()`, `linalg_householder_product()`, `linalg_inv()`, `linalg_inv_ex()`, `linalg_lstsq()`, `linalg_matrix_norm()`, `linalg_matrix_power()`, `linalg_matrix_rank()`, `linalg_multi_dot()`, `linalg_norm()`, `linalg_pinv()`, `linalg_qr()`, `linalg_slogdet()`, `linalg_solve()`, `linalg_solve_triangular()`, `linalg_svd()`, `linalg_svdvals()`, `linalg_tensorinv()`, `linalg_tensorsolve()`, `linalg_vector_norm()`

Examples

```
if (torch_is_installed()) {
a <- torch_randn(3, 3)
linalg_det(a)

a <- torch_randn(3, 3, 3)
linalg_det(a)
}
```

`linalg_eig` *Computes the eigenvalue decomposition of a square matrix if it exists.*

Description

Letting . be . or . , the **eigenvalue decomposition** of a square matrix . (if it exists) is defined as

Usage

```
linalg_eig(A)
```

Arguments

`A`	(Tensor): tensor of shape `(*, n, n)` where `*` is zero or more batch dimensions consisting of diagonalizable matrices.

Details

Equation not displayed. Install 'katex' then re-install 'torch'.

This decomposition exists if and only if . is `diagonalizable_`. This is the case when all its eigenvalues are different. Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if `A` is a batch of matrices then the output has the same batch dimensions.

Value

A list `(eigenvalues, eigenvectors)` which corresponds to . and . above. `eigenvalues` and `eigenvectors` will always be complex-valued, even when `A` is real. The eigenvectors will be given by the columns of `eigenvectors`.

Warning

- This function assumes that `A` is `diagonalizable_` (for example, when all the eigenvalues are different). If it is not diagonalizable, the returned eigenvalues will be correct but . .
- The eigenvectors of a matrix are not unique, nor are they continuous with respect to `A`. Due to this lack of uniqueness, different hardware and software may compute different eigenvectors. This non-uniqueness is caused by the fact that multiplying an eigenvector by a non-zero number produces another set of valid eigenvectors of the matrix. In this implmentation, the returned eigenvectors are normalized to have norm `1` and largest real component.
- Gradients computed using `V` will only be finite when `A` does not have repeated eigenvalues. Furthermore, if the distance between any two eigenvalues is close to zero, the gradient will be numerically unstable, as it depends on the eigenvalues . through the computation of . .

Note

The eigenvalues and eigenvectors of a real matrix may be complex.

See Also

- linalg_eigvals() computes only the eigenvalues. Unlike linalg_eig(), the gradients of linalg_eigvals() are always numerically stable.
- linalg_eigh() for a (faster) function that computes the eigenvalue decomposition for Hermitian and symmetric matrices.
- linalg_svd() for a function that computes another type of spectral decomposition that works on matrices of any shape.
- linalg_qr() for another (much faster) decomposition that works on matrices of any shape.

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
a <- torch_randn(2, 2)
wv <- linalg_eig(a)
}
```

---

linalg_eigh — *Computes the eigenvalue decomposition of a complex Hermitian or real symmetric matrix.*

Description

Letting . be . or . , the **eigenvalue decomposition** of a complex Hermitian or real symmetric matrix . is defined as

Usage

```
linalg_eigh(A, UPLO = "L")
```

Arguments

A	(Tensor): tensor of shape (*, n, n) where * is zero or more batch dimensions consisting of symmetric or Hermitian matrices.
UPLO	('L', 'U', optional): controls whether to use the upper or lower triangular part of A in the computations. Default: 'L'.

Details

Equation not displayed. Install 'katex' then re-install 'torch'.

where . is the conjugate transpose when . is complex, and the transpose when . is real-valued. . is orthogonal in the real case and unitary in the complex case.

Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if `A` is a batch of matrices then the output has the same batch dimensions.

`A` is assumed to be Hermitian (resp. symmetric), but this is not checked internally, instead:

- If `UPLO\= 'L'` (default), only the lower triangular part of the matrix is used in the computation.
- If `UPLO\= 'U'`, only the upper triangular part of the matrix is used. The eigenvalues are returned in ascending order.

Value

A list `(eigenvalues, eigenvectors)` which corresponds to . and . above. `eigenvalues` will always be real-valued, even when `A` is complex.

It will also be ordered in ascending order. `eigenvectors` will have the same dtype as `A` and will contain the eigenvectors as its columns.

Warning

- The eigenvectors of a symmetric matrix are not unique, nor are they continuous with respect to `A`. Due to this lack of uniqueness, different hardware and software may compute different eigenvectors. This non-uniqueness is caused by the fact that multiplying an eigenvector by `-1` in the real case or by . in the complex case produces another set of valid eigenvectors of the matrix. This non-uniqueness problem is even worse when the matrix has repeated eigenvalues. In this case, one may multiply the associated eigenvectors spanning the subspace by a rotation matrix and the resulting eigenvectors will be valid eigenvectors.
- Gradients computed using the `eigenvectors` tensor will only be finite when `A` has unique eigenvalues. Furthermore, if the distance between any two eigvalues is close to zero, the gradient will be numerically unstable, as it depends on the eigenvalues . through the computation of . .

Note

The eigenvalues of real symmetric or complex Hermitian matrices are always real.

See Also

- `linalg_eigvalsh()` computes only the eigenvalues values of a Hermitian matrix. Unlike `linalg_eigh()`, the gradients of `linalg_eigvalsh()` are always numerically stable.
- `linalg_cholesky()` for a different decomposition of a Hermitian matrix. The Cholesky decomposition gives less information about the matrix but is much faster to compute than the eigenvalue decomposition.
- `linalg_eig()` for a (slower) function that computes the eigenvalue decomposition of a not necessarily Hermitian square matrix.

- linalg_svd() for a (slower) function that computes the more general SVD decomposition of matrices of any shape.
- linalg_qr() for another (much faster) decomposition that works on general matrices.

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
a <- torch_randn(2, 2)
linalg_eigh(a)
}
```

---

linalg_eigvals *Computes the eigenvalues of a square matrix.*

Description

Letting . be . or . , the **eigenvalues** of a square matrix . are defined as the roots (counted with multiplicity) of the polynomial p of degree n given by

Usage

```
linalg_eigvals(A)
```

Arguments

A	(Tensor): tensor of shape (*, n, n) where * is zero or more batch dimensions.

Details

Equation not displayed. Install 'katex' then re-install 'torch'.

where . is the n-dimensional identity matrix. Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if A is a batch of matrices then the output has the same batch dimensions.

Note

The eigenvalues of a real matrix may be complex, as the roots of a real polynomial may be complex. The eigenvalues of a matrix are always well-defined, even when the matrix is not diagonalizable.

See Also

linalg_eig() computes the full eigenvalue decomposition.

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
a <- torch_randn(2, 2)
w <- linalg_eigvals(a)
}
```

---

linalg_eigvalsh *Computes the eigenvalues of a complex Hermitian or real symmetric matrix.*

Description

Letting . be . or . , the **eigenvalues** of a complex Hermitian or real symmetric matrix . are defined as the roots (counted with multiplicity) of the polynomial p of degree n given by

Usage

```
linalg_eigvalsh(A, UPLO = "L")
```

Arguments

A	(Tensor): tensor of shape (*, n, n) where * is zero or more batch dimensions consisting of symmetric or Hermitian matrices.
UPLO	('L', 'U', optional): controls whether to use the upper or lower triangular part of A in the computations. Default: 'L'.

Details

Equation not displayed. Install 'katex' then re-install 'torch'.

where . is the n-dimensional identity matrix.

The eigenvalues of a real symmetric or complex Hermitian matrix are always real. Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if A is a batch of matrices then the output has the same batch dimensions. The eigenvalues are returned in ascending order.

A is assumed to be Hermitian (resp. symmetric), but this is not checked internally, instead:

- If UPLO\= 'L' (default), only the lower triangular part of the matrix is used in the computation.
- If UPLO\= 'U', only the upper triangular part of the matrix is used.

Value

A real-valued tensor cointaining the eigenvalues even when `A` is complex. The eigenvalues are returned in ascending order.

See Also

- `linalg_eigh()` computes the full eigenvalue decomposition.

Other linalg: `linalg_cholesky()`, `linalg_cholesky_ex()`, `linalg_det()`, `linalg_eig()`, `linalg_eigh()`, `linalg_eigvals()`, `linalg_householder_product()`, `linalg_inv()`, `linalg_inv_ex()`, `linalg_lstsq()`, `linalg_matrix_norm()`, `linalg_matrix_power()`, `linalg_matrix_rank()`, `linalg_multi_dot()`, `linalg_norm()`, `linalg_pinv()`, `linalg_qr()`, `linalg_slogdet()`, `linalg_solve()`, `linalg_solve_triangular()`, `linalg_svd()`, `linalg_svdvals()`, `linalg_tensorinv()`, `linalg_tensorsolve()`, `linalg_vector_norm()`

Examples

```
if (torch_is_installed()) {
a <- torch_randn(2, 2)
linalg_eigvalsh(a)
}
```

`linalg_householder_product` *Computes the first* `n` *columns of a product of Householder matrices.*

Description

Letting . be . or . , for a matrix . with columns . with . and a vector . with . , this function computes the first . columns of the matrix

Usage

```
linalg_householder_product(A, tau)
```

Arguments

`A`	(Tensor): tensor of shape `(*, m, n)` where `*` is zero or more batch dimensions.
`tau`	(Tensor): tensor of shape `(*, k)` where `*` is zero or more batch dimensions.

Details

Equation not displayed. Install 'katex' then re-install 'torch'.

where . is the `m`-dimensional identity matrix and . is the conjugate transpose when . is complex, and the transpose when . is real-valued. See Representation of Orthogonal or Unitary Matrices for further details.

Supports inputs of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if the inputs are batches of matrices then the output has the same batch dimensions.

Note

This function only uses the values strictly below the main diagonal of A. The other values are ignored.

See Also

- torch_geqrf() can be used together with this function to form the Q from the linalg_qr() decomposition.
- torch_ormqr() is a related function that computes the matrix multiplication of a product of Householder matrices with another matrix. However, that function is not supported by autograd.

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
A <- torch_randn(2, 2)
h_tau <- torch_geqrf(A)
Q <- linalg_householder_product(h_tau[[1]], h_tau[[2]])
torch_allclose(Q, linalg_qr(A)[[1]])
}
```

---

linalg_inv *Computes the inverse of a square matrix if it exists.*

Description

Throws a runtime_error if the matrix is not invertible.

Usage

```
linalg_inv(A)
```

Arguments

A	(Tensor): tensor of shape (*, n, n) where * is zero or more batch dimensions consisting of invertible matrices.

Details

Letting . be . or . , for a matrix . , its **inverse matrix** . (if it exists) is defined as

Equation not displayed. Install 'katex' then re-install 'torch'. where . is the n-dimensional identity matrix.

The inverse matrix exists if and only if . is invertible. In this case, the inverse is unique. Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if A is a batch of matrices then the output has the same batch dimensions.

Consider using linalg_solve() if possible for multiplying a matrix on the left by the inverse, as linalg_solve(A, B) == A$inv() %*% B It is always prefered to use linalg_solve() when possible, as it is faster and more numerically stable than computing the inverse explicitly.

See Also

linalg_pinv() computes the pseudoinverse (Moore-Penrose inverse) of matrices of any shape. linalg_solve() computes A$inv() %*% B with a numerically stable algorithm.

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
A <- torch_randn(4, 4)
linalg_inv(A)
}
```

---

linalg_inv_ex *Computes the inverse of a square matrix if it is invertible.*

Description

Returns a namedtuple (inverse, info). inverse contains the result of inverting A and info stores the LAPACK error codes. If A is not an invertible matrix, or if it's a batch of matrices and one or more of them is not an invertible matrix, then info stores a positive integer for the corresponding matrix. The positive integer indicates the diagonal element of the LU decomposition of the input matrix that is exactly zero. info filled with zeros indicates that the inversion was successful. If check_errors=TRUE and info contains positive integers, then a RuntimeError is thrown. Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if A is a batch of matrices then the output has the same batch dimensions.

Usage

```
linalg_inv_ex(A, check_errors = FALSE)
```

Arguments

A	(Tensor): tensor of shape (*, n, n) where * is zero or more batch dimensions consisting of square matrices.
check_errors	(bool, optional): controls whether to check the content of info. Default: FALSE.

Note

If A is on a CUDA device then this function may synchronize that device with the CPU.

This function is "experimental" and it may change in a future PyTorch release.

See Also

linalg_inv() is a NumPy compatible variant that always checks for errors.

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
A <- torch_randn(3, 3)
out <- linalg_inv_ex(A)
}
```

---

linalg_lstsq *Computes a solution to the least squares problem of a system of linear equations.*

Description

Letting . be . or . , the **least squares problem** for a linear system . with . is defined as

Usage

```
linalg_lstsq(A, B, rcond = NULL, ..., driver = NULL)
```

Arguments

A	(Tensor): lhs tensor of shape (*, m, n) where * is zero or more batch dimensions.
B	(Tensor): rhs tensor of shape (*, m, k) where * is zero or more batch dimensions.
rcond	(float, optional): used to determine the effective rank of A. If rcond = NULL, rcond is set to the machine precision of the dtype of A times max(m, n). Default: NULL.

`...`	currently unused.
`driver`	(str, optional): name of the LAPACK/MAGMA method to be used. If `NULL`, `'gelsy'` is used for CPU inputs and `'gels'` for CUDA inputs. Default: `NULL`.

Details

Equation not displayed. Install 'katex' then re-install 'torch'.

where . denotes the Frobenius norm. Supports inputs of float, double, cfloat and cdouble dtypes.

Also supports batches of matrices, and if the inputs are batches of matrices then the output has the same batch dimensions. `driver` chooses the LAPACK/MAGMA function that will be used.

For CPU inputs the valid values are `'gels'`, `'gelsy'`, `'gelsd`, `'gelss'`. For CUDA input, the only valid driver is `'gels'`, which assumes that `A` is full-rank.

To choose the best driver on CPU consider:

- If `A` is well-conditioned (its condition number is not too large), or you do not mind some precision loss.
- For a general matrix: `'gelsy'` (QR with pivoting) (default)
- If `A` is full-rank: `'gels'` (QR)
- If `A` is not well-conditioned.
- `'gelsd'` (tridiagonal reduction and SVD)
- But if you run into memory issues: `'gelss'` (full SVD).

See also the full description of these drivers

`rcond` is used to determine the effective rank of the matrices in `A` when `driver` is one of (`'gelsy'`, `'gelsd'`, `'gelss'`). In this case, if . are the singular values of `A` in decreasing order, . will be rounded down to zero if . . If `rcond = NULL` (default), `rcond` is set to the machine precision of the dtype of `A`.

This function returns the solution to the problem and some extra information in a list of four tensors `(solution, residuals, rank, singular_values)`. For inputs `A`, `B` of shape `(*, m, n)`, `(*, m, k)` respectively, it cointains

- `solution`: the least squares solution. It has shape `(*, n, k)`.
- `residuals`: the squared residuals of the solutions, that is, . . It has shape equal to the batch dimensions of `A`. It is computed when `m > n` and every matrix in `A` is full-rank, otherwise, it is an empty tensor. If `A` is a batch of matrices and any matrix in the batch is not full rank, then an empty tensor is returned. This behavior may change in a future PyTorch release.
- `rank`: tensor of ranks of the matrices in `A`. It has shape equal to the batch dimensions of `A`. It is computed when `driver` is one of (`'gelsy'`, `'gelsd'`, `'gelss'`), otherwise it is an empty tensor.
- `singular_values`: tensor of singular values of the matrices in `A`. It has shape `(*, min(m, n))`. It is computed when `driver` is one of (`'gelsd'`, `'gelss'`), otherwise it is an empty tensor.

Value

A list `(solution, residuals, rank, singular_values)`.

Warning

The default value of `rcond` may change in a future PyTorch release. It is therefore recommended to use a fixed value to avoid potential breaking changes.

Note

This function computes `X = A$pinverse() %*% B` in a faster and more numerically stable way than performing the computations separately.

See Also

Other linalg: `linalg_cholesky()`, `linalg_cholesky_ex()`, `linalg_det()`, `linalg_eig()`, `linalg_eigh()`, `linalg_eigvals()`, `linalg_eigvalsh()`, `linalg_householder_product()`, `linalg_inv()`, `linalg_inv_ex()`, `linalg_matrix_norm()`, `linalg_matrix_power()`, `linalg_matrix_rank()`, `linalg_multi_dot()`, `linalg_norm()`, `linalg_pinv()`, `linalg_qr()`, `linalg_slogdet()`, `linalg_solve()`, `linalg_solve_triangular()`, `linalg_svd()`, `linalg_svdvals()`, `linalg_tensorinv()`, `linalg_tensorsolve()`, `linalg_vector_norm()`

Examples

```
if (torch_is_installed()) {
A <- torch_tensor(rbind(c(10, 2, 3), c(3, 10, 5), c(5, 6, 12)))$unsqueeze(1) # shape (1, 3, 3)
B <- torch_stack(list(
  rbind(c(2, 5, 1), c(3, 2, 1), c(5, 1, 9)),
  rbind(c(4, 2, 9), c(2, 0, 3), c(2, 5, 3))
), dim = 1) # shape (2, 3, 3)
X <- linalg_lstsq(A, B)$solution # A is broadcasted to shape (2, 3, 3)
}
```

---

linalg_matrix_norm *Computes a matrix norm.*

Description

If `A` is complex valued, it computes the norm of `A$abs()` Support input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices: the norm will be computed over the dimensions specified by the 2-tuple `dim` and the other dimensions will be treated as batch dimensions. The output will have the same batch dimensions.

Usage

```
linalg_matrix_norm(
  A,
  ord = "fro",
  dim = c(-2, -1),
  keepdim = FALSE,
  dtype = NULL
)
```

Arguments

A	(Tensor): tensor with two or more dimensions. By default its shape is interpreted as `(*, m, n)` where `*` is zero or more batch dimensions, but this behavior can be controlled using `dim`.
ord	(int, inf, -inf, 'fro', 'nuc', optional): order of norm. Default: `'fro'`
dim	(int, `Tuple[int]`, optional): dimensions over which to compute the vector or matrix norm. See above for the behavior when `dim=NULL`. Default: `NULL`
keepdim	(bool, optional): If set to `TRUE`, the reduced dimensions are retained in the result as dimensions with size one. Default: `FALSE`
dtype	dtype (`torch_dtype`, optional): If specified, the input tensor is cast to `dtype` before performing the operation, and the returned tensor's type will be `dtype`. Default: `NULL`

Details

`ord` defines the norm that is computed. The following norms are supported:

ord	norm for matrices	norm for vectors
`NULL` (default)	Frobenius norm	2-norm (see below)
`"fro"`	Frobenius norm	– not supported –
`"nuc"`	nuclear norm	– not supported –
`Inf`	`max(sum(abs(x), dim=2))`	`max(abs(x))`
`-Inf`	`min(sum(abs(x), dim=2))`	`min(abs(x))`
`0`	– not supported –	`sum(x != 0)`
`1`	`max(sum(abs(x), dim=1))`	as below
`-1`	`min(sum(abs(x), dim=1))`	as below
`2`	largest singular value	as below
`-2`	smallest singular value	as below
other `int` or `float`	– not supported –	`sum(abs(x)^{ord})^{(1 / ord)}`

See Also

Other linalg: `linalg_cholesky()`, `linalg_cholesky_ex()`, `linalg_det()`, `linalg_eig()`, `linalg_eigh()`, `linalg_eigvals()`, `linalg_eigvalsh()`, `linalg_householder_product()`, `linalg_inv()`, `linalg_inv_ex()`, `linalg_lstsq()`, `linalg_matrix_power()`, `linalg_matrix_rank()`, `linalg_multi_dot()`, `linalg_norm()`, `linalg_pinv()`, `linalg_qr()`, `linalg_slogdet()`, `linalg_solve()`, `linalg_solve_triangular()`, `linalg_svd()`, `linalg_svdvals()`, `linalg_tensorinv()`, `linalg_tensorsolve()`, `linalg_vector_norm()`

Examples

```
if (torch_is_installed()) {
a <- torch_arange(0, 8, dtype = torch_float())$reshape(c(3, 3))
linalg_matrix_norm(a)
linalg_matrix_norm(a, ord = -1)
b <- a$expand(c(2, -1, -1))
linalg_matrix_norm(b)
linalg_matrix_norm(b, dim = c(1, 3))
}
```

`linalg_matrix_power` *Computes the* `n`*-th power of a square matrix for an integer* `n`.

Description

Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if `A` is a batch of matrices then the output has the same batch dimensions.

Usage

```
linalg_matrix_power(A, n)
```

Arguments

`A`	(Tensor): tensor of shape `(*, m, m)` where `*` is zero or more batch dimensions.
`n`	(int): the exponent.

Details

If `n=0`, it returns the identity matrix (or batch) of the same shape as `A`. If `n` is negative, it returns the inverse of each matrix (if invertible) raised to the power of `abs(n)`.

See Also

`linalg_solve()` computes `A$inverse() %*% B` with a numerically stable algorithm.

Other linalg: `linalg_cholesky()`, `linalg_cholesky_ex()`, `linalg_det()`, `linalg_eig()`, `linalg_eigh()`, `linalg_eigvals()`, `linalg_eigvalsh()`, `linalg_householder_product()`, `linalg_inv()`, `linalg_inv_ex()`, `linalg_lstsq()`, `linalg_matrix_norm()`, `linalg_matrix_rank()`, `linalg_multi_dot()`, `linalg_norm()`, `linalg_pinv()`, `linalg_qr()`, `linalg_slogdet()`, `linalg_solve()`, `linalg_solve_triangular()`, `linalg_svd()`, `linalg_svdvals()`, `linalg_tensorinv()`, `linalg_tensorsolve()`, `linalg_vector_norm()`

Examples

```
if (torch_is_installed()) {
A <- torch_randn(3, 3)
linalg_matrix_power(A, 0)
}
```

linalg_matrix_rank *Computes the numerical rank of a matrix.*

Description

The matrix rank is computed as the number of singular values (or eigenvalues in absolute value when `hermitian = TRUE`) that are greater than the specified `tol` threshold.

Usage

```
linalg_matrix_rank(
  A,
  ...,
  atol = NULL,
  rtol = NULL,
  tol = NULL,
  hermitian = FALSE
)
```

Arguments

`A`	(Tensor): tensor of shape `(*, m, n)` where `*` is zero or more batch dimensions.
`...`	Not currently used.
`atol`	the absolute tolerance value. When `NULL` it's considered to be zero.
`rtol`	the relative tolerance value. See above for the value it takes when `NULL`.
`tol`	(float, Tensor, optional): the tolerance value. See above for the value it takes when `NULL`. Default: `NULL`.
`hermitian`	(bool, optional): indicates whether `A` is Hermitian if complex or symmetric if real. Default: `FALSE`.

Details

Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if `A` is a batch of matrices then the output has the same batch dimensions.

If `hermitian = TRUE`, `A` is assumed to be Hermitian if complex or symmetric if real, but this is not checked internally. Instead, just the lower triangular part of the matrix is used in the computations.

If `tol` is not specified and `A` is a matrix of dimensions `(m, n)`, the tolerance is set to be

Equation not displayed. Install 'katex' then re-install 'torch'.

where . is the largest singular value (or eigenvalue in absolute value when `hermitian = TRUE`), and . is the epsilon value for the dtype of `A` (see `torch_finfo()`).

If `A` is a batch of matrices, `tol` is computed this way for every element of the batch.

See Also

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
a <- torch_eye(10)
linalg_matrix_rank(a)
}
```

---

linalg_multi_dot *Efficiently multiplies two or more matrices*

Description

Efficiently multiplies two or more matrices by reordering the multiplications so that the fewest arithmetic operations are performed.

Usage

```
linalg_multi_dot(tensors)
```

Arguments

tensors	(Sequence[Tensor]): two or more tensors to multiply. The first and last tensors may be 1D or 2D. Every other tensor must be 2D.

Details

Supports inputs of float, double, cfloat and cdouble dtypes. This function does not support batched inputs.

Every tensor in tensors must be 2D, except for the first and last which may be 1D. If the first tensor is a 1D vector of shape (n,) it is treated as a row vector of shape (1, n), similarly if the last tensor is a 1D vector of shape (n,) it is treated as a column vector of shape (n, 1).

If the first and last tensors are matrices, the output will be a matrix. However, if either is a 1D vector, then the output will be a 1D vector.

Note

This function is implemented by chaining torch_mm() calls after computing the optimal matrix multiplication order.

The cost of multiplying two matrices with shapes (a, b) and (b, c) is a * b * c. Given matrices A, B, C with shapes (10, 100), (100, 5), (5, 50) respectively, we can calculate the cost of different multiplication orders as follows:

Equation not displayed. Install 'katex' then re-install 'torch'.

In this case, multiplying A and B first followed by C is 10 times faster.

See Also

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {

linalg_multi_dot(list(torch_tensor(c(1, 2)), torch_tensor(c(2, 3))))
}
```

---

linalg_norm *Computes a vector or matrix norm.*

Description

If A is complex valued, it computes the norm of A$abs() Supports input of float, double, cfloat and cdouble dtypes. Whether this function computes a vector or matrix norm is determined as follows:

Usage

```
linalg_norm(A, ord = NULL, dim = NULL, keepdim = FALSE, dtype = NULL)
```

Arguments

A	(Tensor): tensor of shape (*, n) or (*, m, n) where * is zero or more batch dimensions
ord	(int, float, inf, -inf, 'fro', 'nuc', optional): order of norm. Default: NULL
dim	(int, Tuple[int], optional): dimensions over which to compute the vector or matrix norm. See above for the behavior when dim=NULL. Default: NULL
keepdim	(bool, optional): If set to TRUE, the reduced dimensions are retained in the result as dimensions with size one. Default: FALSE

dtype — dtype (torch_dtype, optional): If specified, the input tensor is cast to dtype before performing the operation, and the returned tensor's type will be dtype. Default: NULL

Details

- If dim is an int, the vector norm will be computed.
- If dim is a 2-tuple, the matrix norm will be computed.
- If dim=NULL and ord=NULL, A will be flattened to 1D and the 2-norm of the resulting vector will be computed.
- If dim=NULL and ord!=NULL, A must be 1D or 2D.

ord defines the norm that is computed. The following norms are supported:

ord	norm for matrices	norm for vectors
NULL (default)	Frobenius norm	2-norm (see below)
"fro"	Frobenius norm	– not supported –
"nuc"	nuclear norm	– not supported –
Inf	max(sum(abs(x), dim=2))	max(abs(x))
-Inf	min(sum(abs(x), dim=2))	min(abs(x))
0	– not supported –	sum(x != 0)
1	max(sum(abs(x), dim=1))	as below
-1	min(sum(abs(x), dim=1))	as below
2	largest singular value	as below
-2	smallest singular value	as below
other int or float	– not supported –	sum(abs(x)^{ord})^{(1 / ord)}

See Also

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
a <- torch_arange(0, 8, dtype = torch_float()) - 4
a
b <- a$reshape(c(3, 3))
b

linalg_norm(a)
linalg_norm(b)
}
```

linalg_pinv *Computes the pseudoinverse (Moore-Penrose inverse) of a matrix.*

Description

The pseudoinverse may be defined algebraically_ but it is more computationally convenient to understand it through the SVD_ Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if A is a batch of matrices then the output has the same batch dimensions.

Usage

```
linalg_pinv(A, rcond = NULL, hermitian = FALSE, atol = NULL, rtol = NULL)
```

Arguments

A	(Tensor): tensor of shape (*, m, n) where * is zero or more batch dimensions.
rcond	(float or Tensor, optional): the tolerance value to determine when is a singular value zero If it is a torch_Tensor, its shape must be broadcastable to that of the singular values of A as returned by linalg_svd(). Alias for rtol. Default: 0.
hermitian	(bool, optional): indicates whether A is Hermitian if complex or symmetric if real. Default: FALSE.
atol	the absolute tolerance value. When NULL it's considered to be zero.
rtol	the relative tolerance value. See above for the value it takes when NULL.

Details

If hermitian= TRUE, A is assumed to be Hermitian if complex or symmetric if real, but this is not checked internally. Instead, just the lower triangular part of the matrix is used in the computations. The singular values (or the norm of the eigenvalues when hermitian= TRUE) that are below the specified rcond threshold are treated as zero and discarded in the computation.

Note

This function uses linalg_svd() if hermitian= FALSE and linalg_eigh() if hermitian= TRUE. For CUDA inputs, this function synchronizes that device with the CPU.

Consider using linalg_lstsq() if possible for multiplying a matrix on the left by the pseudoinverse, as linalg_lstsq(A, B)$solution == A$pinv() %*% B

It is always prefered to use linalg_lstsq() when possible, as it is faster and more numerically stable than computing the pseudoinverse explicitly.

See Also

- linalg_inv() computes the inverse of a square matrix.
- linalg_lstsq() computes A$pinv() %*% B with a numerically stable algorithm.

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
A <- torch_randn(3, 5)
linalg_pinv(A)
}
```

---

linalg_qr *Computes the QR decomposition of a matrix.*

Description

Letting . be . or . , the **full QR decomposition** of a matrix . is defined as

Usage

```
linalg_qr(A, mode = "reduced")
```

Arguments

A	(Tensor): tensor of shape (*, m, n) where * is zero or more batch dimensions.
mode	(str, optional): one of 'reduced', 'complete', 'r'. Controls the shape of the returned tensors. Default: 'reduced'.

Details

Equation not displayed. Install 'katex' then re-install 'torch'.

where . is orthogonal in the real case and unitary in the complex case, and . is upper triangular. When m > n (tall matrix), as R is upper triangular, its last m - n rows are zero. In this case, we can drop the last m - n columns of Q to form the **reduced QR decomposition**:

Equation not displayed. Install 'katex' then re-install 'torch'.

The reduced QR decomposition agrees with the full QR decomposition when n >= m (wide matrix). Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if A is a batch of matrices then the output has the same batch dimensions. The parameter mode chooses between the full and reduced QR decomposition.

If A has shape (*, m, n), denoting k = min(m, n)

- mode = 'reduced' (default): Returns (Q, R) of shapes (*, m, k), (*, k, n) respectively.
- mode = 'complete': Returns (Q, R) of shapes (*, m, m), (*, m, n) respectively.
- mode = 'r': Computes only the reduced R. Returns (Q, R) with Q empty and R of shape (*, k, n).

Value

A list (Q, R).

See Also

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
a <- torch_tensor(rbind(c(12., -51, 4), c(6, 167, -68), c(-4, 24, -41)))
qr <- linalg_qr(a)

torch_mm(qr[[1]], qr[[2]])$round()
torch_mm(qr[[1]]$t(), qr[[1]])$round()
}
```

---

linalg_slogdet *Computes the sign and natural logarithm of the absolute value of the determinant of a square matrix.*

Description

For complex A, it returns the angle and the natural logarithm of the modulus of the determinant, that is, a logarithmic polar decomposition of the determinant. Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if A is a batch of matrices then the output has the same batch dimensions.

Usage

```
linalg_slogdet(A)
```

Arguments

A	(Tensor): tensor of shape (*, n, n) where * is zero or more batch dimensions.

Value

A list (sign, logabsdet). logabsdet will always be real-valued, even when A is complex. sign will have the same dtype as A.

Notes

- The determinant can be recovered as sign * exp(logabsdet).
- When a matrix has a determinant of zero, it returns (0, -Inf).

See Also

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
a <- torch_randn(3, 3)
linalg_slogdet(a)
}
```

---

linalg_solve — *Computes the solution of a square system of linear equations with a unique solution.*

Description

Letting . be . or . , this function computes the solution . of the **linear system** associated to . , which is defined as

Usage

```
linalg_solve(A, B)
```

Arguments

A	(Tensor): tensor of shape (*, n, n) where * is zero or more batch dimensions.
B	(Tensor): right-hand side tensor of shape (*, n) or (*, n, k) or (n,) or (n, k) according to the rules described above

Details

$$AX = B$$

This system of linear equations has one solution if and only if . is `invertible_`. This function assumes that . is invertible. Supports inputs of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if the inputs are batches of matrices then the output has the same batch dimensions.

Letting `*` be zero or more batch dimensions,

- If `A` has shape `(*, n, n)` and `B` has shape `(*, n)` (a batch of vectors) or shape `(*, n, k)` (a batch of matrices or "multiple right-hand sides"), this function returns `X` of shape `(*, n)` or `(*, n, k)` respectively.
- Otherwise, if `A` has shape `(*, n, n)` and `B` has shape `(n,)` or `(n, k)`, `B` is broadcasted to have shape `(*, n)` or `(*, n, k)` respectively.

This function then returns the solution of the resulting batch of systems of linear equations.

Note

This function computes `X = A$inverse() @ B` in a faster and more numerically stable way than performing the computations separately.

See Also

Other linalg: `linalg_cholesky()`, `linalg_cholesky_ex()`, `linalg_det()`, `linalg_eig()`, `linalg_eigh()`, `linalg_eigvals()`, `linalg_eigvalsh()`, `linalg_householder_product()`, `linalg_inv()`, `linalg_inv_ex()`, `linalg_lstsq()`, `linalg_matrix_norm()`, `linalg_matrix_power()`, `linalg_matrix_rank()`, `linalg_multi_dot()`, `linalg_norm()`, `linalg_pinv()`, `linalg_qr()`, `linalg_slogdet()`, `linalg_solve_triangular(`
`linalg_svd()`, `linalg_svdvals()`, `linalg_tensorinv()`, `linalg_tensorsolve()`, `linalg_vector_norm()`

Examples

```
if (torch_is_installed()) {
A <- torch_randn(3, 3)
b <- torch_randn(3)
x <- linalg_solve(A, b)
torch_allclose(torch_matmul(A, x), b)
}
```

`linalg_solve_triangular`
Triangular solve

Description

Triangular solve

Usage

```
linalg_solve_triangular(A, B, ..., upper, left = TRUE, unitriangular = FALSE)
```

Arguments

A	tensor of shape (*, n, n) or (*, k, k) if left=TRUE) where * is zero or more batch dimensions.
B	right-hand side tensor of shape (*, n, k)
...	Currently ignored.
upper	whether A is an upper or lower triangular matrix.
left	wheter to solve the system AX=B or XA=B
unitriangular	if TRUE, the diagonal elements of A are assumed to be all equal to 1.

See Also

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

---

linalg_svd *Computes the singular value decomposition (SVD) of a matrix.*

Description

Letting . be . or . , the **full SVD** of a matrix . , if k = min(m,n), is defined as

Usage

```
linalg_svd(A, full_matrices = TRUE)
```

Arguments

A	(Tensor): tensor of shape (*, m, n) where * is zero or more batch dimensions.
full_matrices	(bool, optional): controls whether to compute the full or reduced SVD, and consequently, the shape of the returned tensors U and V. Default: TRUE.

Details

Equation not displayed. Install 'katex' then re-install 'torch'.

where . , . is the conjugate transpose when . is complex, and the transpose when . is real-valued.

The matrices . , . (and thus .) are orthogonal in the real case, and unitary in the complex case. When `m > n` (resp. `m < n`) we can drop the last `m - n` (resp. `n - m`) columns of `U` (resp. `V`) to form the **reduced SVD**:

Equation not displayed. Install 'katex' then re-install 'torch'.

where . .

In this case, . and . also have orthonormal columns. Supports input of float, double, cfloat and cdouble dtypes.

Also supports batches of matrices, and if `A` is a batch of matrices then the output has the same batch dimensions.

The returned decomposition is a named tuple `(U, S, V)` which corresponds to . , . , . above.

The singular values are returned in descending order. The parameter `full_matrices` chooses between the full (default) and reduced SVD.

Value

A list `(U, S, V)` which corresponds to . , . , . above. `S` will always be real-valued, even when `A` is complex. It will also be ordered in descending order. `U` and `V` will have the same dtype as `A`. The left / right singular vectors will be given by the columns of `U` and the rows of `V` respectively.

Warnings

The returned tensors `U` and `V` are not unique, nor are they continuous with respect to `A`. Due to this lack of uniqueness, different hardware and software may compute different singular vectors. This non-uniqueness is caused by the fact that multiplying any pair of singular vectors . by `-1` in the real case or by . in the complex case produces another two valid singular vectors of the matrix. This non-uniqueness problem is even worse when the matrix has repeated singular values. In this case, one may multiply the associated singular vectors of `U` and `V` spanning the subspace by a rotation matrix and the resulting vectors will span the same subspace.

Gradients computed using `U` or `V` will only be finite when `A` does not have zero as a singular value or repeated singular values. Furthermore, if the distance between any two singular values is close to zero, the gradient will be numerically unstable, as it depends on the singular values . through the computation of . . The gradient will also be numerically unstable when `A` has small singular values, as it also depends on the computaiton of . .

Note

When `full_matrices=TRUE`, the gradients with respect to `U[..., :, min(m, n):]` and `Vh[..., min(m, n):, :]` will be ignored, as those vectors can be arbitrary bases of the corresponding subspaces.

See Also

- `linalg_svdvals()` computes only the singular values. Unlike `linalg_svd()`, the gradients of `linalg_svdvals()` are always numerically stable.

- linalg_eig() for a function that computes another type of spectral decomposition of a matrix. The eigendecomposition works just on on square matrices.
- linalg_eigh() for a (faster) function that computes the eigenvalue decomposition for Hermitian and symmetric matrices.
- linalg_qr() for another (much faster) decomposition that works on general matrices.

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {

a <- torch_randn(5, 3)
linalg_svd(a, full_matrices = FALSE)
}
```

---

linalg_svdvals *Computes the singular values of a matrix.*

Description

Supports input of float, double, cfloat and cdouble dtypes. Also supports batches of matrices, and if A is a batch of matrices then the output has the same batch dimensions. The singular values are returned in descending order.

Usage

```
linalg_svdvals(A)
```

Arguments

A	(Tensor): tensor of shape (*, m, n) where * is zero or more batch dimensions.

Value

A real-valued tensor, even when A is complex.

See Also

linalg_svd() computes the full singular value decomposition.

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_tensorinv(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
A <- torch_randn(5, 3)
S <- linalg_svdvals(A)
S
}
```

---

linalg_tensorinv *Computes the multiplicative inverse of* torch_tensordot()

Description

If m is the product of the first ind dimensions of A and n is the product of the rest of the dimensions, this function expects m and n to be equal. If this is the case, it computes a tensor X such that tensordot(A, X, ind) is the identity matrix in dimension m.

Usage

```
linalg_tensorinv(A, ind = 3L)
```

Arguments

A	(Tensor): tensor to invert.
ind	(int): index at which to compute the inverse of torch_tensordot(). Default: 3.

Details

Supports input of float, double, cfloat and cdouble dtypes.

Note

Consider using linalg_tensorsolve() if possible for multiplying a tensor on the left by the tensor inverse as linalg_tensorsolve(A, B) == torch_tensordot(linalg_tensorinv(A), B))

It is always prefered to use linalg_tensorsolve() when possible, as it is faster and more numerically stable than computing the pseudoinverse explicitly.

See Also

- linalg_tensorsolve() computes torch_tensordot(linalg_tensorinv(A), B)).

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_svdvals(), linalg_tensorsolve(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
A <- torch_eye(4 * 6)$reshape(c(4, 6, 8, 3))
Ainv <- linalg_tensorinv(A, ind = 3)
Ainv$shape
B <- torch_randn(4, 6)
torch_allclose(torch_tensordot(Ainv, B), linalg_tensorsolve(A, B))

A <- torch_randn(4, 4)
Atensorinv <- linalg_tensorinv(A, 2)
Ainv <- linalg_inv(A)
torch_allclose(Atensorinv, Ainv)
}
```

---

linalg_tensorsolve *Computes the solution* X *to the system* torch_tensordot(A, X) = B.

Description

If m is the product of the first B\ .ndim dimensions of A and n is the product of the rest of the dimensions, this function expects m and n to be equal. The returned tensor x satisfies tensordot(A, x, dims=x$ndim) == B.

Usage

```
linalg_tensorsolve(A, B, dims = NULL)
```

Arguments

A	(Tensor): tensor to solve for.
B	(Tensor): the solution
dims	(Tuple[int], optional): dimensions of A to be moved. If NULL, no dimensions are moved. Default: NULL.

Details

If dims is specified, A will be reshaped as A = movedim(A, dims, seq(len(dims) - A$ndim + 1, 0))

Supports inputs of float, double, cfloat and cdouble dtypes.

See Also

- linalg_tensorinv() computes the multiplicative inverse of torch_tensordot().

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_vector_norm()

Examples

```
if (torch_is_installed()) {
A <- torch_eye(2 * 3 * 4)$reshape(c(2 * 3, 4, 2, 3, 4))
B <- torch_randn(2 * 3, 4)
X <- linalg_tensorsolve(A, B)
X$shape
torch_allclose(torch_tensordot(A, X, dims = X$ndim), B)

A <- torch_randn(6, 4, 4, 3, 2)
B <- torch_randn(4, 3, 2)
X <- linalg_tensorsolve(A, B, dims = c(1, 3))
A <- A$permute(c(2, 4, 5, 1, 3))
torch_allclose(torch_tensordot(A, X, dims = X$ndim), B, atol = 1e-6)
}
```

---

linalg_vector_norm *Computes a vector norm.*

Description

If A is complex valued, it computes the norm of A$abs() Supports input of float, double, cfloat and cdouble dtypes. This function does not necessarily treat multidimensonal A as a batch of vectors, instead:

Usage

```
linalg_vector_norm(A, ord = 2, dim = NULL, keepdim = FALSE, dtype = NULL)
```

Arguments

A	(Tensor): tensor, flattened by default, but this behavior can be controlled using dim.
ord	(int, float, inf, -inf, 'fro', 'nuc', optional): order of norm. Default: 2
dim	(int, Tuple[int], optional): dimensions over which to compute the vector or matrix norm. See above for the behavior when dim=NULL. Default: NULL
keepdim	(bool, optional): If set to TRUE, the reduced dimensions are retained in the result as dimensions with size one. Default: FALSE

dtype — dtype (torch_dtype, optional): If specified, the input tensor is cast to dtype before performing the operation, and the returned tensor's type will be dtype. Default: NULL

Details

- If dim=NULL, A will be flattened before the norm is computed.
- If dim is an int or a tuple, the norm will be computed over these dimensions and the other dimensions will be treated as batch dimensions.

This behavior is for consistency with linalg_norm().

ord defines the norm that is computed. The following norms are supported:

ord	norm for matrices	norm for vectors
NULL (default)	Frobenius norm	2-norm (see below)
"fro"	Frobenius norm	– not supported –
"nuc"	nuclear norm	– not supported –
Inf	max(sum(abs(x), dim=2))	max(abs(x))
-Inf	min(sum(abs(x), dim=2))	min(abs(x))
0	– not supported –	sum(x != 0)
1	max(sum(abs(x), dim=1))	as below
-1	min(sum(abs(x), dim=1))	as below
2	largest singular value	as below
-2	smallest singular value	as below
other int or float	– not supported –	sum(abs(x)^{ord})^{(1 / ord)}

See Also

Other linalg: linalg_cholesky(), linalg_cholesky_ex(), linalg_det(), linalg_eig(), linalg_eigh(), linalg_eigvals(), linalg_eigvalsh(), linalg_householder_product(), linalg_inv(), linalg_inv_ex(), linalg_lstsq(), linalg_matrix_norm(), linalg_matrix_power(), linalg_matrix_rank(), linalg_multi_dot(), linalg_norm(), linalg_pinv(), linalg_qr(), linalg_slogdet(), linalg_solve(), linalg_solve_triangular(), linalg_svd(), linalg_svdvals(), linalg_tensorinv(), linalg_tensorsolve()

Examples

```
if (torch_is_installed()) {
a <- torch_arange(0, 8, dtype = torch_float()) - 4
a
b <- a$reshape(c(3, 3))
b

linalg_vector_norm(a, ord = 3.5)
linalg_vector_norm(b, ord = 3.5)
}
```

load_state_dict *Load a state dict file*

Description

This function should only be used to load models saved in python. For it to work correctly you need to use `torch.save` with the flag: `_use_new_zipfile_serialization=True` and also remove all `nn.Parameter` classes from the tensors in the dict.

Usage

```
load_state_dict(path, ..., legacy_stream = FALSE)
```

Arguments

`path`	to the state dict file
`...`	additional arguments that are currently not used.
`legacy_stream`	if `TRUE` then the state dict is loaded using a a legacy way of handling streams.

Details

The above might change with development of this in pytorch's C++ api.

Value

a named list of tensors.

local_autocast *Autocast context manager*

Description

Allow regions of your code to run in mixed precision. In these regions, ops run in an op-specific dtype chosen by autocast to improve performance while maintaining accuracy.

Usage

```
local_autocast(
  device_type,
  dtype = NULL,
  enabled = TRUE,
  cache_enabled = NULL,
  ...,
  .env = parent.frame()
)
```

```
with_autocast(
  code,
  ...,
  device_type,
  dtype = NULL,
  enabled = TRUE,
  cache_enabled = NULL
)

set_autocast(device_type, dtype = NULL, enabled = TRUE, cache_enabled = NULL)

unset_autocast(context)
```

Arguments

device_type	a character string indicating whether to use 'cuda' or 'cpu' device
dtype	a torch data type indicating whether to use `torch_float16()` or `torch_bfloat16()`.
enabled	a logical value indicating whether autocasting should be enabled in the region. Default: TRUE
cache_enabled	a logical value indicating whether the weight cache inside autocast should be enabled.
...	currently unused.
.env	The environment to use for scoping.
code	code to be executed with no gradient recording.
context	Returned by `set_autocast` and should be passed when unsetting it.

Details

When entering an autocast-enabled region, Tensors may be any type. You should not call `half()` or `bfloat16()` on your model(s) or inputs when using autocasting.

`autocast` should only be enabled during the forward pass(es) of your network, including the loss computation(s). Backward passes under autocast are not recommended. Backward ops run in the same type that autocast used for corresponding forward ops.

Functions

- `with_autocast()`: A with context for automatic mixed precision.
- `set_autocast()`: Set the autocast context. For advanced users only.
- `unset_autocast()`: Unset the autocast context.

See Also

`cuda_amp_grad_scaler()` to perform dynamic gradient scaling.

Examples

```
if (torch_is_installed()) {
x <- torch_randn(5, 5, dtype = torch_float32())
y <- torch_randn(5, 5, dtype = torch_float32())

foo <- function(x, y) {
  local_autocast(device = "cpu")
  z <- torch_mm(x, y)
  w <- torch_mm(z, x)
  w
}

out <- foo(x, y)
}
```

`local_device` *Device contexts*

Description

Device contexts

Usage

```
local_device(device, ..., .env = parent.frame())

with_device(code, ..., device)
```

Arguments

`device`	A torch device to be used by default when creating new tensors.
`...`	currently unused.
`.env`	The environment to use for scoping.
`code`	The code to be evaluated in the modified environment.

Functions

- `with_device()`: Modifies the default device for the selected context.

lr_cosine_annealing — *Set the learning rate of each parameter group using a cosine annealing schedule*

Description

Set the learning rate of each parameter group using a cosine annealing schedule

Usage

```
lr_cosine_annealing(
  optimizer,
  T_max,
  eta_min = 0,
  last_epoch = -1,
  verbose = FALSE
)
```

Arguments

optimizer	(Optimizer): Wrapped optimizer.
T_max	Maximum number of iterations
eta_min	Minimum learning rate. Default: 0.
last_epoch	The index of the last epoch
verbose	(bool): If TRUE, prints a message to stdout for each update. Default: FALSE.

lr_lambda — *Sets the learning rate of each parameter group to the initial lr times a given function. When last_epoch=-1, sets initial lr as lr.*

Description

Sets the learning rate of each parameter group to the initial lr times a given function. When last_epoch=-1, sets initial lr as lr.

Usage

```
lr_lambda(optimizer, lr_lambda, last_epoch = -1, verbose = FALSE)
```

Arguments

optimizer	(Optimizer): Wrapped optimizer.
lr_lambda	(function or list): A function which computes a multiplicative factor given an integer parameter epoch, or a list of such functions, one for each group in optimizer.param_groups.
last_epoch	(int): The index of last epoch. Default: -1.
verbose	(bool): If TRUE, prints a message to stdout for each update. Default: FALSE.

Examples

```
if (torch_is_installed()) {
# Assuming optimizer has two groups.
lambda1 <- function(epoch) epoch %/% 30
lambda2 <- function(epoch) 0.95^epoch
## Not run:
scheduler <- lr_lambda(optimizer, lr_lambda = list(lambda1, lambda2))
for (epoch in 1:100) {
  train(...)
  validate(...)
  scheduler$step()
}

## End(Not run)

}
```

`lr_multiplicative` *Multiply the learning rate of each parameter group by the factor given in the specified function. When last_epoch=-1, sets initial lr as lr.*

Description

Multiply the learning rate of each parameter group by the factor given in the specified function. When last_epoch=-1, sets initial lr as lr.

Usage

```
lr_multiplicative(optimizer, lr_lambda, last_epoch = -1, verbose = FALSE)
```

Arguments

`optimizer`	(Optimizer): Wrapped optimizer.
`lr_lambda`	(function or list): A function which computes a multiplicative factor given an integer parameter epoch, or a list of such functions, one for each group in optimizer.param_groups.
`last_epoch`	(int): The index of last epoch. Default: -1.
`verbose`	(bool): If `TRUE`, prints a message to stdout for each update. Default: `FALSE`.

Examples

```
if (torch_is_installed()) {
## Not run:
lmbda <- function(epoch) 0.95
scheduler <- lr_multiplicative(optimizer, lr_lambda = lmbda)
for (epoch in 1:100) {
  train(...)
  validate(...)
```

```
  scheduler$step()
}

## End(Not run)

}
```

---

lr_one_cycle *Once cycle learning rate*

Description

Sets the learning rate of each parameter group according to the 1cycle learning rate policy. The 1cycle policy anneals the learning rate from an initial learning rate to some maximum learning rate and then from that maximum learning rate to some minimum learning rate much lower than the initial learning rate.

Usage

```
lr_one_cycle(
  optimizer,
  max_lr,
  total_steps = NULL,
  epochs = NULL,
  steps_per_epoch = NULL,
  pct_start = 0.3,
  anneal_strategy = "cos",
  cycle_momentum = TRUE,
  base_momentum = 0.85,
  max_momentum = 0.95,
  div_factor = 25,
  final_div_factor = 10000,
  last_epoch = -1,
  verbose = FALSE
)
```

Arguments

optimizer	(Optimizer): Wrapped optimizer.
max_lr	(float or list): Upper learning rate boundaries in the cycle for each parameter group.
total_steps	(int): The total number of steps in the cycle. Note that if a value is not provided here, then it must be inferred by providing a value for epochs and steps_per_epoch. Default: NULL
epochs	(int): The number of epochs to train for. This is used along with steps_per_epoch in order to infer the total number of steps in the cycle if a value for total_steps is not provided. Default: NULL

`steps_per_epoch`
: (int): The number of steps per epoch to train for. This is used along with epochs in order to infer the total number of steps in the cycle if a value for total_steps is not provided. Default: NULL

`pct_start`
: (float): The percentage of the cycle (in number of steps) spent increasing the learning rate. Default: 0.3

`anneal_strategy`
: (str): {'cos', 'linear'} Specifies the annealing strategy: "cos" for cosine annealing, "linear" for linear annealing. Default: 'cos'

`cycle_momentum`
: (bool): If `TRUE`, momentum is cycled inversely to learning rate between 'base_momentum' and 'max_momentum'. Default: TRUE

`base_momentum`
: (float or list): Lower momentum boundaries in the cycle for each parameter group. Note that momentum is cycled inversely to learning rate; at the peak of a cycle, momentum is 'base_momentum' and learning rate is 'max_lr'. Default: 0.85

`max_momentum`
: (float or list): Upper momentum boundaries in the cycle for each parameter group. Functionally, it defines the cycle amplitude (max_momentum - base_momentum). Note that momentum is cycled inversely to learning rate; at the start of a cycle, momentum is 'max_momentum' and learning rate is 'base_lr' Default: 0.95

`div_factor`
: (float): Determines the initial learning rate via initial_lr = max_lr/div_factor Default: 25

`final_div_factor`
: (float): Determines the minimum learning rate via min_lr = initial_lr/final_div_factor Default: 1e4

`last_epoch`
: (int): The index of the last batch. This parameter is used when resuming a training job. Since `step()` should be invoked after each batch instead of after each epoch, this number represents the total number of *batches* computed, not the total number of epochs computed. When last_epoch=-1, the schedule is started from the beginning. Default: -1

`verbose`
: (bool): If `TRUE`, prints a message to stdout for each update. Default: `FALSE`.

Details

This policy was initially described in the paper Super-Convergence: Very Fast Training of Neural Networks Using Large Learning Rates.

The 1cycle learning rate policy changes the learning rate after every batch. `step` should be called after a batch has been used for training. This scheduler is not chainable.

Note also that the total number of steps in the cycle can be determined in one of two ways (listed in order of precedence):

- A value for total_steps is explicitly provided.
- A number of epochs (epochs) and a number of steps per epoch (steps_per_epoch) are provided.

In this case, the number of total steps is inferred by total_steps = epochs * steps_per_epoch

You must either provide a value for total_steps or provide a value for both epochs and steps_per_epoch.

Examples

```
if (torch_is_installed()) {
## Not run:
data_loader <- dataloader(...)
optimizer <- optim_sgd(model$parameters, lr = 0.1, momentum = 0.9)
scheduler <- lr_one_cycle(optimizer,
  max_lr = 0.01, steps_per_epoch = length(data_loader),
  epochs = 10
)

for (i in 1:epochs) {
  coro::loop(for (batch in data_loader) {
    train_batch(...)
    scheduler$step()
  })
}

## End(Not run)

}
```

`lr_reduce_on_plateau` *Reduce learning rate on plateau*

Description

Reduce learning rate when a metric has stopped improving. Models often benefit from reducing the learning rate by a factor of 2-10 once learning stagnates. This scheduler reads a metrics quantity and if no improvement is seen for a 'patience' number of epochs, the learning rate is reduced.

Usage

```
lr_reduce_on_plateau(
  optimizer,
  mode = "min",
  factor = 0.1,
  patience = 10,
  threshold = 1e-04,
  threshold_mode = "rel",
  cooldown = 0,
  min_lr = 0,
  eps = 1e-08,
  verbose = FALSE
)
```

Arguments

optimizer	(Optimizer): Wrapped optimizer.
mode	(str): One of min, max. In min mode, lr will be reduced when the quantity monitored has stopped decreasing; in max mode it will be reduced when the quantity monitored has stopped increasing. Default: 'min'.
factor	(float): Factor by which the learning rate will be reduced. new_lr <- lr * factor. Default: 0.1.
patience	(int): Number of epochs with no improvement after which learning rate will be reduced. For example, if patience = 2, then we will ignore the first 2 epochs with no improvement, and will only decrease the LR after the 3rd epoch if the loss still hasn't improved then. Default: 10.
threshold	(float):Threshold for measuring the new optimum, to only focus on significant changes. Default: 1e-4.
threshold_mode	(str): One of rel, abs. In rel mode, dynamic_threshold <- best * (1 + threshold) in 'max' mode or best * (1 - threshold) in min mode. In abs mode, dynamic_threshold <- best + threshold in max mode or best - threshold in min mode. Default: 'rel'.
cooldown	(int): Number of epochs to wait before resuming normal operation after lr has been reduced. Default: 0.
min_lr	(float or list): A scalar or a list of scalars. A lower bound on the learning rate of all param groups or each group respectively. Default: 0.
eps	(float): Minimal decay applied to lr. If the difference between new and old lr is smaller than eps, the update is ignored. Default: 1e-8.
verbose	(bool): If TRUE, prints a message to stdout for each update. Default: FALSE.

Examples

```
if (torch_is_installed()) {
## Not run:
optimizer <- optim_sgd(model$parameters(), lr=0.1, momentum=0.9)
scheduler <- lr_reduce_on_plateau(optimizer, 'min')
for (epoch in 1:10) {
 train(...)
 val_loss <- validate(...)
 # note that step should be called after validate
 scheduler$step(val_loss)
}

## End(Not run)
}
```

lr_scheduler *Creates learning rate schedulers*

Description

Creates learning rate schedulers

Usage

```
lr_scheduler(
  classname = NULL,
  inherit = LRScheduler,
  ...,
  parent_env = parent.frame()
)
```

Arguments

classname	optional name for the learning rate scheduler
inherit	an optional learning rate scheduler to inherit from
...	named list of methods. You must implement the `get_lr()` method that doesn't take any argument and returns learning rates for each `param_group` in the optimizer.
parent_env	passed to `R6::R6Class()`.

lr_step *Step learning rate decay*

Description

Decays the learning rate of each parameter group by gamma every step_size epochs. Notice that such decay can happen simultaneously with other changes to the learning rate from outside this scheduler. When last_epoch=-1, sets initial lr as lr.

Usage

```
lr_step(optimizer, step_size, gamma = 0.1, last_epoch = -1)
```

Arguments

optimizer	(Optimizer): Wrapped optimizer.
step_size	(int): Period of learning rate decay.
gamma	(float): Multiplicative factor of learning rate decay. Default: 0.1.
last_epoch	(int): The index of last epoch. Default: -1.

Examples

```
if (torch_is_installed()) {
## Not run:
# Assuming optimizer uses lr = 0.05 for all groups
# lr = 0.05     if epoch < 30
# lr = 0.005    if 30 <= epoch < 60
# lr = 0.0005   if 60 <= epoch < 90
# ...
scheduler <- lr_step(optimizer, step_size = 30, gamma = 0.1)
for (epoch in 1:100) {
  train(...)
  validate(...)
  scheduler$step()
}

## End(Not run)

}
```

---

nnf_adaptive_avg_pool1d

Adaptive_avg_pool1d

Description

Applies a 1D adaptive average pooling over an input signal composed of several input planes.

Usage

```
nnf_adaptive_avg_pool1d(input, output_size)
```

Arguments

input	input tensor of shape (minibatch , in_channels , iW)
output_size	the target output size (single integer)

---

nnf_adaptive_avg_pool2d

Adaptive_avg_pool2d

Description

Applies a 2D adaptive average pooling over an input signal composed of several input planes.

Usage

```
nnf_adaptive_avg_pool2d(input, output_size)
```

Arguments

`input`	input tensor (minibatch, in_channels , iH , iW)
`output_size`	the target output size (single integer or double-integer tuple)

---

nnf_adaptive_avg_pool3d *Adaptive_avg_pool3d*

Description

Applies a 3D adaptive average pooling over an input signal composed of several input planes.

Usage

```
nnf_adaptive_avg_pool3d(input, output_size)
```

Arguments

`input`	input tensor (minibatch, in_channels , iT * iH , iW)
`output_size`	the target output size (single integer or triple-integer tuple)

---

nnf_adaptive_max_pool1d *Adaptive_max_pool1d*

Description

Applies a 1D adaptive max pooling over an input signal composed of several input planes.

Usage

```
nnf_adaptive_max_pool1d(input, output_size, return_indices = FALSE)
```

Arguments

`input`	input tensor of shape (minibatch , in_channels , iW)
`output_size`	the target output size (single integer)
`return_indices`	whether to return pooling indices. Default: `FALSE`

nnf_adaptive_max_pool2d

Adaptive_max_pool2d

Description

Applies a 2D adaptive max pooling over an input signal composed of several input planes.

Usage

```
nnf_adaptive_max_pool2d(input, output_size, return_indices = FALSE)
```

Arguments

`input`	input tensor (minibatch, in_channels , iH , iW)
`output_size`	the target output size (single integer or double-integer tuple)
`return_indices`	whether to return pooling indices. Default: `FALSE`

nnf_adaptive_max_pool3d

Adaptive_max_pool3d

Description

Applies a 3D adaptive max pooling over an input signal composed of several input planes.

Usage

```
nnf_adaptive_max_pool3d(input, output_size, return_indices = FALSE)
```

Arguments

`input`	input tensor (minibatch, in_channels , iT * iH , iW)
`output_size`	the target output size (single integer or triple-integer tuple)
`return_indices`	whether to return pooling indices. Default:`FALSE`

nnf_affine_grid *Affine_grid*

Description

Generates a 2D or 3D flow field (sampling grid), given a batch of affine matrices `theta`.

Usage

```
nnf_affine_grid(theta, size, align_corners = FALSE)
```

Arguments

`theta`	(Tensor) input batch of affine matrices with shape ($N \times 2 \times 3$) for 2D or ($N \times 3 \times 4$) for 3D
`size`	(torch.Size) the target output image size. ($N \times C \times H \times W$ for 2D or $N \times C \times D \times H \times W$ for 3D) Example: torch.Size((32, 3, 24, 24))
`align_corners`	(bool, optional) if `True`, consider `-1` and `1` to refer to the centers of the corner pixels rather than the image corners. Refer to `nnf_grid_sample()` for a more complete description. A grid generated by `nnf_affine_grid()` should be passed to `nnf_grid_sample()` with the same setting for this option. Default: `False`

Note

This function is often used in conjunction with `nnf_grid_sample()` to build `Spatial Transformer Networks_`
.

nnf_alpha_dropout *Alpha_dropout*

Description

Applies alpha dropout to the input.

Usage

```
nnf_alpha_dropout(input, p = 0.5, training = FALSE, inplace = FALSE)
```

Arguments

`input`	the input tensor
`p`	probability of an element to be zeroed. Default: 0.5
`training`	apply dropout if is `TRUE`. Default: `TRUE`
`inplace`	If set to `TRUE`, will do this operation in-place. Default: `FALSE`

nnf_area_under_min_fpr_fnr

Area under the $Min(FPR, FNR)$ (AUM)

Description

Function that measures Area under the $Min(FPR, FNR)$ (AUM) between each element in the $input$ and $target$.

Usage

```
nnf_area_under_min_fpr_fnr(input, target)
```

Arguments

input	Tensor of arbitrary shape
target	Tensor of the same shape as input. Should be the factor level of the binary outcome, i.e. with values 1L and 2L.

Details

This is used for measuring the error of a binary reconstruction within highly unbalanced dataset, where the goal is optimizing the ROC curve.

nnf_avg_pool1d *Avg_pool1d*

Description

Applies a 1D average pooling over an input signal composed of several input planes.

Usage

```
nnf_avg_pool1d(
  input,
  kernel_size,
  stride = NULL,
  padding = 0,
  ceil_mode = FALSE,
  count_include_pad = TRUE
)
```

Arguments

input	input tensor of shape (minibatch , in_channels , iW)
kernel_size	the size of the window. Can be a single number or a tuple (kW,).
stride	the stride of the window. Can be a single number or a tuple (sW,). Default: kernel_size
padding	implicit zero paddings on both sides of the input. Can be a single number or a tuple (padW,). Default: 0
ceil_mode	when True, will use ceil instead of floor to compute the output shape. Default: FALSE
count_include_pad	when True, will include the zero-padding in the averaging calculation. Default: TRUE

---

nnf_avg_pool2d *Avg_pool2d*

Description

Applies 2D average-pooling operation in $kH * kW$ regions by step size $sH * sW$ steps. The number of output features is equal to the number of input planes.

Usage

```
nnf_avg_pool2d(
  input,
  kernel_size,
  stride = NULL,
  padding = 0,
  ceil_mode = FALSE,
  count_include_pad = TRUE,
  divisor_override = NULL
)
```

Arguments

input	input tensor (minibatch, in_channels , iH , iW)
kernel_size	size of the pooling region. Can be a single number or a tuple (kH, kW)
stride	stride of the pooling operation. Can be a single number or a tuple (sH, sW). Default: kernel_size
padding	implicit zero paddings on both sides of the input. Can be a single number or a tuple (padH, padW). Default: 0
ceil_mode	when True, will use ceil instead of floor in the formula to compute the output shape. Default: FALSE

count_include_pad
: when True, will include the zero-padding in the averaging calculation. Default: TRUE

divisor_override
: if specified, it will be used as divisor, otherwise size of the pooling region will be used. Default: NULL

---

nnf_avg_pool3d *Avg_pool3d*

Description

Applies 3D average-pooling operation in $kT * kH * kW$ regions by step size $sT * sH * sW$ steps. The number of output features is equal to $\lfloor \frac{\text{input planes}}{sT} \rfloor$.

Usage

```
nnf_avg_pool3d(
  input,
  kernel_size,
  stride = NULL,
  padding = 0,
  ceil_mode = FALSE,
  count_include_pad = TRUE,
  divisor_override = NULL
)
```

Arguments

input
: input tensor (minibatch, in_channels , iT * iH , iW)

kernel_size
: size of the pooling region. Can be a single number or a tuple (kT, kH, kW)

stride
: stride of the pooling operation. Can be a single number or a tuple (sT, sH, sW). Default: kernel_size

padding
: implicit zero paddings on both sides of the input. Can be a single number or a tuple (padT, padH, padW), Default: 0

ceil_mode
: when True, will use ceil instead of floor in the formula to compute the output shape

count_include_pad
: when True, will include the zero-padding in the averaging calculation

divisor_override
: NA if specified, it will be used as divisor, otherwise size of the pooling region will be used. Default: NULL

nnf_batch_norm *Batch_norm*

Description

Applies Batch Normalization for each channel across a batch of data.

Usage

```
nnf_batch_norm(
  input,
  running_mean,
  running_var,
  weight = NULL,
  bias = NULL,
  training = FALSE,
  momentum = 0.1,
  eps = 1e-05
)
```

Arguments

input	input tensor
running_mean	the running_mean tensor
running_var	the running_var tensor
weight	the weight tensor
bias	the bias tensor
training	bool wether it's training. Default: FALSE
momentum	the value used for the running_mean and running_var computation. Can be set to None for cumulative moving average (i.e. simple average). Default: 0.1
eps	a value added to the denominator for numerical stability. Default: 1e-5

nnf_bilinear *Bilinear*

Description

Applies a bilinear transformation to the incoming data: $y = x_1 A x_2 + b$

Usage

```
nnf_bilinear(input1, input2, weight, bias = NULL)
```

Arguments

input1	$(N, *, H_{in1})$ where $H_{in1} =$ in1_features and $*$ means any number of additional dimensions. All but the last dimension of the inputs should be the same.
input2	$(N, *, H_{in2})$ where $H_{in2} =$ in2_features
weight	(out_features, in1_features, in2_features)
bias	(out_features)

Value

output $(N, *, H_{out})$ where $H_{out} =$ out_features and all but the last dimension are the same shape as the input.

---

nnf_binary_cross_entropy *Binary_cross_entropy*

Description

Function that measures the Binary Cross Entropy between the target and the output.

Usage

```
nnf_binary_cross_entropy(
  input,
  target,
  weight = NULL,
  reduction = c("mean", "sum", "none")
)
```

Arguments

input	tensor (N,*) where ** means, any number of additional dimensions
target	tensor (N,*) , same shape as the input
weight	(tensor) weight for each value.
reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

nnf_binary_cross_entropy_with_logits *Binary_cross_entropy_with_logits*

Description

Function that measures Binary Cross Entropy between target and output logits.

Usage

```
nnf_binary_cross_entropy_with_logits(
  input,
  target,
  weight = NULL,
  reduction = c("mean", "sum", "none"),
  pos_weight = NULL
)
```

Arguments

input	Tensor of arbitrary shape
target	Tensor of the same shape as input
weight	(Tensor, optional) a manual rescaling weight if provided it's repeated to match input tensor shape.
reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'
pos_weight	(Tensor, optional) a weight of positive examples. Must be a vector with length equal to the number of classes.

nnf_celu *Celu*

Description

Applies element-wise, $CELU(x) = max(0, x) + min(0, \alpha * (exp(x\alpha) - 1))$.

Usage

```
nnf_celu(input, alpha = 1, inplace = FALSE)

nnf_celu_(input, alpha = 1)
```

Arguments

`input`	(N,*) tensor, where * means, any number of additional dimensions
`alpha`	the alpha value for the CELU formulation. Default: 1.0
`inplace`	can optionally do the operation in-place. Default: FALSE

`nnf_contrib_sparsemax` *Sparsemax*

Description

Applies the SparseMax activation.

Usage

```
nnf_contrib_sparsemax(input, dim = -1)
```

Arguments

`input`	the input tensor
`dim`	The dimension over which to apply the sparsemax function. (-1)

Details

The SparseMax activation is described in 'From Softmax to Sparsemax: A Sparse Model of Attention and Multi-Label Classification' The implementation is based on aced125/sparsemax

---

`nnf_conv1d` *Conv1d*

Description

Applies a 1D convolution over an input signal composed of several input planes.

Usage

```
nnf_conv1d(
  input,
  weight,
  bias = NULL,
  stride = 1,
  padding = 0,
  dilation = 1,
  groups = 1
)
```

Arguments

input	input tensor of shape (minibatch, in_channels , iW)
weight	filters of shape (out_channels, in_channels/groups , kW)
bias	optional bias of shape (out_channels). Default: NULL
stride	the stride of the convolving kernel. Can be a single number or a one-element tuple (sW,). Default: 1
padding	implicit paddings on both sides of the input. Can be a single number or a one-element tuple (padW,). Default: 0
dilation	the spacing between kernel elements. Can be a single number or a one-element tuple (dW,). Default: 1
groups	split input into groups, in_channels should be divisible by the number of groups. Default: 1

---

nnf_conv2d *Conv2d*

Description

Applies a 2D convolution over an input image composed of several input planes.

Usage

```
nnf_conv2d(
  input,
  weight,
  bias = NULL,
  stride = 1,
  padding = 0,
  dilation = 1,
  groups = 1
)
```

Arguments

input	input tensor of shape (minibatch, in_channels, iH , iW)
weight	filters of shape (out_channels , in_channels/groups, kH , kW)
bias	optional bias tensor of shape (out_channels). Default: NULL
stride	the stride of the convolving kernel. Can be a single number or a tuple (sH, sW). Default: 1
padding	implicit paddings on both sides of the input. Can be a single number or a tuple (padH, padW). Default: 0
dilation	the spacing between kernel elements. Can be a single number or a tuple (dH, dW). Default: 1
groups	split input into groups, in_channels should be divisible by the number of groups. Default: 1

nnf_conv3d *Conv3d*

Description

Applies a 3D convolution over an input image composed of several input planes.

Usage

```
nnf_conv3d(
  input,
  weight,
  bias = NULL,
  stride = 1,
  padding = 0,
  dilation = 1,
  groups = 1
)
```

Arguments

input	input tensor of shape (minibatch, in_channels , iT , iH , iW)
weight	filters of shape (out_channels , in_channels/groups, kT , kH , kW)
bias	optional bias tensor of shape (out_channels). Default: NULL
stride	the stride of the convolving kernel. Can be a single number or a tuple (sT, sH, sW). Default: 1
padding	implicit paddings on both sides of the input. Can be a single number or a tuple (padT, padH, padW). Default: 0
dilation	the spacing between kernel elements. Can be a single number or a tuple (dT, dH, dW). Default: 1
groups	split input into groups, in_channels should be divisible by the number of groups. Default: 1

nnf_conv_tbc *Conv_tbc*

Description

Applies a 1-dimensional sequence convolution over an input sequence. Input and output dimensions are (Time, Batch, Channels) - hence TBC.

Usage

```
nnf_conv_tbc(input, weight, bias, pad = 0)
```

Arguments

input	input tensor of shape (sequence length $\times$ $batch$ $\times$ in_channels)
weight	filter of shape (kernel width $\times$ in_channels $\times$ out_channels)
bias	bias of shape (out_channels)
pad	number of timesteps to pad. Default: 0

---

nnf_conv_transpose1d *Conv_transpose1d*

Description

Applies a 1D transposed convolution operator over an input signal composed of several input planes, sometimes also called "deconvolution".

Usage

```
nnf_conv_transpose1d(
  input,
  weight,
  bias = NULL,
  stride = 1,
  padding = 0,
  output_padding = 0,
  groups = 1,
  dilation = 1
)
```

Arguments

input	input tensor of shape (minibatch, in_channels , iW)
weight	filters of shape (out_channels, in_channels/groups , kW)
bias	optional bias of shape (out_channels). Default: `NULL`
stride	the stride of the convolving kernel. Can be a single number or a one-element tuple `(sW,)`. Default: 1
padding	implicit paddings on both sides of the input. Can be a single number or a one-element tuple `(padW,)`. Default: 0
output_padding	padding applied to the output
groups	split input into groups, `in_channels` should be divisible by the number of groups. Default: 1
dilation	the spacing between kernel elements. Can be a single number or a one-element tuple `(dW,)`. Default: 1

nnf_conv_transpose2d *Conv_transpose2d*

Description

Applies a 2D transposed convolution operator over an input image composed of several input planes, sometimes also called "deconvolution".

Usage

```
nnf_conv_transpose2d(
  input,
  weight,
  bias = NULL,
  stride = 1,
  padding = 0,
  output_padding = 0,
  groups = 1,
  dilation = 1
)
```

Arguments

`input`	input tensor of shape (minibatch, in_channels, iH , iW)
`weight`	filters of shape (out_channels , in_channels/groups, kH , kW)
`bias`	optional bias tensor of shape (out_channels). Default: `NULL`
`stride`	the stride of the convolving kernel. Can be a single number or a tuple `(sH, sW)`. Default: 1
`padding`	implicit paddings on both sides of the input. Can be a single number or a tuple `(padH, padW)`. Default: 0
`output_padding`	padding applied to the output
`groups`	split input into groups, `in_channels` should be divisible by the number of groups. Default: 1
`dilation`	the spacing between kernel elements. Can be a single number or a tuple `(dH, dW)`. Default: 1

nnf_conv_transpose3d *Conv_transpose3d*

Description

Applies a 3D transposed convolution operator over an input image composed of several input planes, sometimes also called "deconvolution"

Usage

```
nnf_conv_transpose3d(
  input,
  weight,
  bias = NULL,
  stride = 1,
  padding = 0,
  output_padding = 0,
  groups = 1,
  dilation = 1
)
```

Arguments

`input`	input tensor of shape (minibatch, in_channels , iT , iH , iW)
`weight`	filters of shape (out_channels , in_channels/groups, kT , kH , kW)
`bias`	optional bias tensor of shape (out_channels). Default: `NULL`
`stride`	the stride of the convolving kernel. Can be a single number or a tuple `(sT, sH, sW)`. Default: 1
`padding`	implicit paddings on both sides of the input. Can be a single number or a tuple `(padT, padH, padW)`. Default: 0
`output_padding`	padding applied to the output
`groups`	split input into groups, `in_channels` should be divisible by the number of groups. Default: 1
`dilation`	the spacing between kernel elements. Can be a single number or a tuple `(dT, dH, dW)`. Default: 1

nnf_cosine_embedding_loss *Cosine_embedding_loss*

Description

Creates a criterion that measures the loss given input tensors x_1, x_2 and a Tensor label y with values 1 or -1. This is used for measuring whether two inputs are similar or dissimilar, using the cosine distance, and is typically used for learning nonlinear embeddings or semi-supervised learning.

Usage

```
nnf_cosine_embedding_loss(
  input1,
  input2,
  target,
  margin = 0,
  reduction = c("mean", "sum", "none")
)
```

Arguments

input1	the input x_1 tensor
input2	the input x_2 tensor
target	the target tensor
margin	Should be a number from -1 to 1 , 0 to 0.5 is suggested. If margin is missing, the default value is 0.
reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

nnf_cosine_similarity *Cosine_similarity*

Description

Returns cosine similarity between x1 and x2, computed along dim.

Usage

```
nnf_cosine_similarity(x1, x2, dim = 2, eps = 1e-08)
```

Arguments

x1	(Tensor) First input.
x2	(Tensor) Second input (of size matching x1).
dim	(int, optional) Dimension of vectors. Default: 2
eps	(float, optional) Small value to avoid division by zero. Default: 1e-8

Details

$$\text{similarity} = \frac{x_1 \cdot x_2}{\max(\|x_1\|_2 \cdot \|x_2\|_2, \epsilon)}$$

---

nnf_cross_entropy *Cross_entropy*

Description

This criterion combines `log_softmax` and `nll_loss` in a single function.

Usage

```
nnf_cross_entropy(
  input,
  target,
  weight = NULL,
  ignore_index = -100,
  reduction = c("mean", "sum", "none")
)
```

Arguments

input	(Tensor) (N, C) where `C = number of classes` or (N, C, H, W) in case of 2D Loss, or $(N, C, d_1, d_2, ..., d_K)$ where $K \geq 1$ in the case of K-dimensional loss.
target	(Tensor) (N) where each value is $0 \leq \text{targets}[i] \leq C - 1$, or $(N, d_1, d_2, ..., d_K)$ where $K \geq 1$ for K-dimensional loss.
weight	(Tensor, optional) a manual rescaling weight given to each class. If given, has to be a Tensor of size `C`
ignore_index	(int, optional) Specifies a target value that is ignored and does not contribute to the input gradient.
reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

nnf_ctc_loss *Ctc_loss*

Description

The Connectionist Temporal Classification loss.

Usage

```
nnf_ctc_loss(
  log_probs,
  targets,
  input_lengths,
  target_lengths,
  blank = 0,
  reduction = c("mean", "sum", "none"),
  zero_infinity = FALSE
)
```

Arguments

log_probs	(T, N, C) where C = number of characters in alphabet including blank, T = input length, and N = batch size. The logarithmized probabilities of the outputs (e.g. obtained with nnf_log_softmax).
targets	(N, S) or (sum(target_lengths)). Targets cannot be blank. In the second form, the targets are assumed to be concatenated.
input_lengths	(N). Lengths of the inputs (must each be $\leq T$)
target_lengths	(N). Lengths of the targets
blank	(int, optional) Blank label. Default 0.
reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'
zero_infinity	(bool, optional) Whether to zero infinite losses and the associated gradients. Default: FALSE Infinite losses mainly occur when the inputs are too short to be aligned to the targets.

nnf_dropout *Dropout*

Description

During training, randomly zeroes some of the elements of the input tensor with probability p using samples from a Bernoulli distribution.

Usage

```
nnf_dropout(input, p = 0.5, training = TRUE, inplace = FALSE)
```

Arguments

input	the input tensor
p	probability of an element to be zeroed. Default: 0.5
training	apply dropout if is TRUE. Default: TRUE
inplace	If set to TRUE, will do this operation in-place. Default: FALSE

nnf_dropout2d *Dropout2d*

Description

Randomly zero out entire channels (a channel is a 2D feature map, e.g., the j-th channel of the i-th sample in the batched input is a 2D tensor $input[i, j]$) of the input tensor). Each channel will be zeroed out independently on every forward call with probability p using samples from a Bernoulli distribution.

Usage

```
nnf_dropout2d(input, p = 0.5, training = TRUE, inplace = FALSE)
```

Arguments

input	the input tensor
p	probability of a channel to be zeroed. Default: 0.5
training	apply dropout if is TRUE. Default: TRUE.
inplace	If set to TRUE, will do this operation in-place. Default: FALSE

nnf_dropout3d *Dropout3d*

Description

Randomly zero out entire channels (a channel is a 3D feature map, e.g., the j-th channel of the i-th sample in the batched input is a 3D tensor $input[i, j]$) of the input tensor). Each channel will be zeroed out independently on every forward call with probability p using samples from a Bernoulli distribution.

Usage

```
nnf_dropout3d(input, p = 0.5, training = TRUE, inplace = FALSE)
```

Arguments

input	the input tensor
p	probability of a channel to be zeroed. Default: 0.5
training	apply dropout if is TRUE. Default: TRUE.
inplace	If set to TRUE, will do this operation in-place. Default: FALSE

nnf_elu *Elu*

Description

Applies element-wise,

$$ELU(x) = max(0, x) + min(0, \alpha * (exp(x) - 1))$$

.

Usage

```
nnf_elu(input, alpha = 1, inplace = FALSE)

nnf_elu_(input, alpha = 1)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions
alpha	the alpha value for the ELU formulation. Default: 1.0
inplace	can optionally do the operation in-place. Default: FALSE

Examples

```
if (torch_is_installed()) {
x <- torch_randn(2, 2)
y <- nnf_elu(x, alpha = 1)
nnf_elu_(x, alpha = 1)
torch_equal(x, y)
}
```

---

nnf_embedding *Embedding*

Description

A simple lookup table that looks up embeddings in a fixed dictionary and size.

Usage

```
nnf_embedding(
  input,
  weight,
  padding_idx = NULL,
  max_norm = NULL,
  norm_type = 2,
  scale_grad_by_freq = FALSE,
  sparse = FALSE
)
```

Arguments

input	(LongTensor) Tensor containing indices into the embedding matrix
weight	(Tensor) The embedding matrix with number of rows equal to the maximum possible index + 1, and number of columns equal to the embedding size
padding_idx	(int, optional) If given, pads the output with the embedding vector at padding_idx (initialized to zeros) whenever it encounters the index.
max_norm	(float, optional) If given, each embedding vector with norm larger than max_norm is renormalized to have norm max_norm. Note: this will modify weight in-place.
norm_type	(float, optional) The p of the p-norm to compute for the max_norm option. Default 2.
scale_grad_by_freq	(boolean, optional) If given, this will scale gradients by the inverse of frequency of the words in the mini-batch. Default FALSE.
sparse	(bool, optional) If TRUE, gradient w.r.t. weight will be a sparse tensor. See Notes under nn_embedding for more details regarding sparse gradients.

Details

This module is often used to retrieve word embeddings using indices. The input to the module is a list of indices, and the embedding matrix, and the output is the corresponding word embeddings.

`nnf_embedding_bag` *Embedding_bag*

Description

Computes sums, means or maxes of `bags` of embeddings, without instantiating the intermediate embeddings.

Usage

```
nnf_embedding_bag(
  input,
  weight,
  offsets = NULL,
  max_norm = NULL,
  norm_type = 2,
  scale_grad_by_freq = FALSE,
  mode = "mean",
  sparse = FALSE,
  per_sample_weights = NULL,
  include_last_offset = FALSE,
  padding_idx = NULL
)
```

Arguments

`input`	(LongTensor) Tensor containing bags of indices into the embedding matrix
`weight`	(Tensor) The embedding matrix with number of rows equal to the maximum possible index + 1, and number of columns equal to the embedding size
`offsets`	(LongTensor, optional) Only used when `input` is 1D. `offsets` determines the starting index position of each bag (sequence) in `input`.
`max_norm`	(float, optional) If given, each embedding vector with norm larger than `max_norm` is renormalized to have norm `max_norm`. Note: this will modify `weight` in-place.
`norm_type`	(float, optional) The `p` in the `p`-norm to compute for the `max_norm` option. Default `2`.
`scale_grad_by_freq`	(boolean, optional) if given, this will scale gradients by the inverse of frequency of the words in the mini-batch. Default `FALSE`. Note: this option is not supported when `mode="max"`.

mode	(string, optional) "sum", "mean" or "max". Specifies the way to reduce the bag. Default: 'mean'
sparse	(bool, optional) if TRUE, gradient w.r.t. weight will be a sparse tensor. See Notes under nn_embedding for more details regarding sparse gradients. Note: this option is not supported when mode="max".
per_sample_weights	(Tensor, optional) a tensor of float / double weights, or NULL to indicate all weights should be taken to be 1. If specified, per_sample_weights must have exactly the same shape as input and is treated as having the same offsets, if those are not NULL.
include_last_offset	(bool, optional) if TRUE, the size of offsets is equal to the number of bags + 1.
padding_idx	(int, optional) If given, pads the output with the embedding vector at padding_idx (initialized to zeros) whenever it encounters the index.

---

nnf_fold *Fold*

Description

Combines an array of sliding local blocks into a large containing tensor.

Usage

```
nnf_fold(
  input,
  output_size,
  kernel_size,
  dilation = 1,
  padding = 0,
  stride = 1
)
```

Arguments

input	the input tensor
output_size	the shape of the spatial dimensions of the output (i.e., output$sizes()[-c(1,2)])
kernel_size	the size of the sliding blocks
dilation	a parameter that controls the stride of elements within the neighborhood. Default: 1
padding	implicit zero padding to be added on both sides of input. Default: 0
stride	the stride of the sliding blocks in the input spatial dimensions. Default: 1

Warning

Currently, only 4-D output tensors (batched image-like tensors) are supported.

nnf_fractional_max_pool2d

Fractional_max_pool2d

Description

Applies 2D fractional max pooling over an input signal composed of several input planes.

Usage

```
nnf_fractional_max_pool2d(
  input,
  kernel_size,
  output_size = NULL,
  output_ratio = NULL,
  return_indices = FALSE,
  random_samples = NULL
)
```

Arguments

`input`	the input tensor
`kernel_size`	the size of the window to take a max over. Can be a single number k (for a square kernel of $k * k$) or a tuple `(kH, kW)`
`output_size`	the target output size of the image of the form $oH * oW$. Can be a tuple `(oH, oW)` or a single number oH for a square image $oH * oH$
`output_ratio`	If one wants to have an output size as a ratio of the input size, this option can be given. This has to be a number or tuple in the range (0, 1)
`return_indices`	if `True`, will return the indices along with the outputs.
`random_samples`	optional random samples.

Details

Fractional MaxPooling is described in detail in the paper `Fractional MaxPooling_` by Ben Graham

The max-pooling operation is applied in $kH * kW$ regions by a stochastic step size determined by the target output size. The number of output features is equal to the number of input planes.

nnf_fractional_max_pool3d

Fractional_max_pool3d

Description

Applies 3D fractional max pooling over an input signal composed of several input planes.

Usage

```
nnf_fractional_max_pool3d(
  input,
  kernel_size,
  output_size = NULL,
  output_ratio = NULL,
  return_indices = FALSE,
  random_samples = NULL
)
```

Arguments

`input`	the input tensor
`kernel_size`	the size of the window to take a max over. Can be a single number k (for a square kernel of $k * k * k$) or a tuple `(kT, kH, kW)`
`output_size`	the target output size of the form $oT * oH * oW$. Can be a tuple `(oT, oH, oW)` or a single number oH for a cubic output $oH * oH * oH$
`output_ratio`	If one wants to have an output size as a ratio of the input size, this option can be given. This has to be a number or tuple in the range (0, 1)
`return_indices`	if `True`, will return the indices along with the outputs.
`random_samples`	undocumented argument.

Details

Fractional MaxPooling is described in detail in the paper `Fractional MaxPooling_` by Ben Graham

The max-pooling operation is applied in $kT * kH * kW$ regions by a stochastic step size determined by the target output size. The number of output features is equal to the number of input planes.

nnf_gelu *Gelu*

Description

Gelu

Usage

```
nnf_gelu(input, approximate = "none")
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions
approximate	By default it's none, and applies element-wise x*pnorm(x), if 'tanh', then GELU is estimated. See GELU for more info.

gelu(input) -> Tensor

Applies element-wise the function $GELU(x) = x * \Phi(x)$

where $\Phi(x)$ is the Cumulative Distribution Function for Gaussian Distribution.

See Gaussian Error Linear Units (GELUs).

nnf_glu *Glu*

Description

The gated linear unit. Computes:

Usage

```
nnf_glu(input, dim = -1)
```

Arguments

input	(Tensor) input tensor
dim	(int) dimension on which to split the input. Default: -1

Details

$$GLU(a, b) = a \otimes \sigma(b)$$

where `input` is split in half along `dim` to form `a` and `b`, σ is the sigmoid function and $\otimes$ is the element-wise product between matrices.

See Language Modeling with Gated Convolutional Networks.

nnf_grid_sample *Grid_sample*

Description

Given an `input` and a flow-field `grid`, computes the `output` using `input` values and pixel locations from `grid`.

Usage

```
nnf_grid_sample(
  input,
  grid,
  mode = c("bilinear", "nearest"),
  padding_mode = c("zeros", "border", "reflection"),
  align_corners = FALSE
)
```

Arguments

`input`	(Tensor) input of shape $(N, C, H_{\text{in}}, W_{\text{in}})$ (4-D case) or $(N, C, D_{\text{in}}, H_{\text{in}}, W_{\text{in}})$ (5-D case)
`grid`	(Tensor) flow-field of shape $(N, H_{\text{out}}, W_{\text{out}}, 2)$ (4-D case) or $(N, D_{\text{out}}, H_{\text{out}}, W_{\text{out}}, 3)$ (5-D case)
`mode`	(str) interpolation mode to calculate output values `'bilinear' | 'nearest'`. Default: `'bilinear'`
`padding_mode`	(str) padding mode for outside grid values `'zeros' | 'border' | 'reflection'`. Default: `'zeros'`
`align_corners`	(bool, optional) Geometrically, we consider the pixels of the input as squares rather than points. If set to `True`, the extrema (`-1` and `1`) are considered as referring to the center points of the input's corner pixels. If set to `False`, they are instead considered as referring to the corner points of the input's corner pixels, making the sampling more resolution agnostic. This option parallels the `align_corners` option in `nnf_interpolate()`, and so whichever option is used here should also be used there to resize the input image before grid sampling. Default: `False`

Details

Currently, only spatial (4-D) and volumetric (5-D) `input` are supported.

In the spatial (4-D) case, for `input` with shape $(N, C, H_{\text{in}}, W_{\text{in}})$ and `grid` with shape $(N, H_{\text{out}}, W_{\text{out}}, 2)$, the output will have shape $(N, C, H_{\text{out}}, W_{\text{out}})$.

For each output location `output[n, :, h, w]`, the size-2 vector `grid[n, h, w]` specifies `input` pixel locations `x` and `y`, which are used to interpolate the output value `output[n, :, h, w]`. In the case of 5D inputs, `grid[n, d, h, w]` specifies the `x`, `y`, `z` pixel locations for interpolating

output[n, :, d, h, w]. mode argument specifies nearest or bilinear interpolation method to sample the input pixels.

grid specifies the sampling pixel locations normalized by the input spatial dimensions. Therefore, it should have most values in the range of [-1, 1]. For example, values x = -1, y = -1 is the left-top pixel of input, and values x = 1, y = 1 is the right-bottom pixel of input.

If grid has values outside the range of [-1, 1], the corresponding outputs are handled as defined by padding_mode. Options are

- padding_mode="zeros": use 0 for out-of-bound grid locations,
- padding_mode="border": use border values for out-of-bound grid locations,
- padding_mode="reflection": use values at locations reflected by the border for out-of-bound grid locations. For location far away from the border, it will keep being reflected until becoming in bound, e.g., (normalized) pixel location x = -3.5 reflects by border -1 and becomes x' = 1.5, then reflects by border 1 and becomes x'' = -0.5.

Note

This function is often used in conjunction with nnf_affine_grid() to build Spatial Transformer Networks_ .

---

nnf_group_norm *Group_norm*

Description

Applies Group Normalization for last certain number of dimensions.

Usage

```
nnf_group_norm(input, num_groups, weight = NULL, bias = NULL, eps = 1e-05)
```

Arguments

input	the input tensor
num_groups	number of groups to separate the channels into
weight	the weight tensor
bias	the bias tensor
eps	a value added to the denominator for numerical stability. Default: 1e-5

nnf_gumbel_softmax *Gumbel_softmax*

Description

Samples from the Gumbel-Softmax distribution and optionally discretizes.

Usage

```
nnf_gumbel_softmax(logits, tau = 1, hard = FALSE, dim = -1)
```

Arguments

logits	[..., num_features] unnormalized log probabilities
tau	non-negative scalar temperature
hard	if True, the returned samples will be discretized as one-hot vectors, but will be differentiated as if it is the soft sample in autograd
dim	(int) A dimension along which softmax will be computed. Default: -1.

nnf_hardshrink *Hardshrink*

Description

Applies the hard shrinkage function element-wise

Usage

```
nnf_hardshrink(input, lambd = 0.5)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions
lambd	the lambda value for the Hardshrink formulation. Default: 0.5

nnf_hardsigmoid *Hardsigmoid*

Description

Applies the element-wise function Hardsigmoid$(x) = \frac{ReLU6(x+3)}{6}$

Usage

```
nnf_hardsigmoid(input, inplace = FALSE)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions
inplace	NA If set to `True`, will do this operation in-place. Default: `False`

nnf_hardswish *Hardswish*

Description

Applies the hardswish function, element-wise, as described in the paper: Searching for MobileNetV3.

Usage

```
nnf_hardswish(input, inplace = FALSE)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions
inplace	can optionally do the operation in-place. Default: FALSE

Details

$$\text{Hardswish}(x) = \begin{cases} 0 & \text{if } x \leq -3, \\ x & \text{if } x \geq +3, \\ x \cdot (x+3)/6 & \text{otherwise} \end{cases}$$

nnf_hardtanh *Hardtanh*

Description

Applies the HardTanh function element-wise.

Usage

```
nnf_hardtanh(input, min_val = -1, max_val = 1, inplace = FALSE)

nnf_hardtanh_(input, min_val = -1, max_val = 1)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions
min_val	minimum value of the linear region range. Default: -1
max_val	maximum value of the linear region range. Default: 1
inplace	can optionally do the operation in-place. Default: FALSE

nnf_hinge_embedding_loss *Hinge_embedding_loss*

Description

Measures the loss given an input tensor xx and a labels tensor yy (containing 1 or -1). This is usually used for measuring whether two inputs are similar or dissimilar, e.g. using the L1 pairwise distance as xx , and is typically used for learning nonlinear embeddings or semi-supervised learning.

Usage

```
nnf_hinge_embedding_loss(input, target, margin = 1, reduction = "mean")
```

Arguments

input	tensor (N,*) where ** means, any number of additional dimensions
target	tensor (N,*) , same shape as the input
margin	Has a default value of 1.
reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

nnf_instance_norm *Instance_norm*

Description

Applies Instance Normalization for each channel in each data sample in a batch.

Usage

```
nnf_instance_norm(
  input,
  running_mean = NULL,
  running_var = NULL,
  weight = NULL,
  bias = NULL,
  use_input_stats = TRUE,
  momentum = 0.1,
  eps = 1e-05
)
```

Arguments

input	the input tensor
running_mean	the running_mean tensor
running_var	the running var tensor
weight	the weight tensor
bias	the bias tensor
use_input_stats	whether to use input stats
momentum	a double for the momentum
eps	an eps double for numerical stability

nnf_interpolate *Interpolate*

Description

Down/up samples the input to either the given `size` or the given `scale_factor`

Usage

```
nnf_interpolate(
  input,
  size = NULL,
  scale_factor = NULL,
  mode = "nearest",
  align_corners = FALSE,
  recompute_scale_factor = NULL
)
```

Arguments

`input` (Tensor) the input tensor

`size` (int or `Tuple[int]` or `Tuple[int, int]` or `Tuple[int, int, int]`) output spatial size.

`scale_factor` (float or `Tuple[float]`) multiplier for spatial size. Has to match input size if it is a tuple.

`mode` (str) algorithm used for upsampling: 'nearest' | 'linear' | 'bilinear' | 'bicubic' | 'trilinear' | 'area' Default: 'nearest'

`align_corners` (bool, optional) Geometrically, we consider the pixels of the input and output as squares rather than points. If set to TRUE, the input and output tensors are aligned by the center points of their corner pixels, preserving the values at the corner pixels. If set to False, the input and output tensors are aligned by the corner points of their corner pixels, and the interpolation uses edge value padding for out-of-boundary values, making this operation *independent* of input size when `scale_factor` is kept the same. This only has an effect when `mode` is `'linear'`, `'bilinear'`, `'bicubic'` or `'trilinear'`. Default: `False`

`recompute_scale_factor` (bool, optional) recompute the scale_factor for use in the interpolation calculation. When `scale_factor` is passed as a parameter, it is used to compute the `output_size`. If `recompute_scale_factor` is "'True" or not specified, a new `scale_factor` will be computed based on the output and input sizes for use in the interpolation computation (i.e. the computation will be identical to if the computed 'output_size' were passed-in explicitly). Otherwise, the passed-in 'scale_factor' will be used in the interpolation computation. Note that when 'scale_factor' is floating-point, the recomputed scale_factor may differ from the one passed in due to rounding and precision issues.

Details

The algorithm used for interpolation is determined by `mode`.

Currently temporal, spatial and volumetric sampling are supported, i.e. expected inputs are 3-D, 4-D or 5-D in shape.

The input dimensions are interpreted in the form: `mini-batch x channels x [optional depth] x [optional height] x w`

The modes available for resizing are: `nearest`, `linear` (3D-only), `bilinear`, `bicubic` (4D-only), `trilinear` (5D-only), `area`

nnf_kl_div *Kl_div*

Description

The Kullback-Leibler divergence Loss.

Usage

```
nnf_kl_div(input, target, reduction = "mean")
```

Arguments

input	tensor (N,*) where ** means, any number of additional dimensions
target	tensor (N,*) , same shape as the input
reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

nnf_l1_loss *L1_loss*

Description

Function that takes the mean element-wise absolute value difference.

Usage

```
nnf_l1_loss(input, target, reduction = "mean")
```

Arguments

input	tensor (N,*) where ** means, any number of additional dimensions
target	tensor (N,*) , same shape as the input
reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

nnf_layer_norm *Layer_norm*

Description

Applies Layer Normalization for last certain number of dimensions.

Usage

```
nnf_layer_norm(
  input,
  normalized_shape,
  weight = NULL,
  bias = NULL,
  eps = 1e-05
)
```

Arguments

input	the input tensor
normalized_shape	input shape from an expected input of size. If a single integer is used, it is treated as a singleton list, and this module will normalize over the last dimension which is expected to be of that specific size.
weight	the weight tensor
bias	the bias tensor
eps	a value added to the denominator for numerical stability. Default: 1e-5

nnf_leaky_relu *Leaky_relu*

Description

Applies element-wise, $LeakyReLU(x) = max(0, x) + negative_slope * min(0, x)$

Usage

```
nnf_leaky_relu(input, negative_slope = 0.01, inplace = FALSE)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions
negative_slope	Controls the angle of the negative slope. Default: 1e-2
inplace	can optionally do the operation in-place. Default: FALSE

nnf_linear *Linear*

Description

Applies a linear transformation to the incoming data: $y = xA^T + b$.

Usage

```
nnf_linear(input, weight, bias = NULL)
```

Arguments

input	$(N, *, in_features)$ where * means any number of additional dimensions
weight	$(out_features, in_features)$ the weights tensor.
bias	optional tensor $(out_features)$

nnf_local_response_norm *Local_response_norm*

Description

Applies local response normalization over an input signal composed of several input planes, where channels occupy the second dimension. Applies normalization across channels.

Usage

```
nnf_local_response_norm(input, size, alpha = 1e-04, beta = 0.75, k = 1)
```

Arguments

input	the input tensor
size	amount of neighbouring channels used for normalization
alpha	multiplicative factor. Default: 0.0001
beta	exponent. Default: 0.75
k	additive factor. Default: 1

nnf_logsigmoid *Logsigmoid*

Description

Applies element-wise $LogSigmoid(x_i) = log(\frac{1}{1+exp(-x_i)})$

Usage

```
nnf_logsigmoid(input)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions

nnf_log_softmax *Log_softmax*

Description

Applies a softmax followed by a logarithm.

Usage

```
nnf_log_softmax(input, dim = NULL, dtype = NULL)
```

Arguments

input	(Tensor) input
dim	(int) A dimension along which log_softmax will be computed.
dtype	(torch.dtype, optional) the desired data type of returned tensor. If specified, the input tensor is casted to dtype before the operation is performed. This is useful for preventing data type overflows. Default: NULL.

Details

While mathematically equivalent to log(softmax(x)), doing these two operations separately is slower, and numerically unstable. This function uses an alternative formulation to compute the output and gradient correctly.

nnf_lp_pool1d *Lp_pool1d*

Description

Applies a 1D power-average pooling over an input signal composed of several input planes. If the sum of all inputs to the power of p is zero, the gradient is set to zero as well.

Usage

```
nnf_lp_pool1d(input, norm_type, kernel_size, stride = NULL, ceil_mode = FALSE)
```

Arguments

input	the input tensor
norm_type	if inf than one gets max pooling if 0 you get sum pooling (proportional to the avg pooling)
kernel_size	a single int, the size of the window
stride	a single int, the stride of the window. Default value is kernel_size
ceil_mode	when True, will use ceil instead of floor to compute the output shape

nnf_lp_pool2d *Lp_pool2d*

Description

Applies a 2D power-average pooling over an input signal composed of several input planes. If the sum of all inputs to the power of p is zero, the gradient is set to zero as well.

Usage

```
nnf_lp_pool2d(input, norm_type, kernel_size, stride = NULL, ceil_mode = FALSE)
```

Arguments

input	the input tensor
norm_type	if inf than one gets max pooling if 0 you get sum pooling (proportional to the avg pooling)
kernel_size	a single int, the size of the window
stride	a single int, the stride of the window. Default value is kernel_size
ceil_mode	when True, will use ceil instead of floor to compute the output shape

nnf_margin_ranking_loss *Margin_ranking_loss*

Description

Creates a criterion that measures the loss given inputs x1 , x2 , two 1D mini-batch Tensors, and a label 1D mini-batch tensor y (containing 1 or -1).

Usage

```
nnf_margin_ranking_loss(input1, input2, target, margin = 0, reduction = "mean")
```

Arguments

input1	the first tensor
input2	the second input tensor
target	the target tensor
margin	Has a default value of 00 .
reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

nnf_max_pool1d *Max_pool1d*

Description

Applies a 1D max pooling over an input signal composed of several input planes.

Usage

```
nnf_max_pool1d(
  input,
  kernel_size,
  stride = NULL,
  padding = 0,
  dilation = 1,
  ceil_mode = FALSE,
  return_indices = FALSE
)
```

Arguments

input	input tensor of shape (minibatch , in_channels , iW)
kernel_size	the size of the window. Can be a single number or a tuple (kW,).
stride	the stride of the window. Can be a single number or a tuple (sW,). Default: kernel_size
padding	implicit zero paddings on both sides of the input. Can be a single number or a tuple (padW,). Default: 0
dilation	controls the spacing between the kernel points; also known as the à trous algorithm.
ceil_mode	when True, will use ceil instead of floor to compute the output shape. Default: FALSE
return_indices	whether to return the indices where the max occurs.

---

nnf_max_pool2d *Max_pool2d*

Description

Applies a 2D max pooling over an input signal composed of several input planes.

Usage

```
nnf_max_pool2d(
  input,
  kernel_size,
  stride = kernel_size,
  padding = 0,
  dilation = 1,
  ceil_mode = FALSE,
  return_indices = FALSE
)
```

Arguments

input	input tensor (minibatch, in_channels , iH , iW)
kernel_size	size of the pooling region. Can be a single number or a tuple (kH, kW)
stride	stride of the pooling operation. Can be a single number or a tuple (sH, sW). Default: kernel_size
padding	implicit zero paddings on both sides of the input. Can be a single number or a tuple (padH, padW). Default: 0
dilation	controls the spacing between the kernel points; also known as the à trous algorithm.
ceil_mode	when True, will use ceil instead of floor in the formula to compute the output shape. Default: FALSE
return_indices	whether to return the indices where the max occurs.

nnf_max_pool3d *Max_pool3d*

Description

Applies a 3D max pooling over an input signal composed of several input planes.

Usage

```
nnf_max_pool3d(
  input,
  kernel_size,
  stride = NULL,
  padding = 0,
  dilation = 1,
  ceil_mode = FALSE,
  return_indices = FALSE
)
```

Arguments

input	input tensor (minibatch, in_channels , iT * iH , iW)
kernel_size	size of the pooling region. Can be a single number or a tuple `(kT, kH, kW)`
stride	stride of the pooling operation. Can be a single number or a tuple `(sT, sH, sW)`. Default: `kernel_size`
padding	implicit zero paddings on both sides of the input. Can be a single number or a tuple `(padT, padH, padW)`, Default: 0
dilation	controls the spacing between the kernel points; also known as the à trous algorithm.
ceil_mode	when True, will use `ceil` instead of `floor` in the formula to compute the output shape
return_indices	whether to return the indices where the max occurs.

nnf_max_unpool1d *Max_unpool1d*

Description

Computes a partial inverse of `MaxPool1d`.

Usage

```
nnf_max_unpool1d(
  input,
  indices,
  kernel_size,
  stride = NULL,
  padding = 0,
  output_size = NULL
)
```

Arguments

input	the input Tensor to invert
indices	the indices given out by max pool
kernel_size	Size of the max pooling window.
stride	Stride of the max pooling window. It is set to kernel_size by default.
padding	Padding that was added to the input
output_size	the targeted output size

---

nnf_max_unpool2d *Max_unpool2d*

Description

Computes a partial inverse of `MaxPool2d`.

Usage

```
nnf_max_unpool2d(
  input,
  indices,
  kernel_size,
  stride = NULL,
  padding = 0,
  output_size = NULL
)
```

Arguments

input	the input Tensor to invert
indices	the indices given out by max pool
kernel_size	Size of the max pooling window.
stride	Stride of the max pooling window. It is set to kernel_size by default.
padding	Padding that was added to the input
output_size	the targeted output size

nnf_max_unpool3d *Max_unpool3d*

Description

Computes a partial inverse of `MaxPool3d`.

Usage

```
nnf_max_unpool3d(
  input,
  indices,
  kernel_size,
  stride = NULL,
  padding = 0,
  output_size = NULL
)
```

Arguments

`input`	the input Tensor to invert
`indices`	the indices given out by max pool
`kernel_size`	Size of the max pooling window.
`stride`	Stride of the max pooling window. It is set to kernel_size by default.
`padding`	Padding that was added to the input
`output_size`	the targeted output size

nnf_mse_loss *Mse_loss*

Description

Measures the element-wise mean squared error.

Usage

```
nnf_mse_loss(input, target, reduction = "mean")
```

Arguments

`input`	tensor (N,*) where ** means, any number of additional dimensions
`target`	tensor (N,*) , same shape as the input
`reduction`	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

nnf_multilabel_margin_loss

Multilabel_margin_loss

Description

Creates a criterion that optimizes a multi-class multi-classification hinge loss (margin-based loss) between input x (a 2D mini-batch Tensor) and output y (which is a 2D Tensor of target class indices).

Usage

```
nnf_multilabel_margin_loss(input, target, reduction = "mean")
```

Arguments

input	tensor (N,*) where ** means, any number of additional dimensions
target	tensor (N,*) , same shape as the input
reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

nnf_multilabel_soft_margin_loss

Multilabel_soft_margin_loss

Description

Creates a criterion that optimizes a multi-label one-versus-all loss based on max-entropy, between input x and target y of size (N, C).

Usage

```
nnf_multilabel_soft_margin_loss(
  input,
  target,
  weight = NULL,
  reduction = "mean"
)
```

Arguments

input	tensor (N,*) where ** means, any number of additional dimensions
target	tensor (N,*) , same shape as the input
weight	weight tensor to apply on the loss.
reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

Note

It takes a one hot encoded target vector as input.

---

nnf_multi_head_attention_forward

Multi head attention forward

Description

Allows the model to jointly attend to information from different representation subspaces. See reference: Attention Is All You Need

Usage

```
nnf_multi_head_attention_forward(
  query,
  key,
  value,
  embed_dim_to_check,
  num_heads,
  in_proj_weight,
  in_proj_bias,
  bias_k,
  bias_v,
  add_zero_attn,
  dropout_p,
  out_proj_weight,
  out_proj_bias,
  training = TRUE,
  key_padding_mask = NULL,
  need_weights = TRUE,
  attn_mask = NULL,
  avg_weights = TRUE,
  use_separate_proj_weight = FALSE,
  q_proj_weight = NULL,
  k_proj_weight = NULL,
```

```
  v_proj_weight = NULL,
  static_k = NULL,
  static_v = NULL,
  batch_first = FALSE
)
```

Arguments

query	(L, N, E) where L is the target sequence length, N is the batch size, E is the embedding dimension. If batch_first is TRUE, the first two dimensions are transposed.
key	(S, N, E), where S is the source sequence length, N is the batch size, E is the embedding dimension. If batch_first is TRUE, the first two dimensions are transposed.
value	(S, N, E) where S is the source sequence length, N is the batch size, E is the embedding dimension. If batch_first is TRUE, the first two dimensions are transposed.
embed_dim_to_check	total dimension of the model.
num_heads	parallel attention heads.
in_proj_weight	input projection weight.
in_proj_bias	input projection bias.
bias_k	bias of the key and value sequences to be added at dim=0.
bias_v	currently undocumented.
add_zero_attn	add a new batch of zeros to the key and value sequences at dim=1.
dropout_p	probability of an element to be zeroed.
out_proj_weight	the output projection weight.
out_proj_bias	output projection bias.
training	apply dropout if is `TRUE`.
key_padding_mask	(N, S) where N is the batch size, S is the source sequence length. If a ByteTensor is provided, the non-zero positions will be ignored while the position with the zero positions will be unchanged. If a BoolTensor is provided, the positions with the value of `True` will be ignored while the position with the value of `False` will be unchanged.
need_weights	output attn_output_weights.
attn_mask	2D mask (L, S) where L is the target sequence length, S is the source sequence length. 3D mask $(N*num_heads, L, S)$ where N is the batch size, L is the target sequence length, S is the source sequence length. attn_mask ensure that position i is allowed to attend the unmasked positions. If a ByteTensor is provided, the non-zero positions are not allowed to attend while the zero positions will be unchanged. If a BoolTensor is provided, positions with `True` is not allowed to attend while `False` values will be unchanged. If a FloatTensor is provided, it will be added to the attention weight.

avg_weights — Logical; whether to average attn_output_weights over the attention heads before outputting them. This doesn't change the returned value of attn_output; it only affects the returned attention weight matrix.

use_separate_proj_weight — the function accept the proj. weights for query, key, and value in different forms. If false, in_proj_weight will be used, which is a combination of q_proj_weight, k_proj_weight, v_proj_weight.

q_proj_weight — input projection weight and bias.

k_proj_weight — currently undocumented.

v_proj_weight — currently undocumented.

static_k — static key and value used for attention operators.

static_v — currently undocumented.

batch_first — Logical; whether to expect query, key, and value to have batch as their first parameter, and to return output with batch first.

---

nnf_multi_margin_loss *Multi_margin_loss*

Description

Creates a criterion that optimizes a multi-class classification hinge loss (margin-based loss) between input x (a 2D mini-batch Tensor) and output y (which is a 1D tensor of target class indices, `0 <= y <= x$size(2) - 1`).

Usage

```
nnf_multi_margin_loss(
  input,
  target,
  p = 1,
  margin = 1,
  weight = NULL,
  reduction = "mean"
)
```

Arguments

input — tensor (N,*) where ** means, any number of additional dimensions

target — tensor (N,*) , same shape as the input

p — Has a default value of 1. 1 and 2 are the only supported values.

margin — Has a default value of 1.

weight — a manual rescaling weight given to each class. If given, it has to be a Tensor of size C. Otherwise, it is treated as if having all ones.

`reduction` (string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

`nnf_nll_loss` *Nll_loss*

Description

The negative log likelihood loss.

Usage

```
nnf_nll_loss(
  input,
  target,
  weight = NULL,
  ignore_index = -100,
  reduction = "mean"
)
```

Arguments

`input` (N, C) where `C = number of classes` or (N, C, H, W) in case of 2D Loss, or $(N, C, d_1, d_2, ..., d_K)$ where $K \geq 1$ in the case of K-dimensional loss.

`target` (N) where each value is $0 \leq \text{targets}[i] \leq C - 1$, or $(N, d_1, d_2, ..., d_K)$ where $K \geq 1$ for K-dimensional loss.

`weight` (Tensor, optional) a manual rescaling weight given to each class. If given, has to be a Tensor of size `C`

`ignore_index` (int, optional) Specifies a target value that is ignored and does not contribute to the input gradient.

`reduction` (string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

nnf_normalize *Normalize*

Description

Performs L_p normalization of inputs over specified dimension.

Usage

```
nnf_normalize(input, p = 2, dim = 2, eps = 1e-12, out = NULL)
```

Arguments

input	input tensor of any shape
p	(float) the exponent value in the norm formulation. Default: 2
dim	(int) the dimension to reduce. Default: 1
eps	(float) small value to avoid division by zero. Default: 1e-12
out	(Tensor, optional) the output tensor. If out is used, this operation won't be differentiable.

Details

For a tensor input of sizes $(n_0, ..., n_{dim}, ..., n_k)$, each n_{dim} -element vector v along dimension dim is transformed as

$$v = \frac{v}{\max(\|v\|_p, \epsilon)}.$$

With the default arguments it uses the Euclidean norm over vectors along dimension 1 for normalization.

nnf_one_hot *One_hot*

Description

Takes LongTensor with index values of shape (*) and returns a tensor of shape (*, num_classes) that have zeros everywhere except where the index of last dimension matches the corresponding value of the input tensor, in which case it will be 1.

Usage

```
nnf_one_hot(tensor, num_classes = -1)
```

Arguments

`tensor`	(LongTensor) class values of any shape.
`num_classes`	(int) Total number of classes. If set to -1, the number of classes will be inferred as one greater than the largest class value in the input tensor.

Details

One-hot on Wikipedia: https://en.wikipedia.org/wiki/One-hot

`nnf_pad` *Pad*

Description

Pads tensor.

Usage

```
nnf_pad(input, pad, mode = "constant", value = NULL)
```

Arguments

`input`	(Tensor) N-dimensional tensor
`pad`	(tuple) m-elements tuple, where $\frac{m}{2} \leq$ input dimensions and m is even.
`mode`	'constant', 'reflect', 'replicate' or 'circular'. Default: 'constant'
`value`	fill value for 'constant' padding. Default: 0.

Padding size

The padding size by which to pad some dimensions of `input` are described starting from the last dimension and moving forward. $\left\lfloor \frac{\text{len(pad)}}{2} \right\rfloor$ dimensions of `input` will be padded. For example, to pad only the last dimension of the input tensor, then `pad` has the form $(\text{padding_left}, \text{padding_right})$;
to pad the last 2 dimensions of the input tensor, then use $(\text{padding_left}, \text{padding_right}, \text{padding_top}, \text{padding_bottom})$;
to pad the last 3 dimensions, use $(\text{padding_left}, \text{padding_right}, \text{padding_top}, \text{padding_bottom padding_front}, \text{padding_back})$.

Padding mode

See `nn_constant_pad_2d`, `nn_reflection_pad_2d`, and `nn_replication_pad_2d` for concrete examples on how each of the padding modes works. Constant padding is implemented for arbitrary dimensions. tensor, or the last 2 dimensions of 4D input tensor, or the last dimension of 3D input tensor. Reflect padding is only implemented for padding the last 2 dimensions of 4D input tensor, or the last dimension of 3D input tensor.

nnf_pairwise_distance *Pairwise_distance*

Description

Computes the batchwise pairwise distance between vectors using the p-norm.

Usage

```
nnf_pairwise_distance(x1, x2, p = 2, eps = 1e-06, keepdim = FALSE)
```

Arguments

x1	(Tensor) First input.
x2	(Tensor) Second input (of size matching x1).
p	the norm degree. Default: 2
eps	(float, optional) Small value to avoid division by zero. Default: 1e-8
keepdim	Determines whether or not to keep the vector dimension. Default: False

nnf_pdist *Pdist*

Description

Computes the p-norm distance between every pair of row vectors in the input. This is identical to the upper triangular portion, excluding the diagonal, of `torch_norm(input[:, None] - input, dim=2, p=p)`. This function will be faster if the rows are contiguous.

Usage

```
nnf_pdist(input, p = 2)
```

Arguments

input	input tensor of shape $N \times M$.
p	p value for the p-norm distance to calculate between each vector pair $\in [0, \infty]$.

Details

If input has shape $N \times M$ then the output will have shape $\frac{1}{2}N(N-1)$.

nnf_pixel_shuffle *Pixel_shuffle*

Description

Rearranges elements in a tensor of shape $(*, C \times r^2, H, W)$ to a tensor of shape $(*, C, H \times r, W \times r)$.

Usage

```
nnf_pixel_shuffle(input, upscale_factor)
```

Arguments

input	(Tensor) the input tensor
upscale_factor	(int) factor to increase spatial resolution by

nnf_poisson_nll_loss *Poisson_nll_loss*

Description

Poisson negative log likelihood loss.

Usage

```
nnf_poisson_nll_loss(
  input,
  target,
  log_input = TRUE,
  full = FALSE,
  eps = 1e-08,
  reduction = "mean"
)
```

Arguments

input	tensor (N,*) where ** means, any number of additional dimensions
target	tensor (N,*) , same shape as the input
log_input	if TRUE the loss is computed as $\exp(\text{input}) - \text{target} * \text{input}$, if FALSE then loss is $\text{input} - \text{target} * \log(\text{input} + \text{eps})$. Default: TRUE.
full	whether to compute full loss, i. e. to add the Stirling approximation term. Default: FALSE.
eps	(float, optional) Small value to avoid evaluation of $\log(0)$ when log_input=FALSE. Default: 1e-8

reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

---

nnf_prelu *Prelu*

Description

Applies element-wise the function $PReLU(x) = max(0, x) + weight * min(0, x)$ where weight is a learnable parameter.

Usage

```
nnf_prelu(input, weight)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions
weight	(Tensor) the learnable weights

---

nnf_relu *Relu*

Description

Applies the rectified linear unit function element-wise.

Usage

```
nnf_relu(input, inplace = FALSE)

nnf_relu_(input)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions
inplace	can optionally do the operation in-place. Default: FALSE

nnf_relu6 *Relu6*

Description

Applies the element-wise function $ReLU6(x) = min(max(0, x), 6)$.

Usage

```
nnf_relu6(input, inplace = FALSE)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions
inplace	can optionally do the operation in-place. Default: FALSE

nnf_rrelu *Rrelu*

Description

Randomized leaky ReLU.

Usage

```
nnf_rrelu(input, lower = 1/8, upper = 1/3, training = FALSE, inplace = FALSE)

nnf_rrelu_(input, lower = 1/8, upper = 1/3, training = FALSE)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions
lower	lower bound of the uniform distribution. Default: 1/8
upper	upper bound of the uniform distribution. Default: 1/3
training	bool wether it's a training pass. DEfault: FALSE
inplace	can optionally do the operation in-place. Default: FALSE

nnf_selu *Selu*

Description

Applies element-wise,

$$SELU(x) = scale * (max(0, x) + min(0, \alpha * (exp(x) - 1)))$$

, with $\alpha = 1.6732632423543772848170429916717$ and $scale = 1.0507009873554804934193349852946$.

Usage

```
nnf_selu(input, inplace = FALSE)

nnf_selu_(input)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions
inplace	can optionally do the operation in-place. Default: FALSE

Examples

```
if (torch_is_installed()) {
x <- torch_randn(2, 2)
y <- nnf_selu(x)
nnf_selu_(x)
torch_equal(x, y)
}
```

nnf_sigmoid *Sigmoid*

Description

Applies element-wise $Sigmoid(x_i) = \frac{1}{1+exp(-x_i)}$

Usage

```
nnf_sigmoid(input)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions

nnf_silu — *Applies the Sigmoid Linear Unit (SiLU) function, element-wise. See* `nn_silu()` *for more information.*

Description

Applies the Sigmoid Linear Unit (SiLU) function, element-wise. See `nn_silu()` for more information.

Usage

```
nnf_silu(input, inplace = FALSE)
```

Arguments

`input`	(N,*) tensor, where * means, any number of additional dimensions
`inplace`	can optionally do the operation in-place. Default: FALSE

See Also

`nn_silu()`.

nnf_smooth_l1_loss — *Smooth_l1_loss*

Description

Function that uses a squared term if the absolute element-wise error falls below 1 and an L1 term otherwise.

Usage

```
nnf_smooth_l1_loss(input, target, reduction = "mean")
```

Arguments

`input`	tensor (N,*) where ** means, any number of additional dimensions
`target`	tensor (N,*) , same shape as the input
`reduction`	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

nnf_softmax *Softmax*

Description

Applies a softmax function.

Usage

```
nnf_softmax(input, dim, dtype = NULL)
```

Arguments

input	(Tensor) input
dim	(int) A dimension along which softmax will be computed.
dtype	(torch.dtype, optional) the desired data type of returned tensor. If specified, the input tensor is casted to dtype before the operation is performed. This is useful for preventing data type overflows. Default: NULL.

Details

Softmax is defined as:

$$Softmax(x_i) = exp(x_i)/\sum_j exp(x_j)$$

It is applied to all slices along dim, and will re-scale them so that the elements lie in the range [0, 1] and sum to 1.

nnf_softmin *Softmin*

Description

Applies a softmin function.

Usage

```
nnf_softmin(input, dim, dtype = NULL)
```

Arguments

`input`	(Tensor) input
`dim`	(int) A dimension along which softmin will be computed (so every slice along dim will sum to 1).
`dtype`	(`torch.dtype`, optional) the desired data type of returned tensor. If specified, the input tensor is casted to `dtype` before the operation is performed. This is useful for preventing data type overflows. Default: NULL.

Details

Note that

$$Softmin(x) = Softmax(-x)$$

.

See nnf_softmax definition for mathematical formula.

`nnf_softplus` *Softplus*

Description

Applies element-wise, the function $Softplus(x) = 1/\beta * log(1 + exp(\beta * x))$.

Usage

```
nnf_softplus(input, beta = 1, threshold = 20)
```

Arguments

`input`	(N,*) tensor, where * means, any number of additional dimensions
`beta`	the beta value for the Softplus formulation. Default: 1
`threshold`	values above this revert to a linear function. Default: 20

Details

For numerical stability the implementation reverts to the linear function when $input*\beta > threshold$.

nnf_softshrink *Softshrink*

Description

Applies the soft shrinkage function elementwise

Usage

```
nnf_softshrink(input, lambd = 0.5)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions
lambd	the lambda (must be no less than zero) value for the Softshrink formulation. Default: 0.5

nnf_softsign *Softsign*

Description

Applies element-wise, the function $SoftSign(x) = x/(1 + |x|$

Usage

```
nnf_softsign(input)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions

nnf_soft_margin_loss *Soft_margin_loss*

Description

Creates a criterion that optimizes a two-class classification logistic loss between input tensor x and target tensor y (containing 1 or -1).

Usage

```
nnf_soft_margin_loss(input, target, reduction = "mean")
```

Arguments

input	tensor (N,*) where ** means, any number of additional dimensions
target	tensor (N,*) , same shape as the input
reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

nnf_tanhshrink *Tanhshrink*

Description

Applies element-wise, $Tanhshrink(x) = x - Tanh(x)$

Usage

```
nnf_tanhshrink(input)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions

nnf_threshold *Threshold*

Description

Thresholds each element of the input Tensor.

Usage

```
nnf_threshold(input, threshold, value, inplace = FALSE)

nnf_threshold_(input, threshold, value)
```

Arguments

input	(N,*) tensor, where * means, any number of additional dimensions
threshold	The value to threshold at
value	The value to replace with
inplace	can optionally do the operation in-place. Default: FALSE

nnf_triplet_margin_loss *Triplet_margin_loss*

Description

Creates a criterion that measures the triplet loss given an input tensors x1 , x2 , x3 and a margin with a value greater than 0 . This is used for measuring a relative similarity between samples. A triplet is composed by a, p and n (i.e., anchor, positive examples and negative examples respectively). The shapes of all input tensors should be (N, D).

Usage

```
nnf_triplet_margin_loss(
  anchor,
  positive,
  negative,
  margin = 1,
  p = 2,
  eps = 1e-06,
  swap = FALSE,
  reduction = "mean"
)
```

Arguments

anchor	the anchor input tensor
positive	the positive input tensor
negative	the negative input tensor
margin	Default: 1.
p	The norm degree for pairwise distance. Default: 2.
eps	(float, optional) Small value to avoid division by zero.
swap	The distance swap is described in detail in the paper Learning shallow convolutional feature descriptors with triplet losses by V. Balntas, E. Riba et al. Default: FALSE.
reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

---

nnf_triplet_margin_with_distance_loss

Triplet margin with distance loss

Description

See nn_triplet_margin_with_distance_loss()

Usage

```
nnf_triplet_margin_with_distance_loss(
  anchor,
  positive,
  negative,
  distance_function = NULL,
  margin = 1,
  swap = FALSE,
  reduction = "mean"
)
```

Arguments

anchor	the anchor input tensor
positive	the positive input tensor
negative	the negative input tensor
distance_function	(callable, optional): A nonnegative, real-valued function that quantifies the closeness of two tensors. If not specified, nn_pairwise_distance() will be used. Default: None

margin	Default: 1.
swap	The distance swap is described in detail in the paper Learning shallow convolutional feature descriptors with triplet losses by V. Balntas, E. Riba et al. Default: FALSE.
reduction	(string, optional) – Specifies the reduction to apply to the output: 'none' | 'mean' | 'sum'. 'none': no reduction will be applied, 'mean': the sum of the output will be divided by the number of elements in the output, 'sum': the output will be summed. Default: 'mean'

---

nnf_unfold *Unfold*

Description

Extracts sliding local blocks from an batched input tensor.

Usage

```
nnf_unfold(input, kernel_size, dilation = 1, padding = 0, stride = 1)
```

Arguments

input	the input tensor
kernel_size	the size of the sliding blocks
dilation	a parameter that controls the stride of elements within the neighborhood. Default: 1
padding	implicit zero padding to be added on both sides of input. Default: 0
stride	the stride of the sliding blocks in the input spatial dimensions. Default: 1

Warning

More than one element of the unfolded tensor may refer to a single memory location. As a result, in-place operations (especially ones that are vectorized) may result in incorrect behavior. If you need to write to the tensor, please clone it first.

nn_adaptive_avg_pool1d

Applies a 1D adaptive average pooling over an input signal composed of several input planes.

Description

The output size is H, for any input size. The number of output features is equal to the number of input planes.

Usage

```
nn_adaptive_avg_pool1d(output_size)
```

Arguments

output_size	the target output size H

Examples

```
if (torch_is_installed()) {
# target output size of 5
m <- nn_adaptive_avg_pool1d(5)
input <- torch_randn(1, 64, 8)
output <- m(input)
}
```

nn_adaptive_avg_pool2d

Applies a 2D adaptive average pooling over an input signal composed of several input planes.

Description

The output is of size H x W, for any input size. The number of output features is equal to the number of input planes.

Usage

```
nn_adaptive_avg_pool2d(output_size)
```

Arguments

output_size	the target output size of the image of the form H x W. Can be a tuple (H, W) or a single H for a square image H x H. H and W can be either a `int`, or `NULL` which means the size will be the same as that of the input.

Examples

```
if (torch_is_installed()) {
# target output size of 5x7
m <- nn_adaptive_avg_pool2d(c(5, 7))
input <- torch_randn(1, 64, 8, 9)
output <- m(input)
# target output size of 7x7 (square)
m <- nn_adaptive_avg_pool2d(7)
input <- torch_randn(1, 64, 10, 9)
output <- m(input)
}
```

---

nn_adaptive_avg_pool3d

Applies a 3D adaptive average pooling over an input signal composed of several input planes.

Description

The output is of size D x H x W, for any input size. The number of output features is equal to the number of input planes.

Usage

```
nn_adaptive_avg_pool3d(output_size)
```

Arguments

`output_size`	the target output size of the form D x H x W. Can be a tuple (D, H, W) or a single number D for a cube D x D x D. D, H and W can be either a `int`, or `None` which means the size will be the same as that of the input.

Examples

```
if (torch_is_installed()) {
# target output size of 5x7x9
m <- nn_adaptive_avg_pool3d(c(5, 7, 9))
input <- torch_randn(1, 64, 8, 9, 10)
output <- m(input)
# target output size of 7x7x7 (cube)
m <- nn_adaptive_avg_pool3d(7)
input <- torch_randn(1, 64, 10, 9, 8)
output <- m(input)
}
```

nn_adaptive_log_softmax_with_loss

AdaptiveLogSoftmaxWithLoss module

Description

Efficient softmax approximation as described in Efficient softmax approximation for GPUs by Edouard Grave, Armand Joulin, Moustapha Cissé, David Grangier, and Hervé Jégou

Usage

```
nn_adaptive_log_softmax_with_loss(
  in_features,
  n_classes,
  cutoffs,
  div_value = 4,
  head_bias = FALSE
)
```

Arguments

`in_features`	(int): Number of features in the input tensor
`n_classes`	(int): Number of classes in the dataset
`cutoffs`	(Sequence): Cutoffs used to assign targets to their buckets
`div_value`	(float, optional): value used as an exponent to compute sizes of the clusters. Default: 4.0
`head_bias`	(bool, optional): If `True`, adds a bias term to the 'head' of the adaptive softmax. Default: `False`

Details

Adaptive softmax is an approximate strategy for training models with large output spaces. It is most effective when the label distribution is highly imbalanced, for example in natural language modelling, where the word frequency distribution approximately follows the Zipf's law.

Adaptive softmax partitions the labels into several clusters, according to their frequency. These clusters may contain different number of targets each.

Additionally, clusters containing less frequent labels assign lower dimensional embeddings to those labels, which speeds up the computation. For each minibatch, only clusters for which at least one target is present are evaluated.

The idea is that the clusters which are accessed frequently (like the first one, containing most frequent labels), should also be cheap to compute – that is, contain a small number of assigned labels. We highly recommend taking a look at the original paper for more details.

- `cutoffs` should be an ordered Sequence of integers sorted in the increasing order. It controls number of clusters and the partitioning of targets into clusters. For example setting `cutoffs = c(10, 100, 1000)` means that first `10` targets will be assigned to the 'head' of the adaptive softmax, targets `11, 12, ..., 100` will be assigned to the first cluster, and targets `101, 102, ..., 1000` will be assigned to the second cluster, while targets `1001, 1002, ..., n_classes - 1` will be assigned to the last, third cluster.
- `div_value` is used to compute the size of each additional cluster, which is given as $\left\lfloor \frac{\text{in_features}}{\text{div_value}^{idx}} \right\rfloor$, where idx is the cluster index (with clusters for less frequent words having larger indices, and indices starting from 1).
- `head_bias` if set to True, adds a bias term to the 'head' of the adaptive softmax. See paper for details. Set to False in the official implementation.

Value

`NamedTuple` with `output` and `loss` fields:

- **output** is a Tensor of size `N` containing computed target log probabilities for each example
- **loss** is a Scalar representing the computed negative log likelihood loss

Warning

Labels passed as inputs to this module should be sorted according to their frequency. This means that the most frequent label should be represented by the index `0`, and the least frequent label should be represented by the index `n_classes - 1`.

Shape

- input: $(N, \text{in_features})$
- target: (N) where each value satisfies $0 <= \text{target[i]} <= \text{n_classes}$
- output1: (N)
- output2: `Scalar`

Note

This module returns a `NamedTuple` with `output` and `loss` fields. See further documentation for details.

To compute log-probabilities for all classes, the `log_prob` method can be used.

nn_adaptive_max_pool1d

Applies a 1D adaptive max pooling over an input signal composed of several input planes.

Description

The output size is H, for any input size. The number of output features is equal to the number of input planes.

Usage

```
nn_adaptive_max_pool1d(output_size, return_indices = FALSE)
```

Arguments

output_size	the target output size H
return_indices	if TRUE, will return the indices along with the outputs. Useful to pass to nn_max_unpool1d(). Default: FALSE

Examples

```
if (torch_is_installed()) {
# target output size of 5
m <- nn_adaptive_max_pool1d(5)
input <- torch_randn(1, 64, 8)
output <- m(input)
}
```

nn_adaptive_max_pool2d

Applies a 2D adaptive max pooling over an input signal composed of several input planes.

Description

The output is of size H x W, for any input size. The number of output features is equal to the number of input planes.

Usage

```
nn_adaptive_max_pool2d(output_size, return_indices = FALSE)
```

Arguments

output_size	the target output size of the image of the form H x W. Can be a tuple (H, W) or a single H for a square image H x H. H and W can be either a int, or None which means the size will be the same as that of the input.
return_indices	if TRUE, will return the indices along with the outputs. Useful to pass to nn_max_unpool2d(). Default: FALSE

Examples

```
if (torch_is_installed()) {
# target output size of 5x7
m <- nn_adaptive_max_pool2d(c(5, 7))
input <- torch_randn(1, 64, 8, 9)
output <- m(input)
# target output size of 7x7 (square)
m <- nn_adaptive_max_pool2d(7)
input <- torch_randn(1, 64, 10, 9)
output <- m(input)
}
```

---

nn_adaptive_max_pool3d

Applies a 3D adaptive max pooling over an input signal composed of several input planes.

Description

The output is of size D x H x W, for any input size. The number of output features is equal to the number of input planes.

Usage

```
nn_adaptive_max_pool3d(output_size, return_indices = FALSE)
```

Arguments

output_size	the target output size of the image of the form D x H x W. Can be a tuple (D, H, W) or a single D for a cube D x D x D. D, H and W can be either a int, or None which means the size will be the same as that of the input.
return_indices	if TRUE, will return the indices along with the outputs. Useful to pass to nn_max_unpool3d(). Default: FALSE

Examples

```
if (torch_is_installed()) {
# target output size of 5x7x9
m <- nn_adaptive_max_pool3d(c(5, 7, 9))
input <- torch_randn(1, 64, 8, 9, 10)
output <- m(input)
# target output size of 7x7x7 (cube)
m <- nn_adaptive_max_pool3d(7)
input <- torch_randn(1, 64, 10, 9, 8)
output <- m(input)
}
```

---

nn_aum_loss *AUM loss*

Description

Creates a criterion that measures the Area under the $Min(FPR, FNR)$ (AUM) between each element in the input $pred_tensor$ and target $label_tensor$.

Usage

```
nn_aum_loss()
```

Details

This is used for measuring the error of a binary reconstruction within highly unbalanced dataset, where the goal is optimizing the ROC curve. Note that the targets $label_tensor$ should be factor level of the binary outcome, i.e. with values `1L` and `2L`.

References

J. Hillman, T.D. Hocking: Optimizing ROC Curves with a Sort-Based Surrogate Loss for Binary Classification and Changepoint Detection https://jmlr.org/papers/volume24/21-0751/21-0751.pdf

Examples

```
if (torch_is_installed()) {

loss <- nn_aum_loss()
input <- torch_randn(4, 6, requires_grad = TRUE)
target <- input > 1.5
output <- loss(input, target)
output$backward()

}
```

nn_avg_pool1d *Applies a 1D average pooling over an input signal composed of several input planes.*

Description

In the simplest case, the output value of the layer with input size (N, C, L), output (N, C, L_{out}) and `kernel_size` k can be precisely described as:

Usage

```
nn_avg_pool1d(
  kernel_size,
  stride = NULL,
  padding = 0,
  ceil_mode = FALSE,
  count_include_pad = TRUE
)
```

Arguments

`kernel_size`	the size of the window
`stride`	the stride of the window. Default value is `kernel_size`
`padding`	implicit zero padding to be added on both sides
`ceil_mode`	when TRUE, will use `ceil` instead of `floor` to compute the output shape
`count_include_pad`	when TRUE, will include the zero-padding in the averaging calculation

Details

$$\text{out}(N_i, C_j, l) = \frac{1}{k} \sum_{m=0}^{k-1} \text{input}(N_i, C_j, \text{stride} \times l + m)$$

If `padding` is non-zero, then the input is implicitly zero-padded on both sides for `padding` number of points.

The parameters `kernel_size`, `stride`, `padding` can each be an `int` or a one-element tuple.

Shape

- Input: (N, C, L_{in})
- Output: (N, C, L_{out}), where

$$L_{out} = \left\lfloor \frac{L_{in} + 2 \times \text{padding} - \text{kernel_size}}{\text{stride}} + 1 \right\rfloor$$

Examples

```
if (torch_is_installed()) {

# pool with window of size=3, stride=2
m <- nn_avg_pool1d(3, stride = 2)
m(torch_randn(1, 1, 8))
}
```

`nn_avg_pool2d` *Applies a 2D average pooling over an input signal composed of several input planes.*

Description

In the simplest case, the output value of the layer with input size (N, C, H, W), output (N, C, H_{out}, W_{out}) and `kernel_size` (kH, kW) can be precisely described as:

Usage

```
nn_avg_pool2d(
  kernel_size,
  stride = NULL,
  padding = 0,
  ceil_mode = FALSE,
  count_include_pad = TRUE,
  divisor_override = NULL
)
```

Arguments

`kernel_size`	the size of the window
`stride`	the stride of the window. Default value is `kernel_size`
`padding`	implicit zero padding to be added on both sides
`ceil_mode`	when TRUE, will use `ceil` instead of `floor` to compute the output shape
`count_include_pad`	when TRUE, will include the zero-padding in the averaging calculation
`divisor_override`	if specified, it will be used as divisor, otherwise `kernel_size` will be used

Details

$$out(N_i, C_j, h, w) = \frac{1}{kH * kW} \sum_{m=0}^{kH-1} \sum_{n=0}^{kW-1} input(N_i, C_j, stride[0] \times h + m, stride[1] \times w + n)$$

If padding is non-zero, then the input is implicitly zero-padded on both sides for padding number of points.

The parameters kernel_size, stride, padding can either be:

- a single int – in which case the same value is used for the height and width dimension
- a tuple of two ints – in which case, the first int is used for the height dimension, and the second int for the width dimension

Shape

- Input: (N, C, H_{in}, W_{in})
- Output: (N, C, H_{out}, W_{out}), where

$$H_{out} = \left\lfloor \frac{H_{in} + 2 \times \text{padding}[0] - \text{kernel_size}[0]}{\text{stride}[0]} + 1 \right\rfloor$$
$$W_{out} = \left\lfloor \frac{W_{in} + 2 \times \text{padding}[1] - \text{kernel_size}[1]}{\text{stride}[1]} + 1 \right\rfloor$$

Examples

```
if (torch_is_installed()) {

# pool of square window of size=3, stride=2
m <- nn_avg_pool2d(3, stride = 2)
# pool of non-square window
m <- nn_avg_pool2d(c(3, 2), stride = c(2, 1))
input <- torch_randn(20, 16, 50, 32)
output <- m(input)
}
```

---

nn_avg_pool3d *Applies a 3D average pooling over an input signal composed of several input planes.*

Description

In the simplest case, the output value of the layer with input size (N, C, D, H, W), output $(N, C, D_{out}, H_{out}, W_{out})$ and kernel_size (kD, kH, kW) can be precisely described as:

Usage

```
nn_avg_pool3d(
  kernel_size,
  stride = NULL,
  padding = 0,
  ceil_mode = FALSE,
  count_include_pad = TRUE,
  divisor_override = NULL
)
```

Arguments

`kernel_size`	the size of the window
`stride`	the stride of the window. Default value is `kernel_size`
`padding`	implicit zero padding to be added on all three sides
`ceil_mode`	when TRUE, will use `ceil` instead of `floor` to compute the output shape
`count_include_pad`	when TRUE, will include the zero-padding in the averaging calculation
`divisor_override`	if specified, it will be used as divisor, otherwise `kernel_size` will be used

Details

$$\text{out}(N_i, C_j, d, h, w) = \sum_{k=0}^{kD-1} \sum_{m=0}^{kH-1} \sum_{n=0}^{kW-1} \frac{\text{input}(N_i, C_j, \text{stride}[0] \times d+k, \text{stride}[1] \times h+m, \text{stride}[2] \times w+n)}{kD \times kH \times kW}$$

If `padding` is non-zero, then the input is implicitly zero-padded on all three sides for `padding` number of points.

The parameters `kernel_size`, `stride` can either be:

- a single `int` – in which case the same value is used for the depth, height and width dimension
- a `tuple` of three ints – in which case, the first `int` is used for the depth dimension, the second `int` for the height dimension and the third `int` for the width dimension

Shape

- Input: $(N, C, D_{in}, H_{in}, W_{in})$
- Output: $(N, C, D_{out}, H_{out}, W_{out})$, where

$$D_{out} = \left\lfloor \frac{D_{in} + 2 \times \text{padding}[0] - \text{kernel_size}[0]}{\text{stride}[0]} + 1 \right\rfloor$$
$$H_{out} = \left\lfloor \frac{H_{in} + 2 \times \text{padding}[1] - \text{kernel_size}[1]}{\text{stride}[1]} + 1 \right\rfloor$$
$$W_{out} = \left\lfloor \frac{W_{in} + 2 \times \text{padding}[2] - \text{kernel_size}[2]}{\text{stride}[2]} + 1 \right\rfloor$$

Examples

```
if (torch_is_installed()) {

# pool of square window of size=3, stride=2
m <- nn_avg_pool3d(3, stride = 2)
# pool of non-square window
m <- nn_avg_pool3d(c(3, 2, 2), stride = c(2, 1, 2))
input <- torch_randn(20, 16, 50, 44, 31)
output <- m(input)
}
```

nn_batch_norm1d *BatchNorm1D module*

Description

Applies Batch Normalization over a 2D or 3D input (a mini-batch of 1D inputs with optional additional channel dimension) as described in the paper Batch Normalization: Accelerating Deep Network Training by Reducing Internal Covariate Shift

Usage

```
nn_batch_norm1d(
  num_features,
  eps = 1e-05,
  momentum = 0.1,
  affine = TRUE,
  track_running_stats = TRUE
)
```

Arguments

num_features	C from an expected input of size (N, C, L) or L from input of size (N, L)
eps	a value added to the denominator for numerical stability. Default: 1e-5
momentum	the value used for the running_mean and running_var computation. Can be set to NULL for cumulative moving average (i.e. simple average). Default: 0.1
affine	a boolean value that when set to TRUE, this module has learnable affine parameters. Default: TRUE
track_running_stats	a boolean value that when set to TRUE, this module tracks the running mean and variance, and when set to FALSE, this module does not track such statistics and always uses batch statistics in both training and eval modes. Default: TRUE

Details

$$y = \frac{x - \mathrm{E}[x]}{\sqrt{\mathrm{Var}[x] + \epsilon}} * \gamma + \beta$$

The mean and standard-deviation are calculated per-dimension over the mini-batches and γ and β are learnable parameter vectors of size C (where C is the input size). By default, the elements of γ are set to 1 and the elements of β are set to 0.

Also by default, during training this layer keeps running estimates of its computed mean and variance, which are then used for normalization during evaluation. The running estimates are kept with a default :attr:momentum of 0.1. If track_running_stats is set to FALSE, this layer then does not keep running estimates, and batch statistics are instead used during evaluation time as well.

Note

This `momentum` argument is different from one used in optimizer classes and the conventional notion of momentum. Mathematically, the update rule for running statistics here is $\hat{x}_{\text{new}} = (1 - \text{momentum}) \times \hat{x} + \text{momentum} \times x_t$, where $\hat{x}$ is the estimated statistic and x_t is the new observed value.

Because the Batch Normalization is done over the `C` dimension, computing statistics on `(N, L)` slices, it's common terminology to call this Temporal Batch Normalization.

Shape

- Input: (N, C) or (N, C, L)
- Output: (N, C) or (N, C, L) (same shape as input)

Examples

```
if (torch_is_installed()) {
# With Learnable Parameters
m <- nn_batch_norm1d(100)
# Without Learnable Parameters
m <- nn_batch_norm1d(100, affine = FALSE)
input <- torch_randn(20, 100)
output <- m(input)
}
```

---

nn_batch_norm2d *BatchNorm2D*

Description

Applies Batch Normalization over a 4D input (a mini-batch of 2D inputs additional channel dimension) as described in the paper Batch Normalization: Accelerating Deep Network Training by Reducing Internal Covariate Shift.

Usage

```
nn_batch_norm2d(
  num_features,
  eps = 1e-05,
  momentum = 0.1,
  affine = TRUE,
  track_running_stats = TRUE
)
```

Arguments

- `num_features` — C from an expected input of size (N, C, H, W)
- `eps` — a value added to the denominator for numerical stability. Default: 1e-5
- `momentum` — the value used for the running_mean and running_var computation. Can be set to `None` for cumulative moving average (i.e. simple average). Default: 0.1
- `affine` — a boolean value that when set to `TRUE`, this module has learnable affine parameters. Default: `TRUE`
- `track_running_stats` — a boolean value that when set to `TRUE`, this module tracks the running mean and variance, and when set to `FALSE`, this module does not track such statistics and uses batch statistics instead in both training and eval modes if the running mean and variance are `None`. Default: `TRUE`

Details

$$y = \frac{x - \mathrm{E}[x]}{\sqrt{\mathrm{Var}[x] + \epsilon}} * \gamma + \beta$$

The mean and standard-deviation are calculated per-dimension over the mini-batches and γ and β are learnable parameter vectors of size `C` (where `C` is the input size). By default, the elements of γ are set to 1 and the elements of β are set to 0. The standard-deviation is calculated via the biased estimator, equivalent to `torch_var(input, unbiased=FALSE)`. Also by default, during training this layer keeps running estimates of its computed mean and variance, which are then used for normalization during evaluation. The running estimates are kept with a default `momentum` of 0.1.

If `track_running_stats` is set to `FALSE`, this layer then does not keep running estimates, and batch statistics are instead used during evaluation time as well.

Shape

- Input: (N, C, H, W)
- Output: (N, C, H, W) (same shape as input)

Note

This `momentum` argument is different from one used in optimizer classes and the conventional notion of momentum. Mathematically, the update rule for running statistics here is $\hat{x}_{\text{new}} = (1 - \text{momentum}) \times \hat{x} + \text{momentum} \times x_t$, where $\hat{x}$ is the estimated statistic and x_t is the new observed value. Because the Batch Normalization is done over the `C` dimension, computing statistics on `(N, H, W)` slices, it's common terminology to call this Spatial Batch Normalization.

Examples

```
if (torch_is_installed()) {
# With Learnable Parameters
m <- nn_batch_norm2d(100)
# Without Learnable Parameters
m <- nn_batch_norm2d(100, affine = FALSE)
```

```
input <- torch_randn(20, 100, 35, 45)
output <- m(input)
}
```

---

nn_batch_norm3d *BatchNorm3D*

Description

Applies Batch Normalization over a 5D input (a mini-batch of 3D inputs with additional channel dimension) as described in the paper Batch Normalization: Accelerating Deep Network Training by Reducing Internal Covariate Shift.

Usage

```
nn_batch_norm3d(
  num_features,
  eps = 1e-05,
  momentum = 0.1,
  affine = TRUE,
  track_running_stats = TRUE
)
```

Arguments

num_features	C from an expected input of size (N, C, D, H, W)
eps	a value added to the denominator for numerical stability. Default: 1e-5
momentum	the value used for the running_mean and running_var computation. Can be set to None for cumulative moving average (i.e. simple average). Default: 0.1
affine	a boolean value that when set to TRUE, this module has learnable affine parameters. Default: TRUE
track_running_stats	a boolean value that when set to TRUE, this module tracks the running mean and variance, and when set to FALSE, this module does not track such statistics and uses batch statistics instead in both training and eval modes if the running mean and variance are None. Default: TRUE

Details

$$y = \frac{x - \mathrm{E}[x]}{\sqrt{\mathrm{Var}[x] + \epsilon}} * \gamma + \beta$$

The mean and standard-deviation are calculated per-dimension over the mini-batches and γ and β are learnable parameter vectors of size C (where C is the input size). By default, the elements of γ are set to 1 and the elements of β are set to 0. The standard-deviation is calculated via the biased estimator, equivalent to torch_var(input, unbiased = FALSE).

Also by default, during training this layer keeps running estimates of its computed mean and variance, which are then used for normalization during evaluation. The running estimates are kept with a default `momentum` of 0.1.

If `track_running_stats` is set to `FALSE`, this layer then does not keep running estimates, and batch statistics are instead used during evaluation time as well.

Shape

- Input: (N, C, D, H, W)
- Output: (N, C, D, H, W) (same shape as input)

Note

This `momentum` argument is different from one used in optimizer classes and the conventional notion of momentum. Mathematically, the update rule for running statistics here is: $\hat{x}_{\text{new}} = (1 - \text{momentum}) \times \hat{x} + \text{momentum} \times x_t$, where $\hat{x}$ is the estimated statistic and x_t is the new observed value.

Because the Batch Normalization is done over the `C` dimension, computing statistics on `(N, D, H, W)` slices, it's common terminology to call this Volumetric Batch Normalization or Spatio-temporal Batch Normalization.

Examples

```
if (torch_is_installed()) {
# With Learnable Parameters
m <- nn_batch_norm3d(100)
# Without Learnable Parameters
m <- nn_batch_norm3d(100, affine = FALSE)
input <- torch_randn(20, 100, 35, 45, 55)
output <- m(input)
}
```

`nn_bce_loss` *Binary cross entropy loss*

Description

Creates a criterion that measures the Binary Cross Entropy between the target and the output:

Usage

```
nn_bce_loss(weight = NULL, reduction = "mean")
```

Arguments

`weight`	(Tensor, optional): a manual rescaling weight given to the loss of each batch element. If given, has to be a Tensor of size `nbatch`.
`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.

Details

The unreduced (i.e. with `reduction` set to `'none'`) loss can be described as:

$$\ell(x, y) = L = \{l_1, \dots, l_N\}^\top, \quad l_n = -w_n \left[y_n \cdot \log x_n + (1 - y_n) \cdot \log(1 - x_n) \right]$$

where N is the batch size. If `reduction` is not `'none'` (default `'mean'`), then

$$\ell(x, y) = \begin{cases} \text{mean}(L), & \text{if reduction} = \text{'mean';} \\ \text{sum}(L), & \text{if reduction} = \text{'sum'.} \end{cases}$$

This is used for measuring the error of a reconstruction in for example an auto-encoder. Note that the targets y should be numbers between 0 and 1.

Notice that if x_n is either 0 or 1, one of the log terms would be mathematically undefined in the above loss equation. PyTorch chooses to set $\log(0) = -\infty$, since $\lim_{x \to 0} \log(x) = -\infty$.

However, an infinite term in the loss equation is not desirable for several reasons. For one, if either $y_n = 0$ or $(1 - y_n) = 0$, then we would be multiplying 0 with infinity. Secondly, if we have an infinite loss value, then we would also have an infinite term in our gradient, since $\lim_{x \to 0} \frac{d}{dx} \log(x) = \infty$.

This would make BCELoss's backward method nonlinear with respect to x_n, and using it for things like linear regression would not be straight-forward. Our solution is that BCELoss clamps its log function outputs to be greater than or equal to -100. This way, we can always have a finite loss value and a linear backward method.

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Target: $(N, *)$, same shape as the input
- Output: scalar. If `reduction` is `'none'`, then $(N, *)$, same shape as input.

Examples

```
if (torch_is_installed()) {
m <- nn_sigmoid()
loss <- nn_bce_loss()
input <- torch_randn(3, requires_grad = TRUE)
target <- torch_rand(3)
output <- loss(m(input), target)
output$backward()
}
```

nn_bce_with_logits_loss

BCE with logits loss

Description

This loss combines a `Sigmoid` layer and the `BCELoss` in one single class. This version is more numerically stable than using a plain `Sigmoid` followed by a `BCELoss` as, by combining the operations into one layer, we take advantage of the log-sum-exp trick for numerical stability.

Usage

```
nn_bce_with_logits_loss(weight = NULL, reduction = "mean", pos_weight = NULL)
```

Arguments

`weight`	(Tensor, optional): a manual rescaling weight given to the loss of each batch element. If given, has to be a Tensor of size `nbatch`.
`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.
`pos_weight`	(Tensor, optional): a weight of positive examples. Must be a vector with length equal to the number of classes.

Details

The unreduced (i.e. with `reduction` set to `'none'`) loss can be described as:

$$\ell(x, y) = L = \{l_1, \dots, l_N\}^\top, \quad l_n = -w_n \left[y_n \cdot \log \sigma(x_n) + (1 - y_n) \cdot \log(1 - \sigma(x_n)) \right],$$

where N is the batch size. If `reduction` is not `'none'` (default `'mean'`), then

$$\ell(x, y) = \begin{array}{ll} \text{mean}(L), & \text{if reduction} = \text{'mean';} \\ \text{sum}(L), & \text{if reduction} = \text{'sum'.} \end{array}$$

This is used for measuring the error of a reconstruction in for example an auto-encoder. Note that the targets `t[i]` should be numbers between 0 and 1. It's possible to trade off recall and precision by adding weights to positive examples. In the case of multi-label classification the loss can be described as:

$$\ell_c(x, y) = L_c = \{l_{1,c}, \dots, l_{N,c}\}^\top, \quad l_{n,c} = -w_{n,c} \left[p_c y_{n,c} \cdot \log \sigma(x_{n,c}) + (1 - y_{n,c}) \cdot \log(1 - \sigma(x_{n,c})) \right],$$

where c is the class number ($c > 1$ for multi-label binary classification,

$c = 1$ for single-label binary classification), n is the number of the sample in the batch and p_c is the weight of the positive answer for the class c. $p_c > 1$ increases the recall, $p_c < 1$ increases the precision. For example, if a dataset contains 100 positive and 300 negative examples of a single class, then `pos_weight` for the class should be equal to $\frac{300}{100} = 3$. The loss would act as if the dataset contains $3 \times 100 = 300$ positive examples.

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Target: $(N, *)$, same shape as the input
- Output: scalar. If `reduction` is `'none'`, then $(N, *)$, same shape as input.

Examples

```
if (torch_is_installed()) {
loss <- nn_bce_with_logits_loss()
input <- torch_randn(3, requires_grad = TRUE)
target <- torch_empty(3)$random_(1, 2)
output <- loss(input, target)
output$backward()

target <- torch_ones(10, 64, dtype = torch_float32()) # 64 classes, batch size = 10
output <- torch_full(c(10, 64), 1.5) # A prediction (logit)
pos_weight <- torch_ones(64) # All weights are equal to 1
criterion <- nn_bce_with_logits_loss(pos_weight = pos_weight)
criterion(output, target) # -log(sigmoid(1.5))
}
```

---

nn_bilinear *Bilinear module*

Description

Applies a bilinear transformation to the incoming data $y = x_1^T A x_2 + b$

Usage

```
nn_bilinear(in1_features, in2_features, out_features, bias = TRUE)
```

Arguments

`in1_features`	size of each first input sample
`in2_features`	size of each second input sample
`out_features`	size of each output sample
`bias`	If set to `FALSE`, the layer will not learn an additive bias. Default: `TRUE`

Shape

- Input1: $(N, *, H_{in1})$ $H_{in1} =$ in1_features and $*$ means any number of additional dimensions. All but the last dimension of the inputs should be the same.
- Input2: $(N, *, H_{in2})$ where $H_{in2} =$ in2_features.
- Output: $(N, *, H_{out})$ where $H_{out} =$ out_features and all but the last dimension are the same shape as the input.

Attributes

- weight: the learnable weights of the module of shape $(\text{out_features}, \text{in1_features}, \text{in2_features})$. The values are initialized from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$, where $k = \frac{1}{\text{in1_features}}$
- bias: the learnable bias of the module of shape (out_features). If `bias` is `TRUE`, the values are initialized from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$, where $k = \frac{1}{\text{in1_features}}$

Examples

```
if (torch_is_installed()) {
m <- nn_bilinear(20, 30, 50)
input1 <- torch_randn(128, 20)
input2 <- torch_randn(128, 30)
output <- m(input1, input2)
print(output$size())
}
```

---

nn_buffer *Creates a nn_buffer*

Description

Indicates that a tensor is a buffer in a nn_module

Usage

```
nn_buffer(x, persistent = TRUE)
```

Arguments

`x`	the tensor that will be converted to nn_buffer
`persistent`	whether the buffer should be persistent or not.

nn_celu *CELU module*

Description

Applies the element-wise function:

Usage

```
nn_celu(alpha = 1, inplace = FALSE)
```

Arguments

alpha	the α value for the CELU formulation. Default: 1.0
inplace	can optionally do the operation in-place. Default: FALSE

Details

$$\text{CELU}(x) = \max(0, x) + \min(0, \alpha * (\exp(x/\alpha) - 1))$$

More details can be found in the paper Continuously Differentiable Exponential Linear Units.

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_celu()
input <- torch_randn(2)
output <- m(input)
}
```

nn_contrib_sparsemax *Sparsemax activation*

Description

Sparsemax activation module.

Usage

```
nn_contrib_sparsemax(dim = -1)
```

Arguments

dim	The dimension over which to apply the sparsemax function. (-1)

Details

The SparseMax activation is described in 'From Softmax to Sparsemax: A Sparse Model of Attention and Multi-Label Classification' The implementation is based on aced125/sparsemax

nn_conv1d *Conv1D module*

Description

Applies a 1D convolution over an input signal composed of several input planes. In the simplest case, the output value of the layer with input size (N, C_{in}, L) and output $(N, C_{\text{out}}, L_{\text{out}})$ can be precisely described as:

Usage

```
nn_conv1d(
  in_channels,
  out_channels,
  kernel_size,
  stride = 1,
  padding = 0,
  dilation = 1,
  groups = 1,
  bias = TRUE,
  padding_mode = "zeros"
)
```

Arguments

`in_channels`	(int): Number of channels in the input image
`out_channels`	(int): Number of channels produced by the convolution
`kernel_size`	(int or tuple): Size of the convolving kernel
`stride`	(int or tuple, optional): Stride of the convolution. Default: 1
`padding`	(int, tuple or str, optional) – Padding added to both sides of the input. Default: 0
`dilation`	(int or tuple, optional): Spacing between kernel elements. Default: 1
`groups`	(int, optional): Number of blocked connections from input channels to output channels. Default: 1
`bias`	(bool, optional): If `TRUE`, adds a learnable bias to the output. Default: `TRUE`
`padding_mode`	(string, optional): `'zeros'`, `'reflect'`, `'replicate'` or `'circular'`. Default: `'zeros'`

Details

$$\text{out}(N_i, C_{\text{out}_j}) = \text{bias}(C_{\text{out}_j}) + \sum_{k=0}^{C_{in}-1} \text{weight}(C_{\text{out}_j}, k) \star \text{input}(N_i, k)$$

where $\star$ is the valid cross-correlation operator, N is a batch size, C denotes a number of channels, L is a length of signal sequence.

- `stride` controls the stride for the cross-correlation, a single number or a one-element tuple.
- `padding` controls the amount of implicit zero-paddings on both sides for `padding` number of points.
- `dilation` controls the spacing between the kernel points; also known as the à trous algorithm. It is harder to describe, but this link has a nice visualization of what `dilation` does.
- `groups` controls the connections between inputs and outputs. `in_channels` and `out_channels` must both be divisible by `groups`. For example,
  - At groups=1, all inputs are convolved to all outputs.
  - At groups=2, the operation becomes equivalent to having two conv layers side by side, each seeing half the input channels, and producing half the output channels, and both subsequently concatenated.
  - At groups= `in_channels`, each input channel is convolved with its own set of filters, of size $\left\lfloor \frac{out_channels}{in_channels} \right\rfloor$.

Note

Depending of the size of your kernel, several (of the last) columns of the input might be lost, because it is a valid `cross-correlation`*, and not a full* `cross-correlation`. It is up to the user to add proper padding.

When `groups == in_channels` and `out_channels == K * in_channels`, where `K` is a positive integer, this operation is also termed in literature as depthwise convolution. In other words, for an input of size (N, C_{in}, L_{in}), a depthwise convolution with a depthwise multiplier `K`, can be constructed by arguments $(C_{\text{in}} = C_{in}, C_{\text{out}} = C_{in} \times K, ..., \text{groups} = C_{in})$.

Shape

- Input: (N, C_{in}, L_{in})
- Output: (N, C_{out}, L_{out}) where

$$L_{out} = \left\lfloor \frac{L_{in} + 2 \times \text{padding} - \text{dilation} \times (\text{kernel_size} - 1) - 1}{\text{stride}} + 1 \right\rfloor$$

Attributes

- weight (Tensor): the learnable weights of the module of shape $(\text{out_channels}, \frac{\text{in_channels}}{\text{groups}}, \text{kernel_size})$. The values of these weights are sampled from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{groups}{C_{\text{in}} * \text{kernel_size}}$
- bias (Tensor): the learnable bias of the module of shape (out_channels). If `bias` is `TRUE`, then the values of these weights are sampled from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{groups}{C_{\text{in}} * \text{kernel_size}}$

Examples

```
if (torch_is_installed()) {
m <- nn_conv1d(16, 33, 3, stride = 2)
input <- torch_randn(20, 16, 50)
output <- m(input)
}
```

---

nn_conv2d *Conv2D module*

Description

Applies a 2D convolution over an input signal composed of several input planes.

Usage

```
nn_conv2d(
  in_channels,
  out_channels,
  kernel_size,
  stride = 1,
  padding = 0,
  dilation = 1,
  groups = 1,
  bias = TRUE,
  padding_mode = "zeros"
)
```

Arguments

`in_channels`	(int): Number of channels in the input image
`out_channels`	(int): Number of channels produced by the convolution
`kernel_size`	(int or tuple): Size of the convolving kernel
`stride`	(int or tuple, optional): Stride of the convolution. Default: 1
`padding`	(int or tuple or string, optional): Zero-padding added to both sides of the input. controls the amount of padding applied to the input. It can be either a string `'valid'`, `'same'` or a tuple of ints giving the amount of implicit padding applied on both sides. Default: 0
`dilation`	(int or tuple, optional): Spacing between kernel elements. Default: 1
`groups`	(int, optional): Number of blocked connections from input channels to output channels. Default: 1
`bias`	(bool, optional): If `TRUE`, adds a learnable bias to the output. Default: `TRUE`
`padding_mode`	(string, optional): `'zeros'`, `'reflect'`, `'replicate'` or `'circular'`. Default: `'zeros'`

Details

In the simplest case, the output value of the layer with input size (N, C_{in}, H, W) and output $(N, C_{\text{out}}, H_{\text{out}}, W_{\text{out}})$ can be precisely described as:

$$\text{out}(N_i, C_{\text{out}_j}) = \text{bias}(C_{\text{out}_j}) + \sum_{k=0}^{C_{\text{in}}-1} \text{weight}(C_{\text{out}_j}, k) \star \text{input}(N_i, k)$$

where $\star$ is the valid 2D cross-correlation operator, N is a batch size, C denotes a number of channels, H is a height of input planes in pixels, and W is width in pixels.

- `stride` controls the stride for the cross-correlation, a single number or a tuple.
- `padding` controls the amount of implicit zero-paddings on both sides for `padding` number of points for each dimension.
- `dilation` controls the spacing between the kernel points; also known as the à trous algorithm. It is harder to describe, but this `link_` has a nice visualization of what `dilation` does.
- `groups` controls the connections between inputs and outputs. `in_channels` and `out_channels` must both be divisible by `groups`. For example,
  - At groups=1, all inputs are convolved to all outputs.
  - At groups=2, the operation becomes equivalent to having two conv layers side by side, each seeing half the input channels, and producing half the output channels, and both subsequently concatenated.
  - At groups= `in_channels`, each input channel is convolved with its own set of filters, of size: $\left\lfloor \frac{out_channels}{in_channels} \right\rfloor$.

The parameters `kernel_size`, `stride`, `padding`, `dilation` can either be:

- a single `int` – in which case the same value is used for the height and width dimension
- a `tuple` of two ints – in which case, the first `int` is used for the height dimension, and the second `int` for the width dimension

Note

Depending of the size of your kernel, several (of the last) columns of the input might be lost, because it is a valid cross-correlation, and not a full cross-correlation. It is up to the user to add proper padding.

When `groups == in_channels` and `out_channels == K * in_channels`, where `K` is a positive integer, this operation is also termed in literature as depthwise convolution. In other words, for an input of size :math:`(N, C_{in}, H_{in}, W_{in})`, a depthwise convolution with a depthwise multiplier `K`, can be constructed by arguments $(in_channels = C_{in}, out_channels = C_{in} \times K, ..., groups = C_{in})$.

In some circumstances when using the CUDA backend with CuDNN, this operator may select a nondeterministic algorithm to increase performance. If this is undesirable, you can try to make the operation deterministic (potentially at a performance cost) by setting `backends_cudnn_deterministic = TRUE`.

Shape

- Input: $(N, C_{in}, H_{in}, W_{in})$
- Output: $(N, C_{out}, H_{out}, W_{out})$ where

$$H_{out} = \left\lfloor \frac{H_{in} + 2 \times \text{padding}[0] - \text{dilation}[0] \times (\text{kernel_size}[0] - 1) - 1}{\text{stride}[0]} + 1 \right\rfloor$$

$$W_{out} = \left\lfloor \frac{W_{in} + 2 \times \text{padding}[1] - \text{dilation}[1] \times (\text{kernel_size}[1] - 1) - 1}{\text{stride}[1]} + 1 \right\rfloor$$

Attributes

- weight (Tensor): the learnable weights of the module of shape $(\text{out_channels}, \frac{\text{in_channels}}{\text{groups}}, \text{kernel_size}[0], \text{kernel_size}[1])$. The values of these weights are sampled from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{groups}{C_{\text{in}} * \prod_{i=0}^{1} \text{kernel_size}[i]}$
- bias (Tensor): the learnable bias of the module of shape (out_channels). If `bias` is `TRUE`, then the values of these weights are sampled from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{groups}{C_{\text{in}} * \prod_{i=0}^{1} \text{kernel_size}[i]}$

Examples

```
if (torch_is_installed()) {

# With square kernels and equal stride
m <- nn_conv2d(16, 33, 3, stride = 2)
# non-square kernels and unequal stride and with padding
m <- nn_conv2d(16, 33, c(3, 5), stride = c(2, 1), padding = c(4, 2))
# non-square kernels and unequal stride and with padding and dilation
m <- nn_conv2d(16, 33, c(3, 5), stride = c(2, 1), padding = c(4, 2), dilation = c(3, 1))
input <- torch_randn(20, 16, 50, 100)
output <- m(input)
}
```

nn_conv3d *Conv3D module*

Description

Applies a 3D convolution over an input signal composed of several input planes. In the simplest case, the output value of the layer with input size (N, C_{in}, D, H, W) and output $(N, C_{out}, D_{out}, H_{out}, W_{out})$ can be precisely described as:

Usage

```
nn_conv3d(
  in_channels,
  out_channels,
  kernel_size,
  stride = 1,
  padding = 0,
  dilation = 1,
  groups = 1,
  bias = TRUE,
  padding_mode = "zeros"
)
```

Arguments

in_channels	(int): Number of channels in the input image
out_channels	(int): Number of channels produced by the convolution
kernel_size	(int or tuple): Size of the convolving kernel
stride	(int or tuple, optional): Stride of the convolution. Default: 1
padding	(int, tuple or str, optional): padding added to all six sides of the input. Default: 0
dilation	(int or tuple, optional): Spacing between kernel elements. Default: 1
groups	(int, optional): Number of blocked connections from input channels to output channels. Default: 1
bias	(bool, optional): If TRUE, adds a learnable bias to the output. Default: TRUE
padding_mode	(string, optional): 'zeros', 'reflect', 'replicate' or 'circular'. Default: 'zeros'

Details

$$out(N_i, C_{out_j}) = bias(C_{out_j}) + \sum_{k=0}^{C_{in}-1} weight(C_{out_j}, k) \star input(N_i, k)$$

where $\star$ is the valid 3D cross-correlation operator

- `stride` controls the stride for the cross-correlation.
- `padding` controls the amount of implicit zero-paddings on both sides for `padding` number of points for each dimension.
- `dilation` controls the spacing between the kernel points; also known as the à trous algorithm. It is harder to describe, but this `link_` has a nice visualization of what `dilation` does.
- `groups` controls the connections between inputs and outputs. `in_channels` and `out_channels` must both be divisible by `groups`. For example,
- At groups=1, all inputs are convolved to all outputs.
- At groups=2, the operation becomes equivalent to having two conv layers side by side, each seeing half the input channels, and producing half the output channels, and both subsequently concatenated.
- At groups= `in_channels`, each input channel is convolved with its own set of filters, of size $\left\lfloor \frac{out_channels}{in_channels} \right\rfloor$.

The parameters `kernel_size`, `stride`, `padding`, `dilation` can either be:

- a single `int` – in which case the same value is used for the depth, height and width dimension
- a `tuple` of three ints – in which case, the first `int` is used for the depth dimension, the second `int` for the height dimension and the third `int` for the width dimension

Shape

- Input: $(N, C_{in}, D_{in}, H_{in}, W_{in})$
- Output: $(N, C_{out}, D_{out}, H_{out}, W_{out})$ where

$$D_{out} = \left\lfloor \frac{D_{in} + 2 \times \text{padding}[0] - \text{dilation}[0] \times (\text{kernel_size}[0] - 1) - 1}{\text{stride}[0]} + 1 \right\rfloor$$

$$H_{out} = \left\lfloor \frac{H_{in} + 2 \times \text{padding}[1] - \text{dilation}[1] \times (\text{kernel_size}[1] - 1) - 1}{\text{stride}[1]} + 1 \right\rfloor$$

$$W_{out} = \left\lfloor \frac{W_{in} + 2 \times \text{padding}[2] - \text{dilation}[2] \times (\text{kernel_size}[2] - 1) - 1}{\text{stride}[2]} + 1 \right\rfloor$$

Attributes

- weight (Tensor): the learnable weights of the module of shape $(\text{out_channels}, \frac{\text{in_channels}}{\text{groups}}, \text{kernel_size}[0], \text{kernel_size}[1], \text{kernel_size}[2])$. The values of these weights are sampled from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{groups}{C_{\text{in}} * \prod_{i=0}^{2} \text{kernel_size}[i]}$
- bias (Tensor): the learnable bias of the module of shape (out_channels). If `bias` is `True`, then the values of these weights are sampled from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{groups}{C_{\text{in}} * \prod_{i=0}^{2} \text{kernel_size}[i]}$

Note

Depending of the size of your kernel, several (of the last) columns of the input might be lost, because it is a valid `cross-correlation`, *and not a full* `cross-correlation`. It is up to the user to add proper padding.

When `groups == in_channels` and `out_channels == K * in_channels`, where `K` is a positive integer, this operation is also termed in literature as depthwise convolution. In other words, for an input of size $(N, C_{in}, D_{in}, H_{in}, W_{in})$, a depthwise convolution with a depthwise multiplier `K`, can be constructed by arguments $(in_channels = C_{in}, out_channels = C_{in} \times K, ..., groups = C_{in})$.

In some circumstances when using the CUDA backend with CuDNN, this operator may select a nondeterministic algorithm to increase performance. If this is undesirable, you can try to make the operation deterministic (potentially at a performance cost) by setting `torch.backends.cudnn.deterministic = TRUE`. Please see the notes on :doc:`/notes/randomness` for background.

Examples

```
if (torch_is_installed()) {
# With square kernels and equal stride
m <- nn_conv3d(16, 33, 3, stride = 2)
# non-square kernels and unequal stride and with padding
m <- nn_conv3d(16, 33, c(3, 5, 2), stride = c(2, 1, 1), padding = c(4, 2, 0))
input <- torch_randn(20, 16, 10, 50, 100)
output <- m(input)
}
```

`nn_conv_transpose1d` *ConvTranspose1D*

Description

Applies a 1D transposed convolution operator over an input image composed of several input planes.

Usage

```
nn_conv_transpose1d(
  in_channels,
  out_channels,
  kernel_size,
  stride = 1,
  padding = 0,
  output_padding = 0,
  groups = 1,
  bias = TRUE,
  dilation = 1,
  padding_mode = "zeros"
)
```

Arguments

`in_channels`	(int): Number of channels in the input image
`out_channels`	(int): Number of channels produced by the convolution
`kernel_size`	(int or tuple): Size of the convolving kernel
`stride`	(int or tuple, optional): Stride of the convolution. Default: 1
`padding`	(int or tuple, optional): `dilation * (kernel_size - 1) - padding` zero-padding will be added to both sides of the input. Default: 0
`output_padding`	(int or tuple, optional): Additional size added to one side of the output shape. Default: 0
`groups`	(int, optional): Number of blocked connections from input channels to output channels. Default: 1
`bias`	(bool, optional): If `True`, adds a learnable bias to the output. Default: `TRUE`
`dilation`	(int or tuple, optional): Spacing between kernel elements. Default: 1
`padding_mode`	(string, optional): `'zeros'`, `'reflect'`, `'replicate'` or `'circular'`. Default: `'zeros'`

Details

This module can be seen as the gradient of Conv1d with respect to its input. It is also known as a fractionally-strided convolution or a deconvolution (although it is not an actual deconvolution operation).

- `stride` controls the stride for the cross-correlation.
- `padding` controls the amount of implicit zero-paddings on both sides for `dilation * (kernel_size - 1) - padding` number of points. See note below for details.
- `output_padding` controls the additional size added to one side of the output shape. See note below for details.
- `dilation` controls the spacing between the kernel points; also known as the à trous algorithm. It is harder to describe, but this link has a nice visualization of what `dilation` does.
- `groups` controls the connections between inputs and outputs. `in_channels` and `out_channels` must both be divisible by `groups`. For example,
  - At groups=1, all inputs are convolved to all outputs.
  - At groups=2, the operation becomes equivalent to having two conv layers side by side, each seeing half the input channels, and producing half the output channels, and both subsequently concatenated.
  - At groups= `in_channels`, each input channel is convolved with its own set of filters (of size $\left\lfloor \frac{out_channels}{in_channels} \right\rfloor$).

Shape

- Input: (N, C_{in}, L_{in})
- Output: (N, C_{out}, L_{out}) where

$$L_{out} = (L_{in} - 1) \times \text{stride} - 2 \times \text{padding} + \text{dilation} \times (\text{kernel_size} - 1) + \text{output_padding} + 1$$

Attributes

- weight (Tensor): the learnable weights of the module of shape (in_channels, $\frac{\text{out_channels}}{\text{groups}}$, kernel_size). The values of these weights are sampled from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{groups}{C_{\text{out}} * \text{kernel_size}}$
- bias (Tensor): the learnable bias of the module of shape (out_channels). If `bias` is `TRUE`, then the values of these weights are sampled from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{groups}{C_{\text{out}} * \text{kernel_size}}$

Note

Depending of the size of your kernel, several (of the last) columns of the input might be lost, because it is a valid `cross-correlation`*, and not a full* `cross-correlation`. It is up to the user to add proper padding.

The `padding` argument effectively adds `dilation * (kernel_size - 1) - padding` amount of zero padding to both sizes of the input. This is set so that when a `~torch.nn.Conv1d` and a `~torch.nn.ConvTranspose1d` are initialized with same parameters, they are inverses of each other in regard to the input and output shapes. However, when `stride > 1`, `~torch.nn.Conv1d` maps multiple input shapes to the same output shape. `output_padding` is provided to resolve this ambiguity by effectively increasing the calculated output shape on one side. Note that `output_padding` is only used to find output shape, but does not actually add zero-padding to output.

In some circumstances when using the CUDA backend with CuDNN, this operator may select a nondeterministic algorithm to increase performance. If this is undesirable, you can try to make the operation deterministic (potentially at a performance cost) by setting `torch.backends.cudnn.deterministic = TRUE`.

Examples

```
if (torch_is_installed()) {
m <- nn_conv_transpose1d(32, 16, 2)
input <- torch_randn(10, 32, 2)
output <- m(input)
}
```

---

nn_conv_transpose2d *ConvTranpose2D module*

Description

Applies a 2D transposed convolution operator over an input image composed of several input planes.

Usage

```
nn_conv_transpose2d(
  in_channels,
  out_channels,
  kernel_size,
  stride = 1,
```

```
  padding = 0,
  output_padding = 0,
  groups = 1,
  bias = TRUE,
  dilation = 1,
  padding_mode = "zeros"
)
```

Arguments

in_channels	(int): Number of channels in the input image
out_channels	(int): Number of channels produced by the convolution
kernel_size	(int or tuple): Size of the convolving kernel
stride	(int or tuple, optional): Stride of the convolution. Default: 1
padding	(int or tuple, optional): `dilation * (kernel_size - 1) - padding` zero-padding will be added to both sides of each dimension in the input. Default: 0
output_padding	(int or tuple, optional): Additional size added to one side of each dimension in the output shape. Default: 0
groups	(int, optional): Number of blocked connections from input channels to output channels. Default: 1
bias	(bool, optional): If `True`, adds a learnable bias to the output. Default: `True`
dilation	(int or tuple, optional): Spacing between kernel elements. Default: 1
padding_mode	(string, optional): `'zeros'`, `'reflect'`, `'replicate'` or `'circular'`. Default: `'zeros'`

Details

This module can be seen as the gradient of Conv2d with respect to its input. It is also known as a fractionally-strided convolution or a deconvolution (although it is not an actual deconvolution operation).

- `stride` controls the stride for the cross-correlation.
- `padding` controls the amount of implicit zero-paddings on both sides for `dilation * (kernel_size - 1) - padding` number of points. See note below for details.
- `output_padding` controls the additional size added to one side of the output shape. See note below for details.
- `dilation` controls the spacing between the kernel points; also known as the à trous algorithm. It is harder to describe, but this `link_` has a nice visualization of what `dilation` does.
- `groups` controls the connections between inputs and outputs. `in_channels` and `out_channels` must both be divisible by `groups`. For example,
  - At groups=1, all inputs are convolved to all outputs.
  - At groups=2, the operation becomes equivalent to having two conv layers side by side, each seeing half the input channels, and producing half the output channels, and both subsequently concatenated.

  - At groups= `in_channels`, each input channel is convolved with its own set of filters (of size $\left\lfloor \frac{out_channels}{in_channels} \right\rfloor$).

The parameters `kernel_size`, `stride`, `padding`, `output_padding` can either be:

- a single `int` – in which case the same value is used for the height and width dimensions
- a `tuple` of two ints – in which case, the first `int` is used for the height dimension, and the second `int` for the width dimension

Shape

- Input: $(N, C_{in}, H_{in}, W_{in})$
- Output: $(N, C_{out}, H_{out}, W_{out})$ where

$$H_{out} = (H_{in} - 1) \times \text{stride}[0] - 2 \times \text{padding}[0] + \text{dilation}[0] \times (\text{kernel_size}[0] - 1) + \text{output_padding}[0] + 1$$

$$W_{out} = (W_{in} - 1) \times \text{stride}[1] - 2 \times \text{padding}[1] + \text{dilation}[1] \times (\text{kernel_size}[1] - 1) + \text{output_padding}[1] + 1$$

Attributes

- weight (Tensor): the learnable weights of the module of shape $(\text{in_channels}, \frac{\text{out_channels}}{\text{groups}}, \text{kernel_size}[0], \text{kernel_size}[1])$. The values of these weights are sampled from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{groups}{C_{\text{out}} * \prod_{i=0}^{1} \text{kernel_size}[i]}$
- bias (Tensor): the learnable bias of the module of shape (out_channels) If `bias` is `True`, then the values of these weights are sampled from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{groups}{C_{\text{out}} * \prod_{i=0}^{1} \text{kernel_size}[i]}$

Note

Depending of the size of your kernel, several (of the last) columns of the input might be lost, because it is a valid `cross-correlation_`, and not a full `cross-correlation`. It is up to the user to add proper padding.

The `padding` argument effectively adds `dilation * (kernel_size - 1) - padding` amount of zero padding to both sizes of the input. This is set so that when a nn_conv2d and a nn_conv_transpose2d are initialized with same parameters, they are inverses of each other in regard to the input and output shapes. However, when `stride > 1`, nn_conv2d maps multiple input shapes to the same output shape. `output_padding` is provided to resolve this ambiguity by effectively increasing the calculated output shape on one side. Note that `output_padding` is only used to find output shape, but does not actually add zero-padding to output.

In some circumstances when using the CUDA backend with CuDNN, this operator may select a nondeterministic algorithm to increase performance. If this is undesirable, you can try to make the operation deterministic (potentially at a performance cost) by setting `torch.backends.cudnn.deterministic = TRUE`.

Examples

```
if (torch_is_installed()) {
# With square kernels and equal stride
m <- nn_conv_transpose2d(16, 33, 3, stride = 2)
# non-square kernels and unequal stride and with padding
m <- nn_conv_transpose2d(16, 33, c(3, 5), stride = c(2, 1), padding = c(4, 2))
input <- torch_randn(20, 16, 50, 100)
output <- m(input)
# exact output size can be also specified as an argument
input <- torch_randn(1, 16, 12, 12)
downsample <- nn_conv2d(16, 16, 3, stride = 2, padding = 1)
upsample <- nn_conv_transpose2d(16, 16, 3, stride = 2, padding = 1)
h <- downsample(input)
h$size()
output <- upsample(h, output_size = input$size())
output$size()
}
```

---

nn_conv_transpose3d *ConvTranpose3D module*

Description

Applies a 3D transposed convolution operator over an input image composed of several input planes.

Usage

```
nn_conv_transpose3d(
  in_channels,
  out_channels,
  kernel_size,
  stride = 1,
  padding = 0,
  output_padding = 0,
  groups = 1,
  bias = TRUE,
  dilation = 1,
  padding_mode = "zeros"
)
```

Arguments

in_channels	(int): Number of channels in the input image
out_channels	(int): Number of channels produced by the convolution
kernel_size	(int or tuple): Size of the convolving kernel
stride	(int or tuple, optional): Stride of the convolution. Default: 1

padding	(int or tuple, optional): `dilation * (kernel_size - 1) - padding` zero-padding will be added to both sides of each dimension in the input. Default: 0 output_padding (int or tuple, optional): Additional size added to one side of each dimension in the output shape. Default: 0
output_padding	(int or tuple, optional): Additional size added to one side of each dimension in the output shape. Default: 0
groups	(int, optional): Number of blocked connections from input channels to output channels. Default: 1
bias	(bool, optional): If `True`, adds a learnable bias to the output. Default: `True`
dilation	(int or tuple, optional): Spacing between kernel elements. Default: 1
padding_mode	(string, optional): `'zeros'`, `'reflect'`, `'replicate'` or `'circular'`. Default: `'zeros'`

Details

The transposed convolution operator multiplies each input value element-wise by a learnable kernel, and sums over the outputs from all input feature planes.

This module can be seen as the gradient of Conv3d with respect to its input. It is also known as a fractionally-strided convolution or a deconvolution (although it is not an actual deconvolution operation).

- `stride` controls the stride for the cross-correlation.
- `padding` controls the amount of implicit zero-paddings on both sides for `dilation * (kernel_size - 1) - padding` number of points. See note below for details.
- `output_padding` controls the additional size added to one side of the output shape. See note below for details.
- `dilation` controls the spacing between the kernel points; also known as the à trous algorithm. It is harder to describe, but this `link_` has a nice visualization of what `dilation` does.
- `groups` controls the connections between inputs and outputs. `in_channels` and `out_channels` must both be divisible by `groups`. For example,
  - At groups=1, all inputs are convolved to all outputs.
  - At groups=2, the operation becomes equivalent to having two conv layers side by side, each seeing half the input channels, and producing half the output channels, and both subsequently concatenated.
  - At groups= `in_channels`, each input channel is convolved with its own set of filters (of size $\left\lfloor \frac{out_channels}{in_channels} \right\rfloor$).

The parameters `kernel_size`, `stride`, `padding`, `output_padding` can either be:

- a single `int` – in which case the same value is used for the depth, height and width dimensions
- a `tuple` of three ints – in which case, the first `int` is used for the depth dimension, the second `int` for the height dimension and the third `int` for the width dimension

Shape

- Input: $(N, C_{in}, D_{in}, H_{in}, W_{in})$
- Output: $(N, C_{out}, D_{out}, H_{out}, W_{out})$ where

$$D_{out} = (D_{in} - 1) \times \text{stride}[0] - 2 \times \text{padding}[0] + \text{dilation}[0] \times (\text{kernel_size}[0] - 1) + \text{output_padding}[0] + 1$$

$$H_{out} = (H_{in} - 1) \times \text{stride}[1] - 2 \times \text{padding}[1] + \text{dilation}[1] \times (\text{kernel_size}[1] - 1) + \text{output_padding}[1] + 1$$

$$W_{out} = (W_{in} - 1) \times \text{stride}[2] - 2 \times \text{padding}[2] + \text{dilation}[2] \times (\text{kernel_size}[2] - 1) + \text{output_padding}[2] + 1$$

Attributes

- weight (Tensor): the learnable weights of the module of shape $(\text{in_channels}, \frac{\text{out_channels}}{\text{groups}}, \text{kernel_size}[0], \text{kernel_size}[1], \text{kernel_size}[2])$. The values of these weights are sampled from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{groups}{C_{\text{out}} * \prod_{i=0}^{2} \text{kernel_size}[i]}$
- bias (Tensor): the learnable bias of the module of shape (out_channels) If `bias` is `True`, then the values of these weights are sampled from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{groups}{C_{\text{out}} * \prod_{i=0}^{2} \text{kernel_size}[i]}$

Note

Depending of the size of your kernel, several (of the last) columns of the input might be lost, because it is a valid `cross-correlation`*, and not a full* `cross-correlation`. It is up to the user to add proper padding.

The `padding` argument effectively adds `dilation * (kernel_size - 1) - padding` amount of zero padding to both sizes of the input. This is set so that when a `~torch.nn.Conv3d` and a `~torch.nn.ConvTranspose3d` are initialized with same parameters, they are inverses of each other in regard to the input and output shapes. However, when `stride > 1`, `~torch.nn.Conv3d` maps multiple input shapes to the same output shape. `output_padding` is provided to resolve this ambiguity by effectively increasing the calculated output shape on one side. Note that `output_padding` is only used to find output shape, but does not actually add zero-padding to output.

In some circumstances when using the CUDA backend with CuDNN, this operator may select a nondeterministic algorithm to increase performance. If this is undesirable, you can try to make the operation deterministic (potentially at a performance cost) by setting `torch.backends.cudnn.deterministic = TRUE`.

Examples

```
if (torch_is_installed()) {
## Not run:
# With square kernels and equal stride
m <- nn_conv_transpose3d(16, 33, 3, stride = 2)
# non-square kernels and unequal stride and with padding
m <- nn_conv_transpose3d(16, 33, c(3, 5, 2), stride = c(2, 1, 1), padding = c(0, 4, 2))
input <- torch_randn(20, 16, 10, 50, 100)
output <- m(input)

## End(Not run)
}
```

nn_cosine_embedding_loss *Cosine embedding loss*

Description

Creates a criterion that measures the loss given input tensors x_1, x_2 and a `Tensor` label y with values 1 or -1. This is used for measuring whether two inputs are similar or dissimilar, using the cosine distance, and is typically used for learning nonlinear embeddings or semi-supervised learning. The loss function for each sample is:

Usage

```
nn_cosine_embedding_loss(margin = 0, reduction = "mean")
```

Arguments

`margin`	(float, optional): Should be a number from -1 to 1, 0 to 0.5 is suggested. If `margin` is missing, the default value is 0.
`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.

Details

$$\text{loss}(x, y) = \begin{array}{ll} 1 - \cos(x_1, x_2), & \text{if } y = 1 \\ \max(0, \cos(x_1, x_2) - \text{margin}), & \text{if } y = -1 \end{array}$$

nn_cross_entropy_loss *CrossEntropyLoss module*

Description

This criterion combines `nn_log_softmax()` and `nn_nll_loss()` in one single class. It is useful when training a classification problem with `C` classes.

Usage

```
nn_cross_entropy_loss(weight = NULL, ignore_index = -100, reduction = "mean")
```

Arguments

`weight`	(Tensor, optional): a manual rescaling weight given to each class. If given, has to be a Tensor of size `C`
`ignore_index`	(int, optional): Specifies a target value that is ignored and does not contribute to the input gradient. When `size_average` is `TRUE`, the loss is averaged over non-ignored targets.
`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.

Details

If provided, the optional argument `weight` should be a 1D `Tensor` assigning weight to each of the classes.

This is particularly useful when you have an unbalanced training set. The `input` is expected to contain raw, unnormalized scores for each class. `input` has to be a Tensor of size either $(minibatch, C)$ or $(minibatch, C, d_1, d_2, ..., d_K)$ with $K \geq 1$ for the `K`-dimensional case (described later).

This criterion expects a class index in the range $[0, C-1]$ as the `target` for each value of a 1D tensor of size `minibatch`; if `ignore_index` is specified, this criterion also accepts this class index (this index may not necessarily be in the class range).

The loss can be described as:

$$\text{loss}(x, class) = -\log\left(\frac{\exp(x[class])}{\sum_j \exp(x[j])}\right) = -x[class] + \log\left(\sum_j \exp(x[j])\right)$$

or in the case of the `weight` argument being specified:

$$\text{loss}(x, class) = weight[class]\left(-x[class] + \log\left(\sum_j \exp(x[j])\right)\right)$$

The losses are averaged across observations for each minibatch. Can also be used for higher dimension inputs, such as 2D images, by providing an input of size $(minibatch, C, d_1, d_2, ..., d_K)$ with $K \geq 1$, where K is the number of dimensions, and a target of appropriate shape (see below).

Shape

- Input: (N, C) where `C = number of classes`, or $(N, C, d_1, d_2, ..., d_K)$ with $K \geq 1$ in the case of `K`-dimensional loss.
- Target: (N) where each value is $0 \leq \text{targets}[i] \leq C-1$, or $(N, d_1, d_2, ..., d_K)$ with $K \geq 1$ in the case of K-dimensional loss.
- Output: scalar. If `reduction` is `'none'`, then the same size as the target: (N), or $(N, d_1, d_2, ..., d_K)$ with $K \geq 1$ in the case of K-dimensional loss.

Examples

```
if (torch_is_installed()) {
loss <- nn_cross_entropy_loss()
input <- torch_randn(3, 5, requires_grad = TRUE)
target <- torch_randint(low = 1, high = 5, size = 3, dtype = torch_long())
output <- loss(input, target)
output$backward()
}
```

---

nn_ctc_loss *The Connectionist Temporal Classification loss.*

Description

Calculates loss between a continuous (unsegmented) time series and a target sequence. CTCLoss sums over the probability of possible alignments of input to target, producing a loss value which is differentiable with respect to each input node. The alignment of input to target is assumed to be "many-to-one", which limits the length of the target sequence such that it must be $\leq$ the input length.

Usage

```
nn_ctc_loss(blank = 0, reduction = "mean", zero_infinity = FALSE)
```

Arguments

`blank`	(int, optional): blank label. Default 0.
`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the output losses will be divided by the target lengths and then the mean over the batch is taken. Default: `'mean'`
`zero_infinity`	(bool, optional): Whether to zero infinite losses and the associated gradients. Default: `FALSE` Infinite losses mainly occur when the inputs are too short to be aligned to the targets.

Shape

- Log_probs: Tensor of size (T, N, C), where T = input length, N = batch size, and C = number of classes (including blank). The logarithmized probabilities of the outputs (e.g. obtained with [nnf)log_softmax()]).
- Targets: Tensor of size (N, S) or $(\text{sum}(\text{target_lengths}))$, where N = batch size and S = max target length, if shape is (N, S). It represent the target sequences. Each element in the target sequence is a class index. And the target index cannot be blank (default=0). In the (N, S) form, targets are padded to the length of the longest sequence, and stacked. In the $(\text{sum}(\text{target_lengths}))$ form, the targets are assumed to be un-padded and concatenated within 1 dimension.

- Input_lengths: Tuple or tensor of size (N), where $N =$ batch size. It represent the lengths of the inputs (must each be $\leq T$). And the lengths are specified for each sequence to achieve masking under the assumption that sequences are padded to equal lengths.
- Target_lengths: Tuple or tensor of size (N), where $N =$ batch size. It represent lengths of the targets. Lengths are specified for each sequence to achieve masking under the assumption that sequences are padded to equal lengths. If target shape is (N, S), target_lengths are effectively the stop index s_n for each target sequence, such that `target_n = targets[n,0:s_n]` for each target in a batch. Lengths must each be $\leq S$ If the targets are given as a 1d tensor that is the concatenation of individual targets, the target_lengths must add up to the total length of the tensor.
- Output: scalar. If `reduction` is `'none'`, then (N), where $N =$ batch size.

[nnf)log_softmax()]: R:nnf)log_softmax() [n,0:s_n]: R:n,0:s_n

Note

In order to use CuDNN, the following must be satisfied: `targets` must be in concatenated format, all `input_lengths` must be `T`. $blank = 0$, `target_lengths` ≤ 256, the integer arguments must be of The regular implementation uses the (more common in PyTorch) `torch_long` dtype. dtype `torch_int32`.

In some circumstances when using the CUDA backend with CuDNN, this operator may select a nondeterministic algorithm to increase performance. If this is undesirable, you can try to make the operation deterministic (potentially at a performance cost) by setting `torch.backends.cudnn.deterministic = TRUE`.

References

A. Graves et al.: Connectionist Temporal Classification: Labelling Unsegmented Sequence Data with Recurrent Neural Networks: https://www.cs.toronto.edu/~graves/icml_2006.pdf

Examples

```
if (torch_is_installed()) {
# Target are to be padded
T <- 50 # Input sequence length
C <- 20 # Number of classes (including blank)
N <- 16 # Batch size
S <- 30 # Target sequence length of longest target in batch (padding length)
S_min <- 10 # Minimum target length, for demonstration purposes

# Initialize random batch of input vectors, for *size = (T,N,C)
input <- torch_randn(T, N, C)$log_softmax(2)$detach()$requires_grad_()

# Initialize random batch of targets (0 = blank, 1:C = classes)
target <- torch_randint(low = 1, high = C, size = c(N, S), dtype = torch_long())

input_lengths <- torch_full(size = c(N), fill_value = TRUE, dtype = torch_long())
target_lengths <- torch_randint(low = S_min, high = S, size = c(N), dtype = torch_long())
ctc_loss <- nn_ctc_loss()
loss <- ctc_loss(input, target, input_lengths, target_lengths)
```

```
loss$backward()


# Target are to be un-padded
T <- 50 # Input sequence length
C <- 20 # Number of classes (including blank)
N <- 16 # Batch size

# Initialize random batch of input vectors, for *size = (T,N,C)
input <- torch_randn(T, N, C)$log_softmax(2)$detach()$requires_grad_()
input_lengths <- torch_full(size = c(N), fill_value = TRUE, dtype = torch_long())

# Initialize random batch of targets (0 = blank, 1:C = classes)
target_lengths <- torch_randint(low = 1, high = T, size = c(N), dtype = torch_long())
target <- torch_randint(
  low = 1, high = C, size = as.integer(sum(target_lengths)),
  dtype = torch_long()
)
ctc_loss <- nn_ctc_loss()
loss <- ctc_loss(input, target, input_lengths, target_lengths)
loss$backward()
}
```

---

nn_dropout *Dropout module*

Description

During training, randomly zeroes some of the elements of the input tensor with probability p using samples from a Bernoulli distribution. Each channel will be zeroed out independently on every forward call.

Usage

```
nn_dropout(p = 0.5, inplace = FALSE)
```

Arguments

p	probability of an element to be zeroed. Default: 0.5
inplace	If set to TRUE, will do this operation in-place. Default: FALSE.

Details

This has proven to be an effective technique for regularization and preventing the co-adaptation of neurons as described in the paper Improving neural networks by preventing co-adaptation of feature detectors.

Furthermore, the outputs are scaled by a factor of :math:\frac{1}{1-p} during training. This means that during evaluation the module simply computes an identity function.

Shape

- Input: $(*)$. Input can be of any shape
- Output: $(*)$. Output is of the same shape as input

Examples

```
if (torch_is_installed()) {
m <- nn_dropout(p = 0.2)
input <- torch_randn(20, 16)
output <- m(input)
}
```

---

nn_dropout2d *Dropout2D module*

Description

Randomly zero out entire channels (a channel is a 2D feature map, e.g., the j-th channel of the i-th sample in the batched input is a 2D tensor input$[i, j]$).

Usage

```
nn_dropout2d(p = 0.5, inplace = FALSE)
```

Arguments

p	(float, optional): probability of an element to be zero-ed.
inplace	(bool, optional): If set to TRUE, will do this operation in-place

Details

Each channel will be zeroed out independently on every forward call with probability p using samples from a Bernoulli distribution. Usually the input comes from nn_conv2d modules.

As described in the paper Efficient Object Localization Using Convolutional Networks , if adjacent pixels within feature maps are strongly correlated (as is normally the case in early convolution layers) then i.i.d. dropout will not regularize the activations and will otherwise just result in an effective learning rate decrease. In this case, nn_dropout2d will help promote independence between feature maps and should be used instead.

Shape

- Input: (N, C, H, W)
- Output: (N, C, H, W) (same shape as input)

Examples

```
if (torch_is_installed()) {
m <- nn_dropout2d(p = 0.2)
input <- torch_randn(20, 16, 32, 32)
output <- m(input)
}
```

---

nn_dropout3d *Dropout3D module*

Description

Randomly zero out entire channels (a channel is a 3D feature map, e.g., the j-th channel of the i-th sample in the batched input is a 3D tensor input$[i, j]$).

Usage

```
nn_dropout3d(p = 0.5, inplace = FALSE)
```

Arguments

p	(float, optional): probability of an element to be zeroed.
inplace	(bool, optional): If set to TRUE, will do this operation in-place

Details

Each channel will be zeroed out independently on every forward call with probability p using samples from a Bernoulli distribution. Usually the input comes from nn_conv2d modules.

As described in the paper Efficient Object Localization Using Convolutional Networks , if adjacent pixels within feature maps are strongly correlated (as is normally the case in early convolution layers) then i.i.d. dropout will not regularize the activations and will otherwise just result in an effective learning rate decrease.

In this case, nn_dropout3d will help promote independence between feature maps and should be used instead.

Shape

- Input: (N, C, D, H, W)
- Output: (N, C, D, H, W) (same shape as input)

Examples

```
if (torch_is_installed()) {
m <- nn_dropout3d(p = 0.2)
input <- torch_randn(20, 16, 4, 32, 32)
output <- m(input)
}
```

nn_elu *ELU module*

Description

Applies the element-wise function:

Usage

```
nn_elu(alpha = 1, inplace = FALSE)
```

Arguments

alpha	the α value for the ELU formulation. Default: 1.0
inplace	can optionally do the operation in-place. Default: FALSE

Details

$$\text{ELU}(x) = \max(0, x) + \min(0, \alpha * (\exp(x) - 1))$$

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_elu()
input <- torch_randn(2)
output <- m(input)
}
```

nn_embedding *Embedding module*

Description

A simple lookup table that stores embeddings of a fixed dictionary and size. This module is often used to store word embeddings and retrieve them using indices. The input to the module is a list of indices, and the output is the corresponding word embeddings.

Usage

```
nn_embedding(
  num_embeddings,
  embedding_dim,
  padding_idx = NULL,
  max_norm = NULL,
  norm_type = 2,
  scale_grad_by_freq = FALSE,
  sparse = FALSE,
  .weight = NULL
)
```

Arguments

num_embeddings	(int): size of the dictionary of embeddings
embedding_dim	(int): the size of each embedding vector
padding_idx	(int, optional): If given, pads the output with the embedding vector at padding_idx (initialized to zeros) whenever it encounters the index.
max_norm	(float, optional): If given, each embedding vector with norm larger than max_norm is renormalized to have norm max_norm.
norm_type	(float, optional): The p of the p-norm to compute for the max_norm option. Default 2.
scale_grad_by_freq	(boolean, optional): If given, this will scale gradients by the inverse of frequency of the words in the mini-batch. Default False.
sparse	(bool, optional): If True, gradient w.r.t. weight matrix will be a sparse tensor.
.weight	(Tensor) embeddings weights (in case you want to set it manually) See Notes for more details regarding sparse gradients.

Attributes

- weight (Tensor): the learnable weights of the module of shape (num_embeddings, embedding_dim) initialized from $\mathcal{N}(0, 1)$

Shape

- Input: $(*)$, LongTensor of arbitrary shape containing the indices to extract
- Output: $(*, H)$, where $*$ is the input shape and $H =$ embedding_dim

Note

Keep in mind that only a limited number of optimizers support sparse gradients: currently it's optim.SGD (CUDA and CPU), optim.SparseAdam (CUDA and CPU) and optim.Adagrad (CPU)

With padding_idx set, the embedding vector at padding_idx is initialized to all zeros. However, note that this vector can be modified afterwards, e.g., using a customized initialization method, and thus changing the vector used to pad the output. The gradient for this vector from nn_embedding is always zero.

Examples

```
if (torch_is_installed()) {
# an Embedding module containing 10 tensors of size 3
embedding <- nn_embedding(10, 3)
# a batch of 2 samples of 4 indices each
input <- torch_tensor(rbind(c(1, 2, 4, 5), c(4, 3, 2, 9)), dtype = torch_long())
embedding(input)
# example with padding_idx
embedding <- nn_embedding(10, 3, padding_idx = 1)
input <- torch_tensor(matrix(c(1, 3, 1, 6), nrow = 1), dtype = torch_long())
embedding(input)
}
```

---

nn_embedding_bag *Embedding bag module*

Description

Computes sums, means or maxes of bags of embeddings, without instantiating the intermediate embeddings.

Usage

```
nn_embedding_bag(
  num_embeddings,
  embedding_dim,
  max_norm = NULL,
  norm_type = 2,
  scale_grad_by_freq = FALSE,
  mode = "mean",
  sparse = FALSE,
  include_last_offset = FALSE,
  padding_idx = NULL,
  .weight = NULL
)
```

Arguments

num_embeddings	(int): size of the dictionary of embeddings
embedding_dim	(int): the size of each embedding vector
max_norm	(float, optional): If given, each embedding vector with norm larger than max_norm is renormalized to have norm max_norm.
norm_type	(float, optional): The p of the p-norm to compute for the max_norm option. Default 2
scale_grad_by_freq	(boolean, optional): If given, this will scale gradients by the inverse of frequency of the words in the mini-batch. Default False.

mode	(string, optional): "sum", "mean" or "max". Specifies the way to reduce the bag. "sum" computes the weighted sum, taking per_sample_weights into consideration. "mean" computes the average of the values in the bag, "max" computes the max value over each bag.
sparse	(bool, optional): If True, gradient w.r.t. weight matrix will be a sparse tensor. See Notes for more details regarding sparse gradients.
include_last_offset	(bool, optional): if True, offsets has one additional element, where the last element is equivalent to the size of indices. This matches the CSR format.
padding_idx	(int, optional): If given, pads the output with the embedding vector at padding_idx (initialized to zeros) whenever it encounters the index.
.weight	(Tensor, optional) embeddings weights (in case you want to set it manually)

Attributes

- weight (Tensor): the learnable weights of the module of shape (num_embeddings, embedding_dim) initialized from $\mathcal{N}(0, 1)$

Examples

```
if (torch_is_installed()) {
# an EmbeddingBag module containing 10 tensors of size 3
embedding_sum <- nn_embedding_bag(10, 3, mode = 'sum')
# a batch of 2 samples of 4 indices each
input <- torch_tensor(c(1, 2, 4, 5, 4, 3, 2, 9), dtype = torch_long())
offsets <- torch_tensor(c(0, 4), dtype = torch_long())
embedding_sum(input, offsets)
# example with padding_idx
embedding_sum <- nn_embedding_bag(10, 3, mode = 'sum', padding_idx = 1)
input <- torch_tensor(c(2, 2, 2, 2, 4, 3, 2, 9), dtype = torch_long())
offsets <- torch_tensor(c(0, 4), dtype = torch_long())
embedding_sum(input, offsets)
# An EmbeddingBag can be loaded from an Embedding like so
embedding <- nn_embedding(10, 3, padding_idx = 2)
embedding_sum <- nn_embedding_bag$from_pretrained(embedding$weight,
                                                  padding_idx = embedding$padding_idx,
                                                  mode='sum')
}
```

---

nn_flatten *Flattens a contiguous range of dims into a tensor.*

Description

For use with nn_sequential.

Usage

```
nn_flatten(start_dim = 2, end_dim = -1)
```

Arguments

start_dim	first dim to flatten (default = 2).
end_dim	last dim to flatten (default = -1).

Shape

- Input: (*, S_start,..., S_i, ..., S_end, *), where S_i is the size at dimension i and * means any number of dimensions including none.
- Output: (*, S_start*...*S_i*...S_end, *).

See Also

nn_unflatten

Examples

```
if (torch_is_installed()) {
input <- torch_randn(32, 1, 5, 5)
m <- nn_flatten()
m(input)
}
```

---

nn_fractional_max_pool2d

Applies a 2D fractional max pooling over an input signal composed of several input planes.

Description

Fractional MaxPooling is described in detail in the paper Fractional MaxPooling by Ben Graham

Usage

```
nn_fractional_max_pool2d(
  kernel_size,
  output_size = NULL,
  output_ratio = NULL,
  return_indices = FALSE
)
```

Arguments

kernel_size	the size of the window to take a max over. Can be a single number k (for a square kernel of k x k) or a tuple (kh, kw)
output_size	the target output size of the image of the form oH x oW. Can be a tuple (oH, oW) or a single number oH for a square image oH x oH

output_ratio	If one wants to have an output size as a ratio of the input size, this option can be given. This has to be a number or tuple in the range (0, 1)
return_indices	if TRUE, will return the indices along with the outputs. Useful to pass to nn_max_unpool2d(). Default: FALSE

Details

The max-pooling operation is applied in $kH \times kW$ regions by a stochastic step size determined by the target output size. The number of output features is equal to the number of input planes.

Examples

```
if (torch_is_installed()) {
# pool of square window of size=3, and target output size 13x12
m <- nn_fractional_max_pool2d(3, output_size = c(13, 12))
# pool of square window and target output size being half of input image size
m <- nn_fractional_max_pool2d(3, output_ratio = c(0.5, 0.5))
input <- torch_randn(20, 16, 50, 32)
output <- m(input)
}
```

---

nn_fractional_max_pool3d

Applies a 3D fractional max pooling over an input signal composed of several input planes.

Description

Fractional MaxPooling is described in detail in the paper Fractional MaxPooling by Ben Graham

Usage

```
nn_fractional_max_pool3d(
  kernel_size,
  output_size = NULL,
  output_ratio = NULL,
  return_indices = FALSE
)
```

Arguments

kernel_size	the size of the window to take a max over. Can be a single number k (for a square kernel of k x k x k) or a tuple (kt x kh x kw)
output_size	the target output size of the image of the form oT x oH x oW. Can be a tuple (oT, oH, oW) or a single number oH for a square image oH x oH x oH
output_ratio	If one wants to have an output size as a ratio of the input size, this option can be given. This has to be a number or tuple in the range (0, 1)
return_indices	if TRUE, will return the indices along with the outputs. Useful to pass to nn_max_unpool3d(). Default: FALSE

Details

The max-pooling operation is applied in $kTxkHxkW$ regions by a stochastic step size determined by the target output size. The number of output features is equal to the number of input planes.

Examples

```
if (torch_is_installed()) {
# pool of cubic window of size=3, and target output size 13x12x11
m <- nn_fractional_max_pool3d(3, output_size = c(13, 12, 11))
# pool of cubic window and target output size being half of input size
m <- nn_fractional_max_pool3d(3, output_ratio = c(0.5, 0.5, 0.5))
input <- torch_randn(20, 16, 50, 32, 16)
output <- m(input)
}
```

---

nn_gelu *GELU module*

Description

Applies the Gaussian Error Linear Units function:

$$\text{GELU}(x) = x * \Phi(x)$$

Usage

```
nn_gelu(approximate = "none")
```

Arguments

approximate	the gelu approximation algorithm to use: `'none'` or `'tanh'`. Default: `'none'`.

Details

where $\Phi(x)$ is the Cumulative Distribution Function for Gaussian Distribution.

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_gelu()
input <- torch_randn(2)
output <- m(input)
}
```

nn_glu — *GLU module*

Description

Applies the gated linear unit function $GLU(a, b) = a \otimes \sigma(b)$ where a is the first half of the input matrices and b is the second half.

Usage

```
nn_glu(dim = -1)
```

Arguments

dim	(int): the dimension on which to split the input. Default: -1

Shape

- Input: $(*_1, N, *_2)$ where $*$ means, any number of additional dimensions
- Output: $(*_1, M, *_2)$ where $M = N/2$

Examples

```
if (torch_is_installed()) {
m <- nn_glu()
input <- torch_randn(4, 2)
output <- m(input)
}
```

nn_group_norm — *Group normalization*

Description

Applies Group Normalization over a mini-batch of inputs as described in the paper Group Normalization.

Usage

```
nn_group_norm(num_groups, num_channels, eps = 1e-05, affine = TRUE)
```

Arguments

num_groups	(int): number of groups to separate the channels into
num_channels	(int): number of channels expected in input
eps	a value added to the denominator for numerical stability. Default: 1e-5
affine	a boolean value that when set to TRUE, this module has learnable per-channel affine parameters initialized to ones (for weights) and zeros (for biases). Default: TRUE.

Details

$$y = \frac{x - \mathrm{E}[x]}{\sqrt{\mathrm{Var}[x] + \epsilon}} * \gamma + \beta$$

The input channels are separated into num_groups groups, each containing num_channels / num_groups channels. The mean and standard-deviation are calculated separately over the each group. γ and β are learnable per-channel affine transform parameter vectors of size num_channels if affine is TRUE. The standard-deviation is calculated via the biased estimator, equivalent to torch_var(input, unbiased=FALSE).

Shape

- Input: $(N, C, *)$ where $C =$ num_channels
- Output: $(N, C, *)$‘ (same shape as input)

Note

This layer uses statistics computed from input data in both training and evaluation modes.

Examples

```
if (torch_is_installed()) {

input <- torch_randn(20, 6, 10, 10)
# Separate 6 channels into 3 groups
m <- nn_group_norm(3, 6)
# Separate 6 channels into 6 groups (equivalent with [nn_instance_morm])
m <- nn_group_norm(6, 6)
# Put all 6 channels into a single group (equivalent with [nn_layer_norm])
m <- nn_group_norm(1, 6)
# Activating the module
output <- m(input)
}
```

nn_gru *Applies a multi-layer gated recurrent unit (GRU) RNN to an input sequence.*

Description

For each element in the input sequence, each layer computes the following function:

Usage

```
nn_gru(
  input_size,
  hidden_size,
  num_layers = 1,
  bias = TRUE,
  batch_first = FALSE,
  dropout = 0,
  bidirectional = FALSE,
  ...
)
```

Arguments

input_size	The number of expected features in the input x
hidden_size	The number of features in the hidden state h
num_layers	Number of recurrent layers. E.g., setting num_layers=2 would mean stacking two GRUs together to form a stacked GRU, with the second GRU taking in outputs of the first GRU and computing the final results. Default: 1
bias	If FALSE, then the layer does not use bias weights b_ih and b_hh. Default: TRUE
batch_first	If TRUE, then the input and output tensors are provided as (batch, seq, feature). Default: FALSE
dropout	If non-zero, introduces a Dropout layer on the outputs of each GRU layer except the last layer, with dropout probability equal to dropout. Default: 0
bidirectional	If TRUE, becomes a bidirectional GRU. Default: FALSE
...	currently unused.

Details

$$
\begin{aligned}
r_t &= \sigma(W_{ir}x_t + b_{ir} + W_{hr}h_{(t-1)} + b_{hr}) \\
z_t &= \sigma(W_{iz}x_t + b_{iz} + W_{hz}h_{(t-1)} + b_{hz}) \\
n_t &= \tanh(W_{in}x_t + b_{in} + r_t(W_{hn}h_{(t-1)} + b_{hn})) \\
h_t &= (1 - z_t)n_t + z_t h_{(t-1)}
\end{aligned}
$$

where h_t is the hidden state at time t, x_t is the input at time t, $h_{(t-1)}$ is the hidden state of the previous layer at time t-1 or the initial hidden state at time 0, and r_t, z_t, n_t are the reset, update, and new gates, respectively. σ is the sigmoid function.

Inputs

Inputs: input, h_0

- **input** of shape `(seq_len, batch, input_size)`: tensor containing the features of the input sequence. The input can also be a packed variable length sequence. See `nn_utils_rnn_pack_padded_sequence()` for details.
- **h_0** of shape `(num_layers * num_directions, batch, hidden_size)`: tensor containing the initial hidden state for each element in the batch. Defaults to zero if not provided.

Outputs

Outputs: output, h_n

- **output** of shape `(seq_len, batch, num_directions * hidden_size)`: tensor containing the output features h_t from the last layer of the GRU, for each t. If a `PackedSequence` has been given as the input, the output will also be a packed sequence. For the unpacked case, the directions can be separated using `output$view(c(seq_len, batch, num_directions, hidden_size))`, with forward and backward being direction `0` and `1` respectively. Similarly, the directions can be separated in the packed case.
- **h_n** of shape `(num_layers * num_directions, batch, hidden_size)`: tensor containing the hidden state for `t = seq_len` Like *output*, the layers can be separated using `h_n$view(num_layers, num_directions, batch, hidden_size)`.

Attributes

- `weight_ih_l[k]` : the learnable input-hidden weights of the kth layer (W_ir|W_iz|W_in), of shape `(3*hidden_size x input_size)`
- `weight_hh_l[k]` : the learnable hidden-hidden weights of the kth layer (W_hr|W_hz|W_hn), of shape `(3*hidden_size x hidden_size)`
- `bias_ih_l[k]` : the learnable input-hidden bias of the kth layer (b_ir|b_iz|b_in), of shape `(3*hidden_size)`
- `bias_hh_l[k]` : the learnable hidden-hidden bias of the kth layer (b_hr|b_hz|b_hn), of shape `(3*hidden_size)`

Note

All the weights and biases are initialized from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{1}{\text{hidden_size}}$

Examples

```
if (torch_is_installed()) {

rnn <- nn_gru(10, 20, 2)
input <- torch_randn(5, 3, 10)
h0 <- torch_randn(2, 3, 20)
output <- rnn(input, h0)
}
```

nn_hardshrink *Hardshwink module*

Description

Applies the hard shrinkage function element-wise:

Usage

```
nn_hardshrink(lambd = 0.5)
```

Arguments

lambd	the λ value for the Hardshrink formulation. Default: 0.5

Details

$$\text{HardShrink}(x) = \begin{cases} x, & \text{if } x > \lambda \\ x, & \text{if } x < -\lambda \\ 0, & \text{otherwise} \end{cases}$$

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_hardshrink()
input <- torch_randn(2)
output <- m(input)
}
```

nn_hardsigmoid *Hardsigmoid module*

Description

Applies the element-wise function:

Usage

```
nn_hardsigmoid()
```

Details

$$\text{Hardsigmoid}(x) = \begin{cases} 0 & \text{if } x \leq -3, \\ 1 & \text{if } x \geq +3, \\ x/6 + 1/2 & \text{otherwise} \end{cases}$$

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_hardsigmoid()
input <- torch_randn(2)
output <- m(input)
}
```

---

nn_hardswish *Hardswish module*

Description

Applies the hardswish function, element-wise, as described in the paper: Searching for MobileNetV3

Usage

```
nn_hardswish()
```

Details

$$\text{Hardswish}(x) = \begin{cases} 0 & \text{if } x \leq -3, \\ x & \text{if } x \geq +3, \\ x \cdot (x+3)/6 & \text{otherwise} \end{cases}$$

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
## Not run:
m <- nn_hardswish()
input <- torch_randn(2)
output <- m(input)

## End(Not run)

}
```

---

nn_hardtanh *Hardtanh module*

Description

Applies the HardTanh function element-wise HardTanh is defined as:

Usage

```
nn_hardtanh(min_val = -1, max_val = 1, inplace = FALSE)
```

Arguments

min_val	minimum value of the linear region range. Default: -1
max_val	maximum value of the linear region range. Default: 1
inplace	can optionally do the operation in-place. Default: FALSE

Details

$$\text{HardTanh}(x) = \begin{cases} 1 & \text{if } x > 1 \\ -1 & \text{if } x < -1 \\ x & \text{otherwise} \end{cases}$$

The range of the linear region :math:[-1, 1] can be adjusted using min_val and max_val.

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_hardtanh(-2, 2)
input <- torch_randn(2)
output <- m(input)
}
```

nn_hinge_embedding_loss

Hinge embedding loss

Description

Measures the loss given an input tensor x and a labels tensor y (containing 1 or -1).

Usage

```
nn_hinge_embedding_loss(margin = 1, reduction = "mean")
```

Arguments

`margin`	(float, optional): Has a default value of `1`.
`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.

Details

This is usually used for measuring whether two inputs are similar or dissimilar, e.g. using the L1 pairwise distance as x, and is typically used for learning nonlinear embeddings or semi-supervised learning. The loss function for n-th sample in the mini-batch is

$$l_n = \begin{array}{ll} x_n, & \text{if } y_n = 1, \\ \max\{0, \Delta - x_n\}, & \text{if } y_n = -1, \end{array}$$

and the total loss functions is

$$\ell(x, y) = \begin{array}{ll} \text{mean}(L), & \text{if reduction} = \text{'mean';} \\ \text{sum}(L), & \text{if reduction} = \text{'sum'.} \end{array}$$

where $L = \{l_1, \dots, l_N\}^\top$.

Shape

- Input: $(*)$ where $*$ means, any number of dimensions. The sum operation operates over all the elements.
- Target: $(*)$, same shape as the input
- Output: scalar. If `reduction` is `'none'`, then same shape as the input

nn_identity *Identity module*

Description

A placeholder identity operator that is argument-insensitive.

Usage

```
nn_identity(...)
```

Arguments

...	any arguments (unused)

Examples

```
if (torch_is_installed()) {
m <- nn_identity(54, unused_argument1 = 0.1, unused_argument2 = FALSE)
input <- torch_randn(128, 20)
output <- m(input)
print(output$size())
}
```

nn_init_calculate_gain *Calculate gain*

Description

Return the recommended gain value for the given nonlinearity function.

Usage

```
nn_init_calculate_gain(nonlinearity, param = NULL)
```

Arguments

nonlinearity	the non-linear function
param	optional parameter for the non-linear function

nn_init_constant_ *Constant initialization*

Description

Fills the input Tensor with the value `val`.

Usage

```
nn_init_constant_(tensor, val)
```

Arguments

`tensor`	an n-dimensional `Tensor`
`val`	the value to fill the tensor with

Examples

```
if (torch_is_installed()) {
w <- torch_empty(3, 5)
nn_init_constant_(w, 0.3)
}
```

nn_init_dirac_ *Dirac initialization*

Description

Fills the {3, 4, 5}-dimensional input `Tensor` with the Dirac delta function. Preserves the identity of the inputs in `Convolutional` layers, where as many input channels are preserved as possible. In case of groups>1, each group of channels preserves identity.

Usage

```
nn_init_dirac_(tensor, groups = 1)
```

Arguments

`tensor`	a {3, 4, 5}-dimensional `torch.Tensor`
`groups`	(optional) number of groups in the conv layer (default: 1)

Examples

```
if (torch_is_installed()) {
## Not run:
w <- torch_empty(3, 16, 5, 5)
nn_init_dirac_(w)

## End(Not run)

}
```

`nn_init_eye_` *Eye initialization*

Description

Fills the 2-dimensional input `Tensor` with the identity matrix. Preserves the identity of the inputs in `Linear` layers, where as many inputs are preserved as possible.

Usage

```
nn_init_eye_(tensor)
```

Arguments

`tensor`	a 2-dimensional torch tensor.

Examples

```
if (torch_is_installed()) {
w <- torch_empty(3, 5)
nn_init_eye_(w)
}
```

`nn_init_kaiming_normal_` *Kaiming normal initialization*

Description

Fills the input `Tensor` with values according to the method described in `Delving deep into rectifiers: Surpassing huma` - He, K. et al. (2015), using a normal distribution.

Usage

```
nn_init_kaiming_normal_(
  tensor,
  a = 0,
  mode = "fan_in",
  nonlinearity = "leaky_relu"
)
```

Arguments

tensor	an n-dimensional torch.Tensor
a	the negative slope of the rectifier used after this layer (only used with 'leaky_relu')
mode	either 'fan_in' (default) or 'fan_out'. Choosing 'fan_in' preserves the magnitude of the variance of the weights in the forward pass. Choosing 'fan_out' preserves the magnitudes in the backwards pass.
nonlinearity	the non-linear function. recommended to use only with 'relu' or 'leaky_relu' (default).

Examples

```
if (torch_is_installed()) {
w <- torch_empty(3, 5)
nn_init_kaiming_normal_(w, mode = "fan_in", nonlinearity = "leaky_relu")
}
```

---

nn_init_kaiming_uniform_

Kaiming uniform initialization

Description

Fills the input Tensor with values according to the method described in Delving deep into rectifiers: Surpassing huma - He, K. et al. (2015), using a uniform distribution.

Usage

```
nn_init_kaiming_uniform_(
  tensor,
  a = 0,
  mode = "fan_in",
  nonlinearity = "leaky_relu"
)
```

Arguments

tensor	an n-dimensional torch.Tensor
a	the negative slope of the rectifier used after this layer (only used with 'leaky_relu')
mode	either 'fan_in' (default) or 'fan_out'. Choosing 'fan_in' preserves the magnitude of the variance of the weights in the forward pass. Choosing 'fan_out' preserves the magnitudes in the backwards pass.
nonlinearity	the non-linear function. recommended to use only with 'relu' or 'leaky_relu' (default).

Examples

```
if (torch_is_installed()) {
w <- torch_empty(3, 5)
nn_init_kaiming_uniform_(w, mode = "fan_in", nonlinearity = "leaky_relu")
}
```

---

nn_init_normal_ *Normal initialization*

Description

Fills the input Tensor with values drawn from the normal distribution

Usage

```
nn_init_normal_(tensor, mean = 0, std = 1)
```

Arguments

tensor	an n-dimensional Tensor
mean	the mean of the normal distribution
std	the standard deviation of the normal distribution

Examples

```
if (torch_is_installed()) {
w <- torch_empty(3, 5)
nn_init_normal_(w)
}
```

nn_init_ones_ *Ones initialization*

Description

Fills the input Tensor with the scalar value 1

Usage

```
nn_init_ones_(tensor)
```

Arguments

tensor	an n-dimensional Tensor

Examples

```
if (torch_is_installed()) {
w <- torch_empty(3, 5)
nn_init_ones_(w)
}
```

nn_init_orthogonal_ *Orthogonal initialization*

Description

Fills the input Tensor with a (semi) orthogonal matrix, as described in Exact solutions to the nonlinear dynamics of l - Saxe, A. et al. (2013). The input tensor must have at least 2 dimensions, and for tensors with more than 2 dimensions the trailing dimensions are flattened.

Usage

```
nn_init_orthogonal_(tensor, gain = 1)
```

Arguments

tensor	an n-dimensional Tensor
gain	optional scaling factor

Examples

```
if (torch_is_installed()) {
w <- torch_empty(3, 5)
nn_init_orthogonal_(w)
}
```

nn_init_sparse_ *Sparse initialization*

Description

Fills the 2D input `Tensor` as a sparse matrix, where the non-zero elements will be drawn from the normal distribution as described in `Deep learning via Hessian-free optimization` - Martens, J. (2010).

Usage

```
nn_init_sparse_(tensor, sparsity, std = 0.01)
```

Arguments

`tensor`	an n-dimensional `Tensor`
`sparsity`	The fraction of elements in each column to be set to zero
`std`	the standard deviation of the normal distribution used to generate the non-zero values

Examples

```
if (torch_is_installed()) {
## Not run:
w <- torch_empty(3, 5)
nn_init_sparse_(w, sparsity = 0.1)

## End(Not run)
}
```

nn_init_trunc_normal_ *Truncated normal initialization*

Description

Fills the input Tensor with values drawn from a truncated normal distribution.

Usage

```
nn_init_trunc_normal_(tensor, mean = 0, std = 1, a = -2, b = 2)
```

Arguments

tensor	an n-dimensional Tensor
mean	the mean of the normal distribution
std	the standard deviation of the normal distribution
a	the minimum cutoff value
b	the maximum cutoff value

Examples

```
if (torch_is_installed()) {
w <- torch_empty(3, 5)
nn_init_trunc_normal_(w)
}
```

---

nn_init_uniform_ *Uniform initialization*

Description

Fills the input Tensor with values drawn from the uniform distribution

Usage

```
nn_init_uniform_(tensor, a = 0, b = 1)
```

Arguments

tensor	an n-dimensional Tensor
a	the lower bound of the uniform distribution
b	the upper bound of the uniform distribution

Examples

```
if (torch_is_installed()) {
w <- torch_empty(3, 5)
nn_init_uniform_(w)
}
```

nn_init_xavier_normal_

Xavier normal initialization

Description

Fills the input `Tensor` with values according to the method described in `Understanding the difficulty of training deep` - Glorot, X. & Bengio, Y. (2010), using a normal distribution.

Usage

```
nn_init_xavier_normal_(tensor, gain = 1)
```

Arguments

`tensor`	an n-dimensional `Tensor`
`gain`	an optional scaling factor

Examples

```
if (torch_is_installed()) {
w <- torch_empty(3, 5)
nn_init_xavier_normal_(w)
}
```

nn_init_xavier_uniform_

Xavier uniform initialization

Description

Fills the input `Tensor` with values according to the method described in `Understanding the difficulty of training deep` - Glorot, X. & Bengio, Y. (2010), using a uniform distribution.

Usage

```
nn_init_xavier_uniform_(tensor, gain = 1)
```

Arguments

`tensor`	an n-dimensional `Tensor`
`gain`	an optional scaling factor

Examples

```
if (torch_is_installed()) {
w <- torch_empty(3, 5)
nn_init_xavier_uniform_(w)
}
```

---

nn_init_zeros_ *Zeros initialization*

Description

Fills the input Tensor with the scalar value `0`

Usage

```
nn_init_zeros_(tensor)
```

Arguments

`tensor`	an n-dimensional tensor

Examples

```
if (torch_is_installed()) {
w <- torch_empty(3, 5)
nn_init_zeros_(w)
}
```

---

nn_kl_div_loss *Kullback-Leibler divergence loss*

Description

The Kullback-Leibler divergence loss measure Kullback-Leibler divergence is a useful distance measure for continuous distributions and is often useful when performing direct regression over the space of (discretely sampled) continuous output distributions.

Usage

```
nn_kl_div_loss(reduction = "mean")
```

Arguments

`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'batchmean'` | `'sum'` | `'mean'`. `'none'`: no reduction will be applied. `'batchmean'`: the sum of the output will be divided by batchsize. `'sum'`: the output will be summed. `'mean'`: the output will be divided by the number of elements in the output. Default: `'mean'`

Details

As with nn_nll_loss(), the input given is expected to contain *log-probabilities* and is not restricted to a 2D Tensor.

The targets are interpreted as *probabilities* by default, but could be considered as *log-probabilities* with log_target set to TRUE.

This criterion expects a target Tensor of the same size as the input Tensor.

The unreduced (i.e. with reduction set to 'none') loss can be described as:

$$l(x, y) = L = \{l_1, \dots, l_N\}, \quad l_n = y_n \cdot (\log y_n - x_n)$$

where the index N spans all dimensions of input and L has the same shape as input. If reduction is not 'none' (default 'mean'), then:

$$\ell(x, y) = \begin{array}{ll} \text{mean}(L), & \text{if reduction} = \text{'mean';} \\ \text{sum}(L), & \text{if reduction} = \text{'sum'.} \end{array}$$

In default reduction mode 'mean', the losses are averaged for each minibatch over observations **as well as** over dimensions. 'batchmean' mode gives the correct KL divergence where losses are averaged over batch dimension only. 'mean' mode's behavior will be changed to the same as 'batchmean' in the next major release.

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Target: $(N, *)$, same shape as the input
- Output: scalar by default. If reduction is 'none', then $(N, *)$, the same shape as the input

Note

reduction = 'mean' doesn't return the true kl divergence value, please use reduction = 'batchmean' which aligns with KL math definition. In the next major release, 'mean' will be changed to be the same as 'batchmean'.

---

nn_l1_loss *L1 loss*

Description

Creates a criterion that measures the mean absolute error (MAE) between each element in the input x and target y.

Usage

```
nn_l1_loss(reduction = "mean")
```

Arguments

`reduction` (string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.

Details

The unreduced (i.e. with `reduction` set to `'none'`) loss can be described as:

$$\ell(x, y) = L = \{l_1, \dots, l_N\}^\top, \quad l_n = |x_n - y_n|,$$

where N is the batch size. If `reduction` is not `'none'` (default `'mean'`), then:

$$\ell(x, y) = \begin{array}{ll} \text{mean}(L), & \text{if reduction} = \text{'mean';} \\ \text{sum}(L), & \text{if reduction} = \text{'sum'.} \end{array}$$

x and y are tensors of arbitrary shapes with a total of n elements each.

The sum operation still operates over all the elements, and divides by n. The division by n can be avoided if one sets `reduction = 'sum'`.

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Target: $(N, *)$, same shape as the input
- Output: scalar. If `reduction` is `'none'`, then $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
loss <- nn_l1_loss()
input <- torch_randn(3, 5, requires_grad = TRUE)
target <- torch_randn(3, 5)
output <- loss(input, target)
output$backward()
}
```

---

nn_layer_norm *Layer normalization*

Description

Applies Layer Normalization over a mini-batch of inputs as described in the paper Layer Normalization

Usage

```
nn_layer_norm(normalized_shape, eps = 1e-05, elementwise_affine = TRUE)
```

Arguments

`normalized_shape`
: (int or list): input shape from an expected input of size $[* \times \text{normalized_shape}[0] \times \text{normalized_shape}[1] \times \ldots \times \text{normalized_shape}[-1]]$ If a single integer is used, it is treated as a singleton list, and this module will normalize over the last dimension which is expected to be of that specific size.

`eps`
: a value added to the denominator for numerical stability. Default: 1e-5

`elementwise_affine`
: a boolean value that when set to `TRUE`, this module has learnable per-element affine parameters initialized to ones (for weights) and zeros (for biases). Default: `TRUE`.

Details

$$y = \frac{x - \mathrm{E}[x]}{\sqrt{\mathrm{Var}[x] + \epsilon}} * \gamma + \beta$$

The mean and standard-deviation are calculated separately over the last certain number dimensions which have to be of the shape specified by `normalized_shape`.

γ and β are learnable affine transform parameters of `normalized_shape` if `elementwise_affine` is `TRUE`.

The standard-deviation is calculated via the biased estimator, equivalent to `torch_var(input, unbiased=FALSE)`.

Shape

- Input: $(N, *)$
- Output: $(N, *)$ (same shape as input)

Note

Unlike Batch Normalization and Instance Normalization, which applies scalar scale and bias for each entire channel/plane with the `affine` option, Layer Normalization applies per-element scale and bias with `elementwise_affine`.

This layer uses statistics computed from input data in both training and evaluation modes.

Examples

```
if (torch_is_installed()) {

input <- torch_randn(20, 5, 10, 10)
# With Learnable Parameters
m <- nn_layer_norm(input$size()[-1])
```

```
# Without Learnable Parameters
m <- nn_layer_norm(input$size()[-1], elementwise_affine = FALSE)
# Normalize over last two dimensions
m <- nn_layer_norm(c(10, 10))
# Normalize over last dimension of size 10
m <- nn_layer_norm(10)
# Activating the module
output <- m(input)
}
```

`nn_leaky_relu` *LeakyReLU module*

Description

Applies the element-wise function:

Usage

```
nn_leaky_relu(negative_slope = 0.01, inplace = FALSE)
```

Arguments

`negative_slope`	Controls the angle of the negative slope. Default: 1e-2
`inplace`	can optionally do the operation in-place. Default: `FALSE`

Details

$$\text{LeakyReLU}(x) = \max(0, x) + \text{negative_slope} * \min(0, x)$$

or

$$\text{LeakyRELU}(x) = \begin{cases} x, & \text{if } x \geq 0 \\ \text{negative_slope} \times x, & \text{otherwise} \end{cases}$$

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_leaky_relu(0.1)
input <- torch_randn(2)
output <- m(input)
}
```

nn_linear *Linear module*

Description

Applies a linear transformation to the incoming data: `y = xA^T + b`

Usage

```
nn_linear(in_features, out_features, bias = TRUE)
```

Arguments

`in_features`	size of each input sample
`out_features`	size of each output sample
`bias`	If set to `FALSE`, the layer will not learn an additive bias. Default: `TRUE`

Shape

- Input: `(N, *, H_in)` where `*` means any number of additional dimensions and `H_in = in_features`.
- Output: `(N, *, H_out)` where all but the last dimension are the same shape as the input and :math:`H_out = out_features`.

Attributes

- weight: the learnable weights of the module of shape `(out_features, in_features)`. The values are initialized from $U(-\sqrt{k}, \sqrt{k})$s, where $k = \frac{1}{\text{in_features}}$
- bias: the learnable bias of the module of shape (out_features). If `bias` is `TRUE`, the values are initialized from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{1}{\text{in_features}}$

Examples

```
if (torch_is_installed()) {
m <- nn_linear(20, 30)
input <- torch_randn(128, 20)
output <- m(input)
print(output$size())
}
```

nn_log_sigmoid *LogSigmoid module*

Description

Applies the element-wise function:

$$\text{LogSigmoid}(x) = \log\left(\frac{1}{1+\exp(-x)}\right)$$

Usage

```
nn_log_sigmoid()
```

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_log_sigmoid()
input <- torch_randn(2)
output <- m(input)
}
```

nn_log_softmax *LogSoftmax module*

Description

Applies the $\log(\text{Softmax}(x))$ function to an n-dimensional input Tensor. The LogSoftmax formulation can be simplified as:

Usage

```
nn_log_softmax(dim)
```

Arguments

dim	(int): A dimension along which LogSoftmax will be computed.

Details

$$\text{LogSoftmax}(x_i) = \log\left(\frac{\exp(x_i)}{\sum_j \exp(x_j)}\right)$$

Value

a Tensor of the same dimension and shape as the input with values in the range [-inf, 0)

Shape

- Input: $(*)$ where $*$ means, any number of additional dimensions
- Output: $(*)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_log_softmax(1)
input <- torch_randn(2, 3)
output <- m(input)
}
```

---

nn_lp_pool1d — *Applies a 1D power-average pooling over an input signal composed of several input planes.*

Description

On each window, the function computed is:

Usage

```
nn_lp_pool1d(norm_type, kernel_size, stride = NULL, ceil_mode = FALSE)
```

Arguments

`norm_type`	if inf than one gets max pooling if 0 you get sum pooling (proportional to the avg pooling)
`kernel_size`	a single int, the size of the window
`stride`	a single int, the stride of the window. Default value is `kernel_size`
`ceil_mode`	when TRUE, will use `ceil` instead of `floor` to compute the output shape

Details

$$f(X) = \sqrt[p]{\sum_{x \in X} x^p}$$

- At p = ∞, one gets Max Pooling
- At p = 1, one gets Sum Pooling (which is proportional to Average Pooling)

Shape

- Input: (N, C, L_{in})
- Output: (N, C, L_{out}), where

$$L_{out} = \left\lfloor \frac{L_{in} - \text{kernel_size}}{\text{stride}} + 1 \right\rfloor$$

Note

If the sum to the power of p is zero, the gradient of this function is not defined. This implementation will set the gradient to zero in this case.

Examples

```
if (torch_is_installed()) {
# power-2 pool of window of length 3, with stride 2.
m <- nn_lp_pool1d(2, 3, stride = 2)
input <- torch_randn(20, 16, 50)
output <- m(input)
}
```

---

nn_lp_pool2d — *Applies a 2D power-average pooling over an input signal composed of several input planes.*

Description

On each window, the function computed is:

Usage

```
nn_lp_pool2d(norm_type, kernel_size, stride = NULL, ceil_mode = FALSE)
```

Arguments

norm_type	if inf than one gets max pooling if 0 you get sum pooling (proportional to the avg pooling)
kernel_size	the size of the window
stride	the stride of the window. Default value is kernel_size
ceil_mode	when TRUE, will use ceil instead of floor to compute the output shape

Details

$$f(X) = \sqrt[p]{\sum_{x \in X} x^p}$$

- At p = ∞, one gets Max Pooling
- At p = 1, one gets Sum Pooling (which is proportional to average pooling)

The parameters `kernel_size`, `stride` can either be:

- a single `int` – in which case the same value is used for the height and width dimension
- a `tuple` of two ints – in which case, the first `int` is used for the height dimension, and the second `int` for the width dimension

Shape

- Input: (N, C, H_{in}, W_{in})
- Output: (N, C, H_{out}, W_{out}), where

$$H_{out} = \left\lfloor \frac{H_{in} - \text{kernel_size}[0]}{\text{stride}[0]} + 1 \right\rfloor$$

$$W_{out} = \left\lfloor \frac{W_{in} - \text{kernel_size}[1]}{\text{stride}[1]} + 1 \right\rfloor$$

Note

If the sum to the power of `p` is zero, the gradient of this function is not defined. This implementation will set the gradient to zero in this case.

Examples

```
if (torch_is_installed()) {

# power-2 pool of square window of size=3, stride=2
m <- nn_lp_pool2d(2, 3, stride = 2)
# pool of non-square window of power 1.2
m <- nn_lp_pool2d(1.2, c(3, 2), stride = c(2, 1))
input <- torch_randn(20, 16, 50, 32)
output <- m(input)
}
```

`nn_lstm` *Applies a multi-layer long short-term memory (LSTM) RNN to an input sequence.*

Description

For each element in the input sequence, each layer computes the following function:

Usage

```
nn_lstm(
  input_size,
  hidden_size,
  num_layers = 1,
  bias = TRUE,
  batch_first = FALSE,
  dropout = 0,
  bidirectional = FALSE,
  ...
)
```

Arguments

`input_size`	The number of expected features in the input `x`
`hidden_size`	The number of features in the hidden state `h`
`num_layers`	Number of recurrent layers. E.g., setting `num_layers=2` would mean stacking two LSTMs together to form a `stacked LSTM`, with the second LSTM taking in outputs of the first LSTM and computing the final results. Default: 1
`bias`	If `FALSE`, then the layer does not use bias weights `b_ih` and `b_hh`. Default: `TRUE`
`batch_first`	If `TRUE`, then the input and output tensors are provided as (batch, seq, feature). Default: `FALSE`
`dropout`	If non-zero, introduces a `Dropout` layer on the outputs of each LSTM layer except the last layer, with dropout probability equal to `dropout`. Default: 0
`bidirectional`	If `TRUE`, becomes a bidirectional LSTM. Default: `FALSE`
`...`	currently unused.

Details

$$
\begin{aligned}
i_t &= \sigma(W_{ii}x_t + b_{ii} + W_{hi}h_{(t-1)} + b_{hi}) \\
f_t &= \sigma(W_{if}x_t + b_{if} + W_{hf}h_{(t-1)} + b_{hf}) \\
g_t &= \tanh(W_{ig}x_t + b_{ig} + W_{hg}h_{(t-1)} + b_{hg}) \\
o_t &= \sigma(W_{io}x_t + b_{io} + W_{ho}h_{(t-1)} + b_{ho}) \\
c_t &= f_t c_{(t-1)} + i_t g_t \\
h_t &= o_t \tanh(c_t)
\end{aligned}
$$

where h_t is the hidden state at time `t`, c_t is the cell state at time `t`, x_t is the input at time `t`, $h_{(t-1)}$ is the hidden state of the previous layer at time `t-1` or the initial hidden state at time `0`, and i_t, f_t, g_t, o_t are the input, forget, cell, and output gates, respectively. σ is the sigmoid function.

Inputs

Inputs: input, (h_0, c_0)

- **input** of shape `(seq_len, batch, input_size)`: tensor containing the features of the input sequence. The input can also be a packed variable length sequence. See `nn_utils_rnn_pack_padded_sequence()` or `nn_utils_rnn_pack_sequence()` for details.
- **h_0** of shape `(num_layers * num_directions, batch, hidden_size)`: tensor containing the initial hidden state for each element in the batch.
- **c_0** of shape `(num_layers * num_directions, batch, hidden_size)`: tensor containing the initial cell state for each element in the batch.

If `(h_0, c_0)` is not provided, both **h_0** and **c_0** default to zero.

Outputs

Outputs: output, (h_n, c_n)

- **output** of shape `(seq_len, batch, num_directions * hidden_size)`: tensor containing the output features `(h_t)` from the last layer of the LSTM, for each t. If a `torch_nn.utils.rnn.PackedSequence` has been given as the input, the output will also be a packed sequence. For the unpacked case, the directions can be separated using `output$view(c(seq_len, batch, num_directions, hidden_size))`, with forward and backward being direction `0` and `1` respectively. Similarly, the directions can be separated in the packed case.
- **h_n** of shape `(num_layers * num_directions, batch, hidden_size)`: tensor containing the hidden state for `t = seq_len`. Like *output*, the layers can be separated using `h_n$view(c(num_layers, num_directions, batch, hidden_size))` and similarly for *c_n*.
- **c_n** (num_layers * num_directions, batch, hidden_size): tensor containing the cell state for `t = seq_len`

Attributes

- `weight_ih_l[k]` : the learnable input-hidden weights of the kth layer `(W_ii|W_if|W_ig|W_io)`, of shape `(4*hidden_size x input_size)`
- `weight_hh_l[k]` : the learnable hidden-hidden weights of the kth layer `(W_hi|W_hf|W_hg|W_ho)`, of shape `(4*hidden_size x hidden_size)`
- `bias_ih_l[k]` : the learnable input-hidden bias of the kth layer `(b_ii|b_if|b_ig|b_io)`, of shape `(4*hidden_size)`
- `bias_hh_l[k]` : the learnable hidden-hidden bias of the kth layer `(b_hi|b_hf|b_hg|b_ho)`, of shape `(4*hidden_size)`

Note

All the weights and biases are initialized from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{1}{\text{hidden_size}}$

Examples

```
if (torch_is_installed()) {
rnn <- nn_lstm(10, 20, 2)
input <- torch_randn(5, 3, 10)
h0 <- torch_randn(2, 3, 20)
c0 <- torch_randn(2, 3, 20)
output <- rnn(input, list(h0, c0))
}
```

---

nn_margin_ranking_loss

Margin ranking loss

Description

Creates a criterion that measures the loss given inputs $x1$, $x2$, two 1D mini-batch `Tensors`, and a label 1D mini-batch tensor y (containing 1 or -1). If $y = 1$ then it assumed the first input should be ranked higher (have a larger value) than the second input, and vice-versa for $y = -1$.

Usage

```
nn_margin_ranking_loss(margin = 0, reduction = "mean")
```

Arguments

`margin`	(float, optional): Has a default value of 0.
`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.

Details

The loss function for each pair of samples in the mini-batch is:

$$\text{loss}(x1, x2, y) = \max(0, -y * (x1 - x2) + \text{margin})$$

Shape

- Input1: (N) where `N` is the batch size.
- Input2: (N), same shape as the Input1.
- Target: (N), same shape as the inputs.
- Output: scalar. If `reduction` is `'none'`, then (N).

Examples

```
if (torch_is_installed()) {
loss <- nn_margin_ranking_loss()
input1 <- torch_randn(3, requires_grad = TRUE)
input2 <- torch_randn(3, requires_grad = TRUE)
target <- torch_randn(3)$sign()
output <- loss(input1, input2, target)
output$backward()
}
```

---

nn_max_pool1d *MaxPool1D module*

Description

Applies a 1D max pooling over an input signal composed of several input planes.

Usage

```
nn_max_pool1d(
  kernel_size,
  stride = NULL,
  padding = 0,
  dilation = 1,
  return_indices = FALSE,
  ceil_mode = FALSE
)
```

Arguments

kernel_size	the size of the window to take a max over
stride	the stride of the window. Default value is kernel_size
padding	implicit zero padding to be added on both sides
dilation	a parameter that controls the stride of elements in the window
return_indices	if TRUE, will return the max indices along with the outputs. Useful for nn_max_unpool1d() later.
ceil_mode	when TRUE, will use ceil instead of floor to compute the output shape

Details

In the simplest case, the output value of the layer with input size (N, C, L) and output (N, C, L_{out}) can be precisely described as:

$$out(N_i, C_j, k) = \max_{m=0,\ldots,\text{kernel_size}-1} input(N_i, C_j, stride \times k + m)$$

If padding is non-zero, then the input is implicitly zero-padded on both sides for padding number of points. dilation controls the spacing between the kernel points. It is harder to describe, but this link has a nice visualization of what dilation does.

Shape

- Input: (N, C, L_{in})
- Output: (N, C, L_{out}), where

$$L_{out} = \left\lfloor \frac{L_{in} + 2 \times \text{padding} - \text{dilation} \times (\text{kernel_size} - 1) - 1}{\text{stride}} + 1 \right\rfloor$$

Examples

```
if (torch_is_installed()) {
# pool of size=3, stride=2
m <- nn_max_pool1d(3, stride = 2)
input <- torch_randn(20, 16, 50)
output <- m(input)
}
```

---

nn_max_pool2d *MaxPool2D module*

Description

Applies a 2D max pooling over an input signal composed of several input planes.

Usage

```
nn_max_pool2d(
  kernel_size,
  stride = NULL,
  padding = 0,
  dilation = 1,
  return_indices = FALSE,
  ceil_mode = FALSE
)
```

Arguments

kernel_size	the size of the window to take a max over
stride	the stride of the window. Default value is kernel_size
padding	implicit zero padding to be added on both sides
dilation	a parameter that controls the stride of elements in the window
return_indices	if TRUE, will return the max indices along with the outputs. Useful for nn_max_unpool2d() later.
ceil_mode	when TRUE, will use ceil instead of floor to compute the output shape

Details

In the simplest case, the output value of the layer with input size (N, C, H, W), output (N, C, H_{out}, W_{out}) and `kernel_size` (kH, kW) can be precisely described as:

$$\begin{aligned} out(N_i, C_j, h, w) = \quad & \max_{m=0,\ldots,kH-1} \max_{n=0,\ldots,kW-1} \\ & \text{input}(N_i, C_j, \text{stride}[0] \times h + m, \text{stride}[1] \times w + n) \end{aligned}$$

If `padding` is non-zero, then the input is implicitly zero-padded on both sides for `padding` number of points. `dilation` controls the spacing between the kernel points. It is harder to describe, but this `link` has a nice visualization of what `dilation` does.

The parameters `kernel_size`, `stride`, `padding`, `dilation` can either be:

- a single `int` – in which case the same value is used for the height and width dimension
- a `tuple` of two ints – in which case, the first `int` is used for the height dimension, and the second `int` for the width dimension

Shape

- Input: (N, C, H_{in}, W_{in})
- Output: (N, C, H_{out}, W_{out}), where

$$H_{out} = \left\lfloor \frac{H_{in} + 2 * \text{padding}[0] - \text{dilation}[0] \times (\text{kernel_size}[0] - 1) - 1}{\text{stride}[0]} + 1 \right\rfloor$$

$$W_{out} = \left\lfloor \frac{W_{in} + 2 * \text{padding}[1] - \text{dilation}[1] \times (\text{kernel_size}[1] - 1) - 1}{\text{stride}[1]} + 1 \right\rfloor$$

Examples

```
if (torch_is_installed()) {
# pool of square window of size=3, stride=2
m <- nn_max_pool2d(3, stride = 2)
# pool of non-square window
m <- nn_max_pool2d(c(3, 2), stride = c(2, 1))
input <- torch_randn(20, 16, 50, 32)
output <- m(input)
}
```

`nn_max_pool3d` *Applies a 3D max pooling over an input signal composed of several input planes.*

Description

In the simplest case, the output value of the layer with input size (N, C, D, H, W), output $(N, C, D_{out}, H_{out}, W_{out})$ and `kernel_size` (kD, kH, kW) can be precisely described as:

Usage

```
nn_max_pool3d(
  kernel_size,
  stride = NULL,
  padding = 0,
  dilation = 1,
  return_indices = FALSE,
  ceil_mode = FALSE
)
```

Arguments

`kernel_size`	the size of the window to take a max over
`stride`	the stride of the window. Default value is `kernel_size`
`padding`	implicit zero padding to be added on all three sides
`dilation`	a parameter that controls the stride of elements in the window
`return_indices`	if `TRUE`, will return the max indices along with the outputs. Useful for `torch_nn.MaxUnpool3d` later
`ceil_mode`	when TRUE, will use `ceil` instead of `floor` to compute the output shape

Details

$$\begin{aligned}\text{out}(N_i, C_j, d, h, w) = \quad & \max_{k=0,\ldots,kD-1} \max_{m=0,\ldots,kH-1} \max_{n=0,\ldots,kW-1} \\ & \text{input}(N_i, C_j, \text{stride}[0] \times d + k, \text{stride}[1] \times h + m, \text{stride}[2] \times w + n)\end{aligned}$$

If `padding` is non-zero, then the input is implicitly zero-padded on both sides for `padding` number of points. `dilation` controls the spacing between the kernel points. It is harder to describe, but this `link_` has a nice visualization of what `dilation` does. The parameters `kernel_size`, `stride`, `padding`, `dilation` can either be:

- a single `int` – in which case the same value is used for the depth, height and width dimension
- a `tuple` of three ints – in which case, the first `int` is used for the depth dimension, the second `int` for the height dimension and the third `int` for the width dimension

Shape

- Input: $(N, C, D_{in}, H_{in}, W_{in})$
- Output: $(N, C, D_{out}, H_{out}, W_{out})$, where

$$D_{out} = \left\lfloor \frac{D_{in} + 2 \times \text{padding}[0] - \text{dilation}[0] \times (\text{kernel_size}[0] - 1) - 1}{\text{stride}[0]} + 1 \right\rfloor$$

$$H_{out} = \left\lfloor \frac{H_{in} + 2 \times \text{padding}[1] - \text{dilation}[1] \times (\text{kernel_size}[1] - 1) - 1}{\text{stride}[1]} + 1 \right\rfloor$$

$$W_{out} = \left\lfloor \frac{W_{in} + 2 \times \text{padding}[2] - \text{dilation}[2] \times (\text{kernel_size}[2] - 1) - 1}{\text{stride}[2]} + 1 \right\rfloor$$

Examples

```
if (torch_is_installed()) {
# pool of square window of size=3, stride=2
m <- nn_max_pool3d(3, stride = 2)
# pool of non-square window
m <- nn_max_pool3d(c(3, 2, 2), stride = c(2, 1, 2))
input <- torch_randn(20, 16, 50, 44, 31)
output <- m(input)
}
```

---

nn_max_unpool1d *Computes a partial inverse of* MaxPool1d.

Description

MaxPool1d is not fully invertible, since the non-maximal values are lost. MaxUnpool1d takes in as input the output of MaxPool1d including the indices of the maximal values and computes a partial inverse in which all non-maximal values are set to zero.

Usage

```
nn_max_unpool1d(kernel_size, stride = NULL, padding = 0)
```

Arguments

kernel_size	(int or tuple): Size of the max pooling window.
stride	(int or tuple): Stride of the max pooling window. It is set to kernel_size by default.
padding	(int or tuple): Padding that was added to the input

Inputs

- input: the input Tensor to invert
- indices: the indices given out by nn_max_pool1d()
- output_size (optional): the targeted output size

Shape

- Input: (N, C, H_{in})
- Output: (N, C, H_{out}), where

$$H_{out} = (H_{in} - 1) \times \text{stride}[0] - 2 \times \text{padding}[0] + \text{kernel_size}[0]$$

  or as given by output_size in the call operator

Note

MaxPool1d can map several input sizes to the same output sizes. Hence, the inversion process can get ambiguous. To accommodate this, you can provide the needed output size as an additional argument output_size in the forward call. See the Inputs and Example below.

Examples

```
if (torch_is_installed()) {
pool <- nn_max_pool1d(2, stride = 2, return_indices = TRUE)
unpool <- nn_max_unpool1d(2, stride = 2)

input <- torch_tensor(array(1:8 / 1, dim = c(1, 1, 8)))
out <- pool(input)
unpool(out[[1]], out[[2]])

# Example showcasing the use of output_size
input <- torch_tensor(array(1:8 / 1, dim = c(1, 1, 8)))
out <- pool(input)
unpool(out[[1]], out[[2]], output_size = input$size())
unpool(out[[1]], out[[2]])
}
```

---

nn_max_unpool2d *Computes a partial inverse of* MaxPool2d.

Description

MaxPool2d is not fully invertible, since the non-maximal values are lost. MaxUnpool2d takes in as input the output of MaxPool2d including the indices of the maximal values and computes a partial inverse in which all non-maximal values are set to zero.

Usage

```
nn_max_unpool2d(kernel_size, stride = NULL, padding = 0)
```

Arguments

kernel_size	(int or tuple): Size of the max pooling window.
stride	(int or tuple): Stride of the max pooling window. It is set to kernel_size by default.
padding	(int or tuple): Padding that was added to the input

Inputs

- input: the input Tensor to invert
- indices: the indices given out by nn_max_pool2d()
- output_size (optional): the targeted output size

Shape

- Input: (N, C, H_{in}, W_{in})
- Output: (N, C, H_{out}, W_{out}), where

$$H_{out} = (H_{in} - 1) \times \text{stride}[0] - 2 \times \text{padding}[0] + \text{kernel_size}[0]$$

$$W_{out} = (W_{in} - 1) \times \text{stride}[1] - 2 \times \text{padding}[1] + \text{kernel_size}[1]$$

  or as given by `output_size` in the call operator

Note

`MaxPool2d` can map several input sizes to the same output sizes. Hence, the inversion process can get ambiguous. To accommodate this, you can provide the needed output size as an additional argument `output_size` in the forward call. See the Inputs and Example below.

Examples

```
if (torch_is_installed()) {

pool <- nn_max_pool2d(2, stride = 2, return_indices = TRUE)
unpool <- nn_max_unpool2d(2, stride = 2)
input <- torch_randn(1, 1, 4, 4)
out <- pool(input)
unpool(out[[1]], out[[2]])

# specify a different output size than input size
unpool(out[[1]], out[[2]], output_size = c(1, 1, 5, 5))
}
```

---

nn_max_unpool3d *Computes a partial inverse of* `MaxPool3d`.

Description

`MaxPool3d` is not fully invertible, since the non-maximal values are lost. `MaxUnpool3d` takes in as input the output of `MaxPool3d` including the indices of the maximal values and computes a partial inverse in which all non-maximal values are set to zero.

Usage

```
nn_max_unpool3d(kernel_size, stride = NULL, padding = 0)
```

Arguments

`kernel_size`	(int or tuple): Size of the max pooling window.
`stride`	(int or tuple): Stride of the max pooling window. It is set to `kernel_size` by default.
`padding`	(int or tuple): Padding that was added to the input

Inputs

- `input`: the input Tensor to invert
- `indices`: the indices given out by `nn_max_pool3d()`
- `output_size` (optional): the targeted output size

Shape

- Input: $(N, C, D_{in}, H_{in}, W_{in})$
- Output: $(N, C, D_{out}, H_{out}, W_{out})$, where

$$D_{out} = (D_{in} - 1) \times \text{stride}[0] - 2 \times \text{padding}[0] + \text{kernel_size}[0]$$

$$H_{out} = (H_{in} - 1) \times \text{stride}[1] - 2 \times \text{padding}[1] + \text{kernel_size}[1]$$

$$W_{out} = (W_{in} - 1) \times \text{stride}[2] - 2 \times \text{padding}[2] + \text{kernel_size}[2]$$

or as given by `output_size` in the call operator

Note

`MaxPool3d` can map several input sizes to the same output sizes. Hence, the inversion process can get ambiguous. To accommodate this, you can provide the needed output size as an additional argument `output_size` in the forward call. See the Inputs section below.

Examples

```
if (torch_is_installed()) {

# pool of square window of size=3, stride=2
pool <- nn_max_pool3d(3, stride = 2, return_indices = TRUE)
unpool <- nn_max_unpool3d(3, stride = 2)
out <- pool(torch_randn(20, 16, 51, 33, 15))
unpooled_output <- unpool(out[[1]], out[[2]])
unpooled_output$size()
}
```

---

nn_module *Base class for all neural network modules.*

Description

Your models should also subclass this class.

Usage

```
nn_module(
  classname = NULL,
  inherit = nn_Module,
  ...,
  private = NULL,
  active = NULL,
  parent_env = parent.frame()
)
```

Arguments

classname	an optional name for the module
inherit	an optional module to inherit from
...	methods implementation
private	passed to R6::R6Class().
active	passed to R6::R6Class().
parent_env	passed to R6::R6Class().

Details

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes.

You are expected to implement the `initialize` and the `forward` to create a new `nn_module`.

Initialize

The initialize function will be called whenever a new instance of the `nn_module` is created. We use the initialize functions to define submodules and parameters of the module. For example:

```
initialize = function(input_size, output_size) {
   self$conv1 <- nn_conv2d(input_size, output_size, 5)
   self$conv2 <- nn_conv2d(output_size, output_size, 5)
}
```

The initialize function can have any number of parameters. All objects assigned to `self$` will be available for other methods that you implement. Tensors wrapped with `nn_parameter()` or `nn_buffer()` and submodules are automatically tracked when assigned to `self$`.

The initialize function is optional if the module you are defining doesn't have weights, submodules or buffers.

Forward

The forward method is called whenever an instance of `nn_module` is called. This is usually used to implement the computation that the module does with the weights ad submodules defined in the `initialize` function.

For example:

```
forward = function(input) {
   input <- self$conv1(input)
   input <- nnf_relu(input)
   input <- self$conv2(input)
   input <- nnf_relu(input)
   input
 }
```

The `forward` function can use the `self$training` attribute to make different computations depending wether the model is training or not, for example if you were implementing the dropout module.

Cloning

To finalize the cloning of a module, you can define a private `finalize_deep_clone()` method. This method is called on the cloned object when deep-cloning a module, after all the modules, parameters and buffers were already cloned.

Examples

```
if (torch_is_installed()) {
model <- nn_module(
  initialize = function() {
    self$conv1 <- nn_conv2d(1, 20, 5)
    self$conv2 <- nn_conv2d(20, 20, 5)
  },
  forward = function(input) {
    input <- self$conv1(input)
    input <- nnf_relu(input)
    input <- self$conv2(input)
    input <- nnf_relu(input)
    input
  }
)
}
```

---

nn_module_dict *Container that allows named values*

Description

Container that allows named values

Usage

```
nn_module_dict(dict)
```

Arguments

`dict`	A named list of submodules that will be saved in that module.

See Also

nn_module_list()

Examples

```
if (torch_is_installed()) {
nn_module <- nn_module(
  initialize = function() {
    self$dict <- nn_module_dict(list(
      l1 = nn_linear(10, 20),
      l2 = nn_linear(20, 10)
    ))
  },
  forward = function(x) {
    x <- self$dict$l1(x)
    self$dict$l2(x)
  }
)
}
```

---

nn_module_list *Holds submodules in a list.*

Description

nn_module_list can be indexed like a regular R list, but modules it contains are properly registered, and will be visible by all nn_module methods.

Usage

```
nn_module_list(modules = list())
```

Arguments

modules	a list of modules to add

See Also

nn_module_dict()

Examples

```
if (torch_is_installed()) {

my_module <- nn_module(
  initialize = function() {
    self$linears <- nn_module_list(lapply(1:10, function(x) nn_linear(10, 10)))
  },
  forward = function(x) {
```

```
    for (i in 1:length(self$linears)) {
      x <- self$linears[[i]](x)
    }
    x
  }
)
}
```

---

nn_mse_loss *MSE loss*

Description

Creates a criterion that measures the mean squared error (squared L2 norm) between each element in the input x and target y. The unreduced (i.e. with `reduction` set to `'none'`) loss can be described as:

Usage

```
nn_mse_loss(reduction = "mean")
```

Arguments

`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.

Details

$$\ell(x, y) = L = \{l_1, \dots, l_N\}^\top, \quad l_n = \left(x_n - y_n\right)^2,$$

where N is the batch size. If `reduction` is not `'none'` (default `'mean'`), then:

$$\ell(x, y) = \begin{array}{ll} \text{mean}(L), & \text{if reduction} = \text{'mean';} \\ \text{sum}(L), & \text{if reduction} = \text{'sum'.} \end{array}$$

x and y are tensors of arbitrary shapes with a total of n elements each.

The mean operation still operates over all the elements, and divides by n. The division by n can be avoided if one sets `reduction = 'sum'`.

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Target: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
loss <- nn_mse_loss()
input <- torch_randn(3, 5, requires_grad = TRUE)
target <- torch_randn(3, 5)
output <- loss(input, target)
output$backward()
}
```

---

nn_multihead_attention

MultiHead attention

Description

Allows the model to jointly attend to information from different representation subspaces. See reference: Attention Is All You Need

Usage

```
nn_multihead_attention(
  embed_dim,
  num_heads,
  dropout = 0,
  bias = TRUE,
  add_bias_kv = FALSE,
  add_zero_attn = FALSE,
  kdim = NULL,
  vdim = NULL,
  batch_first = FALSE
)
```

Arguments

embed_dim	total dimension of the model.
num_heads	parallel attention heads. Note that embed_dim will be split across num_heads (i.e. each head will have dimension embed_dim %/% num_heads).
dropout	a Dropout layer on attn_output_weights. Default: 0.0.
bias	add bias as module parameter. Default: True.
add_bias_kv	add bias to the key and value sequences at dim=0.
add_zero_attn	add a new batch of zeros to the key and value sequences at dim=1.
kdim	total number of features in key. Default: NULL
vdim	total number of features in value. Default: NULL. Note: if kdim and vdim are NULL, they will be set to embed_dim such that query, key, and value have the same number of features.

batch_first — if TRUE then the input and output tensors are (N, S, E) instead of (S, N, E), where N is the batch size, S is the sequence length, and E is the embedding dimension.

Details

$$\text{MultiHead}(Q, K, V) = \text{Concat}(head_1, \ldots, head_h)W^O \text{where} head_i = \text{Attention}(QW_i^Q, KW_i^K, VW_i^V)$$

Shape

Inputs:

- query: (L, N, E) where L is the target sequence length, N is the batch size, E is the embedding dimension. (but see the `batch_first` argument)
- key: (S, N, E), where S is the source sequence length, N is the batch size, E is the embedding dimension. (but see the `batch_first` argument)
- value: (S, N, E) where S is the source sequence length, N is the batch size, E is the embedding dimension. (but see the `batch_first` argument)
- key_padding_mask: (N, S) where N is the batch size, S is the source sequence length. If a ByteTensor is provided, the non-zero positions will be ignored while the position with the zero positions will be unchanged. If a BoolTensor is provided, the positions with the value of `True` will be ignored while the position with the value of `False` will be unchanged.
- attn_mask: 2D mask (L, S) where L is the target sequence length, S is the source sequence length. 3D mask $(N * num_heads, L, S)$ where N is the batch size, L is the target sequence length, S is the source sequence length. attn_mask ensure that position i is allowed to attend the unmasked positions. If a ByteTensor is provided, the non-zero positions are not allowed to attend while the zero positions will be unchanged. If a BoolTensor is provided, positions with `True` are not allowed to attend while `False` values will be unchanged. If a FloatTensor is provided, it will be added to the attention weight.

Outputs:

- attn_output: (L, N, E) where L is the target sequence length, N is the batch size, E is the embedding dimension. (but see the `batch_first` argument)
- attn_output_weights:
  - if `avg_weights` is `TRUE` (the default), the output attention weights are averaged over the attention heads, giving a tensor of shape (N, L, S) where N is the batch size, L is the target sequence length, S is the source sequence length.
  - if `avg_weights` is `FALSE`, the attention weight tensor is output as-is, with shape (N, H, L, S), where H is the number of attention heads.

Examples

```
if (torch_is_installed()) {
## Not run:
multihead_attn <- nn_multihead_attention(embed_dim, num_heads)
out <- multihead_attn(query, key, value)
```

```
attn_output <- out[[1]]
attn_output_weights <- out[[2]]

## End(Not run)

}
```

---

nn_multilabel_margin_loss
Multilabel margin loss

Description

Creates a criterion that optimizes a multi-class multi-classification hinge loss (margin-based loss) between input x (a 2D mini-batch `Tensor`) and output y (which is a 2D `Tensor` of target class indices). For each sample in the mini-batch:

Usage

```
nn_multilabel_margin_loss(reduction = "mean")
```

Arguments

`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.

Details

$$\text{loss}(x, y) = \sum_{ij} \frac{\max(0, 1 - (x[y[j]] - x[i]))}{\text{x.size}(0)}$$

where $x \in \{0, \cdots, \text{x.size}(0) - 1\}$, \ $y \in \{0, \cdots, \text{y.size}(0) - 1\}$, \ $0 \leq y[j] \leq \text{x.size}(0) - 1$, \ and $i \neq y[j]$ for all i and j. y and x must have the same size.

The criterion only considers a contiguous block of non-negative targets that starts at the front. This allows for different samples to have variable amounts of target classes.

Shape

- Input: (C) or (N, C) where `N` is the batch size and `C` is the number of classes.
- Target: (C) or (N, C), label targets padded by -1 ensuring same shape as the input.
- Output: scalar. If `reduction` is `'none'`, then (N).

Examples

```
if (torch_is_installed()) {
loss <- nn_multilabel_margin_loss()
x <- torch_tensor(c(0.1, 0.2, 0.4, 0.8))$view(c(1, 4))
# for target y, only consider labels 4 and 1, not after label -1
y <- torch_tensor(c(4, 1, -1, 2), dtype = torch_long())$view(c(1, 4))
loss(x, y)
}
```

---

nn_multilabel_soft_margin_loss

Multi label soft margin loss

Description

Creates a criterion that optimizes a multi-label one-versus-all loss based on max-entropy, between input x and target y of size (N, C).

Usage

```
nn_multilabel_soft_margin_loss(weight = NULL, reduction = "mean")
```

Arguments

`weight`	(Tensor, optional): a manual rescaling weight given to each class. If given, it has to be a Tensor of size `C`. Otherwise, it is treated as if having all ones.
`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.

Details

For each sample in the minibatch:

$$loss(x, y) = -\frac{1}{C} * \sum_i y[i] * \log((1 + \exp(-x[i]))^{-1}) + (1 - y[i]) * \log\left(\frac{\exp(-x[i])}{(1 + \exp(-x[i]))}\right)$$

where $i \in \{0, \cdots, \text{x.nElement}() - 1\}$, $y[i] \in \{0, 1\}$.

Shape

- Input: (N, C) where `N` is the batch size and `C` is the number of classes.
- Target: (N, C), label targets padded by -1 ensuring same shape as the input.
- Output: scalar. If `reduction` is `'none'`, then (N).

nn_multi_margin_loss *Multi margin loss*

Description

Creates a criterion that optimizes a multi-class classification hinge loss (margin-based loss) between input x (a 2D mini-batch `Tensor`) and output y (which is a 1D tensor of target class indices, $0 \leq y \leq \text{x.size}(1) - 1$):

Usage

```
nn_multi_margin_loss(p = 1, margin = 1, weight = NULL, reduction = "mean")
```

Arguments

`p`	(int, optional): Has a default value of 1. 1 and 2 are the only supported values.
`margin`	(float, optional): Has a default value of 1.
`weight`	(Tensor, optional): a manual rescaling weight given to each class. If given, it has to be a Tensor of size `C`. Otherwise, it is treated as if having all ones.
`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.

Details

For each mini-batch sample, the loss in terms of the 1D input x and scalar output y is:

$$\text{loss}(x, y) = \frac{\sum_i \max(0, \text{margin} - x[y] + x[i]))^p}{\text{x.size}(0)}$$

where $x \in \{0, \cdots, \text{x.size}(0) - 1\}$ and $i \neq y$.

Optionally, you can give non-equal weighting on the classes by passing a 1D `weight` tensor into the constructor. The loss function then becomes:

$$\text{loss}(x, y) = \frac{\sum_i \max(0, w[y] * (\text{margin} - x[y] + x[i]))^p)}{\text{x.size}(0)}$$

`nn_nll_loss` *Nll loss*

Description

The negative log likelihood loss. It is useful to train a classification problem with `C` classes.

Usage

```
nn_nll_loss(weight = NULL, ignore_index = -100, reduction = "mean")
```

Arguments

`weight`	(Tensor, optional): a manual rescaling weight given to each class. If given, it has to be a Tensor of size `C`. Otherwise, it is treated as if having all ones.
`ignore_index`	(int, optional): Specifies a target value that is ignored and does not contribute to the input gradient.
`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the weighted mean of the output is taken, `'sum'`: the output will be summed.

Details

If provided, the optional argument `weight` should be a 1D Tensor assigning weight to each of the classes. This is particularly useful when you have an unbalanced training set.

The `input` given through a forward call is expected to contain log-probabilities of each class. `input` has to be a Tensor of size either $(minibatch, C)$ or $(minibatch, C, d_1, d_2, ..., d_K)$ with $K \geq 1$ for the `K`-dimensional case (described later).

Obtaining log-probabilities in a neural network is easily achieved by adding a `LogSoftmax` layer in the last layer of your network.

You may use `CrossEntropyLoss` instead, if you prefer not to add an extra layer.

The `target` that this loss expects should be a class index in the range $[0, C-1]$ where `C = number of classes`; if `ignore_index` is specified, this loss also accepts this class index (this index may not necessarily be in the class range).

The unreduced (i.e. with `reduction` set to `'none'`) loss can be described as:

$$\ell(x, y) = L = \{l_1, \dots, l_N\}^\top, \quad l_n = -w_{y_n} x_{n,y_n}, \quad w_c = \text{weight}[c] \cdot 1\{c \neq \text{ignore_index}\},$$

where x is the input, y is the target, w is the weight, and N is the batch size. If `reduction` is not `'none'` (default `'mean'`), then

$$\ell(x, y) = \begin{array}{ll} \sum_{n=1}^{N} \frac{1}{\sum_{n=1}^{N} w_{y_n}} l_n, & \text{if reduction} = \text{'mean'}; \\ \sum_{n=1}^{N} l_n, & \text{if reduction} = \text{'sum'}. \end{array}$$

Can also be used for higher dimension inputs, such as 2D images, by providing an input of size $(minibatch, C, d_1, d_2, ..., d_K)$ with $K \geq 1$, where K is the number of dimensions, and a target of appropriate shape (see below). In the case of images, it computes NLL loss per-pixel.

Shape

- Input: (N, C) where `C = number of classes`, or $(N, C, d_1, d_2, ..., d_K)$ with $K \geq 1$ in the case of `K`-dimensional loss.
- Target: (N) where each value is $0 \leq \text{targets}[i] \leq C - 1$, or $(N, d_1, d_2, ..., d_K)$ with $K \geq 1$ in the case of K-dimensional loss.
- Output: scalar.

If `reduction` is `'none'`, then the same size as the target: (N), or $(N, d_1, d_2, ..., d_K)$ with $K \geq 1$ in the case of K-dimensional loss.

Examples

```
if (torch_is_installed()) {
m <- nn_log_softmax(dim = 2)
loss <- nn_nll_loss()
# input is of size N x C = 3 x 5
input <- torch_randn(3, 5, requires_grad = TRUE)
# each element in target has to have 0 <= value < C
target <- torch_tensor(c(2, 1, 5), dtype = torch_long())
output <- loss(m(input), target)
output$backward()

# 2D loss example (used, for example, with image inputs)
N <- 5
C <- 4
loss <- nn_nll_loss()
# input is of size N x C x height x width
data <- torch_randn(N, 16, 10, 10)
conv <- nn_conv2d(16, C, c(3, 3))
m <- nn_log_softmax(dim = 1)
# each element in target has to have 0 <= value < C
target <- torch_empty(N, 8, 8, dtype = torch_long())$random_(1, C)
output <- loss(m(conv(data)), target)
output$backward()
}
```

`nn_pairwise_distance` *Pairwise distance*

Description

Computes the batchwise pairwise distance between vectors v_1, v_2 using the p-norm:

Usage

```
nn_pairwise_distance(p = 2, eps = 1e-06, keepdim = FALSE)
```

Arguments

p	(real): the norm degree. Default: 2
eps	(float, optional): Small value to avoid division by zero. Default: 1e-6
keepdim	(bool, optional): Determines whether or not to keep the vector dimension. Default: FALSE

Details

$$\|x\|_p = \left(\sum_{i=1}^{n} |x_i|^p \right)^{1/p}.$$

Shape

- Input1: (N, D) where `D = vector dimension`
- Input2: (N, D), same shape as the Input1
- Output: (N). If `keepdim` is `TRUE`, then $(N, 1)$.

Examples

```
if (torch_is_installed()) {
pdist <- nn_pairwise_distance(p = 2)
input1 <- torch_randn(100, 128)
input2 <- torch_randn(100, 128)
output <- pdist(input1, input2)
}
```

---

nn_parameter *Creates an* nn_parameter

Description

Indicates to nn_module that x is a parameter

Usage

```
nn_parameter(x, requires_grad = TRUE)
```

Arguments

x	the tensor that you want to indicate as parameter
requires_grad	whether this parameter should have `requires_grad = TRUE`

nn_poisson_nll_loss *Poisson NLL loss*

Description

Negative log likelihood loss with Poisson distribution of target. The loss can be described as:

Usage

```
nn_poisson_nll_loss(
  log_input = TRUE,
  full = FALSE,
  eps = 1e-08,
  reduction = "mean"
)
```

Arguments

`log_input`	(bool, optional): if `TRUE` the loss is computed as $\exp(\text{input}) - \text{target} * \text{input}$, if `FALSE` the loss is $\text{input} - \text{target} * \log(\text{input} + \text{eps})$.
`full`	(bool, optional): whether to compute full loss, i. e. to add the Stirling approximation term $\text{target} * \log(\text{target}) - \text{target} + 0.5 * \log(2\pi\text{target})$.
`eps`	(float, optional): Small value to avoid evaluation of $\log(0)$ when `log_input = FALSE`. Default: 1e-8
`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none' | 'mean' | 'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.

Details

$$\text{target} \sim \text{Poisson}(\text{input})\text{loss}(\text{input}, \text{target}) = \text{input} - \text{target} * \log(\text{input}) + \log(\text{target!})$$

The last term can be omitted or approximated with Stirling formula. The approximation is used for target values more than 1. For targets less or equal to 1 zeros are added to the loss.

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Target: $(N, *)$, same shape as the input
- Output: scalar by default. If `reduction` is `'none'`, then $(N, *)$, the same shape as the input

Examples

```
if (torch_is_installed()) {
loss <- nn_poisson_nll_loss()
log_input <- torch_randn(5, 2, requires_grad = TRUE)
target <- torch_randn(5, 2)
output <- loss(log_input, target)
output$backward()
}
```

---

nn_prelu *PReLU module*

Description

Applies the element-wise function:

$$\text{PReLU}(x) = \max(0, x) + a * \min(0, x)$$

or

$$\text{PReLU}(x) = \begin{cases} x, & \text{if } x \geq 0 \\ ax, & \text{otherwise} \end{cases}$$

Usage

```
nn_prelu(num_parameters = 1, init = 0.25)
```

Arguments

`num_parameters`	(int): number of a to learn. Although it takes an int as input, there is only two values are legitimate: 1, or the number of channels at input. Default: 1
`init`	(float): the initial value of a. Default: 0.25

Details

Here a is a learnable parameter. When called without arguments, `nn.prelu()` uses a single parameter a across all input channels. If called with `nn_prelu(nChannels)`, a separate a is used for each input channel.

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Attributes

- weight (Tensor): the learnable weights of shape (`num_parameters`).

Note

weight decay should not be used when learning a for good performance.

Channel dim is the 2nd dim of input. When input has dims < 2, then there is no channel dim and the number of channels = 1.

Examples

```
if (torch_is_installed()) {
m <- nn_prelu()
input <- torch_randn(2)
output <- m(input)
}
```

---

nn_prune_head *Prune top layer(s) of a network*

Description

Prune `head_size` last layers of a nn_module in order to replace them by your own head, or in order to use the pruned module as a sequential embedding module.

Usage

```
nn_prune_head(x, head_size)
```

Arguments

`x`	nn_network to prune
`head_size`	number of nn_layers to prune

Value

a nn_sequential network with the top nn_layer removed

Examples

```
if (torch_is_installed()) {
if (torch_is_installed()) {
x <- nn_sequential(
  nn_relu(),
  nn_tanh(),
  nn_relu6(),
  nn_relu(),
  nn_linear(2,10),
  nn_batch_norm1d(10),
  nn_tanh(),
  nn_linear(10,3)
)
```

```
prune <- nn_prune_head(x, 3)
prune
}
}
```

---

nn_relu *ReLU module*

Description

Applies the rectified linear unit function element-wise

$$\text{ReLU}(x) = (x)^+ = \max(0, x)$$

Usage

```
nn_relu(inplace = FALSE)
```

Arguments

inplace	can optionally do the operation in-place. Default: FALSE

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_relu()
input <- torch_randn(2)
m(input)
}
```

---

nn_relu6 *ReLu6 module*

Description

Applies the element-wise function:

Usage

```
nn_relu6(inplace = FALSE)
```

Arguments

`inplace`	can optionally do the operation in-place. Default: `FALSE`

Details

$$\text{ReLU6}(x) = \min(\max(0, x), 6)$$

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_relu6()
input <- torch_randn(2)
output <- m(input)
}
```

---

nn_rnn *RNN module*

Description

Applies a multi-layer Elman RNN with $\tanh$ or ReLU non-linearity to an input sequence.

Usage

```
nn_rnn(
  input_size,
  hidden_size,
  num_layers = 1,
  nonlinearity = NULL,
  bias = TRUE,
  batch_first = FALSE,
  dropout = 0,
  bidirectional = FALSE,
  ...
)
```

Arguments

input_size	The number of expected features in the input x
hidden_size	The number of features in the hidden state h
num_layers	Number of recurrent layers. E.g., setting num_layers=2 would mean stacking two RNNs together to form a stacked RNN, with the second RNN taking in outputs of the first RNN and computing the final results. Default: 1
nonlinearity	The non-linearity to use. Can be either 'tanh' or 'relu'. Default: 'tanh'
bias	If FALSE, then the layer does not use bias weights b_ih and b_hh. Default: TRUE
batch_first	If TRUE, then the input and output tensors are provided as (batch, seq, feature). Default: FALSE
dropout	If non-zero, introduces a Dropout layer on the outputs of each RNN layer except the last layer, with dropout probability equal to dropout. Default: 0
bidirectional	If TRUE, becomes a bidirectional RNN. Default: FALSE
...	other arguments that can be passed to the super class.

Details

For each element in the input sequence, each layer computes the following function:

$$h_t = \tanh(W_{ih}x_t + b_{ih} + W_{hh}h_{(t-1)} + b_{hh})$$

where h_t is the hidden state at time t, x_t is the input at time t, and $h_{(t-1)}$ is the hidden state of the previous layer at time t-1 or the initial hidden state at time 0. If nonlinearity is 'relu', then ReLU is used instead of $\tanh$.

Inputs

- **input** of shape (seq_len, batch, input_size): tensor containing the features of the input sequence. The input can also be a packed variable length sequence.
- **h_0** of shape (num_layers * num_directions, batch, hidden_size): tensor containing the initial hidden state for each element in the batch. Defaults to zero if not provided. If the RNN is bidirectional, num_directions should be 2, else it should be 1.

Outputs

- **output** of shape (seq_len, batch, num_directions * hidden_size): tensor containing the output features (h_t) from the last layer of the RNN, for each t. If a :class:nn_packed_sequence has been given as the input, the output will also be a packed sequence. For the unpacked case, the directions can be separated using output$view(seq_len, batch, num_directions, hidden_size), with forward and backward being direction 0 and 1 respectively. Similarly, the directions can be separated in the packed case.
- **h_n** of shape (num_layers * num_directions, batch, hidden_size): tensor containing the hidden state for t = seq_len. Like *output*, the layers can be separated using h_n$view(num_layers, num_directions, batch, hidden_size).

Shape

- Input1: (L, N, H_{in}) tensor containing input features where H_{in} = input_size and `L` represents a sequence length.
- Input2: (S, N, H_{out}) tensor containing the initial hidden state for each element in the batch. H_{out} = hidden_size Defaults to zero if not provided. where S = num_layers$*$num_directions If the RNN is bidirectional, num_directions should be 2, else it should be 1.
- Output1: (L, N, H_{all}) where H_{all} = num_directions $*$ hidden_size
- Output2: (S, N, H_{out}) tensor containing the next hidden state for each element in the batch

Attributes

- `weight_ih_l[k]`: the learnable input-hidden weights of the k-th layer, of shape `(hidden_size, input_size)` for `k = 0`. Otherwise, the shape is `(hidden_size, num_directions * hidden_size)`
- `weight_hh_l[k]`: the learnable hidden-hidden weights of the k-th layer, of shape `(hidden_size, hidden_size)`
- `bias_ih_l[k]`: the learnable input-hidden bias of the k-th layer, of shape `(hidden_size)`
- `bias_hh_l[k]`: the learnable hidden-hidden bias of the k-th layer, of shape `(hidden_size)`

Note

All the weights and biases are initialized from $\mathcal{U}(-\sqrt{k}, \sqrt{k})$ where $k = \frac{1}{\text{hidden_size}}$

Examples

```
if (torch_is_installed()) {
rnn <- nn_rnn(10, 20, 2)
input <- torch_randn(5, 3, 10)
h0 <- torch_randn(2, 3, 20)
rnn(input, h0)
}
```

---

nn_rrelu *RReLU module*

Description

Applies the randomized leaky rectified liner unit function, element-wise, as described in the paper:

Usage

```
nn_rrelu(lower = 1/8, upper = 1/3, inplace = FALSE)
```

Arguments

`lower`	lower bound of the uniform distribution. Default: $\frac{1}{8}$
`upper`	upper bound of the uniform distribution. Default: $\frac{1}{3}$
`inplace`	can optionally do the operation in-place. Default: `FALSE`

Details

`Empirical Evaluation of Rectified Activations in Convolutional Network.`

The function is defined as:

$$\text{RReLU}(x) = \begin{cases} x & \text{if } x \geq 0 \\ ax & \text{otherwise} \end{cases}$$

where a is randomly sampled from uniform distribution $\mathcal{U}(\text{lower}, \text{upper})$. See: https://arxiv.org/pdf/1505.00853.pdf

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_rrelu(0.1, 0.3)
input <- torch_randn(2)
m(input)
}
```

---

nn_selu *SELU module*

Description

Applied element-wise, as:

Usage

```
nn_selu(inplace = FALSE)
```

Arguments

`inplace`	(bool, optional): can optionally do the operation in-place. Default: `FALSE`

Details

$$\text{SELU}(x) = \text{scale} * (\max(0, x) + \min(0, \alpha * (\exp(x) - 1)))$$

with $\alpha = 1.6732632423543772848170429916717$ and scale $= 1.0507009873554804934193349852946$.

More details can be found in the paper Self-Normalizing Neural Networks.

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_selu()
input <- torch_randn(2)
output <- m(input)
}
```

---

nn_sequential *A sequential container*

Description

A sequential container. Modules will be added to it in the order they are passed in the constructor. See examples.

Usage

```
nn_sequential(...)
```

Arguments

`...`	sequence of modules to be added

Examples

```
if (torch_is_installed()) {

model <- nn_sequential(
  nn_conv2d(1, 20, 5),
  nn_relu(),
  nn_conv2d(20, 64, 5),
  nn_relu()
)
input <- torch_randn(32, 1, 28, 28)
output <- model(input)
}
```

nn_sigmoid *Sigmoid module*

Description

Applies the element-wise function:

Usage

```
nn_sigmoid()
```

Details

$$\text{Sigmoid}(x) = \sigma(x) = \frac{1}{1 + \exp(-x)}$$

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_sigmoid()
input <- torch_randn(2)
output <- m(input)
}
```

nn_silu *Applies the Sigmoid Linear Unit (SiLU) function, element-wise. The SiLU function is also known as the swish function.*

Description

Applies the Sigmoid Linear Unit (SiLU) function, element-wise. The SiLU function is also known as the swish function.

Usage

```
nn_silu(inplace = FALSE)
```

Arguments

`inplace`	can optionally do the operation in-place. Default: `FALSE`

Details

See Gaussian Error Linear Units (GELUs) where the SiLU (Sigmoid Linear Unit) was originally coined, and see Sigmoid-Weighted Linear Units for Neural Network Function Approximation in Reinforcement Learning and Swish: a Self-Gated Activation Function where the SiLU was experimented with later.

---

nn_smooth_l1_loss *Smooth L1 loss*

Description

Creates a criterion that uses a squared term if the absolute element-wise error falls below 1 and an L1 term otherwise. It is less sensitive to outliers than the `MSELoss` and in some cases prevents exploding gradients (e.g. see `Fast R-CNN` paper by Ross Girshick). Also known as the Huber loss:

Usage

```
nn_smooth_l1_loss(reduction = "mean")
```

Arguments

`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.

Details

$$\text{loss}(x, y) = \frac{1}{n} \sum_i z_i$$

where z_i is given by:

$$z_i = \begin{array}{ll} 0.5(x_i - y_i)^2, & \text{if } |x_i - y_i| < 1 \\ |x_i - y_i| - 0.5, & \text{otherwise} \end{array}$$

x and y arbitrary shapes with a total of n elements each the sum operation still operates over all the elements, and divides by n. The division by n can be avoided if sets `reduction = 'sum'`.

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Target: $(N, *)$, same shape as the input
- Output: scalar. If `reduction` is `'none'`, then $(N, *)$, same shape as the input

`nn_softmax` *Softmax module*

Description

Applies the Softmax function to an n-dimensional input Tensor rescaling them so that the elements of the n-dimensional output Tensor lie in the range `[0,1]` and sum to 1. Softmax is defined as:

Usage

```
nn_softmax(dim)
```

Arguments

`dim`	(int): A dimension along which Softmax will be computed (so every slice along dim will sum to 1).

Details

$$\text{Softmax}(x_i) = \frac{\exp(x_i)}{\sum_j \exp(x_j)}$$

When the input Tensor is a sparse tensor then the unspecifed values are treated as `-Inf`.

Value

: a Tensor of the same dimension and shape as the input with values in the range `[0, 1]`

Shape

- Input: $(*)$ where $*$ means, any number of additional dimensions
- Output: $(*)$, same shape as the input

Note

This module doesn't work directly with NLLLoss, which expects the Log to be computed between the Softmax and itself. Use `LogSoftmax` instead (it's faster and has better numerical properties).

Examples

```
if (torch_is_installed()) {
m <- nn_softmax(1)
input <- torch_randn(2, 3)
output <- m(input)
}
```

nn_softmax2d *Softmax2d module*

Description

Applies SoftMax over features to each spatial location. When given an image of `Channels x Height x Width`, it will apply `Softmax` to each location $(Channels, h_i, w_j)$

Usage

```
nn_softmax2d()
```

Value

a Tensor of the same dimension and shape as the input with values in the range `[0, 1]`

Shape

- Input: (N, C, H, W)
- Output: (N, C, H, W) (same shape as input)

Examples

```
if (torch_is_installed()) {
m <- nn_softmax2d()
input <- torch_randn(2, 3, 12, 13)
output <- m(input)
}
```

nn_softmin *Softmin*

Description

Applies the Softmin function to an n-dimensional input Tensor rescaling them so that the elements of the n-dimensional output Tensor lie in the range `[0, 1]` and sum to 1. Softmin is defined as:

Usage

```
nn_softmin(dim)
```

Arguments

`dim`	(int): A dimension along which Softmin will be computed (so every slice along dim will sum to 1).

Details

$$\text{Softmin}(x_i) = \frac{\exp(-x_i)}{\sum_j \exp(-x_j)}$$

Value

a Tensor of the same dimension and shape as the input, with values in the range `[0, 1]`.

Shape

- Input: $(*)$ where $*$ means, any number of additional dimensions
- Output: $(*)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_softmin(dim = 1)
input <- torch_randn(2, 2)
output <- m(input)
}
```

---

nn_softplus *Softplus module*

Description

Applies the element-wise function:

$$\text{Softplus}(x) = \frac{1}{\beta} * \log(1 + \exp(\beta * x))$$

Usage

```
nn_softplus(beta = 1, threshold = 20)
```

Arguments

`beta`	the β value for the Softplus formulation. Default: 1
`threshold`	values above this revert to a linear function. Default: 20

Details

SoftPlus is a smooth approximation to the ReLU function and can be used to constrain the output of a machine to always be positive. For numerical stability the implementation reverts to the linear function when $input \times \beta > threshold$.

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_softplus()
input <- torch_randn(2)
output <- m(input)
}
```

---

nn_softshrink *Softshrink module*

Description

Applies the soft shrinkage function elementwise:

Usage

```
nn_softshrink(lambd = 0.5)
```

Arguments

lambd	the λ (must be no less than zero) value for the Softshrink formulation. Default: 0.5

Details

$$\text{SoftShrinkage}(x) = \begin{cases} x - \lambda, & \text{if } x > \lambda \\ x + \lambda, & \text{if } x < -\lambda \\ 0, & \text{otherwise} \end{cases}$$

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_softshrink()
input <- torch_randn(2)
output <- m(input)
}
```

nn_softsign *Softsign module*

Description

Applies the element-wise function:

$$\text{SoftSign}(x) = \frac{x}{1 + |x|}$$

Usage

```
nn_softsign()
```

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_softsign()
input <- torch_randn(2)
output <- m(input)
}
```

nn_soft_margin_loss *Soft margin loss*

Description

Creates a criterion that optimizes a two-class classification logistic loss between input tensor x and target tensor y (containing 1 or -1).

Usage

```
nn_soft_margin_loss(reduction = "mean")
```

Arguments

`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.

Details

$$\text{loss}(x, y) = \sum_i \frac{\log(1 + \exp(-y[i] * x[i]))}{\text{x.nelement}()}$$

Shape

- Input: $(*)$ where $*$ means, any number of additional dimensions
- Target: $(*)$, same shape as the input
- Output: scalar. If `reduction` is `'none'`, then same shape as the input

---

nn_tanh *Tanh module*

Description

Applies the element-wise function:

Usage

```
nn_tanh()
```

Details

$$\text{Tanh}(x) = \tanh(x) = \frac{\exp(x) - \exp(-x)}{\exp(x) + \exp(-x)}$$

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_tanh()
input <- torch_randn(2)
output <- m(input)
}
```

nn_tanhshrink *Tanhshrink module*

Description

Applies the element-wise function:

Usage

```
nn_tanhshrink()
```

Details

$$\text{Tanhshrink}(x) = x - \tanh(x)$$

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_tanhshrink()
input <- torch_randn(2)
output <- m(input)
}
```

nn_threshold *Threshold module*

Description

Thresholds each element of the input Tensor.

Usage

```
nn_threshold(threshold, value, inplace = FALSE)
```

Arguments

threshold	The value to threshold at
value	The value to replace with
inplace	can optionally do the operation in-place. Default: FALSE

Details

Threshold is defined as:

$$y = \begin{cases} x, & \text{if } x > \text{threshold} \\ \text{value}, & \text{otherwise} \end{cases}$$

Shape

- Input: $(N, *)$ where $*$ means, any number of additional dimensions
- Output: $(N, *)$, same shape as the input

Examples

```
if (torch_is_installed()) {
m <- nn_threshold(0.1, 20)
input <- torch_randn(2)
output <- m(input)
}
```

---

nn_transformer_encoder

Transformer Encoder Module (R torch)

Description

Implements a stack of transformer encoder layers, optionally with a final layer normalization.

Usage

```
nn_transformer_encoder(encoder_layer, num_layers, norm = NULL)
```

Arguments

encoder_layer	(nn_module) an instance of nn_transformer_encoder_layer (or compatible) that defines the layer to be repeated.
num_layers	(integer) the number of encoder layers to stack.
norm	(nn_module or NULL) optional layer normalization module to apply after the last layer (e.g., nn_layer_norm). Default: NULL (no extra normalization).

Details

This module replicates the given encoder_layer num_layers times to construct the Transformer encoder. If a norm module is provided, it will be applied to the output of the final encoder layer. The forward pass sequentially applies each encoder layer to the input.

Value

An nn_module of class nn_transformer_encoder. Calling it on an input tensor of shape (S, N, E) or (N, S, E) (depending on batch_first) returns the encoded output of the same shape.

Examples

```
if (torch_is_installed()) {
if (torch_is_installed()) {
  layer <- nn_transformer_encoder_layer(d_model = 32, nhead = 4, batch_first = TRUE)
  model <- nn_transformer_encoder(layer, num_layers = 2)
  x <- torch_randn(8, 5, 32) # (batch, seq, feature) since batch_first=TRUE
  y <- model(x) # output shape is (8, 5, 32)
}
}
```

---

nn_transformer_encoder_layer

Transformer Encoder Layer Module (R torch)

Description

Implements a single transformer encoder layer as in PyTorch, including self-attention, feed-forward network, residual connections, and layer normalization.

Usage

```
nn_transformer_encoder_layer(
  d_model,
  nhead,
  dim_feedforward = 2048,
  dropout = 0.1,
  activation = "relu",
  layer_norm_eps = 1e-05,
  batch_first = FALSE,
  norm_first = FALSE,
  bias = TRUE
)
```

Arguments

`d_model`	(integer) the number of expected features in the input.
`nhead`	(integer) the number of heads in the multihead attention.
`dim_feedforward`	(integer) the dimension of the feed-forward network model. Default: 2048.
`dropout`	(numeric) the dropout probability for both attention and feed-forward networks. Default: 0.1.
`activation`	(character or function) the activation function of the intermediate layer. Can be `"relu"` or `"gelu"` or an R function mapping a tensor to a tensor. Default: "relu".
`layer_norm_eps`	(numeric) the epsilon value for layer normalization. Default: 1e-5.
`batch_first`	(logical) if TRUE, inputs are (batch, seq, feature) instead of (seq, batch, feature). Default: FALSE.

norm_first	(logical) if TRUE, layer norm is applied before attention and feed-forward sub-layers (Pre-Norm); if FALSE, applied after (Post-Norm). Default: FALSE.
bias	(logical) if FALSE, the Linear layers and LayerNorm will not learn additive bias (LayerNorm will have no affine params). Default: TRUE.

Value

An nn_module object of class nn_transformer_encoder_layer. Calling the module on an input tensor returns the output tensor of the same shape.

Details

This module is equivalent to torch::nn_transformer_encoder_layer in PyTorch, with identical default arguments and behavior. It consists of a multi-head self-attention (self_attn), followed by a feed-forward network (two linear layers with an activation in between), each part having residual connections and dropout. Two LayerNorm layers (norm1, norm2) are used either in pre-norm or post-norm fashion based on norm_first.

The forward() method supports an optional src_mask (attention mask) and src_key_padding_mask to mask out positions, and an is_causal flag for auto-regressive masking. If is_causal=TRUE, a causal mask will be applied (equivalent to a lower-triangular attention mask), which should not be combined with an explicit src_mask.

Examples

```
if (torch_is_installed()) {
if (torch_is_installed()) {
  layer <- nn_transformer_encoder_layer(d_model = 16, nhead = 4)
  x <- torch_randn(10, 2, 16) # (sequence, batch, features)
  y <- layer(x) # output has shape (10, 2, 16)
}
}
```

---

nn_triplet_margin_loss

Triplet margin loss

Description

Creates a criterion that measures the triplet loss given an input tensors $x1$, $x2$, $x3$ and a margin with a value greater than 0. This is used for measuring a relative similarity between samples. A triplet is composed by a, p and n (i.e., anchor, positive examples and negative examples respectively). The shapes of all input tensors should be (N, D).

Usage

```
nn_triplet_margin_loss(
  margin = 1,
  p = 2,
  eps = 1e-06,
  swap = FALSE,
  reduction = "mean"
)
```

Arguments

`margin`	(float, optional): Default: 1.
`p`	(int, optional): The norm degree for pairwise distance. Default: 2.
`eps`	constant to avoid NaN's
`swap`	(bool, optional): The distance swap is described in detail in the paper Learning shallow convolutional feature descriptors with triplet losses by V. Balntas, E. Riba et al. Default: `FALSE`.
`reduction`	(string, optional): Specifies the reduction to apply to the output: `'none'` | `'mean'` | `'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed.

Details

The distance swap is described in detail in the paper Learning shallow convolutional feature descriptors with triplet losses by V. Balntas, E. Riba et al.

The loss function for each sample in the mini-batch is:

$$L(a, p, n) = \max\{d(a_i, p_i) - d(a_i, n_i) + \text{margin}, 0\}$$

where

$$d(x_i, y_i) = |\mathbf{x}_i - \mathbf{y}_i|_p$$

See also `nn_triplet_margin_with_distance_loss()`, which computes the triplet margin loss for input tensors using a custom distance function.

Shape

- Input: (N, D) where D is the vector dimension.
- Output: A Tensor of shape (N) if `reduction` is `'none'`, or a scalar otherwise.

Examples

```
if (torch_is_installed()) {
triplet_loss <- nn_triplet_margin_loss(margin = 1, p = 2)
anchor <- torch_randn(100, 128, requires_grad = TRUE)
positive <- torch_randn(100, 128, requires_grad = TRUE)
negative <- torch_randn(100, 128, requires_grad = TRUE)
output <- triplet_loss(anchor, positive, negative)
output$backward()
}
```

---

nn_triplet_margin_with_distance_loss

Triplet margin with distance loss

Description

Creates a criterion that measures the triplet loss given input tensors a, p, and n (representing anchor, positive, and negative examples, respectively), and a nonnegative, real-valued function ("distance function") used to compute the relationship between the anchor and positive example ("positive distance") and the anchor and negative example ("negative distance").

Usage

```
nn_triplet_margin_with_distance_loss(
  distance_function = NULL,
  margin = 1,
  swap = FALSE,
  reduction = "mean"
)
```

Arguments

`distance_function`
: (callable, optional): A nonnegative, real-valued function that quantifies the closeness of two tensors. If not specified, `nn_pairwise_distance()` will be used. Default: `None`

`margin`
: (float, optional): A non-negative margin representing the minimum difference between the positive and negative distances required for the loss to be 0. Larger margins penalize cases where the negative examples are not distant enough from the anchors, relative to the positives. Default: 1.

`swap`
: (bool, optional): Whether to use the distance swap described in the paper Learning shallow convolutional feature descriptors with triplet losses by V. Balntas, E. Riba et al. If TRUE, and if the positive example is closer to the negative example than the anchor is, swaps the positive example and the anchor in the loss computation. Default: `FALSE`.

`reduction` (string, optional): Specifies the (optional) reduction to apply to the output: `'none' | 'mean' | 'sum'`. `'none'`: no reduction will be applied, `'mean'`: the sum of the output will be divided by the number of elements in the output, `'sum'`: the output will be summed. Default: `'mean'`

Details

The unreduced loss (i.e., with `reduction` set to `'none'`) can be described as:

$$\ell(a, p, n) = L = \{l_1, \dots, l_N\}^\top, \quad l_i = \max\{d(a_i, p_i) - d(a_i, n_i) + \mathrm{margin}, 0\}$$

where N is the batch size; d is a nonnegative, real-valued function quantifying the closeness of two tensors, referred to as the `distance_function`; and $margin$ is a non-negative margin representing the minimum difference between the positive and negative distances that is required for the loss to be 0. The input tensors have N elements each and can be of any shape that the distance function can handle. If `reduction` is not `'none'` (default `'mean'`), then:

$$\ell(x, y) = \begin{array}{ll} \mathrm{mean}(L), & \text{if reduction} = \text{‘mean’;} \\ \mathrm{sum}(L), & \text{if reduction} = \text{‘sum’.} \end{array}$$

See also `nn_triplet_margin_loss()`, which computes the triplet loss for input tensors using the l_p distance as the distance function.

Shape

- Input: $(N, *)$ where $*$ represents any number of additional dimensions as supported by the distance function.
- Output: A Tensor of shape (N) if `reduction` is `'none'`, or a scalar otherwise.

Examples

```
if (torch_is_installed()) {
# Initialize embeddings
embedding <- nn_embedding(1000, 128)
anchor_ids <- torch_randint(1, 1000, 1, dtype = torch_long())
positive_ids <- torch_randint(1, 1000, 1, dtype = torch_long())
negative_ids <- torch_randint(1, 1000, 1, dtype = torch_long())
anchor <- embedding(anchor_ids)
positive <- embedding(positive_ids)
negative <- embedding(negative_ids)

# Built-in Distance Function
triplet_loss <- nn_triplet_margin_with_distance_loss(
  distance_function = nn_pairwise_distance()
)
output <- triplet_loss(anchor, positive, negative)

# Custom Distance Function
l_infinity <- function(x1, x2) {
  torch_max(torch_abs(x1 - x2), dim = 1)[[1]]
}
```

```
triplet_loss <- nn_triplet_margin_with_distance_loss(
  distance_function = l_infinity, margin = 1.5
)
output <- triplet_loss(anchor, positive, negative)

# Custom Distance Function (Lambda)
triplet_loss <- nn_triplet_margin_with_distance_loss(
  distance_function = function(x, y) {
    1 - nnf_cosine_similarity(x, y)
  }
)

output <- triplet_loss(anchor, positive, negative)
}
```

`nn_unflatten` *Unflattens a tensor dim expanding it to a desired shape. For use with [nn_sequential.*

Description

Unflattens a tensor dim expanding it to a desired shape. For use with [nn_sequential.

Usage

```
nn_unflatten(dim, unflattened_size)
```

Arguments

`dim`	Dimension to be unflattened
`unflattened_size`	New shape of the unflattened dimension

Examples

```
if (torch_is_installed()) {
input <- torch_randn(2, 50)

m <- nn_sequential(
  nn_linear(50, 50),
  nn_unflatten(2, c(2, 5, 5))
)
output <- m(input)
output$size()
}
```

nn_upsample *Upsample module*

Description

Upsamples a given multi-channel 1D (temporal), 2D (spatial) or 3D (volumetric) data. The input data is assumed to be of the form minibatch x channels x optional depth x optional height] x width. Hence, for spatial inputs, we expect a 4D Tensor and for volumetric inputs, we expect a 5D Tensor.

Usage

```
nn_upsample(
  size = NULL,
  scale_factor = NULL,
  mode = "nearest",
  align_corners = NULL
)
```

Arguments

`size`	(int or `Tuple[int]` or `Tuple[int, int]` or `Tuple[int, int, int]`, optional): output spatial sizes
`scale_factor`	(float or `Tuple[float]` or `Tuple[float, float]` or `Tuple[float, float, float]`, optional): multiplier for spatial size. Has to match input size if it is a tuple.
`mode`	(str, optional): the upsampling algorithm: one of `'nearest'`, `'linear'`, `'bilinear'`, `'bicubic'` and `'trilinear'`. Default: `'nearest'`
`align_corners`	(bool, optional): if `TRUE`, the corner pixels of the input and output tensors are aligned, and thus preserving the values at those pixels. This only has effect when `mode` is `'linear'`, `'bilinear'`, or `'trilinear'`. Default: `FALSE`

Details

The algorithms available for upsampling are nearest neighbor and linear, bilinear, bicubic and trilinear for 3D, 4D and 5D input Tensor, respectively.

One can either give a scale_factor or the target output size to calculate the output size. (You cannot give both, as it is ambiguous)

Examples

```
if (torch_is_installed()) {
input <- torch_arange(start = 1, end = 4, dtype = torch_float())$view(c(1, 1, 2, 2))
nn_upsample(scale_factor = c(2), mode = "nearest")(input)
nn_upsample(scale_factor = c(2, 2), mode = "nearest")(input)
}
```

nn_utils_clip_grad_norm_

Clips gradient norm of an iterable of parameters.

Description

The norm is computed over all gradients together, as if they were concatenated into a single vector. Gradients are modified in-place.

Usage

```
nn_utils_clip_grad_norm_(parameters, max_norm, norm_type = 2)
```

Arguments

parameters	(IterableTensor or Tensor): an iterable of Tensors or a single Tensor that will have gradients normalized
max_norm	(float or int): max norm of the gradients
norm_type	(float or int): type of the used p-norm. Can be `Inf` for infinity norm.

Value

Total norm of the parameters (viewed as a single vector).

nn_utils_clip_grad_value_

Clips gradient of an iterable of parameters at specified value.

Description

Gradients are modified in-place.

Usage

```
nn_utils_clip_grad_value_(parameters, clip_value)
```

Arguments

parameters	(Iterable(Tensor) or Tensor): an iterable of Tensors or a single Tensor that will have gradients normalized
clip_value	(float or int): maximum allowed value of the gradients.

Details

The gradients are clipped in the range [-clip_value, clip_value]

nn_utils_rnn_pack_padded_sequence

Packs a Tensor containing padded sequences of variable length.

Description

`input` can be of size `T x B x *` where `T` is the length of the longest sequence (equal to `lengths[1]`), `B` is the batch size, and `*` is any number of dimensions (including 0). If `batch_first` is `TRUE`, `B x T x *` `input` is expected.

Usage

```
nn_utils_rnn_pack_padded_sequence(
  input,
  lengths,
  batch_first = FALSE,
  enforce_sorted = TRUE
)
```

Arguments

`input`	(Tensor): padded batch of variable length sequences.
`lengths`	(Tensor): list of sequences lengths of each batch element.
`batch_first`	(bool, optional): if `TRUE`, the input is expected in `B x T x *` format.
`enforce_sorted`	(bool, optional): if `TRUE`, the input is expected to contain sequences sorted by length in a decreasing order. If `FALSE`, the input will get sorted unconditionally. Default: `TRUE`.

Details

For unsorted sequences, use `enforce_sorted = FALSE`. If `enforce_sorted` is `TRUE`, the sequences should be sorted by length in a decreasing order, i.e. `input[,1]` should be the longest sequence, and `input[,B]` the shortest one. `enforce_sorted = TRUE` is only necessary for ONNX export.

Value

a `PackedSequence` object

Note

This function accepts any input that has at least two dimensions. You can apply it to pack the labels, and use the output of the RNN with them to compute the loss directly. A Tensor can be retrieved from a `PackedSequence` object by accessing its `.data` attribute.

nn_utils_rnn_pack_sequence

Packs a list of variable length Tensors

Description

sequences should be a list of Tensors of size L x *, where L is the length of a sequence and * is any number of trailing dimensions, including zero.

Usage

```
nn_utils_rnn_pack_sequence(sequences, enforce_sorted = TRUE)
```

Arguments

sequences	(list[Tensor]): A list of sequences of decreasing length.
enforce_sorted	(bool, optional): if TRUE, checks that the input contains sequences sorted by length in a decreasing order. If FALSE, this condition is not checked. Default: TRUE.

Details

For unsorted sequences, use enforce_sorted = FALSE. If enforce_sorted is TRUE, the sequences should be sorted in the order of decreasing length. enforce_sorted = TRUE is only necessary for ONNX export.

Value

a PackedSequence object

Examples

```
if (torch_is_installed()) {
x <- torch_tensor(c(1, 2, 3), dtype = torch_long())
y <- torch_tensor(c(4, 5), dtype = torch_long())
z <- torch_tensor(c(6), dtype = torch_long())

p <- nn_utils_rnn_pack_sequence(list(x, y, z))
}
```

nn_utils_rnn_pad_packed_sequence

Pads a packed batch of variable length sequences.

Description

It is an inverse operation to nn_utils_rnn_pack_padded_sequence().

Usage

```
nn_utils_rnn_pad_packed_sequence(
  sequence,
  batch_first = FALSE,
  padding_value = 0,
  total_length = NULL
)
```

Arguments

sequence	(PackedSequence): batch to pad
batch_first	(bool, optional): if True, the output will be in "B x T x *' format.
padding_value	(float, optional): values for padded elements.
total_length	(int, optional): if not NULL, the output will be padded to have length total_length. This method will throw ValueError if total_length is less than the max sequence length in sequence.

Details

The returned Tensor's data will be of size T x B x *, where T is the length of the longest sequence and B is the batch size. If batch_first is TRUE, the data will be transposed into B x T x * format.

Value

Tuple of Tensor containing the padded sequence, and a Tensor containing the list of lengths of each sequence in the batch. Batch elements will be re-ordered as they were ordered originally when the batch was passed to nn_utils_rnn_pack_padded_sequence() or nn_utils_rnn_pack_sequence().

Note

total_length is useful to implement the pack sequence -> recurrent network -> unpack sequence pattern in a nn_module wrapped in ~torch.nn.DataParallel.

Examples

```
if (torch_is_installed()) {
seq <- torch_tensor(rbind(c(1, 2, 0), c(3, 0, 0), c(4, 5, 6)))
lens <- c(2, 1, 3)
packed <- nn_utils_rnn_pack_padded_sequence(seq, lens,
  batch_first = TRUE,
  enforce_sorted = FALSE
)
packed
nn_utils_rnn_pad_packed_sequence(packed, batch_first = TRUE)
}
```

---

nn_utils_rnn_pad_sequence

Pad a list of variable length Tensors with `padding_value`

Description

`pad_sequence` stacks a list of Tensors along a new dimension, and pads them to equal length. For example, if the input is list of sequences with size `L x *` and if batch_first is False, and `T x B x *` otherwise.

Usage

```
nn_utils_rnn_pad_sequence(sequences, batch_first = FALSE, padding_value = 0)
```

Arguments

`sequences`	(`list[Tensor]`): list of variable length sequences.
`batch_first`	(bool, optional): output will be in `B x T x *` if `TRUE`, or in `T x B x *` otherwise
`padding_value`	(float, optional): value for padded elements. Default: 0.

Details

`B` is batch size. It is equal to the number of elements in `sequences`. `T` is length of the longest sequence. `L` is length of the sequence. `*` is any number of trailing dimensions, including none.

Value

Tensor of size `T x B x *` if `batch_first` is `FALSE`. Tensor of size `B x T x *` otherwise

Note

This function returns a Tensor of size `T x B x *` or `B x T x *` where `T` is the length of the longest sequence. This function assumes trailing dimensions and type of all the Tensors in sequences are same.

Examples

```
if (torch_is_installed()) {
a <- torch_ones(25, 300)
b <- torch_ones(22, 300)
c <- torch_ones(15, 300)
nn_utils_rnn_pad_sequence(list(a, b, c))$size()
}
```

---

nn_utils_weight_norm *nn_utils_weight_norm*

Description

Applies weight normalization to a parameter in the given module.

Details

```
\eqn{\mathbf{w} = g \dfrac{\mathbf{v}}{\|\mathbf{v}\|}}
```

Weight normalization is a reparameterization that decouples the magnitude of a weight tensor from its direction. This replaces the parameter specified by `name` (e.g. `'weight'`) with two parameters: one specifying the magnitude (e.g. `'weight_g'`) and one specifying the direction (e.g. `'weight_v'`).

Value

The original module with the weight_v and weight_g paramters.

Methods

Public methods:

- `nn_utils_weight_norm$new()`
- `nn_utils_weight_norm$compute_weight()`
- `nn_utils_weight_norm$apply()`
- `nn_utils_weight_norm$call()`
- `nn_utils_weight_norm$recompute()`
- `nn_utils_weight_norm$remove()`
- `nn_utils_weight_norm$clone()`

Method `new()`:

Usage:

```
nn_utils_weight_norm$new(name, dim)
```

Arguments:

`name` (str, optional): name of weight parameter

`dim` (int, optional): dimension over which to compute the norm

Method `compute_weight()`**:**

Usage:

```
nn_utils_weight_norm$compute_weight(module, name = NULL, dim = NULL)
```

Arguments:

`module` (Module): containing module

`name` (str, optional): name of weight parameter

`dim` (int, optional): dimension over which to compute the norm

Method `apply()`**:**

Usage:

```
nn_utils_weight_norm$apply(module, name = NULL, dim = NULL)
```

Arguments:

`module` (Module): containing module

`name` (str, optional): name of weight parameter

`dim` (int, optional): dimension over which to compute the norm

Method `call()`**:**

Usage:

```
nn_utils_weight_norm$call(module)
```

Arguments:

`module` (Module): containing module

Method `recompute()`**:**

Usage:

```
nn_utils_weight_norm$recompute(module)
```

Arguments:

`module` (Module): containing module

Method `remove()`**:**

Usage:

```
nn_utils_weight_norm$remove(module, name = NULL)
```

Arguments:

`module` (Module): containing module

`name` (str, optional): name of weight parameter

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
nn_utils_weight_norm$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

The pytorch Weight normalization is implemented via a hook that recomputes the weight tensor from the magnitude and direction before every `forward()` call. Since torch for R still do not support hooks, the weight recomputation need to be done explicitly inside the `forward()` definition trough a call of the `recompute()` method. See examples.

By default, with `dim = 0`, the norm is computed independently per output channel/plane. To compute a norm over the entire weight tensor, use `dim = NULL`.

@references https://arxiv.org/abs/1602.07868

Examples

```
if (torch_is_installed()) {
x = nn_linear(in_features = 20, out_features = 40)
weight_norm = nn_utils_weight_norm$new(name = 'weight', dim = 2)
weight_norm$apply(x)
x$weight_g$size()
x$weight_v$size()
x$weight

# the recompute() method recomputes the weight using g and v. It must be called
# explicitly inside `forward()`.
weight_norm$recompute(x)

}
```

`optimizer` *Creates a custom optimizer*

Description

When implementing custom optimizers you will usually need to implement the `initialize` and `step` methods. See the example section below for a full example.

Usage

```
optimizer(
  name = NULL,
  inherit = Optimizer,
  ...,
  private = NULL,
  active = NULL,
  parent_env = parent.frame()
)
```

Arguments

name	(optional) name of the optimizer
inherit	(optional) you can inherit from other optimizers to re-use some methods.
...	Pass any number of fields or methods. You should at least define the `initialize` and `step` methods. See the examples section.
private	(optional) a list of private methods for the optimizer.
active	(optional) a list of active methods for the optimizer.
parent_env	used to capture the right environment to define the class. The default is fine for most situations.

Warning

If you need to move a model to GPU via `$cuda()`, please do so before constructing optimizers for it. Parameters of a model after `$cuda()` will be different objects from those before the call. In general, you should make sure that the objects pointed to by model parameters subject to optimization remain the same over the whole lifecycle of optimizer creation and usage.

Examples

```
if (torch_is_installed()) {

# In this example we will create a custom optimizer
# that's just a simplified version of the `optim_sgd` function.

optim_sgd2 <- optimizer(
  initialize = function(params, learning_rate) {
    defaults <- list(
      learning_rate = learning_rate
    )
    super$initialize(params, defaults)
  },
  step = function() {
    with_no_grad({
      for (g in seq_along(self$param_groups)) {
        group <- self$param_groups[[g]]
        for (p in seq_along(group$params)) {
          param <- group$params[[p]]

          if (is.null(param$grad) || is_undefined_tensor(param$grad)) {
            next
          }

          param$add_(param$grad, alpha = -group$learning_rate)
        }
      }
    })
  }
)
```

```
x <- torch_randn(1, requires_grad = TRUE)
opt <- optim_sgd2(x, learning_rate = 0.1)
for (i in 1:100) {
  opt$zero_grad()
  y <- x^2
  y$backward()
  opt$step()
}
all.equal(x$item(), 0, tolerance = 1e-9)
}
```

`OptimizerIgnite` *Abstract Base Class for LibTorch Optimizers*

Description

Abstract base class for wrapping LibTorch C++ optimizers.

Super class

`torch::torch_optimizer` -> `OptimizerIgnite`

Methods

Public methods:

- `OptimizerIgnite$new()`
- `OptimizerIgnite$state_dict()`
- `OptimizerIgnite$load_state_dict()`
- `OptimizerIgnite$step()`
- `OptimizerIgnite$zero_grad()`
- `OptimizerIgnite$add_param_group()`
- `OptimizerIgnite$clone()`

Method `new()`**:** Initializes the optimizer with the specified parameters and defaults.

Usage:

```
OptimizerIgnite$new(params, defaults)
```

Arguments:

`params (list())`
: Either a list of tensors or a list of parameter groups, each containing the `params` to optimizer as well as the optimizer options such as the learning rate, weight decay, etc.

`defaults (list())`
: A list of default optimizer options.

Method `state_dict()`**:** Returns the state dictionary containing the current state of the optimizer. The returned `list()` contains two lists:

- `param_groups`: The parameter groups of the optimizer (`lr`, ...) as well as to which parameters they are applied (`params`, integer indices)
- `state`: The states of the optimizer. The names are the indices of the parameters to which they belong, converted to character.

Usage:

```
OptimizerIgnite$state_dict()
```

Returns: (`list()`)

Method `load_state_dict()`**:** Loads the state dictionary into the optimizer.

Usage:

```
OptimizerIgnite$load_state_dict(state_dict)
```

Arguments:

`state_dict` (`list()`)
The state dictionary to load into the optimizer.

Method `step()`**:** Performs a single optimization step.

Usage:

```
OptimizerIgnite$step(closure = NULL)
```

Arguments:

`closure` (`function()`)
A closure that conducts the forward pass and returns the loss.

Returns: (`numeric()`)
The loss.

Method `zero_grad()`**:** Zeros out the gradients of the parameters.

Usage:

```
OptimizerIgnite$zero_grad()
```

Method `add_param_group()`**:** Adds a new parameter group to the optimizer.

Usage:

```
OptimizerIgnite$add_param_group(param_group)
```

Arguments:

`param_group` (`list()`)
A parameter group to add to the optimizer. This should contain the `params` to optimize as well as the optimizer options. For all options that are not specified, the defaults are used.

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
OptimizerIgnite$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

optimizer_ignite *Abstract Base Class for LibTorch Optimizers*

Description

Abstract base class for wrapping LibTorch C++ optimizers.

Usage

```
optimizer_ignite(
  name = NULL,
  ...,
  private = NULL,
  active = NULL,
  parent_env = parent.frame()
)
```

Arguments

name	(optional) name of the optimizer
...	Pass any number of fields or methods. You should at least define the `initialize` and `step` methods. See the examples section.
private	(optional) a list of private methods for the optimizer.
active	(optional) a list of active methods for the optimizer.
parent_env	used to capture the right environment to define the class. The default is fine for most situations.

optim_adadelta *Adadelta optimizer*

Description

It has been proposed in ADADELTA: An Adaptive Learning Rate Method

Usage

```
optim_adadelta(params, lr = 1, rho = 0.9, eps = 1e-06, weight_decay = 0)
```

Arguments

`params`	(iterable): list of parameters to optimize or list defining parameter groups
`lr`	(float, optional): learning rate (default: 1e-3)
`rho`	(float, optional): coefficient used for computing a running average of squared gradients (default: 0.9)
`eps`	(float, optional): term added to the denominator to improve numerical stability (default: 1e-6)
`weight_decay`	(float, optional): weight decay (L2 penalty) (default: 0)

Warning

If you need to move a model to GPU via `$cuda()`, please do so before constructing optimizers for it. Parameters of a model after `$cuda()` will be different objects from those before the call. In general, you should make sure that the objects pointed to by model parameters subject to optimization remain the same over the whole lifecycle of optimizer creation and usage.

Note

According to the original paper, decaying average of the squared gradients is computed as follows:

$$E[g^2]_t = \rho E[g^2]_{t-1} + (1-\rho){g_t}^2$$

RMS of previous squared gradients up to time t:

$$RMS[g_t] = \sqrt{E[g^2]_t + \epsilon}$$

Adadelta update rule:

$$\Delta\theta_t = -\frac{RMS[\Delta\theta]_{t-1}}{RMS[g]_t}\theta_{t+1} = \theta_t + \Delta\theta_t$$

Examples

```
if (torch_is_installed()) {
## Not run:
optimizer <- optim_adadelta(model$parameters, lr = 0.1)
optimizer$zero_grad()
loss_fn(model(input), target)$backward()
optimizer$step()

## End(Not run)
}
```

optim_adagrad *Adagrad optimizer*

Description

Proposed in Adaptive Subgradient Methods for Online Learning and Stochastic Optimization

Usage

```
optim_adagrad(
  params,
  lr = 0.01,
  lr_decay = 0,
  weight_decay = 0,
  initial_accumulator_value = 0,
  eps = 1e-10
)
```

Arguments

`params` (iterable): list of parameters to optimize or list parameter groups

`lr` (float, optional): learning rate (default: 1e-2)

`lr_decay` (float, optional): learning rate decay (default: 0)

`weight_decay` (float, optional): weight decay (L2 penalty) (default: 0)

`initial_accumulator_value`
the initial value for the accumulator. (default: 0)

Adagrad is an especially good optimizer for sparse data. It individually modifies learning rate for every single parameter, dividing the original learning rate value by sum of the squares of the gradients. It causes that the rarely occurring features get greater learning rates. The main downside of this method is the fact that learning rate may be getting small too fast, so that at some point a model cannot learn anymore.

`eps` (float, optional): term added to the denominator to improve numerical stability (default: 1e-10)

Warning

If you need to move a model to GPU via `$cuda()`, please do so before constructing optimizers for it. Parameters of a model after `$cuda()` will be different objects from those before the call. In general, you should make sure that the objects pointed to by model parameters subject to optimization remain the same over the whole lifecycle of optimizer creation and usage.

Note

Update rule:

$$\theta_{t+1} = \theta_t - \frac{\eta}{\sqrt{G_t + \epsilon}} \odot g_t$$

The equation above and some remarks quoted after *An overview of gradient descent optimization algorithms* by Sebastian Ruder.

`optim_adam` *Implements Adam algorithm.*

Description

It has been proposed in Adam: A Method for Stochastic Optimization.

Usage

```
optim_adam(
  params,
  lr = 0.001,
  betas = c(0.9, 0.999),
  eps = 1e-08,
  weight_decay = 0,
  amsgrad = FALSE
)
```

Arguments

`params`	(iterable): iterable of parameters to optimize or dicts defining parameter groups
`lr`	(float, optional): learning rate (default: 1e-3)
`betas`	(`Tuple[float, float]`, optional): coefficients used for computing running averages of gradient and its square (default: (0.9, 0.999))
`eps`	(float, optional): term added to the denominator to improve numerical stability (default: 1e-8)
`weight_decay`	(float, optional): weight decay (L2 penalty) (default: 0)
`amsgrad`	(boolean, optional): whether to use the AMSGrad variant of this algorithm from the paper On the Convergence of Adam and Beyond (default: FALSE)

Warning

If you need to move a model to GPU via `$cuda()`, please do so before constructing optimizers for it. Parameters of a model after `$cuda()` will be different objects from those before the call. In general, you should make sure that the objects pointed to by model parameters subject to optimization remain the same over the whole lifecycle of optimizer creation and usage.

Examples

```
if (torch_is_installed()) {
## Not run:
optimizer <- optim_adam(model$parameters(), lr = 0.1)
optimizer$zero_grad()
loss_fn(model(input), target)$backward()
optimizer$step()

## End(Not run)

}
```

`optim_adamw` *Implements AdamW algorithm*

Description

For further details regarding the algorithm we refer to Decoupled Weight Decay Regularization

Usage

```
optim_adamw(
  params,
  lr = 0.001,
  betas = c(0.9, 0.999),
  eps = 1e-08,
  weight_decay = 0.01,
  amsgrad = FALSE
)
```

Arguments

`params`	(iterable): iterable of parameters to optimize or dicts defining parameter groups
`lr`	(float, optional): learning rate (default: 1e-3)
`betas`	(`Tuple[float, float]`, optional): coefficients used for computing running averages of gradient and its square (default: (0.9, 0.999))
`eps`	(float, optional): term added to the denominator to improve numerical stability (default: 1e-8)
`weight_decay`	(float, optional): weight decay (L2 penalty) (default: 0)
`amsgrad`	(boolean, optional): whether to use the AMSGrad variant of this algorithm from the paper On the Convergence of Adam and Beyond (default: FALSE)

optim_asgd — *Averaged Stochastic Gradient Descent optimizer*

Description

Proposed in Acceleration of stochastic approximation by averaging, doi:10.1137/0330046

Usage

```
optim_asgd(
  params,
  lr = 0.01,
  lambda = 1e-04,
  alpha = 0.75,
  t0 = 1e+06,
  weight_decay = 0
)
```

Arguments

params	(iterable): iterable of parameters to optimize or lists defining parameter groups
lr	(float): learning rate
lambda	(float, optional): decay term (default: 1e-4)
alpha	(float, optional): power for eta update (default: 0.75)
t0	(float, optional): point at which to start averaging (default: 1e6)
weight_decay	(float, optional): weight decay (L2 penalty) (default: 0)

Warning

If you need to move a model to GPU via `$cuda()`, please do so before constructing optimizers for it. Parameters of a model after `$cuda()` will be different objects from those before the call. In general, you should make sure that the objects pointed to by model parameters subject to optimization remain the same over the whole lifecycle of optimizer creation and usage.

Examples

```
if (torch_is_installed()) {
## Not run:
optimizer <- optim_asgd(model$parameters(), lr = 0.1)
optimizer$zero_grad()
loss_fn(model(input), target)$backward()
optimizer$step()

## End(Not run)

}
```

optim_ignite_adagrad *LibTorch implementation of Adagrad*

Description

Proposed in Adaptive Subgradient Methods for Online Learning and Stochastic Optimization

Usage

```
optim_ignite_adagrad(
  params,
  lr = 0.01,
  lr_decay = 0,
  weight_decay = 0,
  initial_accumulator_value = 0,
  eps = 1e-10
)
```

Arguments

params	(iterable): list of parameters to optimize or list parameter groups
lr	(float, optional): learning rate (default: 1e-2)
lr_decay	(float, optional): learning rate decay (default: 0)
weight_decay	(float, optional): weight decay (L2 penalty) (default: 0)
initial_accumulator_value	the initial value for the accumulator. (default: 0) Adagrad is an especially good optimizer for sparse data. It individually modifies learning rate for every single parameter, dividing the original learning rate value by sum of the squares of the gradients. It causes that the rarely occurring features get greater learning rates. The main downside of this method is the fact that learning rate may be getting small too fast, so that at some point a model cannot learn anymore.
eps	(float, optional): term added to the denominator to improve numerical stability (default: 1e-10)

Fields and Methods

See OptimizerIgnite.

Examples

```
if (torch_is_installed()) {
## Not run:
optimizer <- optim_ignite_adagrad(model$parameters(), lr = 0.1)
optimizer$zero_grad()
loss_fn(model(input), target)$backward()
```

```
optimizer$step()

## End(Not run)
}
```

---

optim_ignite_adam *LibTorch implementation of Adam*

Description

It has been proposed in Adam: A Method for Stochastic Optimization.

Usage

```
optim_ignite_adam(
  params,
  lr = 0.001,
  betas = c(0.9, 0.999),
  eps = 1e-08,
  weight_decay = 0,
  amsgrad = FALSE
)
```

Arguments

params	(iterable): iterable of parameters to optimize or dicts defining parameter groups
lr	(float, optional): learning rate (default: 1e-3)
betas	(Tuple[float, float], optional): coefficients used for computing running averages of gradient and its square (default: (0.9, 0.999))
eps	(float, optional): term added to the denominator to improve numerical stability (default: 1e-8)
weight_decay	(float, optional): weight decay (L2 penalty) (default: 0)
amsgrad	(boolean, optional): whether to use the AMSGrad variant of this algorithm from the paper On the Convergence of Adam and Beyond (default: FALSE)

Fields and Methods

See OptimizerIgnite.

Examples

```
if (torch_is_installed()) {
## Not run:
optimizer <- optim_ignite_adam(model$parameters(), lr = 0.1)
optimizer$zero_grad()
loss_fn(model(input), target)$backward()
optimizer$step()
```

```
## End(Not run)
}
```

---

optim_ignite_adamw *LibTorch implementation of AdamW*

Description

For further details regarding the algorithm we refer to Decoupled Weight Decay Regularization

Usage

```
optim_ignite_adamw(
  params,
  lr = 0.001,
  betas = c(0.9, 0.999),
  eps = 1e-08,
  weight_decay = 0.01,
  amsgrad = FALSE
)
```

Arguments

params	(iterable): iterable of parameters to optimize or dicts defining parameter groups
lr	(float, optional): learning rate (default: 1e-3)
betas	(Tuple[float, float], optional): coefficients used for computing running averages of gradient and its square (default: (0.9, 0.999))
eps	(float, optional): term added to the denominator to improve numerical stability (default: 1e-8)
weight_decay	(float, optional): weight decay (L2 penalty) (default: 0)
amsgrad	(boolean, optional): whether to use the AMSGrad variant of this algorithm from the paper On the Convergence of Adam and Beyond (default: FALSE)

Fields and Methods

See OptimizerIgnite.

Examples

```
if (torch_is_installed()) {
## Not run:
optimizer <- optim_ignite_adamw(model$parameters(), lr = 0.1)
optimizer$zero_grad()
loss_fn(model(input), target)$backward()
optimizer$step()

## End(Not run)
}
```

optim_ignite_rmsprop *LibTorch implementation of RMSprop*

Description

Proposed by G. Hinton in his course.

Usage

```
optim_ignite_rmsprop(
  params,
  lr = 0.01,
  alpha = 0.99,
  eps = 1e-08,
  weight_decay = 0,
  momentum = 0,
  centered = FALSE
)
```

Arguments

params	(iterable): iterable of parameters to optimize or list defining parameter groups
lr	(float, optional): learning rate (default: 1e-2)
alpha	(float, optional): smoothing constant (default: 0.99)
eps	(float, optional): term added to the denominator to improve numerical stability (default: 1e-8)
weight_decay	optional weight decay penalty. (default: 0)
momentum	(float, optional): momentum factor (default: 0)
centered	(bool, optional) : if TRUE, compute the centered RMSProp, the gradient is normalized by an estimation of its variance weight_decay (float, optional): weight decay (L2 penalty) (default: 0)

Fields and Methods

See OptimizerIgnite.

Examples

```
if (torch_is_installed()) {
## Not run:
optimizer <- optim_ignite_rmsprop(model$parameters(), lr = 0.1)
optimizer$zero_grad()
loss_fn(model(input), target)$backward()
optimizer$step()

## End(Not run)
}
```

optim_ignite_sgd *LibTorch implementation of SGD*

Description

Implements stochastic gradient descent (optionally with momentum). Nesterov momentum is based on the formula from On the importance of initialization and momentum in deep learning.

Usage

```
optim_ignite_sgd(
  params,
  lr = optim_required(),
  momentum = 0,
  dampening = 0,
  weight_decay = 0,
  nesterov = FALSE
)
```

Arguments

params	(iterable): iterable of parameters to optimize or dicts defining parameter groups
lr	(float): learning rate
momentum	(float, optional): momentum factor (default: 0)
dampening	(float, optional): dampening for momentum (default: 0)
weight_decay	(float, optional): weight decay (L2 penalty) (default: 0)
nesterov	(bool, optional): enables Nesterov momentum (default: FALSE)

Fields and Methods

See OptimizerIgnite.

Examples

```
if (torch_is_installed()) {
## Not run:
optimizer <- optim_ignite_sgd(model$parameters(), lr = 0.1)
optimizer$zero_grad()
loss_fn(model(input), target)$backward()
optimizer$step()

## End(Not run)
}
```

optim_lbfgs *LBFGS optimizer*

Description

Implements L-BFGS algorithm, heavily inspired by minFunc

Usage

```
optim_lbfgs(
  params,
  lr = 1,
  max_iter = 20,
  max_eval = NULL,
  tolerance_grad = 1e-07,
  tolerance_change = 1e-09,
  history_size = 100,
  line_search_fn = NULL
)
```

Arguments

params	(iterable): iterable of parameters to optimize or dicts defining parameter groups
lr	(float): learning rate (default: 1)
max_iter	(int): maximal number of iterations per optimization step (default: 20)
max_eval	(int): maximal number of function evaluations per optimization step (default: max_iter * 1.25).
tolerance_grad	(float): termination tolerance on first order optimality (default: 1e-5).
tolerance_change	(float): termination tolerance on function value/parameter changes (default: 1e-9).
history_size	(int): update history size (default: 100).
line_search_fn	(str): either 'strong_wolfe' or None (default: None).

Details

This optimizer is different from the others in that in `optimizer$step()`, it needs to be passed a closure that (1) calculates the loss, (2) calls `backward()` on it, and (3) returns it. See example below.

Warning

This optimizer doesn't support per-parameter options and parameter groups (there can be only one).

Right now all parameters have to be on a single device. This will be improved in the future.

If you need to move a model to GPU via `$cuda()`, please do so before constructing optimizers for it. Parameters of a model after `$cuda()` will be different objects from those before the call. In general, you should make sure that the objects pointed to by model parameters subject to optimization remain the same over the whole lifecycle of optimizer creation and usage.

Note

This is a very memory intensive optimizer (it requires additional `param_bytes * (history_size + 1)` bytes). If it doesn't fit in memory try reducing the history size, or use a different algorithm.

Examples

```
if (torch_is_installed()) {
a <- 1
b <- 5
rosenbrock <- function(x) {
  x1 <- x[1]
  x2 <- x[2]
  (a - x1)^2 + b * (x2 - x1^2)^2
}

x <- torch_tensor(c(-1, 1), requires_grad = TRUE)

optimizer <- optim_lbfgs(x)
calc_loss <- function() {
  optimizer$zero_grad()
  value <- rosenbrock(x)
  value$backward()
  value
}

num_iterations <- 2
for (i in 1:num_iterations) {
  optimizer$step(calc_loss)
}

rosenbrock(x)

}
```

`optim_required` *Dummy value indicating a required value.*

Description

Dummy value indicating a required value.

Usage

```
optim_required()
```

`optim_rmsprop` *RMSprop optimizer*

Description

Proposed by G. Hinton in his course.

Usage

```
optim_rmsprop(
  params,
  lr = 0.01,
  alpha = 0.99,
  eps = 1e-08,
  weight_decay = 0,
  momentum = 0,
  centered = FALSE
)
```

Arguments

`params`	(iterable): iterable of parameters to optimize or list defining parameter groups
`lr`	(float, optional): learning rate (default: 1e-2)
`alpha`	(float, optional): smoothing constant (default: 0.99)
`eps`	(float, optional): term added to the denominator to improve numerical stability (default: 1e-8)
`weight_decay`	optional weight decay penalty. (default: 0)
`momentum`	(float, optional): momentum factor (default: 0)
`centered`	(bool, optional) : if `TRUE`, compute the centered RMSProp, the gradient is normalized by an estimation of its variance weight_decay (float, optional): weight decay (L2 penalty) (default: 0)

Warning

If you need to move a model to GPU via `$cuda()`, please do so before constructing optimizers for it. Parameters of a model after `$cuda()` will be different objects from those before the call. In general, you should make sure that the objects pointed to by model parameters subject to optimization remain the same over the whole lifecycle of optimizer creation and usage.

Note

The centered version first appears in Generating Sequences With Recurrent Neural Networks. The implementation here takes the square root of the gradient average before adding epsilon (note that TensorFlow interchanges these two operations). The effective learning rate is thus $\alpha/(\sqrt{v}+\epsilon)$ where α is the scheduled learning rate and v is the weighted moving average of the squared gradient.

Update rule:

$$\theta_{t+1} = \theta_t - \frac{\eta}{\sqrt{E[g^2]_t + \epsilon}} * g_t$$

`optim_rprop` *Implements the resilient backpropagation algorithm.*

Description

Proposed first in RPROP - A Fast Adaptive Learning Algorithm

Usage

```
optim_rprop(params, lr = 0.01, etas = c(0.5, 1.2), step_sizes = c(1e-06, 50))
```

Arguments

`params`	(iterable): iterable of parameters to optimize or lists defining parameter groups
`lr`	(float, optional): learning rate (default: 1e-2)
`etas`	(Tuple(float, float), optional): pair of (etaminus, etaplis), that are multiplicative increase and decrease factors (default: (0.5, 1.2))
`step_sizes`	(vector(float, float), optional): a pair of minimal and maximal allowed step sizes (default: (1e-6, 50))

Warning

If you need to move a model to GPU via `$cuda()`, please do so before constructing optimizers for it. Parameters of a model after `$cuda()` will be different objects from those before the call. In general, you should make sure that the objects pointed to by model parameters subject to optimization remain the same over the whole lifecycle of optimizer creation and usage.

Examples

```
if (torch_is_installed()) {
## Not run:
optimizer <- optim_rprop(model$parameters(), lr = 0.1)
optimizer$zero_grad()
loss_fn(model(input), target)$backward()
optimizer$step()

## End(Not run)
}
```

`optim_sgd` *SGD optimizer*

Description

Implements stochastic gradient descent (optionally with momentum). Nesterov momentum is based on the formula from On the importance of initialization and momentum in deep learning.

Usage

```
optim_sgd(
  params,
  lr = optim_required(),
  momentum = 0,
  dampening = 0,
  weight_decay = 0,
  nesterov = FALSE
)
```

Arguments

`params`	(iterable): iterable of parameters to optimize or dicts defining parameter groups
`lr`	(float): learning rate
`momentum`	(float, optional): momentum factor (default: 0)
`dampening`	(float, optional): dampening for momentum (default: 0)
`weight_decay`	(float, optional): weight decay (L2 penalty) (default: 0)
`nesterov`	(bool, optional): enables Nesterov momentum (default: FALSE)

Note

The implementation of SGD with Momentum-Nesterov subtly differs from Sutskever et. al. and implementations in some other frameworks.

Considering the specific case of Momentum, the update can be written as

$$\begin{aligned} v_{t+1} &= \mu * v_t + g_{t+1}, \\ p_{t+1} &= p_t - \text{lr} * v_{t+1}, \end{aligned}$$

where p, g, v and μ denote the parameters, gradient, velocity, and momentum respectively.

This is in contrast to Sutskever et. al. and other frameworks which employ an update of the form

$$\begin{aligned} v_{t+1} &= \mu * v_t + \text{lr} * g_{t+1}, \\ p_{t+1} &= p_t - v_{t+1}. \end{aligned}$$

The Nesterov version is analogously modified.

Warning

If you need to move a model to GPU via `$cuda()`, please do so before constructing optimizers for it. Parameters of a model after `$cuda()` will be different objects from those before the call. In general, you should make sure that the objects pointed to by model parameters subject to optimization remain the same over the whole lifecycle of optimizer creation and usage.

Examples

```
if (torch_is_installed()) {
## Not run:
optimizer <- optim_sgd(model$parameters(), lr = 0.1, momentum = 0.9)
optimizer$zero_grad()
loss_fn(model(input), target)$backward()
optimizer$step()

## End(Not run)

}
```

---

sampler *Creates a new Sampler*

Description

Samplers can be used with `dataloader()` when creating batches from a torch `dataset()`.

Usage

```
sampler(
  name = NULL,
  inherit = Sampler,
  ...,
  private = NULL,
  active = NULL,
  parent_env = parent.frame()
)
```

Arguments

`name`	(optional) name of the sampler
`inherit`	(optional) you can inherit from other samplers to re-use some methods.
`...`	Pass any number of fields or methods. You should at least define the `initialize` and `step` methods. See the examples section.
`private`	(optional) a list of private methods for the sampler
`active`	(optional) a list of active methods for the sampler.
`parent_env`	used to capture the right environment to define the class. The default is fine for most situations.

Details

A sampler must implement the `.iter` and `.length()` methods.

- `initialize` takes in a `data_source`. In general this is a `dataset()`.
- `.iter` returns a function that returns a dataset index everytime it's called.
- `.length` returns the maximum number of samples that can be retrieved from that sampler.

---

tensor_dataset *Dataset wrapping tensors.*

Description

Each sample will be retrieved by indexing tensors along the first dimension.

Usage

```
tensor_dataset(...)
```

Arguments

`...`	tensors that have the same size of the first dimension.

---

threads *Number of threads*

Description

Get and set the numbers used by torch computations.

Usage

```
torch_set_num_threads(num_threads)

torch_set_num_interop_threads(num_threads)

torch_get_num_interop_threads()

torch_get_num_threads()
```

Arguments

`num_threads`	number of threads to set.

Details

For details see the CPU threading article in the PyTorch documentation.

Note

torch_set_threads do not work on macOS system as it must be 1.

---

torch_abs *Abs*

Description

Abs

Usage

```
torch_abs(self)
```

Arguments

`self`	(Tensor) the input tensor.

abs(input) -> Tensor

Computes the element-wise absolute value of the given `input` tensor.

$$\text{out}_i = |\text{input}_i|$$

Examples

```
if (torch_is_installed()) {

torch_abs(torch_tensor(c(-1, -2, 3)))
}
```

---

torch_absolute *Absolute*

Description

Absolute

Usage

```
torch_absolute(self)
```

Arguments

`self`	(Tensor) the input tensor.

absolute(input, *, out=None) -> Tensor

Alias for `torch_abs()`

torch_acos *Acos*

Description

Acos

Usage

```
torch_acos(self)
```

Arguments

self	(Tensor) the input tensor.

acos(input) -> Tensor

Returns a new tensor with the arccosine of the elements of `input`.

$$\text{out}_i = \cos^{-1}(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_acos(a)
}
```

torch_acosh *Acosh*

Description

Acosh

Usage

```
torch_acosh(self)
```

Arguments

self	(Tensor) the input tensor.

acosh(input, *, out=None) -> Tensor

Returns a new tensor with the inverse hyperbolic cosine of the elements of `input`.

Note

The domain of the inverse hyperbolic cosine is `[1, inf)` and values outside this range will be mapped to `NaN`, except for `+ INF` for which the output is mapped to `+ INF`.

$$\text{out}_i = \cosh^{-1}(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

a <- torch_randn(c(4))$uniform_(1, 2)
a
torch_acosh(a)
}
```

`torch_adaptive_avg_pool1d` *Adaptive_avg_pool1d*

Description

Adaptive_avg_pool1d

Usage

```
torch_adaptive_avg_pool1d(self, output_size)
```

Arguments

`self`	the input tensor
`output_size`	the target output size (single integer)

adaptive_avg_pool1d(input, output_size) -> Tensor

Applies a 1D adaptive average pooling over an input signal composed of several input planes.

See `nn_adaptive_avg_pool1d()` for details and output shape.

torch_add *Add*

Description

Add

Usage

```
torch_add(self, other, alpha = 1L)
```

Arguments

self	(Tensor) the input tensor.
other	(Tensor/Number) the second input tensor/number.
alpha	(Number) the scalar multiplier for other

add(input, other, out=NULL)

Adds the scalar other to each element of the input input and returns a new resulting tensor.

$$\text{out} = \text{input} + \text{other}$$

If input is of type FloatTensor or DoubleTensor, other must be a real number, otherwise it should be an integer.

add(input, other, *, alpha=1, out=NULL)

Each element of the tensor other is multiplied by the scalar alpha and added to each element of the tensor input. The resulting tensor is returned.

The shapes of input and other must be broadcastable .

$$\text{out} = \text{input} + \text{alpha} \times \text{other}$$

If other is of type FloatTensor or DoubleTensor, alpha must be a real number, otherwise it should be an integer.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_add(a, 20)


a = torch_randn(c(4))
a
```

```
b = torch_randn(c(4, 1))
b
torch_add(a, b)
}
```

---

torch_addbmm *Addbmm*

Description

Addbmm

Usage

```
torch_addbmm(self, batch1, batch2, beta = 1L, alpha = 1L)
```

Arguments

self	(Tensor) matrix to be added
batch1	(Tensor) the first batch of matrices to be multiplied
batch2	(Tensor) the second batch of matrices to be multiplied
beta	(Number, optional) multiplier for input (β)
alpha	(Number, optional) multiplier for batch1 @ batch2 (α)

addbmm(input, batch1, batch2, *, beta=1, alpha=1, out=NULL) -> Tensor

Performs a batch matrix-matrix product of matrices stored in batch1 and batch2, with a reduced add step (all matrix multiplications get accumulated along the first dimension). input is added to the final result.

batch1 and batch2 must be 3-D tensors each containing the same number of matrices.

If batch1 is a $(b \times n \times m)$ tensor, batch2 is a $(b \times m \times p)$ tensor, input must be broadcastable with a $(n \times p)$ tensor and out will be a $(n \times p)$ tensor.

$$out = \beta \text{ input} + \alpha \, (\sum_{i=0}^{b-1} \text{batch1}_i \, @ \, \text{batch2}_i)$$

For inputs of type FloatTensor or DoubleTensor, arguments beta and alpha must be real numbers, otherwise they should be integers.

Examples

```
if (torch_is_installed()) {

M = torch_randn(c(3, 5))
batch1 = torch_randn(c(10, 3, 4))
batch2 = torch_randn(c(10, 4, 5))
torch_addbmm(M, batch1, batch2)
}
```

torch_addcdiv *Addcdiv*

Description

Addcdiv

Usage

```
torch_addcdiv(self, tensor1, tensor2, value = 1L)
```

Arguments

self	(Tensor) the tensor to be added
tensor1	(Tensor) the numerator tensor
tensor2	(Tensor) the denominator tensor
value	(Number, optional) multiplier for tensor1/tensor2

addcdiv(input, tensor1, tensor2, *, value=1, out=NULL) -> Tensor

Performs the element-wise division of `tensor1` by `tensor2`, multiply the result by the scalar `value` and add it to `input`.

Warning

Integer division with addcdiv is deprecated, and in a future release addcdiv will perform a true division of `tensor1` and `tensor2`. The current addcdiv behavior can be replicated using `torch_floor_divide()` for integral inputs (`input` + `value` * `tensor1` // `tensor2`) and `torch_div()` for float inputs (`input` + `value` * `tensor1` / `tensor2`). The new addcdiv behavior can be implemented with `torch_true_divide()` (`input` + `value` * torch.true_divide(`tensor1`, `tensor2`).

$$\text{out}_i = \text{input}_i + \text{value} \times \frac{\text{tensor1}_i}{\text{tensor2}_i}$$

The shapes of `input`, `tensor1`, and `tensor2` must be broadcastable .

For inputs of type `FloatTensor` or `DoubleTensor`, `value` must be a real number, otherwise an integer.

Examples

```
if (torch_is_installed()) {

t = torch_randn(c(1, 3))
t1 = torch_randn(c(3, 1))
t2 = torch_randn(c(1, 3))
torch_addcdiv(t, t1, t2, 0.1)
}
```

torch_addcmul *Addcmul*

Description

Addcmul

Usage

```
torch_addcmul(self, tensor1, tensor2, value = 1L)
```

Arguments

self	(Tensor) the tensor to be added
tensor1	(Tensor) the tensor to be multiplied
tensor2	(Tensor) the tensor to be multiplied
value	(Number, optional) multiplier for $tensor1. * tensor2$

addcmul(input, tensor1, tensor2, *, value=1, out=NULL) -> Tensor

Performs the element-wise multiplication of `tensor1` by `tensor2`, multiply the result by the scalar `value` and add it to `input`.

$$\text{out}_i = \text{input}_i + \text{value} \times \text{tensor1}_i \times \text{tensor2}_i$$

The shapes of `tensor`, `tensor1`, and `tensor2` must be broadcastable .

For inputs of type `FloatTensor` or `DoubleTensor`, `value` must be a real number, otherwise an integer.

Examples

```
if (torch_is_installed()) {

t = torch_randn(c(1, 3))
t1 = torch_randn(c(3, 1))
t2 = torch_randn(c(1, 3))
torch_addcmul(t, t1, t2, 0.1)
}
```

torch_addmm *Addmm*

Description

Addmm

Usage

```
torch_addmm(self, mat1, mat2, beta = 1L, alpha = 1L)
```

Arguments

self	(Tensor) matrix to be added
mat1	(Tensor) the first matrix to be multiplied
mat2	(Tensor) the second matrix to be multiplied
beta	(Number, optional) multiplier for input (β)
alpha	(Number, optional) multiplier for $mat1@mat2$ (α)

addmm(input, mat1, mat2, *, beta=1, alpha=1, out=NULL) -> Tensor

Performs a matrix multiplication of the matrices mat1 and mat2. The matrix input is added to the final result.

If mat1 is a $(n \times m)$ tensor, mat2 is a $(m \times p)$ tensor, then input must be broadcastable with a $(n \times p)$ tensor and out will be a $(n \times p)$ tensor.

alpha and beta are scaling factors on matrix-vector product between mat1 and mat2 and the added matrix input respectively.

$$\text{out} = \beta\ \text{input} + \alpha\ (\text{mat1}_i \ @\ \text{mat2}_i)$$

For inputs of type FloatTensor or DoubleTensor, arguments beta and alpha must be real numbers, otherwise they should be integers.

Examples

```
if (torch_is_installed()) {

M = torch_randn(c(2, 3))
mat1 = torch_randn(c(2, 3))
mat2 = torch_randn(c(3, 3))
torch_addmm(M, mat1, mat2)
}
```

torch_addmv *Addmv*

Description

Addmv

Usage

```
torch_addmv(self, mat, vec, beta = 1L, alpha = 1L)
```

Arguments

self	(Tensor) vector to be added
mat	(Tensor) matrix to be multiplied
vec	(Tensor) vector to be multiplied
beta	(Number, optional) multiplier for input (β)
alpha	(Number, optional) multiplier for $mat@vec$ (α)

addmv(input, mat, vec, *, beta=1, alpha=1, out=NULL) -> Tensor

Performs a matrix-vector product of the matrix mat and the vector vec. The vector input is added to the final result.

If mat is a $(n \times m)$ tensor, vec is a 1-D tensor of size m, then input must be broadcastable with a 1-D tensor of size n and out will be 1-D tensor of size n.

alpha and beta are scaling factors on matrix-vector product between mat and vec and the added tensor input respectively.

$$\text{out} = \beta\ \text{input} + \alpha\ (\text{mat} @ \text{vec})$$

For inputs of type FloatTensor or DoubleTensor, arguments beta and alpha must be real numbers, otherwise they should be integers

Examples

```
if (torch_is_installed()) {

M = torch_randn(c(2))
mat = torch_randn(c(2, 3))
vec = torch_randn(c(3))
torch_addmv(M, mat, vec)
}
```

torch_addr *Addr*

Description

Addr

Usage

```
torch_addr(self, vec1, vec2, beta = 1L, alpha = 1L)
```

Arguments

self	(Tensor) matrix to be added
vec1	(Tensor) the first vector of the outer product
vec2	(Tensor) the second vector of the outer product
beta	(Number, optional) multiplier for input (β)
alpha	(Number, optional) multiplier for vec1 $\otimes$ vec2 (α)

addr(input, vec1, vec2, *, beta=1, alpha=1, out=NULL) -> Tensor

Performs the outer-product of vectors vec1 and vec2 and adds it to the matrix input.

Optional values beta and alpha are scaling factors on the outer product between vec1 and vec2 and the added matrix input respectively.

$$\text{out} = \beta\ \text{input} + \alpha\ (\text{vec1} \otimes \text{vec2})$$

If vec1 is a vector of size n and vec2 is a vector of size m, then input must be broadcastable with a matrix of size $(n \times m)$ and out will be a matrix of size $(n \times m)$.

For inputs of type FloatTensor or DoubleTensor, arguments beta and alpha must be real numbers, otherwise they should be integers

Examples

```
if (torch_is_installed()) {

vec1 = torch_arange(1, 3)
vec2 = torch_arange(1, 2)
M = torch_zeros(c(3, 2))
torch_addr(M, vec1, vec2)
}
```

torch_allclose *Allclose*

Description

Allclose

Usage

```
torch_allclose(self, other, rtol = 1e-05, atol = 1e-08, equal_nan = FALSE)
```

Arguments

self	(Tensor) first tensor to compare
other	(Tensor) second tensor to compare
rtol	(float, optional) relative tolerance. Default: 1e-05
atol	(float, optional) absolute tolerance. Default: 1e-08
equal_nan	(bool, optional) if TRUE, then two NaN s will be compared as equal. Default: FALSE

allclose(input, other, rtol=1e-05, atol=1e-08, equal_nan=False) -> bool

This function checks if all input and other satisfy the condition:

$$|\text{input} - \text{other}| \leq \text{atol} + \text{rtol} \times |\text{other}|$$

elementwise, for all elements of input and other. The behaviour of this function is analogous to numpy.allclose <https://docs.scipy.org/doc/numpy/reference/generated/numpy.allclose.html>_

Examples

```
if (torch_is_installed()) {

torch_allclose(torch_tensor(c(10000., 1e-07)), torch_tensor(c(10000.1, 1e-08)))
torch_allclose(torch_tensor(c(10000., 1e-08)), torch_tensor(c(10000.1, 1e-09)))
torch_allclose(torch_tensor(c(1.0, NaN)), torch_tensor(c(1.0, NaN)))
torch_allclose(torch_tensor(c(1.0, NaN)), torch_tensor(c(1.0, NaN)), equal_nan=TRUE)
}
```

torch_amax *Amax*

Description

Amax

Usage

```
torch_amax(self, dim = list(), keepdim = FALSE)
```

Arguments

self	(Tensor) the input tensor.
dim	(int or tuple of ints) the dimension or dimensions to reduce.
keepdim	(bool) whether the output tensor has dim retained or not.

amax(input, dim, keepdim=FALSE, *, out=None) -> Tensor

Returns the maximum value of each slice of the input tensor in the given dimension(s) dim.

Note

The difference between max/min and amax/amin is:

- amax/amin supports reducing on multiple dimensions,
- amax/amin does not return indices,
- amax/amin evenly distributes gradient between equal values, while max(dim)/min(dim) propagates gradient only to a single index in the source tensor.

If keepdim is TRUE, the output tensors are of the same size as inputexcept in the dimension(s)dimwhere the
put‘.

Examples

```
if (torch_is_installed()) {

a <- torch_randn(c(4, 4))
a
torch_amax(a, 1)
}
```

torch_amin *Amin*

Description

Amin

Usage

```
torch_amin(self, dim = list(), keepdim = FALSE)
```

Arguments

self	(Tensor) the input tensor.
dim	(int or tuple of ints) the dimension or dimensions to reduce.
keepdim	(bool) whether the output tensor has dim retained or not.

amin(input, dim, keepdim=FALSE, *, out=None) -> Tensor

Returns the minimum value of each slice of the input tensor in the given dimension(s) dim.

Note

The difference between max/min and amax/amin is:

- amax/amin supports reducing on multiple dimensions,
- amax/amin does not return indices,
- amax/amin evenly distributes gradient between equal values, while max(dim)/min(dim) propagates gradient only to a single index in the source tensor.

If keepdim is TRUE, the output tensors are of the same size as input except in the dimension(s) dim where they are of size 1. Otherwise, dims are squeezed (see torch_squeeze()), resulting in the output tensors having fewer dimensions than input.

Examples

```
if (torch_is_installed()) {

a <- torch_randn(c(4, 4))
a
torch_amin(a, 1)
}
```

torch_angle *Angle*

Description

Angle

Usage

```
torch_angle(self)
```

Arguments

self	(Tensor) the input tensor.

angle(input) -> Tensor

Computes the element-wise angle (in radians) of the given input tensor.

$$\text{out}_i = angle(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {
## Not run:
torch_angle(torch_tensor(c(-1 + 1i, -2 + 2i, 3 - 3i)))*180/3.14159

## End(Not run)

}
```

torch_arange *Arange*

Description

Arange

Usage

```
torch_arange(
  start,
  end,
  step = 1L,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

start	(Number) the starting value for the set of points. Default: 0.
end	(Number) the ending value for the set of points
step	(Number) the gap between each pair of adjacent points. Default: 1.
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type). If dtype is not given, infer the data type from the other input arguments. If any of start, end, or stop are floating-point, the dtype is inferred to be the default dtype, see ~torch.get_default_dtype. Otherwise, the dtype is inferred to be torch.int64.
layout	(torch.layout, optional) the desired layout of returned Tensor. Default: torch_strided.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

arange(start=0, end, step=1, out=NULL, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Returns a 1-D tensor of size $\left\lceil \frac{\text{end} - \text{start}}{\text{step}} \right\rceil$ with values from the interval [start, end) taken with common difference step beginning from start.

Note that non-integer step is subject to floating point rounding errors when comparing against end; to avoid inconsistency, we advise adding a small epsilon to end in such cases.

$$\text{out}_{i+1} = \text{out}_i + \text{step}$$

Examples

```
if (torch_is_installed()) {

torch_arange(start = 0, end = 5)
torch_arange(1, 4)
```

```
torch_arange(1, 2.5, 0.5)
}
```

---

torch_arccos *Arccos*

Description

Arccos

Usage

```
torch_arccos(self)
```

Arguments

self	(Tensor) the input tensor.

arccos(input, *, out=None) -> Tensor

Alias for torch_acos().

---

torch_arccosh *Arccosh*

Description

Arccosh

Usage

```
torch_arccosh(self)
```

Arguments

self	(Tensor) the input tensor.

arccosh(input, *, out=None) -> Tensor

Alias for torch_acosh().

torch_arcsin *Arcsin*

Description

Arcsin

Usage

```
torch_arcsin(self)
```

Arguments

self	(Tensor) the input tensor.

arcsin(input, *, out=None) -> Tensor

Alias for `torch_asin()`.

torch_arcsinh *Arcsinh*

Description

Arcsinh

Usage

```
torch_arcsinh(self)
```

Arguments

self	(Tensor) the input tensor.

arcsinh(input, *, out=None) -> Tensor

Alias for `torch_asinh()`.

torch_arctan *Arctan*

Description

Arctan

Usage

```
torch_arctan(self)
```

Arguments

self	(Tensor) the input tensor.

arctan(input, *, out=None) -> Tensor

Alias for torch_atan().

torch_arctanh *Arctanh*

Description

Arctanh

Usage

```
torch_arctanh(self)
```

Arguments

self	(Tensor) the input tensor.

arctanh(input, *, out=None) -> Tensor

Alias for torch_atanh().

torch_argmax *Argmax*

Description

Argmax

Arguments

self	(Tensor) the input tensor.
dim	(int) the dimension to reduce. If NULL, the argmax of the flattened input is returned.
keepdim	(bool) whether the output tensor has dim retained or not. Ignored if dim=NULL.

argmax(input) -> LongTensor

Returns the indices of the maximum value of all elements in the input tensor.

This is the second value returned by torch_max. See its documentation for the exact semantics of this method.

argmax(input, dim, keepdim=False) -> LongTensor

Returns the indices of the maximum values of a tensor across a dimension.

This is the second value returned by torch_max. See its documentation for the exact semantics of this method.

Examples

```
if (torch_is_installed()) {

## Not run:
a = torch_randn(c(4, 4))
a
torch_argmax(a)

## End(Not run)


a = torch_randn(c(4, 4))
a
torch_argmax(a, dim=1)
}
```

torch_argmin *Argmin*

Description

Argmin

Arguments

self	(Tensor) the input tensor.
dim	(int) the dimension to reduce. If NULL, the argmin of the flattened input is returned.
keepdim	(bool) whether the output tensor has dim retained or not. Ignored if dim=NULL.

argmin(input) -> LongTensor

Returns the indices of the minimum value of all elements in the input tensor.

This is the second value returned by torch_min. See its documentation for the exact semantics of this method.

argmin(input, dim, keepdim=False, out=NULL) -> LongTensor

Returns the indices of the minimum values of a tensor across a dimension.

This is the second value returned by torch_min. See its documentation for the exact semantics of this method.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4, 4))
a
torch_argmin(a)


a = torch_randn(c(4, 4))
a
torch_argmin(a, dim=1)
}
```

torch_argsort *Argsort*

Description

Argsort

Usage

```
torch_argsort(self, dim = -1L, descending = FALSE)
```

Arguments

self	(Tensor) the input tensor.
dim	(int, optional) the dimension to sort along
descending	(bool, optional) controls the sorting order (ascending or descending)

argsort(input, dim=-1, descending=False) -> LongTensor

Returns the indices that sort a tensor along a given dimension in ascending order by value.

This is the second value returned by `torch_sort`. See its documentation for the exact semantics of this method.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4, 4))
a
torch_argsort(a, dim=1)
}
```

torch_asin *Asin*

Description

Asin

Usage

```
torch_asin(self)
```

Arguments

self	(Tensor) the input tensor.

asin(input, out=NULL) -> Tensor

Returns a new tensor with the arcsine of the elements of `input`.

$$\text{out}_i = \sin^{-1}(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_asin(a)
}
```

`torch_asinh` *Asinh*

Description

Asinh

Usage

```
torch_asinh(self)
```

Arguments

`self`	(Tensor) the input tensor.

asinh(input, *, out=None) -> Tensor

Returns a new tensor with the inverse hyperbolic sine of the elements of `input`.

$$\text{out}_i = \sinh^{-1}(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

a <- torch_randn(c(4))
a
torch_asinh(a)
}
```

torch_as_strided *As_strided*

Description

As_strided

Usage

```
torch_as_strided(self, size, stride, storage_offset = NULL)
```

Arguments

self	(Tensor) the input tensor.
size	(tuple or ints) the shape of the output tensor
stride	(tuple or ints) the stride of the output tensor
storage_offset	(int, optional) the offset in the underlying storage of the output tensor

as_strided(input, size, stride, storage_offset=0) -> Tensor

Create a view of an existing `torch_Tensor` `input` with specified `size`, `stride` and `storage_offset`.

Warning

More than one element of a created tensor may refer to a single memory location. As a result, in-place operations (especially ones that are vectorized) may result in incorrect behavior. If you need to write to the tensors, please clone them first.

```
Many PyTorch functions, which return a view of a tensor, are internally
implemented with this function. Those functions, like
`torch_Tensor.expand`, are easier to read and are therefore more
advisable to use.
```

Examples

```
if (torch_is_installed()) {

x = torch_randn(c(3, 3))
x
t = torch_as_strided(x, list(2, 2), list(1, 2))
t
t = torch_as_strided(x, list(2, 2), list(1, 2), 1)
t
}
```

torch_atan *Atan*

Description

Atan

Usage

```
torch_atan(self)
```

Arguments

self	(Tensor) the input tensor.

atan(input, out=NULL) -> Tensor

Returns a new tensor with the arctangent of the elements of `input`.

$$\text{out}_i = \tan^{-1}(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_atan(a)
}
```

torch_atan2 *Atan2*

Description

Atan2

Usage

```
torch_atan2(self, other)
```

Arguments

self	(Tensor) the first input tensor
other	(Tensor) the second input tensor

atan2(input, other, out=NULL) -> Tensor

Element-wise arctangent of $\text{input}_i/\text{other}_i$ with consideration of the quadrant. Returns a new tensor with the signed angles in radians between vector $(\text{other}_i, \text{input}_i)$ and vector $(1, 0)$. (Note that other_i, the second parameter, is the x-coordinate, while input_i, the first parameter, is the y-coordinate.)

The shapes of `input` and `other` must be broadcastable .

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_atan2(a, torch_randn(c(4)))
}
```

`torch_atanh` *Atanh*

Description

Atanh

Usage

```
torch_atanh(self)
```

Arguments

`self`	(Tensor) the input tensor.

atanh(input, *, out=None) -> Tensor

Returns a new tensor with the inverse hyperbolic tangent of the elements of `input`.

Note

The domain of the inverse hyperbolic tangent is `(-1, 1)` and values outside this range will be mapped to `NaN`, except for the values `1` and `-1` for which the output is mapped to `+/-INF` respectively.

$$\text{out}_i = \tanh^{-1}(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))$uniform_(-1, 1)
a
torch_atanh(a)
}
```

---

torch_atleast_1d *Atleast_1d*

Description

Returns a 1-dimensional view of each input tensor with zero dimensions. Input tensors with one or more dimensions are returned as-is.

Usage

```
torch_atleast_1d(self)
```

Arguments

self	(Tensor or list of Tensors)

Examples

```
if (torch_is_installed()) {

x <- torch_randn(c(2))
x
torch_atleast_1d(x)
x <- torch_tensor(1.)
x
torch_atleast_1d(x)
x <- torch_tensor(0.5)
y <- torch_tensor(1.)
torch_atleast_1d(list(x,y))
}
```

torch_atleast_2d *Atleast_2d*

Description

Returns a 2-dimensional view of each each input tensor with zero dimensions. Input tensors with two or more dimensions are returned as-is.

Usage

```
torch_atleast_2d(self)
```

Arguments

self	(Tensor or list of Tensors)

Examples

```
if (torch_is_installed()) {

x <- torch_tensor(1.)
x
torch_atleast_2d(x)
x <- torch_randn(c(2,2))
x
torch_atleast_2d(x)
x <- torch_tensor(0.5)
y <- torch_tensor(1.)
torch_atleast_2d(list(x,y))
}
```

torch_atleast_3d *Atleast_3d*

Description

Returns a 3-dimensional view of each each input tensor with zero dimensions. Input tensors with three or more dimensions are returned as-is.

Usage

```
torch_atleast_3d(self)
```

Arguments

self	(Tensor or list of Tensors)

torch_avg_pool1d *Avg_pool1d*

Description

Avg_pool1d

Usage

```
torch_avg_pool1d(
  self,
  kernel_size,
  stride = list(),
  padding = 0L,
  ceil_mode = FALSE,
  count_include_pad = TRUE
)
```

Arguments

self	input tensor of shape $(\text{minibatch}, \text{in_channels}, iW)$
kernel_size	the size of the window. Can be a single number or a tuple `(kW,)`
stride	the stride of the window. Can be a single number or a tuple `(sW,)`. Default: `kernel_size`
padding	implicit zero paddings on both sides of the input. Can be a single number or a tuple `(padW,)`. Default: 0
ceil_mode	when `TRUE`, will use `ceil` instead of `floor` to compute the output shape. Default: `FALSE`
count_include_pad	when `TRUE`, will include the zero-padding in the averaging calculation. Default: `TRUE`

avg_pool1d(input, kernel_size, stride=NULL, padding=0, ceil_mode=FALSE, count_include_pad=TRUE) -> Tensor

Applies a 1D average pooling over an input signal composed of several input planes.

See `nn_avg_pool1d()` for details and output shape.

torch_baddbmm *Baddbmm*

Description

Baddbmm

Usage

```
torch_baddbmm(self, batch1, batch2, beta = 1L, alpha = 1L)
```

Arguments

self	(Tensor) the tensor to be added
batch1	(Tensor) the first batch of matrices to be multiplied
batch2	(Tensor) the second batch of matrices to be multiplied
beta	(Number, optional) multiplier for input (β)
alpha	(Number, optional) multiplier for batch1 @ batch2 (α)

baddbmm(input, batch1, batch2, *, beta=1, alpha=1, out=NULL) -> Tensor

Performs a batch matrix-matrix product of matrices in batch1 and batch2. input is added to the final result.

batch1 and batch2 must be 3-D tensors each containing the same number of matrices.

If batch1 is a $(b \times n \times m)$ tensor, batch2 is a $(b \times m \times p)$ tensor, then input must be broadcastable with a $(b \times n \times p)$ tensor and out will be a $(b \times n \times p)$ tensor. Both alpha and beta mean the same as the scaling factors used in torch_addbmm.

$$\text{out}_i = \beta\ \text{input}_i + \alpha\ (\text{batch1}_i \ @\ \text{batch2}_i)$$

For inputs of type FloatTensor or DoubleTensor, arguments beta and alpha must be real numbers, otherwise they should be integers.

Examples

```
if (torch_is_installed()) {

M = torch_randn(c(10, 3, 5))
batch1 = torch_randn(c(10, 3, 4))
batch2 = torch_randn(c(10, 4, 5))
torch_baddbmm(M, batch1, batch2)
}
```

torch_bartlett_window *Bartlett_window*

Description

Bartlett_window

Usage

```
torch_bartlett_window(
  window_length,
  periodic = TRUE,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

window_length	(int) the size of returned window
periodic	(bool, optional) If TRUE, returns a window to be used as periodic function. If False, return a symmetric window.
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type). Only floating point types are supported.
layout	(torch.layout, optional) the desired layout of returned window tensor. Only torch_strided (dense layout) is supported.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

bartlett_window(window_length, periodic=TRUE, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Bartlett window function.

$$w[n] = 1 - \left| \frac{2n}{N-1} - 1 \right| = \begin{cases} \frac{2n}{N-1} & \text{if } 0 \leq n \leq \frac{N-1}{2} \\ 2 - \frac{2n}{N-1} & \text{if } \frac{N-1}{2} < n < N \end{cases},$$

where N is the full window size.

The input window_length is a positive integer controlling the returned window size. periodic flag determines whether the returned window trims off the last duplicate value from the symmetric

window and is ready to be used as a periodic window with functions like `torch_stft`. Therefore, if `periodic` is true, the N in above formula is in fact window_length $+ 1$. Also, we always have `torch_bartlett_window(L, periodic=TRUE)` equal to `torch_bartlett_window(L + 1, periodic=False)[:-1])`.

Note

```
If `window_length` \eqn{=1}, the returned window contains a single value 1.
```

`torch_bernoulli` *Bernoulli*

Description

Bernoulli

Usage

```
torch_bernoulli(self, p, generator = NULL)
```

Arguments

`self`	(Tensor) the input tensor of probability values for the Bernoulli distribution
`p`	(Number) a probability value. If `p` is passed than it's used instead of the values in `self` tensor.
`generator`	(`torch.Generator`, optional) a pseudorandom number generator for sampling

bernoulli(input, *, generator=NULL, out=NULL) -> Tensor

Draws binary random numbers (0 or 1) from a Bernoulli distribution.

The `input` tensor should be a tensor containing probabilities to be used for drawing the binary random number. Hence, all values in `input` have to be in the range: $0 \leq \text{input}_i \leq 1$.

The ith element of the output tensor will draw a value 1 according to the ith probability value given in `input`.

$$\text{out}_i \sim \text{Bernoulli}(p = \text{input}_i)$$

The returned `out` tensor only has values 0 or 1 and is of the same shape as `input`.

`out` can have integral `dtype`, but `input` must have floating point `dtype`.

Examples

```
if (torch_is_installed()) {

a = torch_empty(c(3, 3))$uniform_(0, 1)  # generate a uniform random matrix with range c(0, 1)
a
torch_bernoulli(a)
a = torch_ones(c(3, 3)) # probability of drawing "1" is 1
torch_bernoulli(a)
a = torch_zeros(c(3, 3)) # probability of drawing "1" is 0
torch_bernoulli(a)
}
```

---

torch_bincount *Bincount*

Description

Bincount

Arguments

`self`	(Tensor) 1-d int tensor
`weights`	(Tensor) optional, weight for each value in the input tensor. Should be of same size as input tensor.
`minlength`	(int) optional, minimum number of bins. Should be non-negative.

bincount(input, weights=NULL, minlength=0) -> Tensor

Count the frequency of each value in an array of non-negative ints.

The number of bins (size 1) is one larger than the largest value in `input` unless `input` is empty, in which case the result is a tensor of size 0. If `minlength` is specified, the number of bins is at least `minlength` and if `input` is empty, then the result is tensor of size `minlength` filled with zeros. If `n` is the value at position `i`, `out[n] += weights[i]` if `weights` is specified else `out[n] += 1`.

.. include:: cuda_deterministic.rst

Examples

```
if (torch_is_installed()) {

input = torch_randint(1, 8, list(5), dtype=torch_int64())
weights = torch_linspace(0, 1, steps=5)
input
weights
torch_bincount(input, weights)
input$bincount(weights)
}
```

torch_bitwise_and *Bitwise_and*

Description

Bitwise_and

Usage

```
torch_bitwise_and(self, other)
```

Arguments

self	NA the first input tensor
other	NA the second input tensor

bitwise_and(input, other, out=NULL) -> Tensor

Computes the bitwise AND of `input` and `other`. The input tensor must be of integral or Boolean types. For bool tensors, it computes the logical AND.

torch_bitwise_not *Bitwise_not*

Description

Bitwise_not

Usage

```
torch_bitwise_not(self)
```

Arguments

self	(Tensor) the input tensor.

bitwise_not(input, out=NULL) -> Tensor

Computes the bitwise NOT of the given input tensor. The input tensor must be of integral or Boolean types. For bool tensors, it computes the logical NOT.

torch_bitwise_or *Bitwise_or*

Description

Bitwise_or

Usage

```
torch_bitwise_or(self, other)
```

Arguments

self	NA the first input tensor
other	NA the second input tensor

bitwise_or(input, other, out=NULL) -> Tensor

Computes the bitwise OR of `input` and `other`. The input tensor must be of integral or Boolean types. For bool tensors, it computes the logical OR.

torch_bitwise_xor *Bitwise_xor*

Description

Bitwise_xor

Usage

```
torch_bitwise_xor(self, other)
```

Arguments

self	NA the first input tensor
other	NA the second input tensor

bitwise_xor(input, other, out=NULL) -> Tensor

Computes the bitwise XOR of `input` and `other`. The input tensor must be of integral or Boolean types. For bool tensors, it computes the logical XOR.

torch_blackman_window *Blackman_window*

Description

Blackman_window

Usage

```
torch_blackman_window(
  window_length,
  periodic = TRUE,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

window_length	(int) the size of returned window
periodic	(bool, optional) If TRUE, returns a window to be used as periodic function. If False, return a symmetric window.
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type). Only floating point types are supported.
layout	(torch.layout, optional) the desired layout of returned window tensor. Only torch_strided (dense layout) is supported.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

blackman_window(window_length, periodic=TRUE, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Blackman window function.

$$w[n] = 0.42 - 0.5 \cos \left(\frac{2\pi n}{N-1} \right) + 0.08 \cos \left(\frac{4\pi n}{N-1} \right)$$

where N is the full window size.

The input window_length is a positive integer controlling the returned window size. periodic flag determines whether the returned window trims off the last duplicate value from the symmetric

window and is ready to be used as a periodic window with functions like `torch_stft`. Therefore, if `periodic` is true, the N in above formula is in fact window_length $+ 1$. Also, we always have `torch_blackman_window(L, periodic=TRUE)` equal to `torch_blackman_window(L + 1, periodic=False)[:-1])`.

Note

```
If `window_length` \eqn{=1}, the returned window contains a single value 1.
```

`torch_block_diag` *Block_diag*

Description

Create a block diagonal matrix from provided tensors.

Usage

```
torch_block_diag(tensors)
```

Arguments

`tensors`	(list of tensors) One or more tensors with 0, 1, or 2 dimensions.

Examples

```
if (torch_is_installed()) {

A <- torch_tensor(rbind(c(0, 1), c(1, 0)))
B <- torch_tensor(rbind(c(3, 4, 5), c(6, 7, 8)))
C <- torch_tensor(7)
D <- torch_tensor(c(1, 2, 3))
E <- torch_tensor(rbind(4, 5, 6))
torch_block_diag(list(A, B, C, D, E))
}
```

`torch_bmm` *Bmm*

Description

Bmm

Usage

```
torch_bmm(self, mat2)
```

Arguments

`self`	(Tensor) the first batch of matrices to be multiplied
`mat2`	(Tensor) the second batch of matrices to be multiplied

bmm(input, mat2, out=NULL) -> Tensor

Performs a batch matrix-matrix product of matrices stored in `input` and `mat2`.

`input` and `mat2` must be 3-D tensors each containing the same number of matrices.

If `input` is a $(b \times n \times m)$ tensor, `mat2` is a $(b \times m \times p)$ tensor, `out` will be a $(b \times n \times p)$ tensor.

$$\text{out}_i = \text{input}_i \mathbin{@} \text{mat2}_i$$

Note

This function does not broadcast . For broadcasting matrix products, see `torch_matmul`.

Examples

```
if (torch_is_installed()) {

input = torch_randn(c(10, 3, 4))
mat2 = torch_randn(c(10, 4, 5))
res = torch_bmm(input, mat2)
res
}
```

---

torch_broadcast_tensors *Broadcast_tensors*

Description

Broadcast_tensors

Usage

```
torch_broadcast_tensors(tensors)
```

Arguments

`tensors`	a list containing any number of tensors of the same type

broadcast_tensors(tensors) -> List of Tensors

Broadcasts the given tensors according to broadcasting-semantics.

Examples

```
if (torch_is_installed()) {

x = torch_arange(0, 3)$view(c(1, 4))
y = torch_arange(0, 2)$view(c(3, 1))
out = torch_broadcast_tensors(list(x, y))
out[[1]]
}
```

---

torch_bucketize *Bucketize*

Description

Bucketize

Usage

```
torch_bucketize(self, boundaries, out_int32 = FALSE, right = FALSE)
```

Arguments

self	(Tensor or Scalar) N-D tensor or a Scalar containing the search value(s).
boundaries	(Tensor) 1-D tensor, must contain a monotonically increasing sequence.
out_int32	(bool, optional) – indicate the output data type. torch_int32() if True, torch_int64() otherwise. Default value is FALSE, i.e. default output data type is torch_int64().
right	(bool, optional) – if False, return the first suitable location that is found. If True, return the last such index. If no suitable index found, return 0 for non-numerical value (eg. nan, inf) or the size of boundaries (one pass the last index). In other words, if False, gets the lower bound index for each value in input from boundaries. If True, gets the upper bound index instead. Default value is False.

bucketize(input, boundaries, *, out_int32=FALSE, right=FALSE, out=None) -> Tensor

Returns the indices of the buckets to which each value in the input belongs, where the boundaries of the buckets are set by boundaries. Return a new tensor with the same size as input. If right is FALSE (default), then the left boundary is closed.

Examples

```
if (torch_is_installed()) {

boundaries <- torch_tensor(c(1, 3, 5, 7, 9))
boundaries
v <- torch_tensor(rbind(c(3, 6, 9), c(3, 6, 9)))
v
torch_bucketize(v, boundaries)
torch_bucketize(v, boundaries, right=TRUE)
}
```

torch_can_cast *Can_cast*

Description

Can_cast

Usage

```
torch_can_cast(from_, to)
```

Arguments

from_	(dtype) The original torch_dtype.
to	(dtype) The target torch_dtype.

can_cast(from, to) -> bool

Determines if a type conversion is allowed under PyTorch casting rules described in the type promotion documentation .

Examples

```
if (torch_is_installed()) {

torch_can_cast(torch_double(), torch_float())
torch_can_cast(torch_float(), torch_int())
}
```

torch_cartesian_prod *Cartesian_prod*

Description

Do cartesian product of the given sequence of tensors.

Usage

```
torch_cartesian_prod(tensors)
```

Arguments

tensors	a list containing any number of 1 dimensional tensors.

Examples

```
if (torch_is_installed()) {

a = c(1, 2, 3)
b = c(4, 5)
tensor_a = torch_tensor(a)
tensor_b = torch_tensor(b)
torch_cartesian_prod(list(tensor_a, tensor_b))
}
```

---

torch_cat *Cat*

Description

Cat

Usage

```
torch_cat(tensors, dim = 1L)
```

Arguments

tensors	(sequence of Tensors) any python sequence of tensors of the same type. Non-empty tensors provided must have the same shape, except in the cat dimension.
dim	(int, optional) the dimension over which the tensors are concatenated

cat(tensors, dim=0, out=NULL) -> Tensor

Concatenates the given sequence of seq tensors in the given dimension. All tensors must either have the same shape (except in the concatenating dimension) or be empty.

torch_cat can be seen as an inverse operation for torch_split() and torch_chunk.

torch_cat can be best understood via examples.

Examples

```
if (torch_is_installed()) {

x = torch_randn(c(2, 3))
x
torch_cat(list(x, x, x), 1)
torch_cat(list(x, x, x), 2)
}
```

torch_cdist *Cdist*

Description

Cdist

Usage

```
torch_cdist(x1, x2, p = 2L, compute_mode = NULL)
```

Arguments

x1	(Tensor) input tensor of shape $B \times P \times M$.
x2	(Tensor) input tensor of shape $B \times R \times M$.
p	NA p value for the p-norm distance to calculate between each vector pair $\in [0, \infty]$.
compute_mode	NA 'use_mm_for_euclid_dist_if_necessary' - will use matrix multiplication approach to calculate euclidean distance (p = 2) if P > 25 or R > 25 'use_mm_for_euclid_dist' - will always use matrix multiplication approach to calculate euclidean distance (p = 2) 'donot_use_mm_for_euclid_dist' - will never use matrix multiplication approach to calculate euclidean distance (p = 2) Default: use_mm_for_euclid_dist_if_necessary.

TEST

Computes batched the p-norm distance between each pair of the two collections of row vectors.

torch_ceil *Ceil*

Description

Ceil

Usage

```
torch_ceil(self)
```

Arguments

self	(Tensor) the input tensor.

ceil(input, out=NULL) -> Tensor

Returns a new tensor with the ceil of the elements of `input`, the smallest integer greater than or equal to each element.

$$\text{out}_i = \lceil \text{input}_i \rceil = \lfloor \text{input}_i \rfloor + 1$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_ceil(a)
}
```

`torch_celu` *Celu*

Description

Celu

Usage

```
torch_celu(self, alpha = 1L)
```

Arguments

`self`	the input tensor
`alpha`	the alpha value for the CELU formulation. Default: 1.0

celu(input, alpha=1.) -> Tensor

See `nnf_celu()` for more info.

torch_celu_ *Celu_*

Description

Celu_

Usage

```
torch_celu_(self, alpha = 1L)
```

Arguments

self	the input tensor
alpha	the alpha value for the CELU formulation. Default: 1.0

celu_(input, alpha=1.) -> Tensor

In-place version of `torch_celu()`.

torch_chain_matmul *Chain_matmul*

Description

Chain_matmul

Usage

```
torch_chain_matmul(matrices)
```

Arguments

matrices	(Tensors...) a sequence of 2 or more 2-D tensors whose product is to be determined.

TEST

Returns the matrix product of the N 2-D tensors. This product is efficiently computed using the matrix chain order algorithm which selects the order in which incurs the lowest cost in terms of arithmetic operations (`[CLRS]_`). Note that since this is a function to compute the product, N needs to be greater than or equal to 2; if equal to 2 then a trivial matrix-matrix product is returned. If N is 1, then this is a no-op - the original matrix is returned as is.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(3, 4))
b = torch_randn(c(4, 5))
c = torch_randn(c(5, 6))
d = torch_randn(c(6, 7))
torch_chain_matmul(list(a, b, c, d))
}
```

---

torch_channel_shuffle *Channel_shuffle*

Description

Channel_shuffle

Usage

```
torch_channel_shuffle(self, groups)
```

Arguments

self	(Tensor) the input tensor
groups	(int) number of groups to divide channels in and rearrange.

Divide the channels in a tensor of shape

math:`(*, C , H, W)`:

Divide the channels in a tensor of shape $(*, C, H, W)$ into g groups and rearrange them as $(*, C \frac{g}{,} g, H, W)$, while keeping the original tensor shape.

Examples

```
if (torch_is_installed()) {

input <- torch_randn(c(1, 4, 2, 2))
print(input)
output <- torch_channel_shuffle(input, 2)
print(output)
}
```

torch_cholesky *Cholesky*

Description

Cholesky

Usage

```
torch_cholesky(self, upper = FALSE)
```

Arguments

self	(Tensor) the input tensor A of size $(*, n, n)$ where * is zero or more batch dimensions consisting of symmetric positive-definite matrices.
upper	(bool, optional) flag that indicates whether to return a upper or lower triangular matrix. Default: FALSE

cholesky(input, upper=False, out=NULL) -> Tensor

Computes the Cholesky decomposition of a symmetric positive-definite matrix A or for batches of symmetric positive-definite matrices.

If upper is TRUE, the returned matrix U is upper-triangular, and the decomposition has the form:

$$A = U^T U$$

If upper is FALSE, the returned matrix L is lower-triangular, and the decomposition has the form:

$$A = LL^T$$

If upper is TRUE, and A is a batch of symmetric positive-definite matrices, then the returned tensor will be composed of upper-triangular Cholesky factors of each of the individual matrices. Similarly, when upper is FALSE, the returned tensor will be composed of lower-triangular Cholesky factors of each of the individual matrices.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(3, 3))
a = torch_mm(a, a$t()) # make symmetric positive-definite
l = torch_cholesky(a)
a
l
torch_mm(l, l$t())
a = torch_randn(c(3, 2, 2))
## Not run:
a = torch_matmul(a, a$transpose(-1, -2)) + 1e-03 # make symmetric positive-definite
```

```
l = torch_cholesky(a)
z = torch_matmul(l, l$transpose(-1, -2))
torch_max(torch_abs(z - a)) # Max non-zero

## End(Not run)
}
```

---

torch_cholesky_inverse *Cholesky_inverse*

Description

Cholesky_inverse

Usage

```
torch_cholesky_inverse(self, upper = FALSE)
```

Arguments

self	(Tensor) the input 2-D tensor u, a upper or lower triangular Cholesky factor
upper	(bool, optional) whether to return a lower (default) or upper triangular matrix

cholesky_inverse(input, upper=False, out=NULL) -> Tensor

Computes the inverse of a symmetric positive-definite matrix A using its Cholesky factor u: returns matrix inv. The inverse is computed using LAPACK routines dpotri and spotri (and the corresponding MAGMA routines).

If upper is FALSE, u is lower triangular such that the returned tensor is

$$inv = (uu^T)^{-1}$$

If upper is TRUE or not provided, u is upper triangular such that the returned tensor is

$$inv = (u^T u)^{-1}$$

Examples

```
if (torch_is_installed()) {

## Not run:
a = torch_randn(c(3, 3))
a = torch_mm(a, a$t()) + 1e-05 * torch_eye(3) # make symmetric positive definite
u = torch_cholesky(a)
a
torch_cholesky_inverse(u)
a$inverse()
```

```
## End(Not run)
}
```

---

torch_cholesky_solve *Cholesky_solve*

Description

Cholesky_solve

Usage

```
torch_cholesky_solve(self, input2, upper = FALSE)
```

Arguments

self	(Tensor) input matrix b of size $(*, m, k)$, where $*$ is zero or more batch dimensions
input2	(Tensor) input matrix u of size $(*, m, m)$, where $*$ is zero of more batch dimensions composed of upper or lower triangular Cholesky factor
upper	(bool, optional) whether to consider the Cholesky factor as a lower or upper triangular matrix. Default: FALSE.

cholesky_solve(input, input2, upper=False, out=NULL) -> Tensor

Solves a linear system of equations with a positive semidefinite matrix to be inverted given its Cholesky factor matrix u.

If upper is FALSE, u is and lower triangular and c is returned such that:

$$c = (uu^T)^{-1}b$$

If upper is TRUE or not provided, u is upper triangular and c is returned such that:

$$c = (u^T u)^{-1}b$$

torch_cholesky_solve(b, u) can take in 2D inputs b, u or inputs that are batches of 2D matrices. If the inputs are batches, then returns batched outputs c

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(3, 3))
a = torch_mm(a, a$t()) # make symmetric positive definite
u = torch_cholesky(a)
a
b = torch_randn(c(3, 2))
```

```
b
torch_cholesky_solve(b, u)
torch_mm(a$inverse(), b)
}
```

---

torch_chunk *Chunk*

Description

Chunk

Usage

```
torch_chunk(self, chunks, dim = 1L)
```

Arguments

self	(Tensor) the tensor to split
chunks	(int) number of chunks to return
dim	(int) dimension along which to split the tensor

chunk(input, chunks, dim=0) -> List of Tensors

Splits a tensor into a specific number of chunks. Each chunk is a view of the input tensor.

Last chunk will be smaller if the tensor size along the given dimension dim is not divisible by chunks.

---

torch_clamp *Clamp*

Description

Clamp

Usage

```
torch_clamp(self, min = NULL, max = NULL)
```

Arguments

self	(Tensor) the input tensor.
min	(Number) lower-bound of the range to be clamped to
max	(Number) upper-bound of the range to be clamped to

clamp(input, min, max, out=NULL) -> Tensor

Clamp all elements in `input` into the range `[ min, max ]` and return a resulting tensor:

$$y_i = \begin{cases} \text{min} & \text{if } x_i < \text{min} \\ x_i & \text{if min} \leq x_i \leq \text{max} \\ \text{max} & \text{if } x_i > \text{max} \end{cases}$$

If `input` is of type `FloatTensor` or `DoubleTensor`, args `min` and `max` must be real numbers, otherwise they should be integers.

clamp(input, *, min, out=NULL) -> Tensor

Clamps all elements in `input` to be larger or equal `min`.

If `input` is of type `FloatTensor` or `DoubleTensor`, `value` should be a real number, otherwise it should be an integer.

clamp(input, *, max, out=NULL) -> Tensor

Clamps all elements in `input` to be smaller or equal `max`.

If `input` is of type `FloatTensor` or `DoubleTensor`, `value` should be a real number, otherwise it should be an integer.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_clamp(a, min=-0.5, max=0.5)


a = torch_randn(c(4))
a
torch_clamp(a, min=0.5)


a = torch_randn(c(4))
a
torch_clamp(a, max=0.5)
}
```

`torch_clip` *Clip*

Description

Clip

Usage

```
torch_clip(self, min = NULL, max = NULL)
```

Arguments

self	(Tensor) the input tensor.
min	(Number) lower-bound of the range to be clamped to
max	(Number) upper-bound of the range to be clamped to

clip(input, min, max, *, out=None) -> Tensor

Alias for torch_clamp().

---

torch_clone *Clone*

Description

Clone

Usage

```
torch_clone(self, memory_format = NULL)
```

Arguments

self	(Tensor) the input tensor.
memory_format	a torch memory format. see torch_preserve_format().

clone(input, *, memory_format=torch.preserve_format) -> Tensor

Returns a copy of input.

Note

This function is differentiable, so gradients will flow back from the result of this operation to input. To create a tensor without an autograd relationship to input see Tensor$detach.

torch_combinations *Combinations*

Description

Combinations

Usage

```
torch_combinations(self, r = 2L, with_replacement = FALSE)
```

Arguments

self	(Tensor) 1D vector.
r	(int, optional) number of elements to combine
with_replacement	(boolean, optional) whether to allow duplication in combination

combinations(input, r=2, with_replacement=False) -> seq

Compute combinations of length r of the given tensor. The behavior is similar to python's `itertools.combinations` when `with_replacement` is set to `False`, and `itertools.combinations_with_replacement` when `with_replacement` is set to `TRUE`.

Examples

```
if (torch_is_installed()) {

a = c(1, 2, 3)
tensor_a = torch_tensor(a)
torch_combinations(tensor_a)
torch_combinations(tensor_a, r=3)
torch_combinations(tensor_a, with_replacement=TRUE)
}
```

torch_complex *Complex*

Description

Complex

Usage

```
torch_complex(real, imag)
```

Arguments

`real`	(Tensor) The real part of the complex tensor. Must be float or double.
`imag`	(Tensor) The imaginary part of the complex tensor. Must be same dtype as `real`.

complex(real, imag, *, out=None) -> Tensor

Constructs a complex tensor with its real part equal to `real` and its imaginary part equal to `imag`.

Examples

```
if (torch_is_installed()) {

real <- torch_tensor(c(1, 2), dtype=torch_float32())
imag <- torch_tensor(c(3, 4), dtype=torch_float32())
z <- torch_complex(real, imag)
z
z$dtype
}
```

---

torch_conj *Conj*

Description

Conj

Usage

```
torch_conj(self)
```

Arguments

`self`	(Tensor) the input tensor.

conj(input) -> Tensor

Computes the element-wise conjugate of the given `input` tensor.

$$\text{out}_i = conj(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {
## Not run:
torch_conj(torch_tensor(c(-1 + 1i, -2 + 2i, 3 - 3i)))

## End(Not run)
}
```

torch_conv1d *Conv1d*

Description

Conv1d

Usage

```
torch_conv1d(
  input,
  weight,
  bias = list(),
  stride = 1L,
  padding = 0L,
  dilation = 1L,
  groups = 1L
)
```

Arguments

input	input tensor of shape $(\text{minibatch}, \text{in_channels}, iW)$
weight	filters of shape $(\text{out_channels}, \frac{\text{in_channels}}{\text{groups}}, kW)$
bias	optional bias of shape (out_channels). Default: NULL
stride	the stride of the convolving kernel. Can be a single number or a one-element tuple (sW,). Default: 1
padding	implicit paddings on both sides of the input. Can be a single number or a one-element tuple (padW,). Default: 0
dilation	the spacing between kernel elements. Can be a single number or a one-element tuple (dW,). Default: 1
groups	split input into groups, in_channels should be divisible by the number of groups. Default: 1

conv1d(input, weight, bias=NULL, stride=1, padding=0, dilation=1, groups=1) -> Tensor

Applies a 1D convolution over an input signal composed of several input planes.

See nn_conv1d() for details and output shape.

Examples

```
if (torch_is_installed()) {

filters = torch_randn(c(33, 16, 3))
inputs = torch_randn(c(20, 16, 50))
nnf_conv1d(inputs, filters)
}
```

torch_conv2d *Conv2d*

Description

Conv2d

Usage

```
torch_conv2d(
  input,
  weight,
  bias = list(),
  stride = 1L,
  padding = 0L,
  dilation = 1L,
  groups = 1L
)
```

Arguments

input	input tensor of shape $(\text{minibatch}, \text{in_channels}, iH, iW)$
weight	filters of shape $(\text{out_channels}, \frac{\text{in_channels}}{\text{groups}}, kH, kW)$
bias	optional bias tensor of shape (out_channels). Default: `NULL`
stride	the stride of the convolving kernel. Can be a single number or a tuple `(sH, sW)`. Default: 1
padding	implicit paddings on both sides of the input. Can be a single number or a tuple `(padH, padW)`. Default: 0
dilation	the spacing between kernel elements. Can be a single number or a tuple `(dH, dW)`. Default: 1
groups	split input into groups, in_channels should be divisible by the number of groups. Default: 1

conv2d(input, weight, bias=NULL, stride=1, padding=0, dilation=1, groups=1) -> Tensor

Applies a 2D convolution over an input image composed of several input planes.

See `nn_conv2d()` for details and output shape.

Examples

```
if (torch_is_installed()) {

# With square kernels and equal stride
filters = torch_randn(c(8,4,3,3))
inputs = torch_randn(c(1,4,5,5))
nnf_conv2d(inputs, filters, padding=1)
}
```

torch_conv3d *Conv3d*

Description

Conv3d

Usage

```
torch_conv3d(
  input,
  weight,
  bias = list(),
  stride = 1L,
  padding = 0L,
  dilation = 1L,
  groups = 1L
)
```

Arguments

input	input tensor of shape $(\text{minibatch}, \text{in_channels}, iT, iH, iW)$
weight	filters of shape $(\text{out_channels}, \frac{\text{in_channels}}{\text{groups}}, kT, kH, kW)$
bias	optional bias tensor of shape (out_channels). Default: NULL
stride	the stride of the convolving kernel. Can be a single number or a tuple `(sT, sH, sW)`. Default: 1
padding	implicit paddings on both sides of the input. Can be a single number or a tuple `(padT, padH, padW)`. Default: 0
dilation	the spacing between kernel elements. Can be a single number or a tuple `(dT, dH, dW)`. Default: 1
groups	split input into groups, in_channels should be divisible by the number of groups. Default: 1

conv3d(input, weight, bias=NULL, stride=1, padding=0, dilation=1, groups=1) -> Tensor

Applies a 3D convolution over an input image composed of several input planes.

See `nn_conv3d()` for details and output shape.

Examples

```
if (torch_is_installed()) {

# filters = torch_randn(c(33, 16, 3, 3, 3))
# inputs = torch_randn(c(20, 16, 50, 10, 20))
# nnf_conv3d(inputs, filters)
}
```

torch_conv_tbc *Conv_tbc*

Description

Conv_tbc

Usage

```
torch_conv_tbc(self, weight, bias, pad = 0L)
```

Arguments

self	NA input tensor of shape (sequence length $\times$ $batch$ $\times$ in_channels)
weight	NA filter of shape (kernel width $\times$ in_channels $\times$ out_channels)
bias	NA bias of shape (out_channels)
pad	NA number of timesteps to pad. Default: 0

TEST

Applies a 1-dimensional sequence convolution over an input sequence. Input and output dimensions are (Time, Batch, Channels) - hence TBC.

torch_conv_transpose1d *Conv_transpose1d*

Description

Conv_transpose1d

Usage

```
torch_conv_transpose1d(
  input,
  weight,
  bias = list(),
  stride = 1L,
  padding = 0L,
  output_padding = 0L,
  groups = 1L,
  dilation = 1L
)
```

Arguments

`input`	input tensor of shape $(\text{minibatch}, \text{in_channels}, iW)$
`weight`	filters of shape $(\text{in_channels}, \frac{\text{out_channels}}{\text{groups}}, kW)$
`bias`	optional bias of shape (out_channels). Default: NULL
`stride`	the stride of the convolving kernel. Can be a single number or a tuple `(sW,)`. Default: 1
`padding`	`dilation * (kernel_size - 1) - padding` zero-padding will be added to both sides of each dimension in the input. Can be a single number or a tuple `(padW,)`. Default: 0
`output_padding`	additional size added to one side of each dimension in the output shape. Can be a single number or a tuple `(out_padW)`. Default: 0
`groups`	split input into groups, in_channels should be divisible by the number of groups. Default: 1
`dilation`	the spacing between kernel elements. Can be a single number or a tuple `(dW,)`. Default: 1

conv_transpose1d(input, weight, bias=NULL, stride=1, padding=0, output_padding=0, groups=1, dilation=1) -> Tensor

Applies a 1D transposed convolution operator over an input signal composed of several input planes, sometimes also called "deconvolution".

See `nn_conv_transpose1d()` for details and output shape.

Examples

```
if (torch_is_installed()) {

inputs = torch_randn(c(20, 16, 50))
weights = torch_randn(c(16, 33, 5))
nnf_conv_transpose1d(inputs, weights)
}
```

---

torch_conv_transpose2d *Conv_transpose2d*

Description

Conv_transpose2d

Usage

```
torch_conv_transpose2d(
  input,
  weight,
  bias = list(),
  stride = 1L,
  padding = 0L,
  output_padding = 0L,
  groups = 1L,
  dilation = 1L
)
```

Arguments

`input`	input tensor of shape $(\text{minibatch}, \text{in_channels}, iH, iW)$
`weight`	filters of shape $(\text{in_channels}, \frac{\text{out_channels}}{\text{groups}}, kH, kW)$
`bias`	optional bias of shape (out_channels). Default: NULL
`stride`	the stride of the convolving kernel. Can be a single number or a tuple `(sH, sW)`. Default: 1
`padding`	`dilation * (kernel_size - 1) - padding` zero-padding will be added to both sides of each dimension in the input. Can be a single number or a tuple `(padH, padW)`. Default: 0
`output_padding`	additional size added to one side of each dimension in the output shape. Can be a single number or a tuple `(out_padH, out_padW)`. Default: 0
`groups`	split input into groups, in_channels should be divisible by the number of groups. Default: 1
`dilation`	the spacing between kernel elements. Can be a single number or a tuple `(dH, dW)`. Default: 1

conv_transpose2d(input, weight, bias=NULL, stride=1, padding=0, output_padding=0, groups=1, dilation=1) -> Tensor

Applies a 2D transposed convolution operator over an input image composed of several input planes, sometimes also called "deconvolution".

See `nn_conv_transpose2d()` for details and output shape.

Examples

```
if (torch_is_installed()) {

# With square kernels and equal stride
inputs = torch_randn(c(1, 4, 5, 5))
weights = torch_randn(c(4, 8, 3, 3))
nnf_conv_transpose2d(inputs, weights, padding=1)
}
```

torch_conv_transpose3d *Conv_transpose3d*

Description

Conv_transpose3d

Usage

```
torch_conv_transpose3d(
  input,
  weight,
  bias = list(),
  stride = 1L,
  padding = 0L,
  output_padding = 0L,
  groups = 1L,
  dilation = 1L
)
```

Arguments

input	input tensor of shape $(\text{minibatch}, \text{in_channels}, iT, iH, iW)$
weight	filters of shape $(\text{in_channels}, \frac{\text{out_channels}}{\text{groups}}, kT, kH, kW)$
bias	optional bias of shape (out_channels). Default: NULL
stride	the stride of the convolving kernel. Can be a single number or a tuple `(sT, sH, sW)`. Default: 1
padding	`dilation * (kernel_size - 1) - padding` zero-padding will be added to both sides of each dimension in the input. Can be a single number or a tuple `(padT, padH, padW)`. Default: 0
output_padding	additional size added to one side of each dimension in the output shape. Can be a single number or a tuple `(out_padT, out_padH, out_padW)`. Default: 0
groups	split input into groups, in_channels should be divisible by the number of groups. Default: 1
dilation	the spacing between kernel elements. Can be a single number or a tuple `(dT, dH, dW)`. Default: 1

conv_transpose3d(input, weight, bias=NULL, stride=1, padding=0, output_padding=0, groups=1, dilation=1) -> Tensor

Applies a 3D transposed convolution operator over an input image composed of several input planes, sometimes also called "deconvolution"

See `nn_conv_transpose3d()` for details and output shape.

Examples

```
if (torch_is_installed()) {
## Not run:
inputs = torch_randn(c(20, 16, 50, 10, 20))
weights = torch_randn(c(16, 33, 3, 3, 3))
nnf_conv_transpose3d(inputs, weights)

## End(Not run)
}
```

---

torch_cos *Cos*

Description

Cos

Usage

```
torch_cos(self)
```

Arguments

self	(Tensor) the input tensor.

cos(input, out=NULL) -> Tensor

Returns a new tensor with the cosine of the elements of `input`.

$$\text{out}_i = \cos(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_cos(a)
}
```

torch_cosh *Cosh*

Description

Cosh

Usage

```
torch_cosh(self)
```

Arguments

self	(Tensor) the input tensor.

cosh(input, out=NULL) -> Tensor

Returns a new tensor with the hyperbolic cosine of the elements of `input`.

$$\text{out}_i = \cosh(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_cosh(a)
}
```

torch_cosine_similarity *Cosine_similarity*

Description

Cosine_similarity

Usage

```
torch_cosine_similarity(x1, x2, dim = 2L, eps = 1e-08)
```

Arguments

x1	(Tensor) First input.
x2	(Tensor) Second input (of size matching x1).
dim	(int, optional) Dimension of vectors. Default: 1
eps	(float, optional) Small value to avoid division by zero. Default: 1e-8

cosine_similarity(x1, x2, dim=1, eps=1e-8) -> Tensor

Returns cosine similarity between x1 and x2, computed along dim.

$$\text{similarity} = \frac{x_1 \cdot x_2}{\max(\|x_1\|_2 \cdot \|x_2\|_2, \epsilon)}$$

Examples

```
if (torch_is_installed()) {

input1 = torch_randn(c(100, 128))
input2 = torch_randn(c(100, 128))
output = torch_cosine_similarity(input1, input2)
output
}
```

---

torch_count_nonzero *Count_nonzero*

Description

Count_nonzero

Usage

```
torch_count_nonzero(self, dim = NULL)
```

Arguments

self	(Tensor) the input tensor.
dim	(int or tuple of ints, optional) Dim or tuple of dims along which to count non-zeros.

count_nonzero(input, dim=None) -> Tensor

Counts the number of non-zero values in the tensor `input` along the given `dim`. If no dim is specified then all non-zeros in the tensor are counted.

Examples

```
if (torch_is_installed()) {

x <- torch_zeros(3,3)
x[torch_randn(3,3) > 0.5] = 1
x
torch_count_nonzero(x)
torch_count_nonzero(x, dim=1)
}
```

---

torch_cross *Cross*

Description

Cross

Usage

```
torch_cross(self, other, dim = NULL)
```

Arguments

self	(Tensor) the input tensor.
other	(Tensor) the second input tensor
dim	(int, optional) the dimension to take the cross-product in.

cross(input, other, dim=-1, out=NULL) -> Tensor

Returns the cross product of vectors in dimension `dim` of `input` and `other`.

`input` and `other` must have the same size, and the size of their `dim` dimension should be 3.

If `dim` is not given, it defaults to the first dimension found with the size 3.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4, 3))
a
b = torch_randn(c(4, 3))
b
torch_cross(a, b, dim=2)
torch_cross(a, b)
}
```

torch_cummax *Cummax*

Description

Cummax

Usage

```
torch_cummax(self, dim)
```

Arguments

self	(Tensor) the input tensor.
dim	(int) the dimension to do the operation over

cummax(input, dim) -> (Tensor, LongTensor)

Returns a namedtuple (values, indices) where values is the cumulative maximum of elements of input in the dimension dim. And indices is the index location of each maximum value found in the dimension dim.

$$y_i = max(x_1, x_2, x_3, \ldots, x_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(10))
a
torch_cummax(a, dim=1)
}
```

torch_cummin *Cummin*

Description

Cummin

Usage

```
torch_cummin(self, dim)
```

Arguments

self	(Tensor) the input tensor.
dim	(int) the dimension to do the operation over

cummin(input, dim) -> (Tensor, LongTensor)

Returns a namedtuple (values, indices) where values is the cumulative minimum of elements of input in the dimension dim. And indices is the index location of each maximum value found in the dimension dim.

$$y_i = min(x_1, x_2, x_3, \ldots, x_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(10))
a
torch_cummin(a, dim=1)
}
```

---

torch_cumprod *Cumprod*

Description

Cumprod

Usage

```
torch_cumprod(self, dim, dtype = NULL)
```

Arguments

self	(Tensor) the input tensor.
dim	(int) the dimension to do the operation over
dtype	(torch.dtype, optional) the desired data type of returned tensor. If specified, the input tensor is casted to dtype before the operation is performed. This is useful for preventing data type overflows. Default: NULL.

cumprod(input, dim, out=NULL, dtype=NULL) -> Tensor

Returns the cumulative product of elements of input in the dimension dim.

For example, if input is a vector of size N, the result will also be a vector of size N, with elements.

$$y_i = x_1 \times x_2 \times x_3 \times \cdots \times x_i$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(10))
a
torch_cumprod(a, dim=1)
}
```

---

torch_cumsum *Cumsum*

Description

Cumsum

Usage

```
torch_cumsum(self, dim, dtype = NULL)
```

Arguments

self	(Tensor) the input tensor.
dim	(int) the dimension to do the operation over
dtype	(torch.dtype, optional) the desired data type of returned tensor. If specified, the input tensor is casted to dtype before the operation is performed. This is useful for preventing data type overflows. Default: NULL.

cumsum(input, dim, out=NULL, dtype=NULL) -> Tensor

Returns the cumulative sum of elements of input in the dimension dim.

For example, if input is a vector of size N, the result will also be a vector of size N, with elements.

$$y_i = x_1 + x_2 + x_3 + \cdots + x_i$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(10))
a
torch_cumsum(a, dim=1)
}
```

torch_deg2rad *Deg2rad*

Description

Deg2rad

Usage

```
torch_deg2rad(self)
```

Arguments

self	(Tensor) the input tensor.

deg2rad(input, *, out=None) -> Tensor

Returns a new tensor with each of the elements of `input` converted from angles in degrees to radians.

Examples

```
if (torch_is_installed()) {

a <- torch_tensor(rbind(c(180.0, -180.0), c(360.0, -360.0), c(90.0, -90.0)))
torch_deg2rad(a)
}
```

torch_dequantize *Dequantize*

Description

Dequantize

Usage

```
torch_dequantize(tensor)
```

Arguments

tensor	(Tensor) A quantized Tensor or a list oof quantized tensors

dequantize(tensor) -> Tensor

Returns an fp32 Tensor by dequantizing a quantized Tensor

dequantize(tensors) -> sequence of Tensors

Given a list of quantized Tensors, dequantize them and return a list of fp32 Tensors

---

`torch_det` *Det*

Description

Det

Usage

```
torch_det(self)
```

Arguments

`self`	(Tensor) the input tensor of size `(*, n, n)` where `*` is zero or more batch dimensions.

det(input) -> Tensor

Calculates determinant of a square matrix or batches of square matrices.

Note

```
Backward through `det` internally uses SVD results when `input` is
not invertible. In this case, double backward through `det` will be
unstable in when `input` doesn't have distinct singular values. See
`~torch.svd` for details.
```

Examples

```
if (torch_is_installed()) {

A = torch_randn(c(3, 3))
torch_det(A)
A = torch_randn(c(3, 2, 2))
A
A$det()
}
```

torch_device *Create a Device object*

Description

A torch_device is an object representing the device on which a torch_tensor is or will be allocated.

Usage

```
torch_device(type, index = NULL)
```

Arguments

type	(character) a device type "cuda" or "cpu"
index	(integer) optional device ordinal for the device type. If the device ordinal is not present, this object will always represent the current device for the device type, even after torch_cuda_set_device() is called; e.g., a torch_tensor constructed with device 'cuda' is equivalent to 'cuda:X' where X is the result of torch_cuda_current_device(). A torch_device can be constructed via a string or via a string and device ordinal

Examples

```
if (torch_is_installed()) {

# Via string
torch_device("cuda:1")
torch_device("cpu")
torch_device("cuda") # current cuda device

# Via string and device ordinal
torch_device("cuda", 0)
torch_device("cpu", 0)
}
```

torch_diag *Diag*

Description

Diag

Usage

```
torch_diag(self, diagonal = 0L)
```

Arguments

`self`	(Tensor) the input tensor.
`diagonal`	(int, optional) the diagonal to consider

diag(input, diagonal=0, out=NULL) -> Tensor

- If `input` is a vector (1-D tensor), then returns a 2-D square tensor with the elements of `input` as the diagonal.
- If `input` is a matrix (2-D tensor), then returns a 1-D tensor with the diagonal elements of `input`.

The argument `diagonal` controls which diagonal to consider:

- If `diagonal` = 0, it is the main diagonal.
- If `diagonal` > 0, it is above the main diagonal.
- If `diagonal` < 0, it is below the main diagonal.

`torch_diagflat` *Diagflat*

Description

Diagflat

Usage

```
torch_diagflat(self, offset = 0L)
```

Arguments

`self`	(Tensor) the input tensor.
`offset`	(int, optional) the diagonal to consider. Default: 0 (main diagonal).

diagflat(input, offset=0) -> Tensor

- If `input` is a vector (1-D tensor), then returns a 2-D square tensor with the elements of `input` as the diagonal.
- If `input` is a tensor with more than one dimension, then returns a 2-D tensor with diagonal elements equal to a flattened `input`.

The argument `offset` controls which diagonal to consider:

- If `offset` = 0, it is the main diagonal.
- If `offset` > 0, it is above the main diagonal.
- If `offset` < 0, it is below the main diagonal.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(3))
a
torch_diagflat(a)
torch_diagflat(a, 1)
a = torch_randn(c(2, 2))
a
torch_diagflat(a)
}
```

---

torch_diagonal *Diagonal*

Description

Diagonal

Usage

```
torch_diagonal(self, outdim, dim1 = 1L, dim2 = 2L, offset = 0L)
```

Arguments

self	(Tensor) the input tensor. Must be at least 2-dimensional.
outdim	dimension name if self is a named tensor.
dim1	(int, optional) first dimension with respect to which to take diagonal. Default: 0.
dim2	(int, optional) second dimension with respect to which to take diagonal. Default: 1.
offset	(int, optional) which diagonal to consider. Default: 0 (main diagonal).

diagonal(input, offset=0, dim1=0, dim2=1) -> Tensor

Returns a partial view of input with the its diagonal elements with respect to dim1 and dim2 appended as a dimension at the end of the shape.

The argument offset controls which diagonal to consider:

- If offset = 0, it is the main diagonal.
- If offset > 0, it is above the main diagonal.
- If offset < 0, it is below the main diagonal.

Applying torch_diag_embed to the output of this function with the same arguments yields a diagonal matrix with the diagonal entries of the input. However, torch_diag_embed has different default dimensions, so those need to be explicitly specified.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(3, 3))
a
torch_diagonal(a, offset = 0)
torch_diagonal(a, offset = 1)
x = torch_randn(c(2, 5, 4, 2))
torch_diagonal(x, offset=-1, dim1=1, dim2=2)
}
```

---

torch_diag_embed *Diag_embed*

Description

Diag_embed

Usage

```
torch_diag_embed(self, offset = 0L, dim1 = -2L, dim2 = -1L)
```

Arguments

self	(Tensor) the input tensor. Must be at least 1-dimensional.
offset	(int, optional) which diagonal to consider. Default: 0 (main diagonal).
dim1	(int, optional) first dimension with respect to which to take diagonal. Default: -2.
dim2	(int, optional) second dimension with respect to which to take diagonal. Default: -1.

diag_embed(input, offset=0, dim1=-2, dim2=-1) -> Tensor

Creates a tensor whose diagonals of certain 2D planes (specified by `dim1` and `dim2`) are filled by `input`. To facilitate creating batched diagonal matrices, the 2D planes formed by the last two dimensions of the returned tensor are chosen by default.

The argument `offset` controls which diagonal to consider:

- If `offset` = 0, it is the main diagonal.
- If `offset` > 0, it is above the main diagonal.
- If `offset` < 0, it is below the main diagonal.

The size of the new matrix will be calculated to make the specified diagonal of the size of the last input dimension. Note that for `offset` other than 0, the order of `dim1` and `dim2` matters. Exchanging them is equivalent to changing the sign of `offset`.

Applying `torch_diagonal` to the output of this function with the same arguments yields a matrix identical to input. However, `torch_diagonal` has different default dimensions, so those need to be explicitly specified.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(2, 3))
torch_diag_embed(a)
torch_diag_embed(a, offset=1, dim1=1, dim2=3)
}
```

---

torch_diff *Computes the n-th forward difference along the given dimension.*

Description

The first-order differences are given by `out[i] = input[i + 1] - input[i]`. Higher-order differences are calculated by using `torch_diff()` recursively.

Usage

```
torch_diff(self, n = 1L, dim = -1L, prepend = list(), append = list())
```

Arguments

self	the tensor to compute the differences on
n	the number of times to recursively compute the difference
dim	the dimension to compute the difference along. Default is the last dimension.
prepend	values to prepend to input along dim before computing the difference. Their dimensions must be equivalent to that of input, and their shapes must match input's shape except on dim.
append	values to append to input along dim before computing the difference. Their dimensions must be equivalent to that of input, and their shapes must match input's shape except on dim.

Note

Only n = 1 is currently supported

Examples

```
if (torch_is_installed()) {
a <- torch_tensor(c(1,2,3))
torch_diff(a)

b <- torch_tensor(c(4, 5))
torch_diff(a, append = b)

c <- torch_tensor(rbind(c(1,2,3), c(3,4,5)))
torch_diff(c, dim = 1)
```

```
torch_diff(c, dim = 2)

}
```

---

torch_digamma *Digamma*

Description

Digamma

Usage

```
torch_digamma(self)
```

Arguments

self	(Tensor) the tensor to compute the digamma function on

digamma(input, out=NULL) -> Tensor

Computes the logarithmic derivative of the gamma function on `input`.

$$\psi(x) = \frac{d}{dx} \ln \left(\Gamma\left(x\right)\right) = \frac{\Gamma'(x)}{\Gamma(x)}$$

Examples

```
if (torch_is_installed()) {

a = torch_tensor(c(1, 0.5))
torch_digamma(a)
}
```

---

torch_dist *Dist*

Description

Dist

Usage

```
torch_dist(self, other, p = 2L)
```

Arguments

self	(Tensor) the input tensor.
other	(Tensor) the Right-hand-side input tensor
p	(float, optional) the norm to be computed

dist(input, other, p=2) -> Tensor

Returns the p-norm of (input - other)

The shapes of input and other must be broadcastable .

Examples

```
if (torch_is_installed()) {

x = torch_randn(c(4))
x
y = torch_randn(c(4))
y
torch_dist(x, y, 3.5)
torch_dist(x, y, 3)
torch_dist(x, y, 0)
torch_dist(x, y, 1)
}
```

---

torch_div *Div*

Description

Div

Usage

```
torch_div(self, other, rounding_mode)
```

Arguments

self	(Tensor) the input tensor.
other	(Number) the number to be divided to each element of input
rounding_mode	(str, optional) – Type of rounding applied to the result: • NULL - default behavior. Performs no rounding and, if both input and other are integer types, promotes the inputs to the default scalar type. Equivalent to true division in Python (the / operator) and NumPy's np.true_divide. • "trunc" - rounds the results of the division towards zero. Equivalent to C-style integer division. • "floor" - rounds the results of the division down. Equivalent to floor division in Python (the // operator) and NumPy's np.floor_divide.

div(input, other, out=NULL) -> Tensor

Divides each element of the input `input` with the scalar `other` and returns a new resulting tensor.

Each element of the tensor `input` is divided by each element of the tensor `other`. The resulting tensor is returned.

$$\text{out}_i = \frac{\text{input}_i}{\text{other}_i}$$

The shapes of `input` and `other` must be broadcastable . If the `torch_dtype` of `input` and `other` differ, the `torch_dtype` of the result tensor is determined following rules described in the type promotion documentation . If `out` is specified, the result must be castable to the `torch_dtype` of the specified output tensor. Integral division by zero leads to undefined behavior.

Warning

Integer division using div is deprecated, and in a future release div will perform true division like `torch_true_divide()`. Use `torch_floor_divide()` to perform integer division, instead.

$$\text{out}_i = \frac{\text{input}_i}{\text{other}}$$

If the `torch_dtype` of `input` and `other` differ, the `torch_dtype` of the result tensor is determined following rules described in the type promotion documentation . If `out` is specified, the result must be castable to the `torch_dtype` of the specified output tensor. Integral division by zero leads to undefined behavior.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(5))
a
torch_div(a, 0.5)


a = torch_randn(c(4, 4))
a
b = torch_randn(c(4))
b
torch_div(a, b)
}
```

`torch_divide` *Divide*

Description

Divide

Usage

```
torch_divide(self, other, rounding_mode)
```

Arguments

`self`	(Tensor) the input tensor.
`other`	(Number) the number to be divided to each element of `input`
`rounding_mode`	(str, optional) – Type of rounding applied to the result: • `NULL` - default behavior. Performs no rounding and, if both input and other are integer types, promotes the inputs to the default scalar type. Equivalent to true division in Python (the / operator) and NumPy's `np.true_divide`. • "trunc" - rounds the results of the division towards zero. Equivalent to C-style integer division. • "floor" - rounds the results of the division down. Equivalent to floor division in Python (the // operator) and NumPy's `np.floor_divide`.

divide(input, other, *, out=None) -> Tensor

Alias for `torch_div()`.

---

torch_dot *Dot*

Description

Dot

Usage

```
torch_dot(self, tensor)
```

Arguments

`self`	the input tensor
`tensor`	the other input tensor

dot(input, tensor) -> Tensor

Computes the dot product (inner product) of two tensors.

Note

This function does not broadcast .

Examples

```
if (torch_is_installed()) {

torch_dot(torch_tensor(c(2, 3)), torch_tensor(c(2, 1)))
}
```

---

torch_dstack *Dstack*

Description

Dstack

Usage

```
torch_dstack(tensors)
```

Arguments

tensors	(sequence of Tensors) sequence of tensors to concatenate

dstack(tensors, *, out=None) -> Tensor

Stack tensors in sequence depthwise (along third axis).

This is equivalent to concatenation along the third axis after 1-D and 2-D tensors have been reshaped by torch_atleast_3d().

Examples

```
if (torch_is_installed()) {

a <- torch_tensor(c(1, 2, 3))
b <- torch_tensor(c(4, 5, 6))
torch_dstack(list(a,b))
a <- torch_tensor(rbind(1,2,3))
b <- torch_tensor(rbind(4,5,6))
torch_dstack(list(a,b))
}
```

torch_dtype *Torch data types*

Description

Returns the correspondent data type.

Usage

```
torch_float32()

torch_float()

torch_float64()

torch_double()

torch_cfloat32()

torch_chalf()

torch_cfloat()

torch_cfloat64()

torch_cdouble()

torch_cfloat128()

torch_float16()

torch_half()

torch_bfloat16()

torch_uint8()

torch_int8()

torch_int16()

torch_short()

torch_int32()

torch_int()
```

```
torch_int64()

torch_long()

torch_bool()

torch_quint8()

torch_qint8()

torch_qint32()
```

---

torch_eig *Eig*

Description

Eig

Arguments

self	(Tensor) the square matrix of shape $(n \times n)$ for which the eigenvalues and eigenvectors will be computed
eigenvectors	(bool) TRUE to compute both eigenvalues and eigenvectors; otherwise, only eigenvalues will be computed

eig(input, eigenvectors=False, out=NULL) -> (Tensor, Tensor)

Computes the eigenvalues and eigenvectors of a real square matrix.

---

torch_einsum *Einsum*

Description

Einsum

Usage

```
torch_einsum(equation, tensors, path = NULL)
```

Arguments

`equation` (string) The equation is given in terms of lower case letters (indices) to be associated with each dimension of the operands and result. The left hand side lists the operands dimensions, separated by commas. There should be one index letter per tensor dimension. The right hand side follows after `->` and gives the indices for the output. If the `->` and right hand side are omitted, it implicitly defined as the alphabetically sorted list of all indices appearing exactly once in the left hand side. The indices not apprearing in the output are summed over after multiplying the operands entries. If an index appears several times for the same operand, a diagonal is taken. Ellipses `...` represent a fixed number of dimensions. If the right hand side is inferred, the ellipsis dimensions are at the beginning of the output.

`tensors` (Tensor) The operands to compute the Einstein sum of.

`path` (int) This function uses opt_einsum to speed up computation or to consume less memory by optimizing contraction order. This optimization occurs when there are at least three inputs, since the order does not matter otherwise. Note that finding *the* optimal path is an NP-hard problem, thus, `opt_einsum` relies on different heuristics to achieve near-optimal results. If `opt_einsum` is not available, the default order is to contract from left to right. The path argument is used to changed that default, but it should only be set by advanced users.

einsum(equation, *operands) -> Tensor

This function provides a way of computing multilinear expressions (i.e. sums of products) using the Einstein summation convention.

Examples

```
if (torch_is_installed()) {

x = torch_randn(c(5))
y = torch_randn(c(4))
torch_einsum('i,j->ij', list(x, y))  # outer product
A = torch_randn(c(3,5,4))
l = torch_randn(c(2,5))
r = torch_randn(c(2,4))
torch_einsum('bn,anm,bm->ba', list(l, A, r)) # compare torch_nn$functional$bilinear
As = torch_randn(c(3,2,5))
Bs = torch_randn(c(3,5,4))
torch_einsum('bij,bjk->bik', list(As, Bs)) # batch matrix multiplication
A = torch_randn(c(3, 3))
torch_einsum('ii->i', list(A)) # diagonal
A = torch_randn(c(4, 3, 3))
torch_einsum('...ii->...i', list(A)) # batch diagonal
A = torch_randn(c(2, 3, 4, 5))
torch_einsum('...ij->...ji', list(A))$shape # batch permute

}
```

torch_empty *Empty*

Description

Empty

Usage

```
torch_empty(
  ...,
  names = NULL,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

...	a sequence of integers defining the shape of the output tensor.
names	optional character vector naming each dimension.
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type).
layout	(torch.layout, optional) the desired layout of returned Tensor. Default: torch_strided.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

empty(*size, out=NULL, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False, pin_memory=False) -> Tensor

Returns a tensor filled with uninitialized data. The shape of the tensor is defined by the variable argument size.

Examples

```
if (torch_is_installed()) {

torch_empty(c(2, 3))
}
```

torch_empty_like *Empty_like*

Description

Empty_like

Usage

```
torch_empty_like(
  input,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE,
  memory_format = torch_preserve_format()
)
```

Arguments

input	(Tensor) the size of `input` will determine size of the output tensor.
dtype	(`torch.dtype`, optional) the desired data type of returned Tensor. Default: if `NULL`, defaults to the dtype of `input`.
layout	(`torch.layout`, optional) the desired layout of returned tensor. Default: if `NULL`, defaults to the layout of `input`.
device	(`torch.device`, optional) the desired device of returned tensor. Default: if `NULL`, defaults to the device of `input`.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: `FALSE`.
memory_format	(`torch.memory_format`, optional) the desired memory format of returned Tensor. Default: `torch_preserve_format`.

empty_like(input, dtype=NULL, layout=NULL, device=NULL, requires_grad=False, memory_format=torch.preserve_for -> Tensor

Returns an uninitialized tensor with the same size as `input`. `torch_empty_like(input)` is equivalent to `torch_empty(input.size(), dtype=input.dtype, layout=input.layout, device=input.device)`.

Examples

```
if (torch_is_installed()) {

torch_empty(list(2,3), dtype = torch_int64())
}
```

torch_empty_strided *Empty_strided*

Description

Empty_strided

Usage

```
torch_empty_strided(
  size,
  stride,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE,
  pin_memory = FALSE
)
```

Arguments

size	(tuple of ints) the shape of the output tensor
stride	(tuple of ints) the strides of the output tensor
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type).
layout	(torch.layout, optional) the desired layout of returned Tensor. Default: torch_strided.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.
pin_memory	(bool, optional) If set, returned tensor would be allocated in the pinned memory. Works only for CPU tensors. Default: FALSE.

empty_strided(size, stride, dtype=NULL, layout=NULL, device=NULL, requires_grad=False, pin_memory=False) -> Tensor

Returns a tensor filled with uninitialized data. The shape and strides of the tensor is defined by the variable argument size and stride respectively. torch_empty_strided(size, stride) is equivalent to torch_empty(size).as_strided(size, stride).

Warning

More than one element of the created tensor may refer to a single memory location. As a result, in-place operations (especially ones that are vectorized) may result in incorrect behavior. If you need to write to the tensors, please clone them first.

Examples

```
if (torch_is_installed()) {

a = torch_empty_strided(list(2, 3), list(1, 2))
a
a$stride(1)
a$size(1)
}
```

---

torch_eq *Eq*

Description

Eq

Usage

```
torch_eq(self, other)
```

Arguments

self	(Tensor) the tensor to compare
other	(Tensor or float) the tensor or value to compare Must be a ByteTensor

eq(input, other, out=NULL) -> Tensor

Computes element-wise equality

The second argument can be a number or a tensor whose shape is broadcastable with the first argument.

Examples

```
if (torch_is_installed()) {

torch_eq(torch_tensor(c(1,2,3,4)), torch_tensor(c(1, 3, 2, 4)))
}
```

torch_equal *Equal*

Description

Equal

Usage

```
torch_equal(self, other)
```

Arguments

self	the input tensor
other	the other input tensor

equal(input, other) -> bool

TRUE if two tensors have the same size and elements, FALSE otherwise.

Examples

```
if (torch_is_installed()) {

torch_equal(torch_tensor(c(1, 2)), torch_tensor(c(1, 2)))
}
```

torch_erf *Erf*

Description

Erf

Usage

```
torch_erf(self)
```

Arguments

self	(Tensor) the input tensor.

erf(input, out=NULL) -> Tensor

Computes the error function of each element. The error function is defined as follows:

$$\mathrm{erf}(x) = \frac{2}{\sqrt{\pi}} \int_0^x e^{-t^2} dt$$

Examples

```
if (torch_is_installed()) {

torch_erf(torch_tensor(c(0, -1., 10.)))
}
```

---

torch_erfc *Erfc*

Description

Erfc

Usage

```
torch_erfc(self)
```

Arguments

self	(Tensor) the input tensor.

erfc(input, out=NULL) -> Tensor

Computes the complementary error function of each element of `input`. The complementary error function is defined as follows:

$$\operatorname{erfc}(x) = 1 - \frac{2}{\sqrt{\pi}} \int_0^x e^{-t^2} dt$$

Examples

```
if (torch_is_installed()) {

torch_erfc(torch_tensor(c(0, -1., 10.)))
}
```

torch_erfinv *Erfinv*

Description

Erfinv

Usage

```
torch_erfinv(self)
```

Arguments

self	(Tensor) the input tensor.

erfinv(input, out=NULL) -> Tensor

Computes the inverse error function of each element of `input`. The inverse error function is defined in the range $(-1, 1)$ as:

$$\mathrm{erfinv}(\mathrm{erf}(x)) = x$$

Examples

```
if (torch_is_installed()) {

torch_erfinv(torch_tensor(c(0, 0.5, -1.)))
}
```

torch_exp *Exp*

Description

Exp

Usage

```
torch_exp(self)
```

Arguments

self	(Tensor) the input tensor.

exp(input, out=NULL) -> Tensor

Returns a new tensor with the exponential of the elements of the input tensor `input`.

$$y_i = e^{x_i}$$

Examples

```
if (torch_is_installed()) {

torch_exp(torch_tensor(c(0, log(2))))
}
```

`torch_exp2` *Exp2*

Description

Exp2

Usage

```
torch_exp2(self)
```

Arguments

`self`	(Tensor) the input tensor.

exp2(input, *, out=None) -> Tensor

Computes the base two exponential function of `input`.

$$y_i = 2^{x_i}$$

Examples

```
if (torch_is_installed()) {

torch_exp2(torch_tensor(c(0, log2(2.), 3, 4)))
}
```

torch_expm1 *Expm1*

Description

Expm1

Usage

```
torch_expm1(self)
```

Arguments

self	(Tensor) the input tensor.

expm1(input, out=NULL) -> Tensor

Returns a new tensor with the exponential of the elements minus 1 of input.

$$y_i = e^{x_i} - 1$$

Examples

```
if (torch_is_installed()) {

torch_expm1(torch_tensor(c(0, log(2))))
}
```

torch_eye *Eye*

Description

Eye

Usage

```
torch_eye(
  n,
  m = n,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

n	(int) the number of rows
m	(int, optional) the number of columns with default being n
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type).
layout	(torch.layout, optional) the desired layout of returned Tensor. Default: torch_strided.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

eye(n, m=NULL, out=NULL, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Returns a 2-D tensor with ones on the diagonal and zeros elsewhere.

Examples

```
if (torch_is_installed()) {

torch_eye(3)
}
```

---

torch_fft_fft *Fft*

Description

Computes the one dimensional discrete Fourier transform of input.

Usage

```
torch_fft_fft(self, n = NULL, dim = -1L, norm = NULL)
```

Arguments

self	(Tensor) the input tensor
n	(int) Signal length. If given, the input will either be zero-padded or trimmed to this length before computing the FFT.
dim	(int, optional) The dimension along which to take the one dimensional FFT.
norm	(str, optional) Normalization mode. For the forward transform, these correspond to: • "forward" - normalize by 1/n

- "backward" - no normalization
- "ortho" - normalize by 1/sqrt(n) (making the FFT orthonormal) Calling the backward transform (ifft()) with the same normalization mode will apply an overall normalization of 1/n between the two transforms. This is required to make IFFT the exact inverse. Default is "backward" (no normalization).

Note

The Fourier domain representation of any real signal satisfies the Hermitian property: `X[i] = conj(X[-i])`. This function always returns both the positive and negative frequency terms even though, for real inputs, the negative frequencies are redundant. rfft() returns the more compact one-sided representation where only the positive frequencies are returned.

Examples

```
if (torch_is_installed()) {
t <- torch_arange(start = 0, end = 3)
t
torch_fft_fft(t, norm = "backward")

}
```

---

torch_fft_fftfreq *fftfreq*

Description

Computes the discrete Fourier Transform sample frequencies for a signal of size `n`.

Usage

```
torch_fft_fftfreq(
  n,
  d = 1,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

`n`	(integer) – the FFT length
`d`	(float, optional) – the sampling length scale. The spacing between individual samples of the FFT input. The default assumes unit spacing, dividing that result by the actual spacing gives the result in physical frequency units.
`dtype`	(default: `torch_get_default_dtype()`) the desired data type of returned tensor.

layout	(default: torch_strided()) the desired layout of returned tensor.
device	(default: NULL) the desired device of returned tensor. Default: If NULL, uses the current device for the default tensor type.
requires_grad	(default: FALSE) If autograd should record operations on the returned tensor.

Note

By convention, torch_fft_fft() returns positive frequency terms first, followed by the negative frequencies in reverse order, so that f[-i] for all 0 < i <= n/2 gives the negative frequency terms. For an FFT of length n and with inputs spaced in length unit d, the frequencies are: f = [0, 1, ..., (n - 1) // 2, -(n // 2), ..., -1] / (d * n)

For even lengths, the Nyquist frequency at f[n/2] can be thought of as either negative or positive. fftfreq() follows NumPy's convention of taking it to be negative.

Examples

```
if (torch_is_installed()) {
torch_fft_fftfreq(5) # Nyquist frequency at f[3] is positive
torch_fft_fftfreq(4) # Nyquist frequency at f[3] is given as negative

}
```

---

torch_fft_ifft *Ifft*

Description

Computes the one dimensional inverse discrete Fourier transform of input.

Usage

```
torch_fft_ifft(self, n = NULL, dim = -1L, norm = NULL)
```

Arguments

self	(Tensor) the input tensor
n	(int, optional) – Signal length. If given, the input will either be zero-padded or trimmed to this length before computing the IFFT.
dim	(int, optional) – The dimension along which to take the one dimensional IFFT.
norm	(str, optional) – Normalization mode. For the backward transform, these correspond to: • "forward" - no normalization • "backward" - normalize by 1/n • "ortho" - normalize by 1/sqrt(n) (making the IFFT orthonormal) Calling the forward transform with the same normalization mode will apply an overall normalization of 1/n between the two transforms. This is required to make ifft() the exact inverse. Default is "backward" (normalize by 1/n).

Examples

```
if (torch_is_installed()) {
t <- torch_arange(start = 0, end = 3)
t
x <- torch_fft_fft(t, norm = "backward")
torch_fft_ifft(x)


}
```

---

torch_fft_irfft *Irfft*

Description

Computes the inverse of torch_fft_rfft(). Input is interpreted as a one-sided Hermitian signal in the Fourier domain, as produced by torch_fft_rfft(). By the Hermitian property, the output will be real-valued.

Usage

```
torch_fft_irfft(self, n = NULL, dim = -1L, norm = NULL)
```

Arguments

self	(Tensor) the input tensor representing a half-Hermitian signal
n	(int) Output signal length. This determines the length of the output signal. If given, the input will either be zero-padded or trimmed to this length before computing the real IFFT. Defaults to even output: `n=2*(input.size(dim) - 1)`.
dim	(int, optional) – The dimension along which to take the one dimensional real IFFT.
norm	(str, optional) – Normalization mode. For the backward transform, these correspond to: • "forward" - no normalization • "backward" - normalize by 1/n • "ortho" - normalize by 1/sqrt(n) (making the real IFFT orthonormal) Calling the forward transform (torch_fft_rfft()) with the same normalization mode will apply an overall normalization of 1/n between the two transforms. This is required to make irfft() the exact inverse. Default is "backward" (normalize by 1/n).

Note

Some input frequencies must be real-valued to satisfy the Hermitian property. In these cases the imaginary component will be ignored. For example, any imaginary component in the zero-frequency term cannot be represented in a real output and so will always be ignored.

The correct interpretation of the Hermitian input depends on the length of the original data, as given by n. This is because each input shape could correspond to either an odd or even length signal. By default, the signal is assumed to be even length and odd signals will not round-trip properly. So, it is recommended to always pass the signal length n.

Examples

```
if (torch_is_installed()) {
t <- torch_arange(start = 0, end = 4)
x <- torch_fft_rfft(t)
torch_fft_irfft(x)
torch_fft_irfft(x, n = t$numel())

}
```

---

torch_fft_rfft *Rfft*

Description

Computes the one dimensional Fourier transform of real-valued input.

Usage

```
torch_fft_rfft(self, n = NULL, dim = -1L, norm = NULL)
```

Arguments

self	(Tensor) the real input tensor
n	(int) Signal length. If given, the input will either be zero-padded or trimmed to this length before computing the real FFT.
dim	(int, optional) – The dimension along which to take the one dimensional real FFT.
norm	norm (str, optional) – Normalization mode. For the forward transform, these correspond to: • "forward" - normalize by 1/n • "backward" - no normalization • "ortho" - normalize by 1/sqrt(n) (making the FFT orthonormal) Calling the backward transform (`torch_fft_irfft()`) with the same normalization mode will apply an overall normalization of 1/n between the two transforms. This is required to make irfft() the exact inverse. Default is "backward" (no normalization).

Details

The FFT of a real signal is Hermitian-symmetric, `X[i] = conj(X[-i])` so the output contains only the positive frequencies below the Nyquist frequency. To compute the full output, use `torch_fft_fft()`.

Examples

```
if (torch_is_installed()) {
t <- torch_arange(start = 0, end = 3)
torch_fft_rfft(t)

}
```

---

torch_finfo *Floating point type info*

Description

A list that represents the numerical properties of a floating point torch.dtype

Usage

```
torch_finfo(dtype)
```

Arguments

`dtype`	dtype to check information

---

torch_fix *Fix*

Description

Fix

Usage

```
torch_fix(self)
```

Arguments

`self`	(Tensor) the input tensor.

fix(input, *, out=None) -> Tensor

Alias for `torch_trunc()`

torch_flatten *Flatten*

Description

Flatten

Usage

```
torch_flatten(self, dims, start_dim = 1L, end_dim = -1L, out_dim)
```

Arguments

self	(Tensor) the input tensor.
dims	if tensor is named you can pass the name of the dimensions to flatten
start_dim	(int) the first dim to flatten
end_dim	(int) the last dim to flatten
out_dim	the name of the resulting dimension if a named tensor.

flatten(input, start_dim=0, end_dim=-1) -> Tensor

Flattens a contiguous range of dims in a tensor.

Examples

```
if (torch_is_installed()) {

t = torch_tensor(matrix(c(1, 2), ncol = 2))
torch_flatten(t)
torch_flatten(t, start_dim=2)
}
```

torch_flip *Flip*

Description

Flip

Usage

```
torch_flip(self, dims)
```

Arguments

`self`	(Tensor) the input tensor.
`dims`	(a list or tuple) axis to flip on

flip(input, dims) -> Tensor

Reverse the order of a n-D tensor along given axis in dims.

Examples

```
if (torch_is_installed()) {

x <- torch_arange(1, 8)$view(c(2, 2, 2))
x
torch_flip(x, c(1, 2))
}
```

---

torch_fliplr *Fliplr*

Description

Fliplr

Usage

```
torch_fliplr(self)
```

Arguments

`self`	(Tensor) Must be at least 2-dimensional.

fliplr(input) -> Tensor

Flip array in the left/right direction, returning a new tensor.

Flip the entries in each row in the left/right direction. Columns are preserved, but appear in a different order than before.

Note

Equivalent to `input[,-1]`. Requires the array to be at least 2-D.

Examples

```
if (torch_is_installed()) {

x <- torch_arange(start = 1, end = 4)$view(c(2, 2))
x
torch_fliplr(x)
}
```

---

torch_flipud *Flipud*

Description

Flipud

Usage

```
torch_flipud(self)
```

Arguments

self	(Tensor) Must be at least 1-dimensional.

flipud(input) -> Tensor

Flip array in the up/down direction, returning a new tensor.

Flip the entries in each column in the up/down direction. Rows are preserved, but appear in a different order than before.

Note

Equivalent to `input[-1,]`. Requires the array to be at least 1-D.

Examples

```
if (torch_is_installed()) {

x <- torch_arange(start = 1, end = 4)$view(c(2, 2))
x
torch_flipud(x)
}
```

torch_floor *Floor*

Description

Floor

Usage

```
torch_floor(self)
```

Arguments

self	(Tensor) the input tensor.

floor(input, out=NULL) -> Tensor

Returns a new tensor with the floor of the elements of `input`, the largest integer less than or equal to each element.

$$\text{out}_i = \lfloor \text{input}_i \rfloor$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_floor(a)
}
```

torch_floor_divide *Floor_divide*

Description

Floor_divide

Usage

```
torch_floor_divide(self, other)
```

Arguments

self	(Tensor) the numerator tensor
other	(Tensor or Scalar) the denominator

floor_divide(input, other, out=NULL) -> Tensor

Return the division of the inputs rounded down to the nearest integer. See torch_div for type promotion and broadcasting rules.

$$\text{out}_i = \left\lfloor \frac{\text{input}_i}{\text{other}_i} \right\rfloor$$

Examples

```
if (torch_is_installed()) {

a = torch_tensor(c(4.0, 3.0))
b = torch_tensor(c(2.0, 2.0))
torch_floor_divide(a, b)
torch_floor_divide(a, 1.4)
}
```

---

torch_fmod *Fmod*

Description

Fmod

Usage

```
torch_fmod(self, other)
```

Arguments

self	(Tensor) the dividend
other	(Tensor or float) the divisor, which may be either a number or a tensor of the same shape as the dividend

fmod(input, other, out=NULL) -> Tensor

Computes the element-wise remainder of division.

The dividend and divisor may contain both for integer and floating point numbers. The remainder has the same sign as the dividend input.

When other is a tensor, the shapes of input and other must be broadcastable .

Examples

```
if (torch_is_installed()) {

torch_fmod(torch_tensor(c(-3., -2, -1, 1, 2, 3)), 2)
torch_fmod(torch_tensor(c(1., 2, 3, 4, 5)), 1.5)
}
```

torch_frac *Frac*

Description

Frac

Usage

```
torch_frac(self)
```

Arguments

self	the input tensor.

frac(input, out=NULL) -> Tensor

Computes the fractional portion of each element in `input`.

$$\text{out}_i = \text{input}_i - \lfloor |\text{input}_i| \rfloor * \text{sgn}(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

torch_frac(torch_tensor(c(1, 2.5, -3.2)))
}
```

torch_full *Full*

Description

Full

Usage

```
torch_full(
  size,
  fill_value,
  names = NULL,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

size	(int...) a list, tuple, or torch_Size of integers defining the shape of the output tensor.
fill_value	NA the number to fill the output tensor with.
names	optional names of the dimensions
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type).
layout	(torch.layout, optional) the desired layout of returned Tensor. Default: torch_strided.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

full(size, fill_value, out=NULL, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Returns a tensor of size size filled with fill_value.

Warning

In PyTorch 1.5 a bool or integral fill_value will produce a warning if dtype or out are not set. In a future PyTorch release, when dtype and out are not set a bool fill_value will return a tensor of torch.bool dtype, and an integral fill_value will return a tensor of torch.long dtype.

Examples

```
if (torch_is_installed()) {

torch_full(list(2, 3), 3.141592)
}
```

---

torch_full_like *Full_like*

Description

Full_like

Usage

```
torch_full_like(
  input,
  fill_value,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE,
  memory_format = torch_preserve_format()
)
```

Arguments

input	(Tensor) the size of input will determine size of the output tensor.
fill_value	the number to fill the output tensor with.
dtype	(torch.dtype, optional) the desired data type of returned Tensor. Default: if NULL, defaults to the dtype of input.
layout	(torch.layout, optional) the desired layout of returned tensor. Default: if NULL, defaults to the layout of input.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, defaults to the device of input.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.
memory_format	(torch.memory_format, optional) the desired memory format of returned Tensor. Default: torch_preserve_format.

full_like(input, fill_value, out=NULL, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False,

memory_format=torch.preserve_format) -> Tensor

Returns a tensor with the same size as input filled with fill_value. torch_full_like(input, fill_value) is equivalent to torch_full(input.size(), fill_value, dtype=input.dtype, layout=input.layout, device=input.device).

---

torch_gather *Gather*

Description

Gather

Usage

```
torch_gather(self, dim, index, sparse_grad = FALSE)
```

Arguments

self	(Tensor) the source tensor
dim	(int) the axis along which to index
index	(LongTensor) the indices of elements to gather
sparse_grad	(bool,optional) If TRUE, gradient w.r.t. input will be a sparse tensor.

gather(input, dim, index, sparse_grad=FALSE) -> Tensor

Gathers values along an axis specified by dim.

For a 3-D tensor the output is specified by::

```
out[i][j][k] = input[index[i][j][k]][j][k]  # if dim == 0
out[i][j][k] = input[i][index[i][j][k]][k]  # if dim == 1
out[i][j][k] = input[i][j][index[i][j][k]]  # if dim == 2
```

If input is an n-dimensional tensor with size $(x_0, x_1..., x_{i-1}, x_i, x_{i+1}, ..., x_{n-1})$ and dim = i, then index must be an n-dimensional tensor with size $(x_0, x_1, ..., x_{i-1}, y, x_{i+1}, ..., x_{n-1})$ where $y \geq 1$ and out will have the same size as index.

Examples

```
if (torch_is_installed()) {

t = torch_tensor(matrix(c(1,2,3,4), ncol = 2, byrow = TRUE))
torch_gather(t, 2, torch_tensor(matrix(c(1,1,2,1), ncol = 2, byrow=TRUE), dtype = torch_int64()))
}
```

---

torch_gcd *Gcd*

Description

Gcd

Usage

```
torch_gcd(self, other)
```

Arguments

self	(Tensor) the input tensor.
other	(Tensor) the second input tensor

gcd(input, other, *, out=None) -> Tensor

Computes the element-wise greatest common divisor (GCD) of input and other.

Both input and other must have integer types.

Note

This defines $gcd(0, 0) = 0$.

Examples

```
if (torch_is_installed()) {

if (torch::cuda_is_available()) {
a <- torch_tensor(c(5, 10, 15), dtype = torch_long(), device = "cuda")
b <- torch_tensor(c(3, 4, 5), dtype = torch_long(), device = "cuda")
torch_gcd(a, b)
c <- torch_tensor(c(3L), device = "cuda")
torch_gcd(a, c)
}
}
```

---

torch_ge *Ge*

Description

Ge

Usage

```
torch_ge(self, other)
```

Arguments

self	(Tensor) the tensor to compare
other	(Tensor or float) the tensor or value to compare

ge(input, other, out=NULL) -> Tensor

Computes input $\geq$ other element-wise.

The second argument can be a number or a tensor whose shape is broadcastable with the first argument.

Examples

```
if (torch_is_installed()) {

torch_ge(torch_tensor(matrix(1:4, ncol = 2, byrow=TRUE)),
         torch_tensor(matrix(c(1,1,4,4), ncol = 2, byrow=TRUE)))
}
```

torch_generator *Create a Generator object*

Description

A torch_generator is an object which manages the state of the algorithm that produces pseudo random numbers. Used as a keyword argument in many In-place random sampling functions.

Usage

```
torch_generator()
```

Examples

```
if (torch_is_installed()) {

# Via string
generator <- torch_generator()
generator$current_seed()
generator$set_current_seed(1234567L)
generator$current_seed()

}
```

torch_geqrf *Geqrf*

Description

Geqrf

Usage

```
torch_geqrf(self)
```

Arguments

self	(Tensor) the input matrix

geqrf(input, out=NULL) -> (Tensor, Tensor)

This is a low-level function for calling LAPACK directly. This function returns a namedtuple (a, tau) as defined in `LAPACK documentation for geqrf_` .

You'll generally want to use `torch_qr` instead.

Computes a QR decomposition of `input`, but without constructing Q and R as explicit separate matrices.

Rather, this directly calls the underlying LAPACK function `?geqrf` which produces a sequence of 'elementary reflectors'.

See `LAPACK documentation for geqrf_` for further details.

---

torch_ger *Ger*

Description

Ger

Usage

```
torch_ger(self, vec2)
```

Arguments

`self`	(Tensor) 1-D input vector
`vec2`	(Tensor) 1-D input vector

ger(input, vec2, out=NULL) -> Tensor

Outer product of `input` and `vec2`. If `input` is a vector of size n and `vec2` is a vector of size m, then `out` must be a matrix of size $(n \times m)$.

Note

This function does not broadcast .

Examples

```
if (torch_is_installed()) {

v1 = torch_arange(1., 5.)
v2 = torch_arange(1., 4.)
torch_ger(v1, v2)
}
```

torch_get_rng_state *RNG state management*

Description

Low level functionality to set and change the RNG state. It's recommended to use `torch_manual_seed()` for most cases.

Usage

```
torch_get_rng_state()

torch_set_rng_state(state)

cuda_get_rng_state(device = NULL)

cuda_set_rng_state(state, device = NULL)
```

Arguments

`state`	A tensor with the current state or a list containing the state for each device - (for CUDA).
`device`	The cuda device index to get or set the state. If `NULL` gets the state for all available devices.

Functions

- `torch_set_rng_state()`: Sets the RNG state for the CPU
- `cuda_get_rng_state()`: Gets the RNG state for CUDA.
- `cuda_set_rng_state()`: Sets the RNG state for CUDA.

torch_greater *Greater*

Description

Greater

Usage

```
torch_greater(self, other)
```

Arguments

`self`	(Tensor) the tensor to compare
`other`	(Tensor or float) the tensor or value to compare

greater(input, other, *, out=None) -> Tensor

Alias for `torch_gt()`.

`torch_greater_equal` *Greater_equal*

Description

Greater_equal

Usage

```
torch_greater_equal(self, other)
```

Arguments

`self`	(Tensor) the tensor to compare
`other`	(Tensor or float) the tensor or value to compare

greater_equal(input, other, *, out=None) -> Tensor

Alias for `torch_ge()`.

`torch_gt` *Gt*

Description

Gt

Usage

```
torch_gt(self, other)
```

Arguments

`self`	(Tensor) the tensor to compare
`other`	(Tensor or float) the tensor or value to compare

gt(input, other, out=NULL) -> Tensor

Computes input $>$ other element-wise.

The second argument can be a number or a tensor whose shape is broadcastable with the first argument.

Examples

```
if (torch_is_installed()) {

torch_gt(torch_tensor(matrix(1:4, ncol = 2, byrow=TRUE)),
         torch_tensor(matrix(c(1,1,4,4), ncol = 2, byrow=TRUE)))
}
```

---

torch_hamming_window *Hamming_window*

Description

Hamming_window

Usage

```
torch_hamming_window(
  window_length,
  periodic = TRUE,
  alpha = 0.54,
  beta = 0.46,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

window_length	(int) the size of returned window
periodic	(bool, optional) If TRUE, returns a window to be used as periodic function. If False, return a symmetric window.
alpha	(float, optional) The coefficient α in the equation above
beta	(float, optional) The coefficient β in the equation above
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type). Only floating point types are supported.
layout	(torch.layout, optional) the desired layout of returned window tensor. Only torch_strided (dense layout) is supported.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

hamming_window(window_length, periodic=TRUE, alpha=0.54, beta=0.46, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Hamming window function.

$$w[n] = \alpha - \beta\ \cos\left(\frac{2\pi n}{N-1}\right),$$

where N is the full window size.

The input `window_length` is a positive integer controlling the returned window size. `periodic` flag determines whether the returned window trims off the last duplicate value from the symmetric window and is ready to be used as a periodic window with functions like `torch_stft`. Therefore, if `periodic` is true, the N in above formula is in fact window_length $+ 1$. Also, we always have `torch_hamming_window(L, periodic=TRUE)` equal to `torch_hamming_window(L + 1, periodic=False)[:-1])`.

Note

```
If `window_length` \eqn{=1}, the returned window contains a single value 1.

This is a generalized version of `torch_hann_window`.
```

`torch_hann_window` *Hann_window*

Description

Hann_window

Usage

```
torch_hann_window(
  window_length,
  periodic = TRUE,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

`window_length`	(int) the size of returned window
`periodic`	(bool, optional) If TRUE, returns a window to be used as periodic function. If False, return a symmetric window.
`dtype`	(`torch.dtype`, optional) the desired data type of returned tensor. Default: if `NULL`, uses a global default (see `torch_set_default_tensor_type`). Only floating point types are supported.

layout	(torch.layout, optional) the desired layout of returned window tensor. Only torch_strided (dense layout) is supported.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

hann_window(window_length, periodic=TRUE, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Hann window function.

$$w[n] = \frac{1}{2}\left[1 - \cos\left(\frac{2\pi n}{N-1}\right)\right] = \sin^2\left(\frac{\pi n}{N-1}\right),$$

where N is the full window size.

The input window_length is a positive integer controlling the returned window size. periodic flag determines whether the returned window trims off the last duplicate value from the symmetric window and is ready to be used as a periodic window with functions like torch_stft. Therefore, if periodic is true, the N in above formula is in fact window_length $+ 1$. Also, we always have torch_hann_window(L, periodic=TRUE) equal to torch_hann_window(L + 1, periodic=False)[:-1]).

Note

```
If `window_length` \eqn{=1}, the returned window contains a single value 1.
```

---

torch_heaviside *Heaviside*

Description

Heaviside

Usage

```
torch_heaviside(self, values)
```

Arguments

self	(Tensor) the input tensor.
values	(Tensor) The values to use where input is zero.

heaviside(input, values, *, out=None) -> Tensor

Computes the Heaviside step function for each element in `input`. The Heaviside step function is defined as:

$$\text{heaviside}(input, values) = \begin{array}{ll} 0, & \text{if input} < 0 \\ values, & \text{if input} == 0 \\ 1, & \text{if input} > 0 \end{array}$$

Examples

```
if (torch_is_installed()) {

input <- torch_tensor(c(-1.5, 0, 2.0))
values <- torch_tensor(c(0.5))
torch_heaviside(input, values)
values <- torch_tensor(c(1.2, -2.0, 3.5))
torch_heaviside(input, values)
}
```

---

torch_histc *Histc*

Description

Histc

Usage

```
torch_histc(self, bins = 100L, min = 0L, max = 0L)
```

Arguments

`self`	(Tensor) the input tensor.
`bins`	(int) number of histogram bins
`min`	(int) lower end of the range (inclusive)
`max`	(int) upper end of the range (inclusive)

histc(input, bins=100, min=0, max=0, out=NULL) -> Tensor

Computes the histogram of a tensor.

The elements are sorted into equal width bins between `min` and `max`. If `min` and `max` are both zero, the minimum and maximum values of the data are used.

Examples

```
if (torch_is_installed()) {

torch_histc(torch_tensor(c(1., 2, 1)), bins=4, min=0, max=3)
}
```

torch_hstack *Hstack*

Description

Hstack

Usage

```
torch_hstack(tensors)
```

Arguments

tensors	(sequence of Tensors) sequence of tensors to concatenate

hstack(tensors, *, out=None) -> Tensor

Stack tensors in sequence horizontally (column wise).

This is equivalent to concatenation along the first axis for 1-D tensors, and along the second axis for all other tensors.

Examples

```
if (torch_is_installed()) {

a <- torch_tensor(c(1, 2, 3))
b <- torch_tensor(c(4, 5, 6))
torch_hstack(list(a,b))
a <- torch_tensor(rbind(1,2,3))
b <- torch_tensor(rbind(4,5,6))
torch_hstack(list(a,b))
}
```

torch_hypot *Hypot*

Description

Hypot

Usage

```
torch_hypot(self, other)
```

Arguments

`self`	(Tensor) the first input tensor
`other`	(Tensor) the second input tensor

hypot(input, other, *, out=None) -> Tensor

Given the legs of a right triangle, return its hypotenuse.

$$\text{out}_i = \sqrt{\text{input}_i^2 + \text{other}_i^2}$$

The shapes of `input` and `other` must be broadcastable .

Examples

```
if (torch_is_installed()) {

torch_hypot(torch_tensor(c(4.0)), torch_tensor(c(3.0, 4.0, 5.0)))
}
```

---

torch_i0 *I0*

Description

I0

Usage

```
torch_i0(self)
```

Arguments

`self`	(Tensor) the input tensor

i0(input, *, out=None) -> Tensor

Computes the zeroth order modified Bessel function of the first kind for each element of `input`.

$$\text{out}_i = I_0(\text{input}_i) = \sum_{k=0}^{\infty} \frac{(\text{input}_i^2/4)^k}{(k!)^2}$$

Examples

```
if (torch_is_installed()) {

torch_i0(torch_arange(start = 0, end = 5, dtype=torch_float32()))
}
```

torch_iinfo *Integer type info*

Description

A list that represents the numerical properties of a integer type.

Usage

```
torch_iinfo(dtype)
```

Arguments

dtype	dtype to get information from.

torch_imag *Imag*

Description

Imag

Usage

```
torch_imag(self)
```

Arguments

self	(Tensor) the input tensor.

imag(input) -> Tensor

Returns the imaginary part of the `input` tensor.

Warning

Not yet implemented.

$$\text{out}_i = imag(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {
## Not run:
torch_imag(torch_tensor(c(-1 + 1i, -2 + 2i, 3 - 3i)))

## End(Not run)
}
```

torch_index *Index torch tensors*

Description

Helper functions to index tensors.

Usage

```
torch_index(self, indices)
```

Arguments

self	(Tensor) Tensor that will be indexed.
indices	(List[Tensor]) List of indices. Indices are torch tensors with torch_long() dtype.

torch_index_put *Modify values selected by* indices.

Description

Modify values selected by indices.

Usage

```
torch_index_put(self, indices, values, accumulate = FALSE)
```

Arguments

self	(Tensor) Tensor that will be indexed.
indices	(List[Tensor]) List of indices. Indices are torch tensors with torch_long() dtype.
values	(Tensor) values that will be replaced the indexed location. Used for torch_index_put and torch_index_put_.
accumulate	(bool) Wether instead of replacing the current values with values, you want to add them.

torch_index_put_ *In-place version of* torch_index_put.

Description

In-place version of torch_index_put.

Usage

```
torch_index_put_(self, indices, values, accumulate = FALSE)
```

Arguments

self	(Tensor) Tensor that will be indexed.
indices	(List[Tensor]) List of indices. Indices are torch tensors with torch_long() dtype.
values	(Tensor) values that will be replaced the indexed location. Used for torch_index_put and torch_index_put_.
accumulate	(bool) Wether instead of replacing the current values with values, you want to add them.

torch_index_select *Index_select*

Description

Index_select

Usage

```
torch_index_select(self, dim, index)
```

Arguments

self	(Tensor) the input tensor.
dim	(int) the dimension in which we index
index	(LongTensor) the 1-D tensor containing the indices to index

index_select(input, dim, index, out=NULL) -> Tensor

Returns a new tensor which indexes the input tensor along dimension dim using the entries in index which is a LongTensor.

The returned tensor has the same number of dimensions as the original tensor (input). The dim\ th dimension has the same size as the length of index; other dimensions have the same size as in the original tensor.

Note

The returned tensor does **not** use the same storage as the original tensor. If `out` has a different shape than expected, we silently change it to the correct shape, reallocating the underlying storage if necessary.

Examples

```
if (torch_is_installed()) {

x = torch_randn(c(3, 4))
x
indices = torch_tensor(c(1, 3), dtype = torch_int64())
torch_index_select(x, 1, indices)
torch_index_select(x, 2, indices)
}
```

---

torch_install_path — *A simple exported version of install_path Returns the torch installation path.*

Description

A simple exported version of install_path Returns the torch installation path.

Usage

```
torch_install_path()
```

---

torch_inverse — *Inverse*

Description

Inverse

Usage

```
torch_inverse(self)
```

Arguments

`self`	(Tensor) the input tensor of size $(*, n, n)$ where $*$ is zero or more batch dimensions

inverse(input, out=NULL) -> Tensor

Takes the inverse of the square matrix `input`. `input` can be batches of 2D square tensors, in which case this function would return a tensor composed of individual inverses.

Note

```
Irrespective of the original strides, the returned tensors will be
transposed, i.e. with strides like `input.contiguous().transpose(-2, -1).stride()`
```

Examples

```
if (torch_is_installed()) {
## Not run:
x = torch_rand(c(4, 4))
y = torch_inverse(x)
z = torch_mm(x, y)
z
torch_max(torch_abs(z - torch_eye(4))) # Max non-zero
# Batched inverse example
x = torch_randn(c(2, 3, 4, 4))
y = torch_inverse(x)
z = torch_matmul(x, y)
torch_max(torch_abs(z - torch_eye(4)$expand_as(x))) # Max non-zero

## End(Not run)
}
```

---

torch_isclose *Isclose*

Description

Isclose

Usage

```
torch_isclose(self, other, rtol = 1e-05, atol = 1e-08, equal_nan = FALSE)
```

Arguments

`self`	(Tensor) first tensor to compare
`other`	(Tensor) second tensor to compare
`rtol`	(float, optional) relative tolerance. Default: 1e-05
`atol`	(float, optional) absolute tolerance. Default: 1e-08
`equal_nan`	(bool, optional) if `TRUE`, then two `NaN` s will be considered equal. Default: `FALSE`

isclose(input, other, rtol=1e-05, atol=1e-08, equal_nan=FALSE) -> Tensor

Returns a new tensor with boolean elements representing if each element of `input` is "close" to the corresponding element of `other`. Closeness is defined as:

$$|\text{input} - \text{other}| \leq \text{atol} + \text{rtol} \times |\text{other}|$$

where `input` and `other` are finite. Where `input` and/or `other` are nonfinite they are close if and only if they are equal, with NaNs being considered equal to each other when `equal_nan` is TRUE.

Examples

```
if (torch_is_installed()) {

torch_isclose(torch_tensor(c(1., 2, 3)), torch_tensor(c(1 + 1e-10, 3, 4)))
torch_isclose(torch_tensor(c(Inf, 4)), torch_tensor(c(Inf, 6)), rtol=.5)
}
```

`torch_isfinite` *Isfinite*

Description

Isfinite

Usage

```
torch_isfinite(self)
```

Arguments

`self`	(Tensor) A tensor to check

TEST

Returns a new tensor with boolean elements representing if each element is `Finite` or not.

Examples

```
if (torch_is_installed()) {

torch_isfinite(torch_tensor(c(1, Inf, 2, -Inf, NaN)))
}
```

torch_isinf *Isinf*

Description

Isinf

Usage

```
torch_isinf(self)
```

Arguments

self	(Tensor) A tensor to check

TEST

Returns a new tensor with boolean elements representing if each element is +/-INF or not.

Examples

```
if (torch_is_installed()) {

torch_isinf(torch_tensor(c(1, Inf, 2, -Inf, NaN)))
}
```

torch_isnan *Isnan*

Description

Isnan

Usage

```
torch_isnan(self)
```

Arguments

self	(Tensor) A tensor to check

TEST

Returns a new tensor with boolean elements representing if each element is NaN or not.

Examples

```
if (torch_is_installed()) {

torch_isnan(torch_tensor(c(1, NaN, 2)))
}
```

---

torch_isneginf *Isneginf*

Description

Isneginf

Usage

```
torch_isneginf(self)
```

Arguments

self	(Tensor) the input tensor.

isneginf(input, *, out=None) -> Tensor

Tests if each element of `input` is negative infinity or not.

Examples

```
if (torch_is_installed()) {

a <- torch_tensor(c(-Inf, Inf, 1.2))
torch_isneginf(a)
}
```

---

torch_isposinf *Isposinf*

Description

Isposinf

Usage

```
torch_isposinf(self)
```

Arguments

self	(Tensor) the input tensor.

isposinf(input, *, out=None) -> Tensor

Tests if each element of `input` is positive infinity or not.

Examples

```
if (torch_is_installed()) {

a <- torch_tensor(c(-Inf, Inf, 1.2))
torch_isposinf(a)
}
```

`torch_isreal` *Isreal*

Description

Isreal

Usage

```
torch_isreal(self)
```

Arguments

`self`	(Tensor) the input tensor.

isreal(input) -> Tensor

Returns a new tensor with boolean elements representing if each element of `input` is real-valued or not. All real-valued types are considered real. Complex values are considered real when their imaginary part is 0.

Examples

```
if (torch_is_installed()) {
if (FALSE) {
torch_isreal(torch_tensor(c(1, 1+1i, 2+0i)))
}
}
```

torch_istft *Istft*

Description

Inverse short time Fourier Transform. This is expected to be the inverse of torch_stft().

Usage

```
torch_istft(
  self,
  n_fft,
  hop_length = NULL,
  win_length = NULL,
  window = list(),
  center = TRUE,
  normalized = FALSE,
  onesided = NULL,
  length = NULL,
  return_complex = FALSE
)
```

Arguments

self	(Tensor) The input tensor. Expected to be output of torch_stft(), can either be complex (channel, fft_size, n_frame), or real (channel, fft_size, n_frame, 2) where the channel dimension is optional.
n_fft	(int) Size of Fourier transform
hop_length	(Optional[int]) The distance between neighboring sliding window frames. (Default: n_fft %% 4)
win_length	(Optional[int]) The size of window frame and STFT filter. (Default: n_fft)
window	(Optional(torch.Tensor)) The optional window function. (Default: torch_ones(win_length))
center	(bool) Whether input was padded on both sides so that the t-th frame is centered at time $t \times$ hop_length. (Default: TRUE)
normalized	(bool) Whether the STFT was normalized. (Default: FALSE)
onesided	(Optional(bool)) Whether the STFT was onesided. (Default: TRUE if n_fft != fft_size in the input size)
length	(Optional(int)]) The amount to trim the signal by (i.e. the original signal length). (Default: whole signal)
return_complex	(Optional(bool)) Whether the output should be complex, or if the input should be assumed to derive from a real signal and window. Note that this is incompatible with onesided=TRUE. (Default: FALSE)

Details

It has the same parameters (+ additional optional parameter of `length`) and it should return the least squares estimation of the original signal. The algorithm will check using the NOLA condition (nonzero overlap).

Important consideration in the parameters `window` and `center` so that the envelop created by the summation of all the windows is never zero at certain point in time. Specifically, $\sum_{t=-\infty}^{\infty} |w|^2(n - t \times hop_length) \neq 0$.

Since `torch_stft()` discards elements at the end of the signal if they do not fit in a frame, `istft` may return a shorter signal than the original signal (can occur if `center` is FALSE since the signal isn't padded).

If `center` is `TRUE`, then there will be padding e.g. `'constant'`, `'reflect'`, etc. Left padding can be trimmed off exactly because they can be calculated but right padding cannot be calculated without additional information.

Example: Suppose the last window is: `[c(17, 18, 0, 0, 0)` vs `c(18, 0, 0, 0, 0)`

The `n_fft`, `hop_length`, `win_length` are all the same which prevents the calculation of right padding. These additional values could be zeros or a reflection of the signal so providing `length` could be useful. If `length` is `None` then padding will be aggressively removed (some loss of signal).

D. W. Griffin and J. S. Lim, "Signal estimation from modified short-time Fourier transform," IEEE Trans. ASSP, vol.32, no.2, pp.236-243, Apr. 1984.

`torch_is_complex` *Is_complex*

Description

Is_complex

Usage

```
torch_is_complex(self)
```

Arguments

`self`	(Tensor) the PyTorch tensor to test

is_complex(input) -> (bool)

Returns TRUE if the data type of `input` is a complex data type i.e., one of `torch_complex64`, and `torch.complex128`.

torch_is_floating_point *Is_floating_point*

Description

Is_floating_point

Usage

```
torch_is_floating_point(self)
```

Arguments

`self`	(Tensor) the PyTorch tensor to test

is_floating_point(input) -> (bool)

Returns TRUE if the data type of `input` is a floating point data type i.e., one of `torch_float64`, `torch.float32` and `torch.float16`.

torch_is_installed *Verifies if torch is installed*

Description

Verifies if torch is installed

Usage

```
torch_is_installed()
```

torch_is_nonzero *Is_nonzero*

Description

Is_nonzero

Usage

```
torch_is_nonzero(self)
```

Arguments

self	(Tensor) the input tensor.

is_nonzero(input) -> (bool)

Returns TRUE if the `input` is a single element tensor which is not equal to zero after type conversions. i.e. not equal to `torch_tensor(c(0))` or `torch_tensor(c(0))` or `torch_tensor(c(FALSE))`. Throws a `RuntimeError` if `torch_numel() != 1` (even in case of sparse tensors).

Examples

```
if (torch_is_installed()) {

torch_is_nonzero(torch_tensor(c(0.)))
torch_is_nonzero(torch_tensor(c(1.5)))
torch_is_nonzero(torch_tensor(c(FALSE)))
torch_is_nonzero(torch_tensor(c(3)))
if (FALSE) {
torch_is_nonzero(torch_tensor(c(1, 3, 5)))
torch_is_nonzero(torch_tensor(c()))
}
}
```

torch_kaiser_window *Kaiser_window*

Description

Kaiser_window

Usage

```
torch_kaiser_window(
  window_length,
  periodic,
  beta,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = NULL
)
```

Arguments

window_length	(int) length of the window.
periodic	(bool, optional) If TRUE, returns a periodic window suitable for use in spectral analysis. If FALSE, returns a symmetric window suitable for use in filter design.
beta	(float, optional) shape parameter for the window.
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type). If dtype is not given, infer the data type from the other input arguments. If any of start, end, or stop are floating-point, the dtype is inferred to be the default dtype, see ~torch.get_default_dtype. Otherwise, the dtype is inferred to be torch.int64.
layout	(torch.layout, optional) the desired layout of returned Tensor. Default: torch_strided.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

kaiser_window(window_length, periodic=TRUE, beta=12.0, *, dtype=None, layout=torch.strided, device=None, requires_grad=FALSE) -> Tensor

Computes the Kaiser window with window length window_length and shape parameter beta.

Let I_0 be the zeroth order modified Bessel function of the first kind (see torch_i0()) and N = L - 1 if periodic is FALSE and L if periodic is TRUE, where L is the window_length. This function computes:

$$out_i = I_0 \left(\beta \sqrt{1 - \left(\frac{i - N/2}{N/2} \right)^2} \right) / I_0(\beta)$$

Calling torch_kaiser_window(L, B, periodic=TRUE) is equivalent to calling torch_kaiser_window(L + 1, B, periodi
The periodic argument is intended as a helpful shorthand to produce a periodic window as input to functions like torch_stft().

Note

If `window_length` is one, then the returned window is a single element tensor containing a one.

---

torch_kron *Kronecker product*

Description

Computes the Kronecker product of `self` and `other`.

Usage

```
torch_kron(self, other)
```

Arguments

`self`	(`Tensor`) input Tensor
`other`	(`Tensor`) other tensor.

---

torch_kthvalue *Kthvalue*

Description

Kthvalue

Usage

```
torch_kthvalue(self, k, dim = -1L, keepdim = FALSE)
```

Arguments

`self`	(Tensor) the input tensor.
`k`	(int) k for the k-th smallest element
`dim`	(int, optional) the dimension to find the kth value along
`keepdim`	(bool) whether the output tensor has `dim` retained or not.

kthvalue(input, k, dim=NULL, keepdim=False, out=NULL) -> (Tensor, LongTensor)

Returns a namedtuple `(values, indices)` where `values` is the `k` th smallest element of each row of the `input` tensor in the given dimension `dim`. And `indices` is the index location of each element found.

If `dim` is not given, the last dimension of the `input` is chosen.

If `keepdim` is `TRUE`, both the `values` and `indices` tensors are the same size as `input`, except in the dimension `dim` where they are of size 1. Otherwise, `dim` is squeezed (see `torch_squeeze`), resulting in both the `values` and `indices` tensors having 1 fewer dimension than the `input` tensor.

Examples

```
if (torch_is_installed()) {

x <- torch_arange(1, 6)
x
torch_kthvalue(x, 4)
x <- torch_arange(1,6)$resize_(c(2,3))
x
torch_kthvalue(x, 2, 1, TRUE)
}
```

---

torch_layout *Creates the corresponding layout*

Description

Creates the corresponding layout

Usage

```
torch_strided()

torch_sparse_coo()
```

---

torch_lcm *Lcm*

Description

Lcm

Usage

```
torch_lcm(self, other)
```

Arguments

self	(Tensor) the input tensor.
other	(Tensor) the second input tensor

lcm(input, other, *, out=None) -> Tensor

Computes the element-wise least common multiple (LCM) of `input` and `other`.

Both `input` and `other` must have integer types.

Note

This defines $lcm(0, 0) = 0$ and $lcm(0, a) = 0$.

Examples

```
if (torch_is_installed()) {

if (torch::cuda_is_available()) {
a <- torch_tensor(c(5, 10, 15), dtype = torch_long(), device = "cuda")
b <- torch_tensor(c(3, 4, 5), dtype = torch_long(), device = "cuda")
torch_lcm(a, b)
c <- torch_tensor(c(3L), device = "cuda")
torch_lcm(a, c)
}
}
```

---

torch_le *Le*

Description

Le

Usage

```
torch_le(self, other)
```

Arguments

self	(Tensor) the tensor to compare
other	(Tensor or float) the tensor or value to compare

le(input, other, out=NULL) -> Tensor

Computes input $\leq$ other element-wise.

The second argument can be a number or a tensor whose shape is broadcastable with the first argument.

Examples

```
if (torch_is_installed()) {

torch_le(torch_tensor(matrix(1:4, ncol = 2, byrow=TRUE)),
         torch_tensor(matrix(c(1,1,4,4), ncol = 2, byrow=TRUE)))
}
```

torch_lerp *Lerp*

Description

Lerp

Usage

```
torch_lerp(self, end, weight)
```

Arguments

self	(Tensor) the tensor with the starting points
end	(Tensor) the tensor with the ending points
weight	(float or tensor) the weight for the interpolation formula

lerp(input, end, weight, out=NULL)

Does a linear interpolation of two tensors start (given by input) and end based on a scalar or tensor weight and returns the resulting out tensor.

$$\text{out}_i = \text{start}_i + \text{weight}_i \times (\text{end}_i - \text{start}_i)$$

The shapes of start and end must be broadcastable . If weight is a tensor, then the shapes of weight, start, and end must be broadcastable .

Examples

```
if (torch_is_installed()) {

start = torch_arange(1, 4)
end = torch_empty(4)$fill_(10)
start
end
torch_lerp(start, end, 0.5)
torch_lerp(start, end, torch_full_like(start, 0.5))
}
```

torch_less *Less*

Description

Less

Usage

```
torch_less(self, other)
```

Arguments

self	(Tensor) the tensor to compare
other	(Tensor or float) the tensor or value to compare

less(input, other, *, out=None) -> Tensor

Alias for torch_lt().

torch_less_equal *Less_equal*

Description

Less_equal

Usage

```
torch_less_equal(self, other)
```

Arguments

self	(Tensor) the tensor to compare
other	(Tensor or float) the tensor or value to compare

less_equal(input, other, *, out=None) -> Tensor

Alias for torch_le().

torch_lgamma *Lgamma*

Description

Lgamma

Usage

```
torch_lgamma(self)
```

Arguments

self	(Tensor) the input tensor.

lgamma(input, out=NULL) -> Tensor

Computes the logarithm of the gamma function on `input`.

$$\text{out}_i = \log \Gamma(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_arange(0.5, 2, 0.5)
torch_lgamma(a)
}
```

torch_linspace *Linspace*

Description

Linspace

Usage

```
torch_linspace(
  start,
  end,
  steps = 100,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

start	(float) the starting value for the set of points
end	(float) the ending value for the set of points
steps	(int) number of points to sample between start and end. Default: 100.
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type).
layout	(torch.layout, optional) the desired layout of returned Tensor. Default: torch_strided.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

linspace(start, end, steps=100, out=NULL, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Returns a one-dimensional tensor of steps equally spaced points between start and end.

The output tensor is 1-D of size steps.

Examples

```
if (torch_is_installed()) {

torch_linspace(3, 10, steps=5)
torch_linspace(-10, 10, steps=5)
torch_linspace(start=-10, end=10, steps=5)
torch_linspace(start=-10, end=10, steps=1)
}
```

---

torch_load *Loads a saved object*

Description

Loads a saved object

Usage

```
torch_load(path, device = "cpu")
```

Arguments

path	a path to the saved object
device	a device to load tensors to. By default we load to the cpu but you can also load them to any cuda device. If NULL then the device where the tensor has been saved will be reused.

See Also

Other torch_save: `torch_save()`, `torch_serialize()`

---

torch_log *Log*

Description

Log

Usage

```
torch_log(self)
```

Arguments

`self`	(Tensor) the input tensor.

log(input, out=NULL) -> Tensor

Returns a new tensor with the natural logarithm of the elements of `input`.

$$y_i = \log_e(x_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(5))
a
torch_log(a)
}
```

---

torch_log10 *Log10*

Description

Log10

Usage

```
torch_log10(self)
```

Arguments

`self`	(Tensor) the input tensor.

log10(input, out=NULL) -> Tensor

Returns a new tensor with the logarithm to the base 10 of the elements of `input`.

$$y_i = \log_{10}(x_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_rand(5)
a
torch_log10(a)
}
```

---

torch_log1p *Log1p*

Description

Log1p

Usage

```
torch_log1p(self)
```

Arguments

`self`	(Tensor) the input tensor.

log1p(input, out=NULL) -> Tensor

Returns a new tensor with the natural logarithm of (1 + `input`).

$$y_i = \log_e(x_i + 1)$$

Note

This function is more accurate than `torch_log` for small values of `input`

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(5))
a
torch_log1p(a)
}
```

---

torch_log2 *Log2*

Description

Log2

Usage

```
torch_log2(self)
```

Arguments

self	(Tensor) the input tensor.

log2(input, out=NULL) -> Tensor

Returns a new tensor with the logarithm to the base 2 of the elements of `input`.

$$y_i = \log_2(x_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_rand(5)
a
torch_log2(a)
}
```

torch_logaddexp *Logaddexp*

Description

Logaddexp

Usage

```
torch_logaddexp(self, other)
```

Arguments

self	(Tensor) the input tensor.
other	(Tensor) the second input tensor

logaddexp(input, other, *, out=None) -> Tensor

Logarithm of the sum of exponentiations of the inputs.

Calculates pointwise $\log\left(e^x + e^y\right)$. This function is useful in statistics where the calculated probabilities of events may be so small as to exceed the range of normal floating point numbers. In such cases the logarithm of the calculated probability is stored. This function allows adding probabilities stored in such a fashion.

This op should be disambiguated with `torch_logsumexp()` which performs a reduction on a single tensor.

Examples

```
if (torch_is_installed()) {

torch_logaddexp(torch_tensor(c(-1.0)), torch_tensor(c(-1.0, -2, -3)))
torch_logaddexp(torch_tensor(c(-100.0, -200, -300)), torch_tensor(c(-1.0, -2, -3)))
torch_logaddexp(torch_tensor(c(1.0, 2000, 30000)), torch_tensor(c(-1.0, -2, -3)))
}
```

torch_logaddexp2 *Logaddexp2*

Description

Logaddexp2

Usage

```
torch_logaddexp2(self, other)
```

Arguments

`self`	(Tensor) the input tensor.
`other`	(Tensor) the second input tensor

logaddexp2(input, other, *, out=None) -> Tensor

Logarithm of the sum of exponentiations of the inputs in base-2.

Calculates pointwise $\log_2 (2^x + 2^y)$. See `torch_logaddexp()` for more details.

---

torch_logcumsumexp *Logcumsumexp*

Description

Logcumsumexp

Usage

```
torch_logcumsumexp(self, dim)
```

Arguments

`self`	(Tensor) the input tensor.
`dim`	(int) the dimension to do the operation over

logcumsumexp(input, dim, *, out=None) -> Tensor

Returns the logarithm of the cumulative summation of the exponentiation of elements of `input` in the dimension `dim`.

For summation index j given by `dim` and other indices i, the result is

$$\text{logcumsumexp}(x)_{ij} = \log \sum_{j=0}^{i} \exp(x_{ij})$$

Examples

```
if (torch_is_installed()) {

a <- torch_randn(c(10))
torch_logcumsumexp(a, dim=1)
}
```

torch_logdet *Logdet*

Description

Logdet

Usage

```
torch_logdet(self)
```

Arguments

self	(Tensor) the input tensor of size (*, n, n) where * is zero or more batch dimensions.

logdet(input) -> Tensor

Calculates log determinant of a square matrix or batches of square matrices.

Note

```
Result is `-inf` if `input` has zero log determinant, and is `NaN` if
`input` has negative determinant.

Backward through `logdet` internally uses SVD results when `input`
is not invertible. In this case, double backward through `logdet` will
be unstable in when `input` doesn't have distinct singular values. See
`~torch.svd` for details.
```

Examples

```
if (torch_is_installed()) {

A = torch_randn(c(3, 3))
torch_det(A)
torch_logdet(A)
A
A$det()
A$det()$log()
}
```

torch_logical_and *Logical_and*

Description

Logical_and

Usage

```
torch_logical_and(self, other)
```

Arguments

self	(Tensor) the input tensor.
other	(Tensor) the tensor to compute AND with

logical_and(input, other, out=NULL) -> Tensor

Computes the element-wise logical AND of the given input tensors. Zeros are treated as FALSE and nonzeros are treated as TRUE.

Examples

```
if (torch_is_installed()) {

torch_logical_and(torch_tensor(c(TRUE, FALSE, TRUE)), torch_tensor(c(TRUE, FALSE, FALSE)))
a = torch_tensor(c(0, 1, 10, 0), dtype=torch_int8())
b = torch_tensor(c(4, 0, 1, 0), dtype=torch_int8())
torch_logical_and(a, b)
## Not run:
torch_logical_and(a, b, out=torch_empty(4, dtype=torch_bool()))

## End(Not run)
}
```

torch_logical_not *Logical_not*

Description

Logical_not

Arguments

self	(Tensor) the input tensor.

logical_not(input, out=NULL) -> Tensor

Computes the element-wise logical NOT of the given input tensor. If not specified, the output tensor will have the bool dtype. If the input tensor is not a bool tensor, zeros are treated as FALSE and non-zeros are treated as TRUE.

Examples

```
if (torch_is_installed()) {

torch_logical_not(torch_tensor(c(TRUE, FALSE)))
torch_logical_not(torch_tensor(c(0, 1, -10), dtype=torch_int8()))
torch_logical_not(torch_tensor(c(0., 1.5, -10.), dtype=torch_double()))
}
```

---

torch_logical_or *Logical_or*

Description

Logical_or

Usage

```
torch_logical_or(self, other)
```

Arguments

self	(Tensor) the input tensor.
other	(Tensor) the tensor to compute OR with

logical_or(input, other, out=NULL) -> Tensor

Computes the element-wise logical OR of the given input tensors. Zeros are treated as FALSE and nonzeros are treated as TRUE.

Examples

```
if (torch_is_installed()) {

torch_logical_or(torch_tensor(c(TRUE, FALSE, TRUE)), torch_tensor(c(TRUE, FALSE, FALSE)))
a = torch_tensor(c(0, 1, 10, 0), dtype=torch_int8())
b = torch_tensor(c(4, 0, 1, 0), dtype=torch_int8())
torch_logical_or(a, b)
## Not run:
torch_logical_or(a$double(), b$double())
torch_logical_or(a$double(), b)
torch_logical_or(a, b, out=torch_empty(4, dtype=torch_bool()))

## End(Not run)
}
```

torch_logical_xor *Logical_xor*

Description

Logical_xor

Usage

```
torch_logical_xor(self, other)
```

Arguments

self	(Tensor) the input tensor.
other	(Tensor) the tensor to compute XOR with

logical_xor(input, other, out=NULL) -> Tensor

Computes the element-wise logical XOR of the given input tensors. Zeros are treated as FALSE and nonzeros are treated as TRUE.

Examples

```
if (torch_is_installed()) {

torch_logical_xor(torch_tensor(c(TRUE, FALSE, TRUE)), torch_tensor(c(TRUE, FALSE, FALSE)))
a = torch_tensor(c(0, 1, 10, 0), dtype=torch_int8())
b = torch_tensor(c(4, 0, 1, 0), dtype=torch_int8())
torch_logical_xor(a, b)
torch_logical_xor(a$to(dtype=torch_double()), b$to(dtype=torch_double()))
torch_logical_xor(a$to(dtype=torch_double()), b)
}
```

torch_logit *Logit*

Description

Logit

Usage

```
torch_logit(self, eps = NULL)
```

Arguments

`self`	(Tensor) the input tensor.
`eps`	(float, optional) the epsilon for input clamp bound. Default: `None`

logit(input, eps=None, *, out=None) -> Tensor

Returns a new tensor with the logit of the elements of `input`. `input` is clamped to `[eps, 1 - eps]` when eps is not None. When eps is None and `input` < 0 or `input` > 1, the function will yields NaN.

$$y_i = \ln(\frac{z_i}{1 - z_i})z_i = \begin{array}{ll} x_i & \text{if eps is None} \\ \text{eps} & \text{if } x_i < \text{eps} \\ x_i & \text{if eps} \leq x_i \leq 1 - \text{eps} \\ 1 - \text{eps} & \text{if } x_i > 1 - \text{eps} \end{array}$$

Examples

```
if (torch_is_installed()) {

a <- torch_rand(5)
a
torch_logit(a, eps=1e-6)
}
```

---

torch_logspace *Logspace*

Description

Logspace

Usage

```
torch_logspace(
  start,
  end,
  steps = 100,
  base = 10,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

start	(float) the starting value for the set of points
end	(float) the ending value for the set of points
steps	(int) number of points to sample between start and end. Default: 100.
base	(float) base of the logarithm function. Default: 10.0.
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type).
layout	(torch.layout, optional) the desired layout of returned Tensor. Default: torch_strided.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

logspace(start, end, steps=100, base=10.0, out=NULL, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Returns a one-dimensional tensor of steps points logarithmically spaced with base base between $\text{base}^{\text{start}}$ and base^{end}.

The output tensor is 1-D of size steps.

Examples

```
if (torch_is_installed()) {

torch_logspace(start=-10, end=10, steps=5)
torch_logspace(start=0.1, end=1.0, steps=5)
torch_logspace(start=0.1, end=1.0, steps=1)
torch_logspace(start=2, end=2, steps=1, base=2)
}
```

---

torch_logsumexp *Logsumexp*

Description

Logsumexp

Usage

```
torch_logsumexp(self, dim, keepdim = FALSE)
```

Arguments

`self`	(Tensor) the input tensor.
`dim`	(int or tuple of ints) the dimension or dimensions to reduce.
`keepdim`	(bool) whether the output tensor has `dim` retained or not.

logsumexp(input, dim, keepdim=False, out=NULL)

Returns the log of summed exponentials of each row of the `input` tensor in the given dimension `dim`. The computation is numerically stabilized.

For summation index j given by `dim` and other indices i, the result is

$$\text{logsumexp}(x)_i = \log \sum_j \exp(x_{ij})$$

If `keepdim` is `TRUE`, the output tensor is of the same size as `input` except in the dimension(s) `dim` where it is of size 1. Otherwise, `dim` is squeezed (see `torch_squeeze`), resulting in the output tensor having 1 (or `len(dim)`) fewer dimension(s).

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(3, 3))
torch_logsumexp(a, 1)
}
```

---

torch_lstsq *Lstsq*

Description

Lstsq

Arguments

`self`	(Tensor) the matrix B
`A`	(Tensor) the m by n matrix A

lstsq(input, A, out=NULL) -> Tensor

Computes the solution to the least squares and least norm problems for a full rank matrix A of size $(m \times n)$ and a matrix B of size $(m \times k)$.

If $m \geq n$, `torch_lstsq()` solves the least-squares problem:

$$\min_X \quad \|AX - B\|_2.$$

If $m < n$, torch_lstsq() solves the least-norm problem:

$$\min_X \quad \|X\|_2 \quad \text{subject to} \quad AX = B.$$

Returned tensor X has shape $(\max(m, n) \times k)$. The first n rows of X contains the solution. If $m \geq n$, the residual sum of squares for the solution in each column is given by the sum of squares of elements in the remaining $m - n$ rows of that column.

Note

The case when \eqn{m < n} is not supported on the GPU.

---

torch_lt *Lt*

Description

Lt

Usage

```
torch_lt(self, other)
```

Arguments

self	(Tensor) the tensor to compare
other	(Tensor or float) the tensor or value to compare

lt(input, other, out=NULL) -> Tensor

Computes input $<$ other element-wise.

The second argument can be a number or a tensor whose shape is broadcastable with the first argument.

Examples

```
if (torch_is_installed()) {

torch_lt(torch_tensor(matrix(1:4, ncol = 2, byrow=TRUE)),
         torch_tensor(matrix(c(1,1,4,4), ncol = 2, byrow=TRUE)))
}
```

torch_lu *LU*

Description

Computes the LU factorization of a matrix or batches of matrices A. Returns a tuple containing the LU factorization and pivots of A. Pivoting is done if pivot is set to True.

Usage

```
torch_lu(A, pivot = TRUE, get_infos = FALSE, out = NULL)
```

Arguments

A	(Tensor) the tensor to factor of size *(, m, n)(*,m,n)
pivot	(bool, optional) – controls whether pivoting is done. Default: TRUE
get_infos	(bool, optional) – if set to True, returns an info IntTensor. Default: FALSE
out	(tuple, optional) – optional output tuple. If get_infos is True, then the elements in the tuple are Tensor, IntTensor, and IntTensor. If get_infos is False, then the elements in the tuple are Tensor, IntTensor. Default: NULL

Examples

```
if (torch_is_installed()) {

A <- torch_randn(c(2, 3, 3))
torch_lu(A)
}
```

torch_lu_solve *Lu_solve*

Description

Lu_solve

Usage

```
torch_lu_solve(self, LU_data, LU_pivots)
```

Arguments

self	(Tensor) the RHS tensor of size $(*, m, k)$, where $*$ is zero or more batch dimensions.
LU_data	(Tensor) the pivoted LU factorization of A from torch_lu of size $(*, m, m)$, where $*$ is zero or more batch dimensions.
LU_pivots	(IntTensor) the pivots of the LU factorization from torch_lu of size $(*, m)$, where $*$ is zero or more batch dimensions. The batch dimensions of LU_pivots must be equal to the batch dimensions of LU_data.

lu_solve(input, LU_data, LU_pivots, out=NULL) -> Tensor

Returns the LU solve of the linear system $Ax = b$ using the partially pivoted LU factorization of A from torch_lu.

Examples

```
if (torch_is_installed()) {
A = torch_randn(c(2, 3, 3))
b = torch_randn(c(2, 3, 1))
out = torch_lu(A)
x = torch_lu_solve(b, out[[1]], out[[2]])
torch_norm(torch_bmm(A, x) - b)
}
```

---

torch_lu_unpack *Lu_unpack*

Description

Lu_unpack

Usage

```
torch_lu_unpack(LU_data, LU_pivots, unpack_data = TRUE, unpack_pivots = TRUE)
```

Arguments

LU_data	(Tensor) – the packed LU factorization data
LU_pivots	(Tensor) – the packed LU factorization pivots
unpack_data	(logical) – flag indicating if the data should be unpacked. If FALSE, then the returned L and U are NULL Default: TRUE
unpack_pivots	(logical) – flag indicating if the pivots should be unpacked into a permutation matrix P. If FALSE, then the returned P is None. Default: TRUE

lu_unpack(LU_data, LU_pivots, unpack_data = TRUE, unpack_pivots=TRUE) -> Tensor

Unpacks the data and pivots from a LU factorization of a tensor into tensors `L` and `U` and a permutation tensor `P` such that `LU_data_and_pivots <- torch_lu(P$matmul(L)$matmul(U))`. Returns a list of tensors as `list(the P tensor (permutation matrix), the L tensor, the U tensor)`

`torch_manual_seed` *Sets the seed for generating random numbers.*

Description

Sets the seed for generating random numbers.

Usage

```
torch_manual_seed(seed)

local_torch_manual_seed(seed, .env = parent.frame())

with_torch_manual_seed(code, ..., seed)
```

Arguments

`seed`	integer seed.
`.env`	environment that will take the modifications from manual_seed.
`code`	expression to run in the context of the seed
`...`	unused currently.

Functions

- `local_torch_manual_seed()`: Modifies the torch seed in the environment scope.
- `with_torch_manual_seed()`: A with context to change the seed during the function execution.

Note

Currently the `local_torch_manual_seed` and `with_torch_manual_seed` won't work with Tensors in the MPS device. You can sample the tensors on CPU and move them to MPS if reproducibility is required.

torch_masked_select *Masked_select*

Description

Masked_select

Usage

```
torch_masked_select(self, mask)
```

Arguments

self	(Tensor) the input tensor.
mask	(BoolTensor) the tensor containing the binary mask to index with

masked_select(input, mask, out=NULL) -> Tensor

Returns a new 1-D tensor which indexes the `input` tensor according to the boolean mask `mask` which is a `BoolTensor`.

The shapes of the `mask` tensor and the `input` tensor don't need to match, but they must be broadcastable .

Note

The returned tensor does **not** use the same storage as the original tensor

Examples

```
if (torch_is_installed()) {

x = torch_randn(c(3, 4))
x
mask = x$ge(0.5)
mask
torch_masked_select(x, mask)
}
```

torch_matmul *Matmul*

Description

Matmul

Usage

```
torch_matmul(self, other)
```

Arguments

self	(Tensor) the first tensor to be multiplied
other	(Tensor) the second tensor to be multiplied

matmul(input, other, out=NULL) -> Tensor

Matrix product of two tensors.

The behavior depends on the dimensionality of the tensors as follows:

- If both tensors are 1-dimensional, the dot product (scalar) is returned.
- If both arguments are 2-dimensional, the matrix-matrix product is returned.
- If the first argument is 1-dimensional and the second argument is 2-dimensional, a 1 is prepended to its dimension for the purpose of the matrix multiply. After the matrix multiply, the prepended dimension is removed.
- If the first argument is 2-dimensional and the second argument is 1-dimensional, the matrix-vector product is returned.
- If both arguments are at least 1-dimensional and at least one argument is N-dimensional (where N > 2), then a batched matrix multiply is returned. If the first argument is 1-dimensional, a 1 is prepended to its dimension for the purpose of the batched matrix multiply and removed after. If the second argument is 1-dimensional, a 1 is appended to its dimension for the purpose of the batched matrix multiple and removed after. The non-matrix (i.e. batch) dimensions are broadcasted (and thus must be broadcastable). For example, if `input` is a $(j \times 1 \times n \times m)$ tensor and `other` is a $(k \times m \times p)$ tensor, `out` will be an $(j \times k \times n \times p)$ tensor.

Note

```
The 1-dimensional dot product version of this function does not support an `out` parameter.
```

Examples

```
if (torch_is_installed()) {

# vector x vector
tensor1 = torch_randn(c(3))
tensor2 = torch_randn(c(3))
torch_matmul(tensor1, tensor2)
# matrix x vector
tensor1 = torch_randn(c(3, 4))
tensor2 = torch_randn(c(4))
torch_matmul(tensor1, tensor2)
# batched matrix x broadcasted vector
tensor1 = torch_randn(c(10, 3, 4))
tensor2 = torch_randn(c(4))
torch_matmul(tensor1, tensor2)
# batched matrix x batched matrix
tensor1 = torch_randn(c(10, 3, 4))
tensor2 = torch_randn(c(10, 4, 5))
torch_matmul(tensor1, tensor2)
# batched matrix x broadcasted matrix
tensor1 = torch_randn(c(10, 3, 4))
tensor2 = torch_randn(c(4, 5))
torch_matmul(tensor1, tensor2)
}
```

---

torch_matrix_exp *Matrix_exp*

Description

Matrix_exp

Usage

```
torch_matrix_exp(self)
```

Arguments

`self`	(Tensor) the input tensor.

matrix_power(input) -> Tensor

Returns the matrix exponential. Supports batched input. For a matrix `A`, the matrix exponential is defined as

$$\exp^A = \sum_{k=0}^{\infty} A^k/k!.$$

The implementation is based on: Bader, P.; Blanes, S.; Casas, F. Computing the Matrix Exponential with an Optimized Taylor Polynomial Approximation. Mathematics 2019, 7, 1174.

Examples

```
if (torch_is_installed()) {

a <- torch_randn(c(2, 2, 2))
a[1, , ] <- torch_eye(2, 2)
a[2, , ] <- 2 * torch_eye(2, 2)
a
torch_matrix_exp(a)

x <- torch_tensor(rbind(c(0, pi/3), c(-pi/3, 0)))
x$matrix_exp() # should be [[cos(pi/3), sin(pi/3)], [-sin(pi/3), cos(pi/3)]]
}
```

---

torch_matrix_power *Matrix_power*

Description

Matrix_power

Usage

```
torch_matrix_power(self, n)
```

Arguments

self	(Tensor) the input tensor.
n	(int) the power to raise the matrix to

matrix_power(input, n) -> Tensor

Returns the matrix raised to the power n for square matrices. For batch of matrices, each individual matrix is raised to the power n.

If n is negative, then the inverse of the matrix (if invertible) is raised to the power n. For a batch of matrices, the batched inverse (if invertible) is raised to the power n. If n is 0, then an identity matrix is returned.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(2, 2, 2))
a
torch_matrix_power(a, 3)
}
```

torch_matrix_rank *Matrix_rank*

Description

Matrix_rank

Arguments

self	(Tensor) the input 2-D tensor
tol	(float, optional) the tolerance value. Default: NULL
symmetric	(bool, optional) indicates whether input is symmetric. Default: FALSE

matrix_rank(input, tol=NULL, symmetric=False) -> Tensor

Returns the numerical rank of a 2-D tensor. The method to compute the matrix rank is done using SVD by default. If symmetric is TRUE, then input is assumed to be symmetric, and the computation of the rank is done by obtaining the eigenvalues.

tol is the threshold below which the singular values (or the eigenvalues when symmetric is TRUE) are considered to be 0. If tol is not specified, tol is set to S.max() * max(S.size()) * eps where S is the singular values (or the eigenvalues when symmetric is TRUE), and eps is the epsilon value for the datatype of input.

torch_max *Max*

Description

Max

Arguments

self	(Tensor) the input tensor.
dim	(int) the dimension to reduce.
keepdim	(bool) whether the output tensor has dim retained or not. Default: FALSE.
out	(tuple, optional) the result tuple of two output tensors (max, max_indices)
other	(Tensor) the second input tensor

max(input) -> Tensor

Returns the maximum value of all elements in the input tensor.

max(input, dim, keepdim=False, out=NULL) -> (Tensor, LongTensor)

Returns a namedtuple `(values, indices)` where `values` is the maximum value of each row of the `input` tensor in the given dimension `dim`. And `indices` is the index location of each maximum value found (argmax).

Warning

`indices` does not necessarily contain the first occurrence of each maximal value found, unless it is unique. The exact implementation details are device-specific. Do not expect the same result when run on CPU and GPU in general.

If `keepdim` is `TRUE`, the output tensors are of the same size as `input` except in the dimension `dim` where they are of size 1. Otherwise, `dim` is squeezed (see `torch_squeeze`), resulting in the output tensors having 1 fewer dimension than `input`.

max(input, other, out=NULL) -> Tensor

Each element of the tensor `input` is compared with the corresponding element of the tensor `other` and an element-wise maximum is taken.

The shapes of `input` and `other` don't need to match, but they must be broadcastable .

$$\text{out}_i = \max(\text{tensor}_i, \text{other}_i)$$

Note

When the shapes do not match, the shape of the returned output tensor follows the broadcasting rules .

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(1, 3))
a
torch_max(a)


a = torch_randn(c(4, 4))
a
torch_max(a, dim = 1)


a = torch_randn(c(4))
a
b = torch_randn(c(4))
b
torch_max(a, other = b)
}
```

torch_maximum *Maximum*

Description

Maximum

Usage

```
torch_maximum(self, other)
```

Arguments

self	(Tensor) the input tensor.
other	(Tensor) the second input tensor

maximum(input, other, *, out=None) -> Tensor

Computes the element-wise maximum of `input` and `other`.

Note

If one of the elements being compared is a NaN, then that element is returned. `torch_maximum()` is not supported for tensors with complex dtypes.

Examples

```
if (torch_is_installed()) {

a <- torch_tensor(c(1, 2, -1))
b <- torch_tensor(c(3, 0, 4))
torch_maximum(a, b)
}
```

torch_mean *Mean*

Description

Mean

Usage

```
torch_mean(self, dim, keepdim = FALSE, dtype = NULL)
```

Arguments

self	(Tensor) the input tensor.
dim	(int or tuple of ints) the dimension or dimensions to reduce.
keepdim	(bool) whether the output tensor has dim retained or not.
dtype	the resulting data type.

mean(input) -> Tensor

Returns the mean value of all elements in the input tensor.

mean(input, dim, keepdim=False, out=NULL) -> Tensor

Returns the mean value of each row of the input tensor in the given dimension dim. If dim is a list of dimensions, reduce over all of them.

If keepdim is TRUE, the output tensor is of the same size as input except in the dimension(s) dim where it is of size 1. Otherwise, dim is squeezed (see torch_squeeze), resulting in the output tensor having 1 (or len(dim)) fewer dimension(s).

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(1, 3))
a
torch_mean(a)


a = torch_randn(c(4, 4))
a
torch_mean(a, 1)
torch_mean(a, 1, TRUE)
}
```

---

torch_median *Median*

Description

Median

Usage

```
torch_median(self, dim, keepdim = FALSE)
```

Arguments

self	(Tensor) the input tensor.
dim	(int) the dimension to reduce.
keepdim	(bool) whether the output tensor has dim retained or not.

median(input) -> Tensor

Returns the median value of all elements in the input tensor.

median(input, dim=-1, keepdim=False, out=NULL) -> (Tensor, LongTensor)

Returns a namedtuple (values, indices) where values is the median value of each row of the input tensor in the given dimension dim. And indices is the index location of each median value found.

By default, dim is the last dimension of the input tensor.

If keepdim is TRUE, the output tensors are of the same size as input except in the dimension dim where they are of size 1. Otherwise, dim is squeezed (see torch_squeeze), resulting in the outputs tensor having 1 fewer dimension than input.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(1, 3))
a
torch_median(a)


a = torch_randn(c(4, 5))
a
torch_median(a, 1)
}
```

---

torch_memory_format *Memory format*

Description

Returns the correspondent memory format.

Usage

```
torch_contiguous_format()

torch_preserve_format()

torch_channels_last_format()
```

torch_meshgrid *Meshgrid*

Description

Take N tensors, each of which can be either scalar or 1-dimensional vector, and create N N-dimensional grids, where the i th grid is defined by expanding the i th input over dimensions defined by other inputs.

Usage

```
torch_meshgrid(tensors, indexing)
```

Arguments

tensors	(list of Tensor) list of scalars or 1 dimensional tensors. Scalars will be treated (1,).
indexing	(str, optional): the indexing mode, either "xy" or "ij", defaults to "ij". See warning for future changes. If "xy" is selected, the first dimension corresponds to the cardinality of the second input and the second dimension corresponds to the cardinality of the first input. If "ij" is selected, the dimensions are in the same order as the cardinality of the inputs.

Warning

In the future torch_meshgrid will transition to indexing='xy' as the default. This issue tracks this issue with the goal of migrating to NumPy's behavior.

Examples

```
if (torch_is_installed()) {

x = torch_tensor(c(1, 2, 3))
y = torch_tensor(c(4, 5, 6))
out = torch_meshgrid(list(x, y))
out
}
```

torch_min *Min*

Description

Min

Arguments

`self`	(Tensor) the input tensor.
`dim`	(int) the dimension to reduce.
`keepdim`	(bool) whether the output tensor has `dim` retained or not.
`out`	(tuple, optional) the tuple of two output tensors (min, min_indices)
`other`	(Tensor) the second input tensor

min(input) -> Tensor

Returns the minimum value of all elements in the `input` tensor.

min(input, dim, keepdim=False, out=NULL) -> (Tensor, LongTensor)

Returns a namedtuple `(values, indices)` where `values` is the minimum value of each row of the `input` tensor in the given dimension `dim`. And `indices` is the index location of each minimum value found (argmin).

Warning

`indices` does not necessarily contain the first occurrence of each minimal value found, unless it is unique. The exact implementation details are device-specific. Do not expect the same result when run on CPU and GPU in general.

If `keepdim` is `TRUE`, the output tensors are of the same size as `input` except in the dimension `dim` where they are of size 1. Otherwise, `dim` is squeezed (see `torch_squeeze`), resulting in the output tensors having 1 fewer dimension than `input`.

min(input, other, out=NULL) -> Tensor

Each element of the tensor `input` is compared with the corresponding element of the tensor `other` and an element-wise minimum is taken. The resulting tensor is returned.

The shapes of `input` and `other` don't need to match, but they must be broadcastable .

$$\text{out}_i = \min(\text{tensor}_i, \text{other}_i)$$

Note

When the shapes do not match, the shape of the returned output tensor follows the broadcasting rules .

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(1, 3))
a
torch_min(a)
```

```
a = torch_randn(c(4, 4))
a
torch_min(a, dim = 1)


a = torch_randn(c(4))
a
b = torch_randn(c(4))
b
torch_min(a, other = b)
}
```

---

torch_minimum *Minimum*

Description

Minimum

Usage

```
torch_minimum(self, other)
```

Arguments

self	(Tensor) the input tensor.
other	(Tensor) the second input tensor

minimum(input, other, *, out=None) -> Tensor

Computes the element-wise minimum of `input` and `other`.

Note

If one of the elements being compared is a NaN, then that element is returned. `torch_minimum()` is not supported for tensors with complex dtypes.

Examples

```
if (torch_is_installed()) {

a <- torch_tensor(c(1, 2, -1))
b <- torch_tensor(c(3, 0, 4))
torch_minimum(a, b)
}
```

torch_mm *Mm*

Description

Mm

Usage

```
torch_mm(self, mat2)
```

Arguments

self	(Tensor) the first matrix to be multiplied
mat2	(Tensor) the second matrix to be multiplied

mm(input, mat2, out=NULL) -> Tensor

Performs a matrix multiplication of the matrices input and mat2.

If input is a $(n \times m)$ tensor, mat2 is a $(m \times p)$ tensor, out will be a $(n \times p)$ tensor.

Note

This function does not broadcast . For broadcasting matrix products, see torch_matmul.

Examples

```
if (torch_is_installed()) {

mat1 = torch_randn(c(2, 3))
mat2 = torch_randn(c(3, 3))
torch_mm(mat1, mat2)
}
```

torch_mode *Mode*

Description

Mode

Usage

```
torch_mode(self, dim = -1L, keepdim = FALSE)
```

Arguments

self	(Tensor) the input tensor.
dim	(int) the dimension to reduce.
keepdim	(bool) whether the output tensor has dim retained or not.

mode(input, dim=-1, keepdim=False, out=NULL) -> (Tensor, LongTensor)

Returns a namedtuple (values, indices) where values is the mode value of each row of the input tensor in the given dimension dim, i.e. a value which appears most often in that row, and indices is the index location of each mode value found.

By default, dim is the last dimension of the input tensor.

If keepdim is TRUE, the output tensors are of the same size as input except in the dimension dim where they are of size 1. Otherwise, dim is squeezed (see torch_squeeze), resulting in the output tensors having 1 fewer dimension than input.

Note

This function is not defined for torch_cuda.Tensor yet.

Examples

```
if (torch_is_installed()) {

a = torch_randint(0, 50, size = list(5))
a
torch_mode(a, 1)
}
```

---

torch_movedim *Movedim*

Description

Movedim

Usage

```
torch_movedim(self, source, destination)
```

Arguments

self	(Tensor) the input tensor.
source	(int or tuple of ints) Original positions of the dims to move. These must be unique.
destination	(int or tuple of ints) Destination positions for each of the original dims. These must also be unique.

movedim(input, source, destination) -> Tensor

Moves the dimension(s) of `input` at the position(s) in `source` to the position(s) in `destination`.

Other dimensions of `input` that are not explicitly moved remain in their original order and appear at the positions not specified in `destination`.

Examples

```
if (torch_is_installed()) {

t <- torch_randn(c(3,2,1))
t
torch_movedim(t, 2, 1)$shape
torch_movedim(t, 2, 1)
torch_movedim(t, c(2, 3), c(1, 2))$shape
torch_movedim(t, c(2, 3), c(1, 2))
}
```

`torch_mul` *Mul*

Description

Mul

Usage

```
torch_mul(self, other)
```

Arguments

`self`	(Tensor) the first multiplicand tensor
`other`	(Tensor) the second multiplicand tensor

mul(input, other, out=NULL)

Multiplies each element of the input `input` with the scalar `other` and returns a new resulting tensor.

$$\text{out}_i = \text{other} \times \text{input}_i$$

If `input` is of type `FloatTensor` or `DoubleTensor`, `other` should be a real number, otherwise it should be an integer

Each element of the tensor `input` is multiplied by the corresponding element of the Tensor `other`. The resulting tensor is returned.

The shapes of `input` and `other` must be broadcastable .

$$\text{out}_i = \text{input}_i \times \text{other}_i$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(3))
a
torch_mul(a, 100)


a = torch_randn(c(4, 1))
a
b = torch_randn(c(1, 4))
b
torch_mul(a, b)
}
```

---

torch_multinomial *Multinomial*

Description

Multinomial

Usage

```
torch_multinomial(self, num_samples, replacement = FALSE, generator = NULL)
```

Arguments

self	(Tensor) the input tensor containing probabilities
num_samples	(int) number of samples to draw
replacement	(bool, optional) whether to draw with replacement or not
generator	(torch.Generator, optional) a pseudorandom number generator for sampling

multinomial(input, num_samples, replacement=False, *, generator=NULL, out=NULL) -> LongTensor

Returns a tensor where each row contains num_samples indices sampled from the multinomial probability distribution located in the corresponding row of tensor input.

Note

```
The rows of `input` do not need to sum to one (in which case we use
the values as weights), but must be non-negative, finite and have
a non-zero sum.
```

Indices are ordered from left to right according to when each was sampled (first samples are placed in first column).

If input is a vector, out is a vector of size num_samples.

If input is a matrix with m rows, out is an matrix of shape $(m \times \text{num_samples})$.

If replacement is TRUE, samples are drawn with replacement.

If not, they are drawn without replacement, which means that when a sample index is drawn for a row, it cannot be drawn again for that row.

```
When drawn without replacement, `num_samples` must be lower than
number of non-zero elements in `input` (or the min number of non-zero
elements in each row of `input` if it is a matrix).
```

Examples

```
if (torch_is_installed()) {

weights = torch_tensor(c(0, 10, 3, 0), dtype=torch_float()) # create a tensor of weights
torch_multinomial(weights, 2)
torch_multinomial(weights, 4, replacement=TRUE)
}
```

---

torch_multiply *Multiply*

Description

Multiply

Usage

```
torch_multiply(self, other)
```

Arguments

self	(Tensor) the first multiplicand tensor
other	(Tensor) the second multiplicand tensor

multiply(input, other, *, out=None)

Alias for torch_mul().

torch_mv *Mv*

Description

Mv

Usage

```
torch_mv(self, vec)
```

Arguments

self	(Tensor) matrix to be multiplied
vec	(Tensor) vector to be multiplied

mv(input, vec, out=NULL) -> Tensor

Performs a matrix-vector product of the matrix `input` and the vector `vec`.

If `input` is a $(n \times m)$ tensor, `vec` is a 1-D tensor of size m, `out` will be 1-D of size n.

Note

This function does not broadcast .

Examples

```
if (torch_is_installed()) {

mat = torch_randn(c(2, 3))
vec = torch_randn(c(3))
torch_mv(mat, vec)
}
```

torch_mvlgamma *Mvlgamma*

Description

Mvlgamma

Usage

```
torch_mvlgamma(self, p)
```

Arguments

self	(Tensor) the tensor to compute the multivariate log-gamma function
p	(int) the number of dimensions

mvlgamma(input, p) -> Tensor

Computes the multivariate log-gamma function <https://en.wikipedia.org/wiki/Multivariate_gamma_functio
with dimension p element-wise, given by

$$\log(\Gamma_p(a)) = C + \sum_{i=1}^{p} \log\left(\Gamma\left(a - \frac{i-1}{2}\right)\right)$$

where $C = \log(\pi) \times \frac{p(p-1)}{4}$ and $\Gamma(\cdot)$ is the Gamma function.

All elements must be greater than $\frac{p-1}{2}$, otherwise an error would be thrown.

Examples

```
if (torch_is_installed()) {

a = torch_empty(c(2, 3))$uniform_(1, 2)
a
torch_mvlgamma(a, 2)
}
```

---

torch_nanquantile *Nanquantile*

Description

Nanquantile

Usage

```
torch_nanquantile(
  self,
  q,
  dim = NULL,
  keepdim = FALSE,
  interpolation = "linear"
)
```

Arguments

self	(Tensor) the input tensor.
q	(float or Tensor) a scalar or 1D tensor of quantile values in the range [0, 1]
dim	(int) the dimension to reduce.
keepdim	(bool) whether the output tensor has dim retained or not.
interpolation	The interpolation method.

nanquantile(input, q, dim=None, keepdim=FALSE, *, out=None) -> Tensor

This is a variant of `torch_quantile()` that "ignores" `NaN` values, computing the quantiles `q` as if `NaN` values in `input` did not exist. If all values in a reduced row are `NaN` then the quantiles for that reduction will be `NaN`. See the documentation for `torch_quantile()`.

Examples

```
if (torch_is_installed()) {

t <- torch_tensor(c(NaN, 1, 2))
t$quantile(0.5)
t$nanquantile(0.5)
t <- torch_tensor(rbind(c(NaN, NaN), c(1, 2)))
t
t$nanquantile(0.5, dim=1)
t$nanquantile(0.5, dim=2)
torch_nanquantile(t, 0.5, dim = 1)
torch_nanquantile(t, 0.5, dim = 2)
}
```

`torch_nansum` *Nansum*

Description

Nansum

Usage

```
torch_nansum(self, dim = NULL, keepdim = FALSE, dtype = NULL)
```

Arguments

`self`	(Tensor) the input tensor.
`dim`	(int or tuple of ints) the dimension or dimensions to reduce.
`keepdim`	(bool) whether the output tensor has `dim` retained or not.
`dtype`	the desired data type of returned tensor. If specified, the input tensor is casted to dtype before the operation is performed. This is useful for preventing data type overflows. Default: `NULL`.

nansum(input, *, dtype=None) -> Tensor

Returns the sum of all elements, treating Not a Numbers (NaNs) as zero.

nansum(input, dim, keepdim=FALSE, *, dtype=None) -> Tensor

Returns the sum of each row of the `input` tensor in the given dimension `dim`, treating Not a Numbers (NaNs) as zero. If `dim` is a list of dimensions, reduce over all of them.

If `keepdim` is `TRUE`, the output tensor is of the same size as `input` except in the dimension(s) `dim` where it is of size 1. Otherwise, `dim` is squeezed (see `torch_squeeze`), resulting in the output tensor having 1 (or `len(dim)`) fewer dimension(s).

Examples

```
if (torch_is_installed()) {

a <- torch_tensor(c(1., 2., NaN, 4.))
torch_nansum(a)


torch_nansum(torch_tensor(c(1., NaN)))
a <- torch_tensor(rbind(c(1, 2), c(3., NaN)))
torch_nansum(a)
torch_nansum(a, dim=1)
torch_nansum(a, dim=2)
}
```

---

torch_narrow *Narrow*

Description

Narrow

Usage

```
torch_narrow(self, dim, start, length)
```

Arguments

`self`	(Tensor) the tensor to narrow
`dim`	(int) the dimension along which to narrow
`start`	(int) the starting dimension
`length`	(int) the distance to the ending dimension

narrow(input, dim, start, length) -> Tensor

Returns a new tensor that is a narrowed version of `input` tensor. The dimension `dim` is input from `start` to `start + length`. The returned tensor and `input` tensor share the same underlying storage.

Examples

```
if (torch_is_installed()) {

x = torch_tensor(matrix(c(1:9), ncol = 3, byrow= TRUE))
torch_narrow(x, 1, 1, 2)
torch_narrow(x, 2, 2, 2)
}
```

---

torch_ne *Ne*

Description

Ne

Usage

```
torch_ne(self, other)
```

Arguments

self	(Tensor) the tensor to compare
other	(Tensor or float) the tensor or value to compare

ne(input, other, out=NULL) -> Tensor

Computes $input \neq other$ element-wise.

The second argument can be a number or a tensor whose shape is broadcastable with the first argument.

Examples

```
if (torch_is_installed()) {

torch_ne(torch_tensor(matrix(1:4, ncol = 2, byrow=TRUE)),
         torch_tensor(matrix(rep(c(1,4), each = 2), ncol = 2, byrow=TRUE)))
}
```

torch_neg *Neg*

Description

Neg

Usage

```
torch_neg(self)
```

Arguments

self	(Tensor) the input tensor.

neg(input, out=NULL) -> Tensor

Returns a new tensor with the negative of the elements of `input`.

$$\text{out} = -1 \times \text{input}$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(5))
a
torch_neg(a)
}
```

torch_negative *Negative*

Description

Negative

Usage

```
torch_negative(self)
```

Arguments

self	(Tensor) the input tensor.

negative(input, *, out=None) -> Tensor

Alias for `torch_neg()`

torch_nextafter *Nextafter*

Description

Nextafter

Usage

```
torch_nextafter(self, other)
```

Arguments

self	(Tensor) the first input tensor
other	(Tensor) the second input tensor

nextafter(input, other, *, out=None) -> Tensor

Return the next floating-point value after input towards other, elementwise.

The shapes of input and other must be broadcastable .

Examples

```
if (torch_is_installed()) {

eps <- torch_finfo(torch_float32())$eps
torch_nextafter(torch_tensor(c(1, 2)), torch_tensor(c(2, 1))) == torch_tensor(c(eps + 1, 2 - eps))
}
```

torch_nonzero *Nonzero*

Description

Nonzero elements of tensors.

Usage

```
torch_nonzero(self, as_list = FALSE)
```

Arguments

`self`	(Tensor) the input tensor.
`as_list`	If `FALSE`, the output tensor containing indices. If `TRUE`, one 1-D tensor for each dimension, containing the indices of each nonzero element along that dimension. **When** `as_list` **is** `FALSE` **(default)**: Returns a tensor containing the indices of all non-zero elements of `input`. Each row in the result contains the indices of a non-zero element in `input`. The result is sorted lexicographically, with the last index changing the fastest (C-style). If `input` has n dimensions, then the resulting indices tensor `out` is of size $(z \times n)$, where z is the total number of non-zero elements in the `input` tensor. **When** `as_list` **is** `TRUE`: Returns a tuple of 1-D tensors, one for each dimension in `input`, each containing the indices (in that dimension) of all non-zero elements of `input` . If `input` has n dimensions, then the resulting tuple contains n tensors of size z, where z is the total number of non-zero elements in the `input` tensor. As a special case, when `input` has zero dimensions and a nonzero scalar value, it is treated as a one-dimensional tensor with one element.

Examples

```
if (torch_is_installed()) {

torch_nonzero(torch_tensor(c(1, 1, 1, 0, 1)))
}
```

---

torch_norm *Norm*

Description

Norm

Usage

```
torch_norm(self, p = 2L, dim, keepdim = FALSE, dtype)
```

Arguments

`self`	(Tensor) the input tensor
`p`	(int, float, inf, -inf, 'fro', 'nuc', optional) the order of norm. Default: `'fro'` The following norms can be calculated: ===== ========== ========== ord matrix norm vector norm ===== ========== ========== NULL Frobenius norm 2-norm 'fro' Frobenius norm – 'nuc' nuclear norm – Other as vec norm when dim is NULL sum(abs(x)**ord**)(1./ord) ===== ========== ==========

dim	(int, 2-tuple of ints, 2-list of ints, optional) If it is an int, vector norm will be calculated, if it is 2-tuple of ints, matrix norm will be calculated. If the value is NULL, matrix norm will be calculated when the input tensor only has two dimensions, vector norm will be calculated when the input tensor only has one dimension. If the input tensor has more than two dimensions, the vector norm will be applied to last dimension.
keepdim	(bool, optional) whether the output tensors have dim retained or not. Ignored if dim = NULL and out = NULL. Default: FALSE Ignored if dim = NULL and out = NULL.
dtype	(torch.dtype, optional) the desired data type of returned tensor. If specified, the input tensor is casted to 'dtype' while performing the operation. Default: NULL.

TEST

Returns the matrix norm or vector norm of a given tensor.

Examples

```
if (torch_is_installed()) {

a <- torch_arange(1, 9, dtype = torch_float())
b <- a$reshape(list(3, 3))
torch_norm(a)
torch_norm(b)
torch_norm(a, Inf)
torch_norm(b, Inf)

}
```

---

torch_normal *Normal*

Description

Normal

Normal distributed

Usage

```
torch_normal(mean, std, size = NULL, generator = NULL, ...)
```

Arguments

mean	(tensor or scalar double) Mean of the normal distribution. If this is a torch_tensor() then the output has the same dim as mean and it represents the per-element mean. If it's a scalar value, it's reused for all elements.

std	(tensor or scalar double) The standard deviation of the normal distribution. If this is a torch_tensor() then the output has the same size as std and it represents the per-element standard deviation. If it's a scalar value, it's reused for all elements.
size	(integers, optional) only used if both mean and std are scalars.
generator	a random number generator created with torch_generator(). If NULL a default generator is used.
...	Tensor option parameters like dtype, layout, and device. Can only be used when mean and std are both scalar numerics.

normal(mean, std, *) -> Tensor

Returns a tensor of random numbers drawn from separate normal distributions whose mean and standard deviation are given.

The mean is a tensor with the mean of each output element's normal distribution

The std is a tensor with the standard deviation of each output element's normal distribution

The shapes of mean and std don't need to match, but the total number of elements in each tensor need to be the same.

normal(mean=0.0, std) -> Tensor

Similar to the function above, but the means are shared among all drawn elements.

normal(mean, std=1.0) -> Tensor

Similar to the function above, but the standard-deviations are shared among all drawn elements.

normal(mean, std, size, *) -> Tensor

Similar to the function above, but the means and standard deviations are shared among all drawn elements. The resulting tensor has size given by size.

Note

When the shapes do not match, the shape of mean is used as the shape for the returned output tensor

Examples

```
if (torch_is_installed()) {

torch_normal(mean=0, std=torch_arange(1, 0, -0.1) + 1e-6)
torch_normal(mean=0.5, std=torch_arange(1., 6.))
torch_normal(mean=torch_arange(1., 6.))
torch_normal(2, 3, size=c(1, 4))

}
```

torch_not_equal *Not_equal*

Description

Not_equal

Usage

```
torch_not_equal(self, other)
```

Arguments

self	(Tensor) the tensor to compare
other	(Tensor or float) the tensor or value to compare

not_equal(input, other, *, out=None) -> Tensor

Alias for torch_ne().

torch_ones *Ones*

Description

Ones

Usage

```
torch_ones(
  ...,
  names = NULL,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

...	(int...) a sequence of integers defining the shape of the output tensor. Can be a variable number of arguments or a collection like a list or tuple.
names	optional names for the dimensions
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type).

layout	(torch.layout, optional) the desired layout of returned Tensor. Default: torch_strided.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

ones(*size, out=NULL, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Returns a tensor filled with the scalar value 1, with the shape defined by the variable argument size.

Examples

```
if (torch_is_installed()) {

torch_ones(c(2, 3))
torch_ones(c(5))
}
```

---

torch_ones_like *Ones_like*

Description

Ones_like

Usage

```
torch_ones_like(
  input,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE,
  memory_format = torch_preserve_format()
)
```

Arguments

input	(Tensor) the size of input will determine size of the output tensor.
dtype	(torch.dtype, optional) the desired data type of returned Tensor. Default: if NULL, defaults to the dtype of input.
layout	(torch.layout, optional) the desired layout of returned tensor. Default: if NULL, defaults to the layout of input.

device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, defaults to the device of input.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.
memory_format	(torch.memory_format, optional) the desired memory format of returned Tensor. Default: torch_preserve_format.

ones_like(input, dtype=NULL, layout=NULL, device=NULL, requires_grad=False, memory_format=torch.preserve_form -> Tensor

Returns a tensor filled with the scalar value 1, with the same size as input. torch_ones_like(input) is equivalent to torch_ones(input.size(), dtype=input.dtype, layout=input.layout, device=input.device).

Warning

As of 0.4, this function does not support an out keyword. As an alternative, the old torch_ones_like(input, out=output) is equivalent to torch_ones(input.size(), out=output).

Examples

```
if (torch_is_installed()) {

input = torch_empty(c(2, 3))
torch_ones_like(input)
}
```

---

torch_orgqr *Orgqr*

Description

Orgqr

Usage

```
torch_orgqr(self, input2)
```

Arguments

self	(Tensor) the a from torch_geqrf.
input2	(Tensor) the tau from torch_geqrf.

orgqr(input, input2) -> Tensor

Computes the orthogonal matrix Q of a QR factorization, from the (input, input2) tuple returned by torch_geqrf.

This directly calls the underlying LAPACK function ?orgqr. See LAPACK documentation for orgqr_ for further details.

torch_ormqr *Ormqr*

Description

Ormqr

Usage

```
torch_ormqr(self, input2, input3, left = TRUE, transpose = FALSE)
```

Arguments

self	(Tensor) the a from torch_geqrf.
input2	(Tensor) the tau from torch_geqrf.
input3	(Tensor) the matrix to be multiplied.
left	see LAPACK documentation
transpose	see LAPACK documentation

ormqr(input, input2, input3, left=TRUE, transpose=False) -> Tensor

Multiplies mat (given by input3) by the orthogonal Q matrix of the QR factorization formed by torch_geqrf() that is represented by (a, tau) (given by (input, input2)).

This directly calls the underlying LAPACK function ?ormqr.

torch_outer *Outer*

Description

Outer

Usage

```
torch_outer(self, vec2)
```

Arguments

self	(Tensor) 1-D input vector
vec2	(Tensor) 1-D input vector

outer(input, vec2, *, out=None) -> Tensor

Outer product of input and vec2. If input is a vector of size n and vec2 is a vector of size m, then out must be a matrix of size $(n \times m)$.

Note

This function does not broadcast.

Examples

```
if (torch_is_installed()) {

v1 <- torch_arange(1., 5.)
v2 <- torch_arange(1., 4.)
torch_outer(v1, v2)
}
```

---

torch_pdist *Pdist*

Description

Pdist

Usage

```
torch_pdist(self, p = 2L)
```

Arguments

self	NA input tensor of shape $N \times M$.
p	NA p value for the p-norm distance to calculate between each vector pair $\in [0, \infty]$.

pdist(input, p=2) -> Tensor

Computes the p-norm distance between every pair of row vectors in the input. This is identical to the upper triangular portion, excluding the diagonal, of `torch_norm(input[:, NULL] - input, dim=2, p=p)`. This function will be faster if the rows are contiguous.

If input has shape $N \times M$ then the output will have shape $\frac{1}{2}N(N-1)$.

This function is equivalent to `scipy.spatial.distance.pdist(input, 'minkowski', p=p)` if $p \in (0, \infty)$. When $p = 0$ it is equivalent to `scipy.spatial.distance.pdist(input, 'hamming') * M`. When $p = \infty$, the closest scipy function is `scipy.spatial.distance.pdist(xn, lambda x, y: np.abs(x - y).max(`

torch_pinverse *Pinverse*

Description

Pinverse

Usage

```
torch_pinverse(self, rcond = 1e-15)
```

Arguments

self	(Tensor) The input tensor of size $(*, m, n)$ where $*$ is zero or more batch dimensions
rcond	(float) A floating point value to determine the cutoff for small singular values. Default: 1e-15

pinverse(input, rcond=1e-15) -> Tensor

Calculates the pseudo-inverse (also known as the Moore-Penrose inverse) of a 2D tensor. Please look at `Moore-Penrose inverse_` for more details

Note

```
This method is implemented using the Singular Value Decomposition.

The pseudo-inverse is not necessarily a continuous function in the elements of the matrix `[1]`_.
Therefore, derivatives are not always existent, and exist for a constant rank only `[2]`_.
However, this method is backprop-able due to the implementation by using SVD results, and
could be unstable. Double-backward will also be unstable due to the usage of SVD internally.
See `~torch.svd` for more details.
```

Examples

```
if (torch_is_installed()) {

input = torch_randn(c(3, 5))
input
torch_pinverse(input)
# Batched pinverse example
a = torch_randn(c(2,6,3))
b = torch_pinverse(a)
torch_matmul(b, a)
}
```

torch_pixel_shuffle *Pixel_shuffle*

Description

Pixel_shuffle

Usage

```
torch_pixel_shuffle(self, upscale_factor)
```

Arguments

self	(Tensor) the input tensor
upscale_factor	(int) factor to increase spatial resolution by

Rearranges elements in a tensor of shape

math:`(*, C \times r^2, H, W)` to a :

Rearranges elements in a tensor of shape $(*, C \times r^2, H, W)$ to a tensor of shape $(*, C, H \times r, W \times r)$.

See `~torch.nn.PixelShuffle` for details.

Examples

```
if (torch_is_installed()) {

input = torch_randn(c(1, 9, 4, 4))
output = nnf_pixel_shuffle(input, 3)
print(output$size())
}
```

torch_poisson *Poisson*

Description

Poisson

Usage

```
torch_poisson(self, generator = NULL)
```

Arguments

self	(Tensor) the input tensor containing the rates of the Poisson distribution
generator	(`torch.Generator`, optional) a pseudorandom number generator for sampling

poisson(input *, generator=NULL) -> Tensor

Returns a tensor of the same size as `input` with each element sampled from a Poisson distribution with rate parameter given by the corresponding element in `input` i.e.,

$$\text{out}_i \sim \text{Poisson}(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

rates = torch_rand(c(4, 4)) * 5  # rate parameter between 0 and 5
torch_poisson(rates)
}
```

`torch_polar` *Polar*

Description

Polar

Usage

```
torch_polar(abs, angle)
```

Arguments

`abs`	(Tensor) The absolute value the complex tensor. Must be float or double.
`angle`	(Tensor) The angle of the complex tensor. Must be same dtype as `abs`.

polar(abs, angle, *, out=None) -> Tensor

Constructs a complex tensor whose elements are Cartesian coordinates corresponding to the polar coordinates with absolute value `abs` and angle `angle`.

$$\text{out} = \text{abs} \cdot \cos(\text{angle}) + \text{abs} \cdot \sin(\text{angle}) \cdot j$$

Examples

```
if (torch_is_installed()) {

abs <- torch_tensor(c(1, 2), dtype=torch_float64())
angle <- torch_tensor(c(pi / 2, 5 * pi / 4), dtype=torch_float64())
z <- torch_polar(abs, angle)
z
}
```

torch_polygamma *Polygamma*

Description

Polygamma

Usage

```
torch_polygamma(n, input)
```

Arguments

n	(int) the order of the polygamma function
input	(Tensor) the input tensor.

polygamma(n, input, out=NULL) -> Tensor

Computes the nth derivative of the digamma function on `input`. $n \geq 0$ is called the order of the polygamma function.

$$\psi^{(n)}(x) = \frac{d^{(n)}}{dx^{(n)}}\psi(x)$$

Note

This function is not implemented for \eqn{n \geq 2}.

Examples

```
if (torch_is_installed()) {
## Not run:
a = torch_tensor(c(1, 0.5))
torch_polygamma(1, a)

## End(Not run)
}
```

torch_pow *Pow*

Description

Pow

Usage

```
torch_pow(self, exponent)
```

Arguments

self	(float) the scalar base value for the power operation
exponent	(float or tensor) the exponent value

pow(input, exponent, out=NULL) -> Tensor

Takes the power of each element in `input` with `exponent` and returns a tensor with the result.

`exponent` can be either a single `float` number or a `Tensor` with the same number of elements as `input`.

When `exponent` is a scalar value, the operation applied is:

$$\text{out}_i = x_i^{\text{exponent}}$$

When `exponent` is a tensor, the operation applied is:

$$\text{out}_i = x_i^{\text{exponent}_i}$$

When `exponent` is a tensor, the shapes of `input` and `exponent` must be broadcastable .

pow(self, exponent, out=NULL) -> Tensor

`self` is a scalar `float` value, and `exponent` is a tensor. The returned tensor `out` is of the same shape as `exponent`

The operation applied is:

$$\text{out}_i = \text{self}^{\text{exponent}_i}$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_pow(a, 2)
exp <- torch_arange(1, 5)
a <- torch_arange(1, 5)
a
exp
torch_pow(a, exp)


exp <- torch_arange(1, 5)
base <- 2
torch_pow(base, exp)
}
```

---

torch_prod *Prod*

Description

Prod

Usage

```
torch_prod(self, dim, keepdim = FALSE, dtype = NULL)
```

Arguments

self	(Tensor) the input tensor.
dim	(int) the dimension to reduce.
keepdim	(bool) whether the output tensor has dim retained or not.
dtype	(torch.dtype, optional) the desired data type of returned tensor. If specified, the input tensor is casted to dtype before the operation is performed. This is useful for preventing data type overflows. Default: NULL.

prod(input, dtype=NULL) -> Tensor

Returns the product of all elements in the input tensor.

prod(input, dim, keepdim=False, dtype=NULL) -> Tensor

Returns the product of each row of the input tensor in the given dimension dim.

If keepdim is TRUE, the output tensor is of the same size as input except in the dimension dim where it is of size 1. Otherwise, dim is squeezed (see torch_squeeze), resulting in the output tensor having 1 fewer dimension than input.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(1, 3))
a
torch_prod(a)


a = torch_randn(c(4, 2))
a
torch_prod(a, 1)
}
```

---

torch_promote_types *Promote_types*

Description

Promote_types

Usage

```
torch_promote_types(type1, type2)
```

Arguments

type1	(torch.dtype)
type2	(torch.dtype)

promote_types(type1, type2) -> dtype

Returns the torch_dtype with the smallest size and scalar kind that is not smaller nor of lower kind than either type1 or type2. See type promotion documentation for more information on the type promotion logic.

Examples

```
if (torch_is_installed()) {

torch_promote_types(torch_int32(), torch_float32())
torch_promote_types(torch_uint8(), torch_long())
}
```

torch_qr *Qr*

Description

Qr

Usage

```
torch_qr(self, some = TRUE)
```

Arguments

self	(Tensor) the input tensor of size $(*, m, n)$ where * is zero or more batch dimensions consisting of matrices of dimension $m \times n$.
some	(bool, optional) Set to TRUE for reduced QR decomposition and FALSE for complete QR decomposition.

qr(input, some=TRUE, out=NULL) -> (Tensor, Tensor)

Computes the QR decomposition of a matrix or a batch of matrices input, and returns a namedtuple (Q, R) of tensors such that input $= QR$ with Q being an orthogonal matrix or batch of orthogonal matrices and R being an upper triangular matrix or batch of upper triangular matrices.

If some is TRUE, then this function returns the thin (reduced) QR factorization. Otherwise, if some is FALSE, this function returns the complete QR factorization.

Note

precision may be lost if the magnitudes of the elements of input are large

While it should always give you a valid decomposition, it may not give you the same one across platforms - it will depend on your LAPACK implementation.

Examples

```
if (torch_is_installed()) {

a = torch_tensor(matrix(c(12., -51, 4, 6, 167, -68, -4, 24, -41), ncol = 3, byrow = TRUE))
out = torch_qr(a)
q = out[[1]]
r = out[[2]]
torch_mm(q, r)$round()
torch_mm(q$t(), q)$round()
}
```

torch_qscheme *Creates the corresponding Scheme object*

Description

Creates the corresponding Scheme object

Usage

```
torch_per_channel_affine()

torch_per_tensor_affine()

torch_per_channel_symmetric()

torch_per_tensor_symmetric()
```

torch_quantile *Quantile*

Description

Quantile

Usage

```
torch_quantile(self, q, dim = NULL, keepdim = FALSE, interpolation = "linear")
```

Arguments

self	(Tensor) the input tensor.
q	(float or Tensor) a scalar or 1D tensor of quantile values in the range `[0, 1]`
dim	(int) the dimension to reduce.
keepdim	(bool) whether the output tensor has `dim` retained or not.
interpolation	The interpolation method.

quantile(input, q) -> Tensor

Returns the q-th quantiles of all elements in the `input` tensor, doing a linear interpolation when the q-th quantile lies between two data points.

quantile(input, q, dim=None, keepdim=FALSE, *, out=None) -> Tensor

Returns the q-th quantiles of each row of the `input` tensor along the dimension `dim`, doing a linear interpolation when the q-th quantile lies between two data points. By default, `dim` is `None` resulting in the `input` tensor being flattened before computation.

If `keepdim` is `TRUE`, the output dimensions are of the same size as `input` except in the dimensions being reduced (`dim` or all if `dim` is `NULL`) where they have size 1. Otherwise, the dimensions being reduced are squeezed (see `torch_squeeze`). If `q` is a 1D tensor, an extra dimension is prepended to the output tensor with the same size as `q` which represents the quantiles.

Examples

```
if (torch_is_installed()) {

a <- torch_randn(c(1, 3))
a
q <- torch_tensor(c(0, 0.5, 1))
torch_quantile(a, q)


a <- torch_randn(c(2, 3))
a
q <- torch_tensor(c(0.25, 0.5, 0.75))
torch_quantile(a, q, dim=1, keepdim=TRUE)
torch_quantile(a, q, dim=1, keepdim=TRUE)$shape
}
```

---

torch_quantize_per_channel

Quantize_per_channel

Description

Quantize_per_channel

Usage

```
torch_quantize_per_channel(self, scales, zero_points, axis, dtype)
```

Arguments

`self`	(Tensor) float tensor to quantize
`scales`	(Tensor) float 1D tensor of scales to use, size should match `input.size(axis)`
`zero_points`	(int) integer 1D tensor of offset to use, size should match `input.size(axis)`
`axis`	(int) dimension on which apply per-channel quantization
`dtype`	(`torch.dtype`) the desired data type of returned tensor. Has to be one of the quantized dtypes: `torch_quint8`, `torch.qint8`, `torch.qint32`

quantize_per_channel(input, scales, zero_points, axis, dtype) -> Tensor

Converts a float tensor to per-channel quantized tensor with given scales and zero points.

Examples

```
if (torch_is_installed()) {
x = torch_tensor(matrix(c(-1.0, 0.0, 1.0, 2.0), ncol = 2, byrow = TRUE))
torch_quantize_per_channel(x, torch_tensor(c(0.1, 0.01)),
                           torch_tensor(c(10L, 0L)), 0, torch_quint8())
torch_quantize_per_channel(x, torch_tensor(c(0.1, 0.01)),
                           torch_tensor(c(10L, 0L)), 0, torch_quint8())$int_repr()
}
```

---

torch_quantize_per_tensor *Quantize_per_tensor*

Description

Quantize_per_tensor

Usage

```
torch_quantize_per_tensor(self, scale, zero_point, dtype)
```

Arguments

self	(Tensor) float tensor to quantize
scale	(float) scale to apply in quantization formula
zero_point	(int) offset in integer value that maps to float zero
dtype	(torch.dtype) the desired data type of returned tensor. Has to be one of the quantized dtypes: torch_quint8, torch.qint8, torch.qint32

quantize_per_tensor(input, scale, zero_point, dtype) -> Tensor

Converts a float tensor to quantized tensor with given scale and zero point.

Examples

```
if (torch_is_installed()) {
torch_quantize_per_tensor(torch_tensor(c(-1.0, 0.0, 1.0, 2.0)), 0.1, 10, torch_quint8())
torch_quantize_per_tensor(torch_tensor(c(-1.0, 0.0, 1.0, 2.0)), 0.1, 10, torch_quint8())$int_repr()
}
```

torch_rad2deg *Rad2deg*

Description

Rad2deg

Usage

```
torch_rad2deg(self)
```

Arguments

self	(Tensor) the input tensor.

rad2deg(input, *, out=None) -> Tensor

Returns a new tensor with each of the elements of `input` converted from angles in radians to degrees.

Examples

```
if (torch_is_installed()) {

a <- torch_tensor(rbind(c(3.142, -3.142), c(6.283, -6.283), c(1.570, -1.570)))
torch_rad2deg(a)
}
```

torch_rand *Rand*

Description

Rand

Usage

```
torch_rand(
  ...,
  names = NULL,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

...	(int...) a sequence of integers defining the shape of the output tensor. Can be a variable number of arguments or a collection like a list or tuple.
names	optional dimension names
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type).
layout	(torch.layout, optional) the desired layout of returned Tensor. Default: torch_strided.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

rand(*size, out=NULL, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Returns a tensor filled with random numbers from a uniform distribution on the interval $[0, 1)$

The shape of the tensor is defined by the variable argument size.

Examples

```
if (torch_is_installed()) {

torch_rand(4)
torch_rand(c(2, 3))
}
```

---

torch_randint *Randint*

Description

Randint

Usage

```
torch_randint(
  low,
  high,
  size,
  generator = NULL,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE,
  memory_format = torch_preserve_format()
)
```

Arguments

low	(int, optional) Lowest integer to be drawn from the distribution. Default: 0.
high	(int) One above the highest integer to be drawn from the distribution.
size	(tuple) a tuple defining the shape of the output tensor.
generator	(torch.Generator, optional) a pseudorandom number generator for sampling
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type).
layout	(torch.layout, optional) the desired layout of returned Tensor. Default: torch_strided.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.
memory_format	memory format for the resulting tensor.

**randint(low=0, high, size, *, generator=NULL, out=NULL, **

dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Returns a tensor filled with random integers generated uniformly between low (inclusive) and high (exclusive).

The shape of the tensor is defined by the variable argument size.

.. note: With the global dtype default (torch_float32), this function returns a tensor with dtype torch_int64.

Examples

```
if (torch_is_installed()) {

torch_randint(3, 5, list(3))
torch_randint(0, 10, size = list(2, 2))
torch_randint(3, 10, list(2, 2))
}
```

---

torch_randint_like *Randint_like*

Description

Randint_like

Usage

```
torch_randint_like(
  input,
  low,
  high,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

input	(Tensor) the size of input will determine size of the output tensor.
low	(int, optional) Lowest integer to be drawn from the distribution. Default: 0.
high	(int) One above the highest integer to be drawn from the distribution.
dtype	(torch.dtype, optional) the desired data type of returned Tensor. Default: if NULL, defaults to the dtype of input.
layout	(torch.layout, optional) the desired layout of returned tensor. Default: if NULL, defaults to the layout of input.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, defaults to the device of input.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

randint_like(input, low=0, high, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False,

memory_format=torch.preserve_format) -> Tensor

Returns a tensor with the same shape as Tensor input filled with random integers generated uniformly between low (inclusive) and high (exclusive).

.. note: With the global dtype default (torch_float32), this function returns a tensor with dtype torch_int64.

---

torch_randn *Randn*

Description

Randn

Usage

```
torch_randn(
  ...,
  names = NULL,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

`...`	(int...) a sequence of integers defining the shape of the output tensor. Can be a variable number of arguments or a collection like a list or tuple.
`names`	optional names for the dimensions
`dtype`	(`torch.dtype`, optional) the desired data type of returned tensor. Default: if `NULL`, uses a global default (see `torch_set_default_tensor_type`).
`layout`	(`torch.layout`, optional) the desired layout of returned Tensor. Default: `torch_strided`.
`device`	(`torch.device`, optional) the desired device of returned tensor. Default: if `NULL`, uses the current device for the default tensor type (see `torch_set_default_tensor_type`). `device` will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
`requires_grad`	(bool, optional) If autograd should record operations on the returned tensor. Default: `FALSE`.

randn(*size, out=NULL, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Returns a tensor filled with random numbers from a normal distribution with mean `0` and variance `1` (also called the standard normal distribution).

$$\text{out}_i \sim \mathcal{N}(0, 1)$$

The shape of the tensor is defined by the variable argument `size`.

Examples

```
if (torch_is_installed()) {

torch_randn(c(4))
torch_randn(c(2, 3))
}
```

torch_randn_like *Randn_like*

Description

Randn_like

Usage

```
torch_randn_like(
  input,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE,
  memory_format = torch_preserve_format()
)
```

Arguments

input	(Tensor) the size of `input` will determine size of the output tensor.
dtype	(`torch.dtype`, optional) the desired data type of returned Tensor. Default: if `NULL`, defaults to the dtype of `input`.
layout	(`torch.layout`, optional) the desired layout of returned tensor. Default: if `NULL`, defaults to the layout of `input`.
device	(`torch.device`, optional) the desired device of returned tensor. Default: if `NULL`, defaults to the device of `input`.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: `FALSE`.
memory_format	(`torch.memory_format`, optional) the desired memory format of returned Tensor. Default: `torch_preserve_format`.

randn_like(input, dtype=NULL, layout=NULL, device=NULL, requires_grad=False, memory_format=torch.preserve_for -> Tensor

Returns a tensor with the same size as `input` that is filled with random numbers from a normal distribution with mean 0 and variance 1. `torch_randn_like(input)` is equivalent to `torch_randn(input.size(), dtype=input.dtype, layout=input.layout, device=input.device)`.

torch_randperm *Randperm*

Description

Randperm

Usage

```
torch_randperm(
  n,
  dtype = torch_int64(),
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

n	(int) the upper bound (exclusive)
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: torch_int64.
layout	(torch.layout, optional) the desired layout of returned Tensor. Default: torch_strided.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

randperm(n, out=NULL, dtype=torch.int64, layout=torch.strided, device=NULL, requires_grad=False) -> LongTensor

Returns a random permutation of integers from 0 to n - 1.

Examples

```
if (torch_is_installed()) {

torch_randperm(4)
}
```

torch_rand_like *Rand_like*

Description

Rand_like

Usage

```
torch_rand_like(
  input,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE,
  memory_format = torch_preserve_format()
)
```

Arguments

input	(Tensor) the size of `input` will determine size of the output tensor.
dtype	(`torch.dtype`, optional) the desired data type of returned Tensor. Default: if `NULL`, defaults to the dtype of `input`.
layout	(`torch.layout`, optional) the desired layout of returned tensor. Default: if `NULL`, defaults to the layout of `input`.
device	(`torch.device`, optional) the desired device of returned tensor. Default: if `NULL`, defaults to the device of `input`.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: `FALSE`.
memory_format	(`torch.memory_format`, optional) the desired memory format of returned Tensor. Default: `torch_preserve_format`.

rand_like(input, dtype=NULL, layout=NULL, device=NULL, requires_grad=False, memory_format=torch.preserve_forn -> Tensor

Returns a tensor with the same size as `input` that is filled with random numbers from a uniform distribution on the interval $[0, 1)$. `torch_rand_like(input)` is equivalent to `torch_rand(input.size(), dtype=input.dtype, layout=input.layout, device=input.device)`.

torch_range *Range*

Description

Range

Usage

```
torch_range(
  start,
  end,
  step = 1,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

start	(float) the starting value for the set of points. Default: 0.
end	(float) the ending value for the set of points
step	(float) the gap between each pair of adjacent points. Default: 1.
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type). If dtype is not given, infer the data type from the other input arguments. If any of start, end, or stop are floating-point, the dtype is inferred to be the default dtype, see ~torch.get_default_dtype. Otherwise, the dtype is inferred to be torch.int64.
layout	(torch.layout, optional) the desired layout of returned Tensor. Default: torch_strided.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

range(start=0, end, step=1, out=NULL, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Returns a 1-D tensor of size $\left\lfloor \frac{\text{end}-\text{start}}{\text{step}} \right\rfloor + 1$ with values from start to end with step step. Step is the gap between two values in the tensor.

$$\text{out}_{i+1} = \text{out}_i + \text{step}.$$

Warning

This function is deprecated in favor of torch_arange.

Examples

```
if (torch_is_installed()) {

torch_range(1, 4)
torch_range(1, 4, 0.5)
}
```

---

torch_real *Real*

Description

Real

Usage

```
torch_real(self)
```

Arguments

self	(Tensor) the input tensor.

real(input) -> Tensor

Returns the real part of the input tensor. If input is a real (non-complex) tensor, this function just returns it.

Warning

Not yet implemented for complex tensors.

$$\text{out}_i = real(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {
## Not run:
torch_real(torch_tensor(c(-1 + 1i, -2 + 2i, 3 - 3i)))

## End(Not run)
}
```

torch_reciprocal *Reciprocal*

Description

Reciprocal

Usage

```
torch_reciprocal(self)
```

Arguments

self	(Tensor) the input tensor.

reciprocal(input, out=NULL) -> Tensor

Returns a new tensor with the reciprocal of the elements of `input`

$$\text{out}_i = \frac{1}{\text{input}_i}$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_reciprocal(a)
}
```

torch_reduction *Creates the reduction objet*

Description

Creates the reduction objet

Usage

```
torch_reduction_sum()

torch_reduction_mean()

torch_reduction_none()
```

torch_relu *Relu*

Description

Relu

Usage

```
torch_relu(self)
```

Arguments

self	the input tensor

relu(input) -> Tensor

Computes the relu tranformation.

torch_relu_ *Relu_*

Description

Relu_

Usage

```
torch_relu_(self)
```

Arguments

self	the input tensor

relu_(input) -> Tensor

In-place version of `torch_relu()`.

torch_remainder *Remainder*

Description

Remainder

Usage

```
torch_remainder(self, other)
```

Arguments

self	(Tensor) the dividend
other	(Tensor or float) the divisor that may be either a number or a Tensor of the same shape as the dividend

remainder(input, other, out=NULL) -> Tensor

Computes the element-wise remainder of division.

The divisor and dividend may contain both for integer and floating point numbers. The remainder has the same sign as the divisor.

When `other` is a tensor, the shapes of `input` and `other` must be broadcastable .

Examples

```
if (torch_is_installed()) {

torch_remainder(torch_tensor(c(-3., -2, -1, 1, 2, 3)), 2)
torch_remainder(torch_tensor(c(1., 2, 3, 4, 5)), 1.5)
}
```

torch_renorm *Renorm*

Description

Renorm

Usage

```
torch_renorm(self, p, dim, maxnorm)
```

Arguments

self	(Tensor) the input tensor.
p	(float) the power for the norm computation
dim	(int) the dimension to slice over to get the sub-tensors
maxnorm	(float) the maximum norm to keep each sub-tensor under

renorm(input, p, dim, maxnorm, out=NULL) -> Tensor

Returns a tensor where each sub-tensor of `input` along dimension `dim` is normalized such that the `p`-norm of the sub-tensor is lower than the value `maxnorm`

Note

If the norm of a row is lower than `maxnorm`, the row is unchanged

Examples

```
if (torch_is_installed()) {
x = torch_ones(c(3, 3))
x[2,]$fill_(2)
x[3,]$fill_(3)
x
torch_renorm(x, 1, 1, 5)
}
```

---

torch_repeat_interleave *Repeat_interleave*

Description

Repeat_interleave

Usage

```
torch_repeat_interleave(self, repeats, dim = NULL, output_size = NULL)
```

Arguments

self	(Tensor) the input tensor.
repeats	(Tensor or int) The number of repetitions for each element. repeats is broadcasted to fit the shape of the given axis.
dim	(int, optional) The dimension along which to repeat values. By default, use the flattened input array, and return a flat output array.
output_size	(int, optional) – Total output size for the given axis (e.g. sum of repeats). If given, it will avoid stream syncronization needed to calculate output shape of the tensor.

repeat_interleave(input, repeats, dim=NULL) -> Tensor

Repeat elements of a tensor.

Warning

This is different from `torch_Tensor.repeat` but similar to `numpy.repeat`.

repeat_interleave(repeats) -> Tensor

If the repeats is tensor([n1, n2, n3, ...]), then the output will be tensor([0, 0, ..., 1, 1, ..., 2, 2, ..., ...]) where 0 appears n1 times, 1 appears n2 times, 2 appears n3 times, etc.

Examples

```
if (torch_is_installed()) {
## Not run:
x = torch_tensor(c(1, 2, 3))
x$repeat_interleave(2)
y = torch_tensor(matrix(c(1, 2, 3, 4), ncol = 2, byrow=TRUE))
torch_repeat_interleave(y, 2)
torch_repeat_interleave(y, 3, dim=1)
torch_repeat_interleave(y, torch_tensor(c(1, 2)), dim=1)

## End(Not run)
}
```

---

torch_reshape *Reshape*

Description

Reshape

Usage

```
torch_reshape(self, shape)
```

Arguments

self	(Tensor) the tensor to be reshaped
shape	(tuple of ints) the new shape

reshape(input, shape) -> Tensor

Returns a tensor with the same data and number of elements as `input`, but with the specified shape. When possible, the returned tensor will be a view of `input`. Otherwise, it will be a copy. Contiguous inputs and inputs with compatible strides can be reshaped without copying, but you should not depend on the copying vs. viewing behavior.

See `torch_Tensor.view` on when it is possible to return a view.

A single dimension may be -1, in which case it's inferred from the remaining dimensions and the number of elements in `input`.

Examples

```
if (torch_is_installed()) {

a <- torch_arange(0, 3)
torch_reshape(a, list(2, 2))
b <- torch_tensor(matrix(c(0, 1, 2, 3), ncol = 2, byrow=TRUE))
torch_reshape(b, list(-1))
}
```

---

torch_result_type *Result_type*

Description

Result_type

Usage

```
torch_result_type(tensor1, tensor2)
```

Arguments

`tensor1`	(Tensor or Number) an input tensor or number
`tensor2`	(Tensor or Number) an input tensor or number

result_type(tensor1, tensor2) -> dtype

Returns the `torch_dtype` that would result from performing an arithmetic operation on the provided input tensors. See type promotion documentation for more information on the type promotion logic.

Examples

```
if (torch_is_installed()) {

torch_result_type(tensor1 = torch_tensor(c(1, 2), dtype=torch_int()), tensor2 = 1)
}
```

torch_roll *Roll*

Description

Roll

Usage

```
torch_roll(self, shifts, dims = list())
```

Arguments

self	(Tensor) the input tensor.
shifts	(int or tuple of ints) The number of places by which the elements of the tensor are shifted. If shifts is a tuple, dims must be a tuple of the same size, and each dimension will be rolled by the corresponding value
dims	(int or tuple of ints) Axis along which to roll

roll(input, shifts, dims=NULL) -> Tensor

Roll the tensor along the given dimension(s). Elements that are shifted beyond the last position are re-introduced at the first position. If a dimension is not specified, the tensor will be flattened before rolling and then restored to the original shape.

Examples

```
if (torch_is_installed()) {

x = torch_tensor(c(1, 2, 3, 4, 5, 6, 7, 8))$view(c(4, 2))
x
torch_roll(x, 1, 1)
torch_roll(x, -1, 1)
torch_roll(x, shifts=list(2, 1), dims=list(1, 2))
}
```

torch_rot90 *Rot90*

Description

Rot90

Usage

```
torch_rot90(self, k = 1L, dims = c(0, 1))
```

Arguments

`self`	(Tensor) the input tensor.
`k`	(int) number of times to rotate
`dims`	(a list or tuple) axis to rotate

rot90(input, k, dims) -> Tensor

Rotate a n-D tensor by 90 degrees in the plane specified by dims axis. Rotation direction is from the first towards the second axis if k > 0, and from the second towards the first for k < 0.

Examples

```
if (torch_is_installed()) {

x <- torch_arange(1, 4)$view(c(2, 2))
x
torch_rot90(x, 1, c(1, 2))
x <- torch_arange(1, 8)$view(c(2, 2, 2))
x
torch_rot90(x, 1, c(1, 2))
}
```

---

torch_round *Round*

Description

Round

Usage

```
torch_round(self, decimals)
```

Arguments

`self`	(Tensor) the input tensor.
`decimals`	Number of decimal places to round to (default: 0). If decimals is negative, it specifies the number of positions to the left of the decimal point.

round(input, out=NULL) -> Tensor

Returns a new tensor with each of the elements of `input` rounded to the closest integer.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_round(a)
}
```

---

torch_rrelu_ *Rrelu_*

Description

Rrelu_

Usage

```
torch_rrelu_(
  self,
  lower = 0.125,
  upper = 0.333333333333333,
  training = FALSE,
  generator = NULL
)
```

Arguments

self	the input tensor
lower	lower bound of the uniform distribution. Default: 1/8
upper	upper bound of the uniform distribution. Default: 1/3
training	bool wether it's a training pass. DEfault: FALSE
generator	random number generator

rrelu_(input, lower=1./8, upper=1./3, training=False) -> Tensor

In-place version of `torch_rrelu`.

torch_rsqrt *Rsqrt*

Description

Rsqrt

Usage

```
torch_rsqrt(self)
```

Arguments

self	(Tensor) the input tensor.

rsqrt(input, out=NULL) -> Tensor

Returns a new tensor with the reciprocal of the square-root of each of the elements of `input`.

$$\text{out}_i = \frac{1}{\sqrt{\text{input}_i}}$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_rsqrt(a)
}
```

torch_save *Saves an object to a disk file.*

Description

This function is experimental, don't use for long term storage.

Usage

```
torch_save(obj, path, ..., compress = TRUE)
```

Arguments

obj	the saved object
path	a connection or the name of the file to save.
...	not currently used.
compress	a logical specifying whether saving to a named file is to use "gzip" compression, or one of "gzip", "bzip2" or "xz" to indicate the type of compression to be used. Ignored if file is a connection.

See Also

Other torch_save: torch_load(), torch_serialize()

---

torch_scalar_tensor *Scalar tensor*

Description

Creates a singleton dimension tensor.

Usage

```
torch_scalar_tensor(value, dtype = NULL, device = NULL, requires_grad = FALSE)
```

Arguments

value	the value you want to use
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, uses a global default (see torch_set_default_tensor_type).
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

torch_searchsorted *Searchsorted*

Description

Searchsorted

Usage

```
torch_searchsorted(
  sorted_sequence,
  self,
  out_int32 = FALSE,
  right = FALSE,
  side = NULL,
  sorter = list()
)
```

Arguments

sorted_sequence	(Tensor) N-D or 1-D tensor, containing monotonically increasing sequence on the *innermost* dimension.
self	(Tensor or Scalar) N-D tensor or a Scalar containing the search value(s).
out_int32	(bool, optional) – indicate the output data type. torch_int32() if True, torch_int64() otherwise. Default value is FALSE, i.e. default output data type is torch_int64().
right	(bool, optional) – if False, return the first suitable location that is found. If True, return the last such index. If no suitable index found, return 0 for non-numerical value (eg. nan, inf) or the size of boundaries (one pass the last index). In other words, if False, gets the lower bound index for each value in input from boundaries. If True, gets the upper bound index instead. Default value is False.
side	the same as right but preferred. "left" corresponds to FALSE for right and "right" corresponds to TRUE for right. It will error if this is set to "left" while right is TRUE.
sorter	if provided, a tensor matching the shape of the unsorted sorted_sequence containing a sequence of indices that sort it in the ascending order on the innermost dimension.

searchsorted(sorted_sequence, values, *, out_int32=FALSE, right=FALSE, out=None) -> Tensor

Find the indices from the *innermost* dimension of sorted_sequence such that, if the corresponding values in values were inserted before the indices, the order of the corresponding *innermost* dimension within sorted_sequence would be preserved. Return a new tensor with the same size as values. If right is FALSE (default), then the left boundary of sorted_sequence is closed.

Examples

```
if (torch_is_installed()) {

sorted_sequence <- torch_tensor(rbind(c(1, 3, 5, 7, 9), c(2, 4, 6, 8, 10)))
sorted_sequence
values <- torch_tensor(rbind(c(3, 6, 9), c(3, 6, 9)))
values
torch_searchsorted(sorted_sequence, values)
torch_searchsorted(sorted_sequence, values, right=TRUE)
sorted_sequence_1d <- torch_tensor(c(1, 3, 5, 7, 9))
sorted_sequence_1d
torch_searchsorted(sorted_sequence_1d, values)
}
```

---

torch_selu *Selu*

Description

Selu

Usage

```
torch_selu(self)
```

Arguments

self	the input tensor

selu(input) -> Tensor

Computes the selu transformation.

---

torch_selu_ *Selu_*

Description

Selu_

Usage

```
torch_selu_(self)
```

Arguments

self	the input tensor

selu_(input) -> Tensor

In-place version of `torch_selu()`.

`torch_serialize` *Serialize a torch object returning a raw object*

Description

It's just a wraper around `torch_save()`.

Usage

```
torch_serialize(obj, ...)
```

Arguments

`obj`	the saved object
`...`	Additional arguments passed to `torch_save()`. `obj` and `path` are not accepted as they are set by `torch_serialize()`.

Value

A raw vector containing the serialized object. Can be reloaded using `torch_load()`.

See Also

Other torch_save: `torch_load()`, `torch_save()`

`torch_set_default_dtype` *Gets and sets the default floating point dtype.*

Description

Gets and sets the default floating point dtype.

Usage

```
torch_set_default_dtype(d)

torch_get_default_dtype()
```

Arguments

`d`	The default floating point dtype to set. Initially set to `torch_float()`.

torch_sgn *Sgn*

Description

Sgn

Usage

```
torch_sgn(self)
```

Arguments

self	(Tensor) the input tensor.

sgn(input, *, out=None) -> Tensor

For complex tensors, this function returns a new tensor whose elemants have the same angle as that of the elements of `input` and absolute value 1. For a non-complex tensor, this function returns the signs of the elements of `input` (see `torch_sign`).

$\text{out}_i = 0$, if $|\text{input}_i| == 0$ $\text{out}_i = \frac{\text{input}_i}{|\text{input}_i|}$, otherwise

Examples

```
if (torch_is_installed()) {
if (FALSE) {
x <- torch_tensor(c(3+4i, 7-24i, 0, 1+2i))
x$sgn()
torch_sgn(x)
}
}
```

torch_sigmoid *Sigmoid*

Description

Sigmoid

Usage

```
torch_sigmoid(self)
```

Arguments

self	(Tensor) the input tensor.

sigmoid(input, out=NULL) -> Tensor

Returns a new tensor with the sigmoid of the elements of `input`.

$$\text{out}_i = \frac{1}{1 + e^{-\text{input}_i}}$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_sigmoid(a)
}
```

`torch_sign` *Sign*

Description

Sign

Usage

```
torch_sign(self)
```

Arguments

`self`	(Tensor) the input tensor.

sign(input, out=NULL) -> Tensor

Returns a new tensor with the signs of the elements of `input`.

$$\text{out}_i = \text{sgn}(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_tensor(c(0.7, -1.2, 0., 2.3))
a
torch_sign(a)
}
```

torch_signbit *Signbit*

Description

Signbit

Usage

```
torch_signbit(self)
```

Arguments

self	(Tensor) the input tensor.

signbit(input, *, out=None) -> Tensor

Tests if each element of `input` has its sign bit set (is less than zero) or not.

Examples

```
if (torch_is_installed()) {

a <- torch_tensor(c(0.7, -1.2, 0., 2.3))
torch_signbit(a)
}
```

torch_sin *Sin*

Description

Sin

Usage

```
torch_sin(self)
```

Arguments

self	(Tensor) the input tensor.

sin(input, out=NULL) -> Tensor

Returns a new tensor with the sine of the elements of `input`.

$$\text{out}_i = \sin(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_sin(a)
}
```

---

torch_sinh *Sinh*

Description

Sinh

Usage

```
torch_sinh(self)
```

Arguments

self	(Tensor) the input tensor.

sinh(input, out=NULL) -> Tensor

Returns a new tensor with the hyperbolic sine of the elements of `input`.

$$\text{out}_i = \sinh(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_sinh(a)
}
```

torch_slogdet *Slogdet*

Description

Slogdet

Usage

```
torch_slogdet(self)
```

Arguments

self	(Tensor) the input tensor of size (*, n, n) where * is zero or more batch dimensions.

slogdet(input) -> (Tensor, Tensor)

Calculates the sign and log absolute value of the determinant(s) of a square matrix or batches of square matrices.

Note

```
If `input` has zero determinant, this returns `(0, -inf)`.


Backward through `slogdet` internally uses SVD results when `input`
is not invertible. In this case, double backward through `slogdet`
will be unstable in when `input` doesn't have distinct singular values.
See `~torch.svd` for details.
```

Examples

```
if (torch_is_installed()) {

A = torch_randn(c(3, 3))
A
torch_det(A)
torch_logdet(A)
torch_slogdet(A)
}
```

torch_sort *Sort*

Description

Sort

Arguments

self	(Tensor) the input tensor.
dim	(int, optional) the dimension to sort along
descending	(bool, optional) controls the sorting order (ascending or descending)
stable	(bool, optional) – makes the sorting routine stable, which guarantees that the order of equivalent elements is preserved.

sort(input, dim=-1, descending=FALSE) -> (Tensor, LongTensor)

Sorts the elements of the `input` tensor along a given dimension in ascending order by value.

If `dim` is not given, the last dimension of the `input` is chosen.

If `descending` is `TRUE` then the elements are sorted in descending order by value.

A namedtuple of (values, indices) is returned, where the `values` are the sorted values and `indices` are the indices of the elements in the original `input` tensor.

Examples

```
if (torch_is_installed()) {

x = torch_randn(c(3, 4))
out = torch_sort(x)
out
out = torch_sort(x, 1)
out
}
```

torch_sparse_coo_tensor *Sparse_coo_tensor*

Description

Sparse_coo_tensor

Usage

```
torch_sparse_coo_tensor(
  indices,
  values,
  size = NULL,
  dtype = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

indices	(array_like) Initial data for the tensor. Can be a list, tuple, NumPy ndarray, scalar, and other types. Will be cast to a torch_LongTensor internally. The indices are the coordinates of the non-zero values in the matrix, and thus should be two-dimensional where the first dimension is the number of tensor dimensions and the second dimension is the number of non-zero values.
values	(array_like) Initial values for the tensor. Can be a list, tuple, NumPy ndarray, scalar, and other types.
size	(list, tuple, or torch.Size, optional) Size of the sparse tensor. If not provided the size will be inferred as the minimum size big enough to hold all non-zero elements.
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, infers data type from values.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: FALSE.

sparse_coo_tensor(indices, values, size=NULL, dtype=NULL, device=NULL, requires_grad=False) -> Tensor

Constructs a sparse tensors in COO(rdinate) format with non-zero elements at the given indices with the given values. A sparse tensor can be uncoalesced, in that case, there are duplicate coordinates in the indices, and the value at that index is the sum of all duplicate value entries: torch_sparse_.

Examples

```
if (torch_is_installed()) {

i = torch_tensor(matrix(c(1, 2, 2, 3, 1, 3), ncol = 3, byrow = TRUE), dtype=torch_int64())
v = torch_tensor(c(3, 4, 5), dtype=torch_float32())
torch_sparse_coo_tensor(i, v)
torch_sparse_coo_tensor(i, v, c(2, 4))
```

```
# create empty sparse tensors
S = torch_sparse_coo_tensor(
  torch_empty(c(1, 0), dtype = torch_int64()),
  torch_tensor(numeric(), dtype = torch_float32()),
  c(1)
)
S = torch_sparse_coo_tensor(
  torch_empty(c(1, 0), dtype = torch_int64()),
  torch_empty(c(0, 2)),
  c(1, 2)
)
}
```

`torch_split` *Split*

Description

Splits the tensor into chunks. Each chunk is a view of the original tensor.

Usage

```
torch_split(self, split_size, dim = 1L)
```

Arguments

`self`	(Tensor) tensor to split.
`split_size`	(int) size of a single chunk or list of sizes for each chunk
`dim`	(int) dimension along which to split the tensor.

Details

If `split_size` is an integer type, then `tensor` will be split into equally sized chunks (if possible). Last chunk will be smaller if the tensor size along the given dimension `dim` is not divisible by `split_size`.

If `split_size` is a list, then `tensor` will be split into `length(split_size)` chunks with sizes in `dim` according to `split_size_or_sections`.

torch_sqrt *Sqrt*

Description

Sqrt

Usage

```
torch_sqrt(self)
```

Arguments

self	(Tensor) the input tensor.

sqrt(input, out=NULL) -> Tensor

Returns a new tensor with the square-root of the elements of `input`.

$$\text{out}_i = \sqrt{\text{input}_i}$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_sqrt(a)
}
```

torch_square *Square*

Description

Square

Usage

```
torch_square(self)
```

Arguments

self	(Tensor) the input tensor.

square(input, out=NULL) -> Tensor

Returns a new tensor with the square of the elements of `input`.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_square(a)
}
```

`torch_squeeze` *Squeeze*

Description

Squeeze

Usage

```
torch_squeeze(self, dim)
```

Arguments

`self`	(Tensor) the input tensor.
`dim`	(int, optional) if given, the input will be squeezed only in this dimension

squeeze(input, dim=NULL, out=NULL) -> Tensor

Returns a tensor with all the dimensions of `input` of size `1` removed.

For example, if `input` is of shape: $(A \times 1 \times B \times C \times 1 \times D)$ then the `out` tensor will be of shape: $(A \times B \times C \times D)$.

When `dim` is given, a squeeze operation is done only in the given dimension. If `input` is of shape: $(A \times 1 \times B)$, `squeeze(input, 0)` leaves the tensor unchanged, but `squeeze(input, 1)` will squeeze the tensor to the shape $(A \times B)$.

Note

The returned tensor shares the storage with the input tensor, so changing the contents of one will change the contents of the other.

Examples

```
if (torch_is_installed()) {

x = torch_zeros(c(2, 1, 2, 1, 2))
x
y = torch_squeeze(x)
y
y = torch_squeeze(x, 1)
y
y = torch_squeeze(x, 2)
y
}
```

---

torch_stack *Stack*

Description

Stack

Usage

```
torch_stack(tensors, dim = 1L)
```

Arguments

tensors	(sequence of Tensors) sequence of tensors to concatenate
dim	(int) dimension to insert. Has to be between 0 and the number of dimensions of concatenated tensors (inclusive)

stack(tensors, dim=0, out=NULL) -> Tensor

Concatenates sequence of tensors along a new dimension.

All tensors need to be of the same size.

---

torch_std *Std*

Description

Std

Usage

```
torch_std(self, dim, unbiased = TRUE, keepdim = FALSE)
```

Arguments

self	(Tensor) the input tensor.
dim	(int or tuple of ints) the dimension or dimensions to reduce.
unbiased	(bool) whether to use the unbiased estimation or not
keepdim	(bool) whether the output tensor has dim retained or not.

std(input, unbiased=TRUE) -> Tensor

Returns the standard-deviation of all elements in the input tensor.

If unbiased is FALSE, then the standard-deviation will be calculated via the biased estimator. Otherwise, Bessel's correction will be used.

std(input, dim, unbiased=TRUE, keepdim=False, out=NULL) -> Tensor

Returns the standard-deviation of each row of the input tensor in the dimension dim. If dim is a list of dimensions, reduce over all of them.

If keepdim is TRUE, the output tensor is of the same size as input except in the dimension(s) dim where it is of size 1. Otherwise, dim is squeezed (see torch_squeeze), resulting in the output tensor having 1 (or len(dim)) fewer dimension(s).

If unbiased is FALSE, then the standard-deviation will be calculated via the biased estimator. Otherwise, Bessel's correction will be used.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(1, 3))
a
torch_std(a)


a = torch_randn(c(4, 4))
a
torch_std(a, dim=1)
}
```

---

torch_std_mean *Std_mean*

Description

Std_mean

Usage

```
torch_std_mean(self, dim, unbiased = TRUE, keepdim = FALSE)
```

Arguments

self	(Tensor) the input tensor.
dim	(int or tuple of ints) the dimension or dimensions to reduce.
unbiased	(bool) whether to use the unbiased estimation or not
keepdim	(bool) whether the output tensor has dim retained or not.

std_mean(input, unbiased=TRUE) -> (Tensor, Tensor)

Returns the standard-deviation and mean of all elements in the input tensor.

If unbiased is FALSE, then the standard-deviation will be calculated via the biased estimator. Otherwise, Bessel's correction will be used.

std_mean(input, dim, unbiased=TRUE, keepdim=False) -> (Tensor, Tensor)

Returns the standard-deviation and mean of each row of the input tensor in the dimension dim. If dim is a list of dimensions, reduce over all of them.

If keepdim is TRUE, the output tensor is of the same size as input except in the dimension(s) dim where it is of size 1. Otherwise, dim is squeezed (see torch_squeeze), resulting in the output tensor having 1 (or len(dim)) fewer dimension(s).

If unbiased is FALSE, then the standard-deviation will be calculated via the biased estimator. Otherwise, Bessel's correction will be used.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(1, 3))
a
torch_std_mean(a)


a = torch_randn(c(4, 4))
a
torch_std_mean(a, 1)
}
```

---

torch_stft *Stft*

Description

Stft

Usage

```
torch_stft(
  input,
  n_fft,
  hop_length = NULL,
  win_length = NULL,
  window = NULL,
  center = TRUE,
  pad_mode = "reflect",
  normalized = FALSE,
  onesided = NULL,
  return_complex = NULL
)
```

Arguments

input	(Tensor) the input tensor
n_fft	(int) size of Fourier transform
hop_length	(int, optional) the distance between neighboring sliding window frames. Default: NULL (treated as equal to floor(n_fft / 4))
win_length	(int, optional) the size of window frame and STFT filter. Default: NULL (treated as equal to n_fft)
window	(Tensor, optional) the optional window function. Default: NULL (treated as window of all 1 s)
center	(bool, optional) whether to pad input on both sides so that the t-th frame is centered at time $t \times$ hop_length. Default: TRUE
pad_mode	(string, optional) controls the padding method used when center is TRUE. Default: "reflect"
normalized	(bool, optional) controls whether to return the normalized STFT results Default: FALSE
onesided	(bool, optional) controls whether to return half of results to avoid redundancy Default: TRUE
return_complex	(bool, optional) controls whether to return complex tensors or not.

Short-time Fourier transform (STFT).

Short-time Fourier transform (STFT).

```
Ignoring the optional batch dimension, this method computes the following
expression:
```

$$X[m,\omega] = \sum_{k=0}^{\text{win_length-1}} \text{window}[k]\ \text{input}[m \times \text{hop_length} + k]\ \exp\left(-j\frac{2\pi \cdot \omega k}{\text{win_length}}\right),$$

where m is the index of the sliding window, and ω is the frequency that $0 \leq \omega <$ n_fft. When onesided is the default value TRUE,

```
* `input` must be either a 1-D time sequence or a 2-D batch of time
  sequences.

* If `hop_length` is `NULL` (default), it is treated as equal to
  `floor(n_fft / 4)`.

* If `win_length` is `NULL` (default), it is treated as equal to
  `n_fft`.

* `window` can be a 1-D tensor of size `win_length`, e.g., from
  `torch_hann_window`. If `window` is `NULL` (default), it is
  treated as if having \eqn{1} everywhere in the window. If
  \eqn{\mbox{win\_length} < \mbox{n\_fft}}, `window` will be padded on
  both sides to length `n_fft` before being applied.

* If `center` is `TRUE` (default), `input` will be padded on
  both sides so that the \eqn{t}-th frame is centered at time
  \eqn{t \times \mbox{hop\_length}}. Otherwise, the \eqn{t}-th frame
  begins at time  \eqn{t \times \mbox{hop\_length}}.

* `pad_mode` determines the padding method used on `input` when
  `center` is `TRUE`. See `torch_nn.functional.pad` for
  all available options. Default is `"reflect"`.

* If `onesided` is `TRUE` (default), only values for \eqn{\omega}
 in \eqn{\left[0, 1, 2, \dots, \left\lfloor \frac{\mbox{n\_fft}}{2} \right\rfloor + 1\right]}
  are returned because the real-to-complex Fourier transform satisfies the
  conjugate symmetry, i.e., \eqn{X[m, \omega] = X[m, \mbox{n\_fft} - \omega]^*}.

* If `normalized` is `TRUE` (default is `FALSE`), the function
 returns the normalized STFT results, i.e., multiplied by \eqn{(\mbox{frame\_length})^{-0.5}}.

Returns the real and the imaginary parts together as one tensor of size
\eqn{(* \times N \times T \times 2)}, where \eqn{*} is the optional
batch size of `input`, \eqn{N} is the number of frequencies where
STFT is applied, \eqn{T} is the total number of frames used, and each pair
in the last dimension represents a complex number as the real part and the
imaginary part.
```

Warning

This function changed signature at version 0.4.1. Calling with the previous signature may cause error or return incorrect result.

torch_sub *Sub*

Description

Sub

Usage

```
torch_sub(self, other, alpha = 1L)
```

Arguments

self	(Tensor) the input tensor.
other	(Tensor or Scalar) the tensor or scalar to subtract from input
alpha	the scalar multiplier for other

sub(input, other, *, alpha=1, out=None) -> Tensor

Subtracts other, scaled by alpha, from input.

$$\text{out}_i = \text{input}_i - \text{alpha} \times \text{other}_i$$

Supports broadcasting to a common shape , type promotion , and integer, float, and complex inputs.

Examples

```
if (torch_is_installed()) {

a <- torch_tensor(c(1, 2))
b <- torch_tensor(c(0, 1))
torch_sub(a, b, alpha=2)
}
```

torch_subtract *Subtract*

Description

Subtract

Usage

```
torch_subtract(self, other, alpha = 1L)
```

Arguments

self	(Tensor) the input tensor.
other	(Tensor or Scalar) the tensor or scalar to subtract from input
alpha	the scalar multiplier for other

subtract(input, other, *, alpha=1, out=None) -> Tensor

Alias for torch_sub().

---

torch_sum *Sum*

Description

Sum

Usage

```
torch_sum(self, dim, keepdim = FALSE, dtype = NULL)
```

Arguments

self	(Tensor) the input tensor.
dim	(int or tuple of ints) the dimension or dimensions to reduce.
keepdim	(bool) whether the output tensor has dim retained or not.
dtype	(torch.dtype, optional) the desired data type of returned tensor. If specified, the input tensor is casted to dtype before the operation is performed. This is useful for preventing data type overflows. Default: NULL.

sum(input, dtype=NULL) -> Tensor

Returns the sum of all elements in the input tensor.

sum(input, dim, keepdim=False, dtype=NULL) -> Tensor

Returns the sum of each row of the input tensor in the given dimension dim. If dim is a list of dimensions, reduce over all of them.

If keepdim is TRUE, the output tensor is of the same size as input except in the dimension(s) dim where it is of size 1. Otherwise, dim is squeezed (see torch_squeeze), resulting in the output tensor having 1 (or len(dim)) fewer dimension(s).

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(1, 3))
a
torch_sum(a)


a <- torch_randn(c(4, 4))
a
torch_sum(a, 1)
b <- torch_arange(1, 4 * 5 * 6)$view(c(4, 5, 6))
torch_sum(b, list(2, 1))
}
```

---

torch_svd *Svd*

Description

Svd

Usage

```
torch_svd(self, some = TRUE, compute_uv = TRUE)
```

Arguments

self	(Tensor) the input tensor of size $(*, m, n)$ where * is zero or more batch dimensions consisting of $m \times n$ matrices.
some	(bool, optional) controls the shape of returned U and V
compute_uv	(bool, optional) option whether to compute U and V or not

svd(input, some=TRUE, compute_uv=TRUE) -> (Tensor, Tensor, Tensor)

This function returns a namedtuple (U, S, V) which is the singular value decomposition of a input real matrix or batches of real matrices input such that $input = U \times diag(S) \times V^T$.

If some is TRUE (default), the method returns the reduced singular value decomposition i.e., if the last two dimensions of input are m and n, then the returned U and V matrices will contain only $min(n, m)$ orthonormal columns.

If compute_uv is FALSE, the returned U and V matrices will be zero matrices of shape $(m \times m)$ and $(n \times n)$ respectively. some will be ignored here.

Note

The singular values are returned in descending order. If `input` is a batch of matrices, then the singular values of each matrix in the batch is returned in descending order.

The implementation of SVD on CPU uses the LAPACK routine `?gesdd` (a divide-and-conquer algorithm) instead of `?gesvd` for speed. Analogously, the SVD on GPU uses the MAGMA routine `gesdd` as well.

Irrespective of the original strides, the returned matrix `U` will be transposed, i.e. with strides `U.contiguous().transpose(-2, -1).stride()`

Extra care needs to be taken when backward through `U` and `V` outputs. Such operation is really only stable when `input` is full rank with all distinct singular values. Otherwise, `NaN` can appear as the gradients are not properly defined. Also, notice that double backward will usually do an additional backward through `U` and `V` even if the original backward is only on `S`.

When `some = FALSE`, the gradients on `U[..., :, min(m, n):]` and `V[..., :, min(m, n):]` will be ignored in backward as those vectors can be arbitrary bases of the subspaces.

When `compute_uv = FALSE`, backward cannot be performed since `U` and `V` from the forward pass is required for the backward operation.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(5, 3))
a
out = torch_svd(a)
u = out[[1]]
s = out[[2]]
v = out[[3]]
torch_dist(a, torch_mm(torch_mm(u, torch_diag(s)), v$t()))
a_big = torch_randn(c(7, 5, 3))
out = torch_svd(a_big)
u = out[[1]]
s = out[[2]]
v = out[[3]]
torch_dist(a_big, torch_matmul(torch_matmul(u, torch_diag_embed(s)), v$transpose(-2, -1)))
}
```

`torch_t` *T*

Description

T

Usage

```
torch_t(self)
```

Arguments

`self`	(Tensor) the input tensor.

t(input) -> Tensor

Expects `input` to be <= 2-D tensor and transposes dimensions 0 and 1.

0-D and 1-D tensors are returned as is. When input is a 2-D tensor this is equivalent to `transpose(input, 0, 1)`.

Examples

```
if (torch_is_installed()) {

x = torch_randn(c(2,3))
x
torch_t(x)
x = torch_randn(c(3))
x
torch_t(x)
x = torch_randn(c(2, 3))
x
torch_t(x)
}
```

---

torch_take *Take*

Description

Take

Usage

```
torch_take(self, index)
```

Arguments

`self`	(Tensor) the input tensor.
`index`	(LongTensor) the indices into tensor

take(input, index) -> Tensor

Returns a new tensor with the elements of `input` at the given indices. The input tensor is treated as if it were viewed as a 1-D tensor. The result takes the same shape as the indices.

Examples

```
if (torch_is_installed()) {

src = torch_tensor(matrix(c(4,3,5,6,7,8), ncol = 3, byrow = TRUE))
torch_take(src, torch_tensor(c(1, 2, 5), dtype = torch_int64()))
}
```

`torch_take_along_dim` *Selects values from input at the 1-dimensional indices from indices along the given dim.*

Description

Selects values from input at the 1-dimensional indices from indices along the given dim.

Usage

```
torch_take_along_dim(self, indices, dim = NULL)
```

Arguments

`self`	the input tensor.
`indices`	the indices into input. Must have long dtype.
`dim`	the dimension to select along. Default is `NULL`.

Note

If dim is `NULL`, the input array is treated as if it has been flattened to 1d.

Functions that return indices along a dimension, like `torch_argmax()` and `torch_argsort()`, are designed to work with this function. See the examples below.

Examples

```
if (torch_is_installed()) {
t <- torch_tensor(matrix(c(10, 30, 20, 60, 40, 50), nrow = 2))
max_idx <- torch_argmax(t)
torch_take_along_dim(t, max_idx)

sorted_idx <- torch_argsort(t, dim=2)
torch_take_along_dim(t, sorted_idx, dim=2)

}
```

torch_tan *Tan*

Description

Tan

Usage

```
torch_tan(self)
```

Arguments

self	(Tensor) the input tensor.

tan(input, out=NULL) -> Tensor

Returns a new tensor with the tangent of the elements of `input`.

$$\text{out}_i = \tan(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_tan(a)
}
```

torch_tanh *Tanh*

Description

Tanh

Usage

```
torch_tanh(self)
```

Arguments

self	(Tensor) the input tensor.

tanh(input, out=NULL) -> Tensor

Returns a new tensor with the hyperbolic tangent of the elements of `input`.

$$\text{out}_i = \tanh(\text{input}_i)$$

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_tanh(a)
}
```

`torch_tensor` *Converts R objects to a torch tensor*

Description

Converts R objects to a torch tensor

Usage

```
torch_tensor(
  data,
  dtype = NULL,
  device = NULL,
  requires_grad = FALSE,
  pin_memory = FALSE
)
```

Arguments

`data`	an R atomic vector, matrix or array
`dtype`	a torch_dtype instance
`device`	a device creted with `torch_device()`
`requires_grad`	if autograd should record operations on the returned tensor.
`pin_memory`	If set, returned tensor would be allocated in the pinned memory.

Examples

```
if (torch_is_installed()) {
torch_tensor(c(1, 2, 3, 4))
torch_tensor(c(1, 2, 3, 4), dtype = torch_int())
}
```

torch_tensordot *Tensordot*

Description

Returns a contraction of a and b over multiple dimensions. `tensordot` implements a generalized matrix product.

Usage

```
torch_tensordot(a, b, dims = 2)
```

Arguments

a	(Tensor) Left tensor to contract
b	(Tensor) Right tensor to contract
dims	(int or tuple of two lists of integers) number of dimensions to contract or explicit lists of dimensions for a and b respectively

Examples

```
if (torch_is_installed()) {

a <- torch_arange(start = 1, end = 60)$reshape(c(3, 4, 5))
b <- torch_arange(start = 1, end = 24)$reshape(c(4, 3, 2))
torch_tensordot(a, b, dims = list(c(2, 1), c(1, 2)))
## Not run:
a = torch_randn(3, 4, 5, device='cuda')
b = torch_randn(4, 5, 6, device='cuda')
c = torch_tensordot(a, b, dims=2)$cpu()

## End(Not run)
}
```

torch_tensor_from_buffer *Creates a tensor from a buffer of memory*

Description

It creates a tensor without taking ownership of the memory it points to. You must call `clone` if you want to copy the memory over a new tensor.

Usage

```
torch_tensor_from_buffer(buffer, shape, dtype = "float")

buffer_from_torch_tensor(tensor)
```

Arguments

buffer	An R atomic object containing the data in a contiguous array.
shape	The shape of the resulting tensor.
dtype	A torch data type for the tresulting tensor.
tensor	Tensor object that will be converted into a buffer.

Functions

- `buffer_from_torch_tensor()`: Creates a raw vector containing the tensor data. Causes a data copy.

---

torch_threshold_ *Threshold_*

Description

Threshold_

Usage

```
torch_threshold_(self, threshold, value)
```

Arguments

self	input tensor
threshold	The value to threshold at
value	The value to replace with

threshold_(input, threshold, value) -> Tensor

In-place version of `torch_threshold`.

torch_topk *Topk*

Description

Topk

Usage

```
torch_topk(self, k, dim = -1L, largest = TRUE, sorted = TRUE)
```

Arguments

self	(Tensor) the input tensor.
k	(int) the k in "top-k"
dim	(int, optional) the dimension to sort along
largest	(bool, optional) controls whether to return largest or smallest elements
sorted	(bool, optional) controls whether to return the elements in sorted order

topk(input, k, dim=NULL, largest=TRUE, sorted=TRUE) -> (Tensor, LongTensor)

Returns the k largest elements of the given input tensor along a given dimension.

If dim is not given, the last dimension of the input is chosen.

If largest is FALSE then the k smallest elements are returned.

A namedtuple of (values, indices) is returned, where the indices are the indices of the elements in the original input tensor.

The boolean option sorted if TRUE, will make sure that the returned k elements are themselves sorted

Examples

```
if (torch_is_installed()) {

x = torch_arange(1., 6.)
x
torch_topk(x, 3)
}
```

torch_trace *Trace*

Description

Trace

Usage

```
torch_trace(self)
```

Arguments

self	the input tensor

trace(input) -> Tensor

Returns the sum of the elements of the diagonal of the input 2-D matrix.

Examples

```
if (torch_is_installed()) {

x <- torch_arange(1, 9)$view(c(3, 3))
x
torch_trace(x)
}
```

torch_transpose *Transpose*

Description

Transpose

Usage

```
torch_transpose(self, dim0, dim1)
```

Arguments

self	(Tensor) the input tensor.
dim0	(int) the first dimension to be transposed
dim1	(int) the second dimension to be transposed

transpose(input, dim0, dim1) -> Tensor

Returns a tensor that is a transposed version of `input`. The given dimensions `dim0` and `dim1` are swapped.

The resulting `out` tensor shares it's underlying storage with the `input` tensor, so changing the content of one would change the content of the other.

Examples

```
if (torch_is_installed()) {

x = torch_randn(c(2, 3))
x
torch_transpose(x, 1, 2)
}
```

`torch_trapz` *Trapz*

Description

Trapz

Usage

```
torch_trapz(y, dx = 1L, x, dim = -1L)
```

Arguments

`y`	(Tensor) The values of the function to integrate
`dx`	(float) The distance between points at which `y` is sampled.
`x`	(Tensor) The points at which the function `y` is sampled. If `x` is not in ascending order, intervals on which it is decreasing contribute negatively to the estimated integral (i.e., the convention $\int_a^b f = -\int_b^a f$ is followed).
`dim`	(int) The dimension along which to integrate. By default, use the last dimension.

trapz(y, x, *, dim=-1) -> Tensor

Estimate $\int y\,dx$ along `dim`, using the trapezoid rule.

trapz(y, *, dx=1, dim=-1) -> Tensor

As above, but the sample points are spaced uniformly at a distance of `dx`.

Examples

```
if (torch_is_installed()) {

y = torch_randn(list(2, 3))
y
x = torch_tensor(matrix(c(1, 3, 4, 1, 2, 3), ncol = 3, byrow=TRUE))
torch_trapz(y, x = x)

}
```

---

torch_triangular_solve *Triangular_solve*

Description

Triangular_solve

Usage

```
torch_triangular_solve(
  self,
  A,
  upper = TRUE,
  transpose = FALSE,
  unitriangular = FALSE
)
```

Arguments

self	(Tensor) multiple right-hand sides of size $(*, m, k)$ where $*$ is zero of more batch dimensions (b)
A	(Tensor) the input triangular coefficient matrix of size $(*, m, m)$ where $*$ is zero or more batch dimensions
upper	(bool, optional) whether to solve the upper-triangular system of equations (default) or the lower-triangular system of equations. Default: TRUE.
transpose	(bool, optional) whether A should be transposed before being sent into the solver. Default: FALSE.
unitriangular	(bool, optional) whether A is unit triangular. If TRUE, the diagonal elements of A are assumed to be 1 and not referenced from A. Default: FALSE.

triangular_solve(input, A, upper=TRUE, transpose=False, unitriangular=False) -> (Tensor, Tensor)

Solves a system of equations with a triangular coefficient matrix A and multiple right-hand sides b.

In particular, solves $AX = b$ and assumes A is upper-triangular with the default keyword arguments.

`torch_triangular_solve(b, A)` can take in 2D inputs `b, A` or inputs that are batches of 2D matrices. If the inputs are batches, then returns batched outputs `X`

Examples

```
if (torch_is_installed()) {

A = torch_randn(c(2, 2))$triu()
A
b = torch_randn(c(2, 3))
b
torch_triangular_solve(b, A)
}
```

`torch_tril` *Tril*

Description

Tril

Usage

```
torch_tril(self, diagonal = 0L)
```

Arguments

`self`	(Tensor) the input tensor.
`diagonal`	(int, optional) the diagonal to consider

tril(input, diagonal=0, out=NULL) -> Tensor

Returns the lower triangular part of the matrix (2-D tensor) or batch of matrices `input`, the other elements of the result tensor `out` are set to 0.

The lower triangular part of the matrix is defined as the elements on and below the diagonal.

The argument `diagonal` controls which diagonal to consider. If `diagonal` = 0, all elements on and below the main diagonal are retained. A positive value includes just as many diagonals above the main diagonal, and similarly a negative value excludes just as many diagonals below the main diagonal. The main diagonal are the set of indices $\{(i, i)\}$ for $i \in [0, \min\{d_1, d_2\} - 1]$ where d_1, d_2 are the dimensions of the matrix.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(3, 3))
a
torch_tril(a)
b = torch_randn(c(4, 6))
b
torch_tril(b, diagonal=1)
torch_tril(b, diagonal=-1)
}
```

---

torch_tril_indices *Tril_indices*

Description

Tril_indices

Usage

```
torch_tril_indices(
  row,
  col,
  offset = 0,
  dtype = NULL,
  device = NULL,
  layout = NULL
)
```

Arguments

row	(int) number of rows in the 2-D matrix.
col	(int) number of columns in the 2-D matrix.
offset	(int) diagonal offset from the main diagonal. Default: if not provided, 0.
dtype	(torch.dtype, optional) the desired data type of returned tensor. Default: if NULL, torch_long.
device	(torch.device, optional) the desired device of returned tensor. Default: if NULL, uses the current device for the default tensor type (see torch_set_default_tensor_type). device will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
layout	(torch.layout, optional) currently only support torch_strided.

tril_indices(row, col, offset=0, dtype=torch.long, device='cpu', layout=torch.strided) -> Tensor

Returns the indices of the lower triangular part of a `row`-by- `col` matrix in a 2-by-N Tensor, where the first row contains row coordinates of all indices and the second row contains column coordinates. Indices are ordered based on rows and then columns.

The lower triangular part of the matrix is defined as the elements on and below the diagonal.

The argument `offset` controls which diagonal to consider. If `offset` = 0, all elements on and below the main diagonal are retained. A positive value includes just as many diagonals above the main diagonal, and similarly a negative value excludes just as many diagonals below the main diagonal. The main diagonal are the set of indices $\{(i, i)\}$ for $i \in [0, \min\{d_1, d_2\} - 1]$ where d_1, d_2 are the dimensions of the matrix.

Note

```
When running on CUDA, `row * col` must be less than \eqn{2^{59}} to
prevent overflow during calculation.
```

Examples

```
if (torch_is_installed()) {
## Not run:
a = torch_tril_indices(3, 3)
a
a = torch_tril_indices(4, 3, -1)
a
a = torch_tril_indices(4, 3, 1)
a

## End(Not run)
}
```

`torch_triu` *Triu*

Description

Triu

Usage

```
torch_triu(self, diagonal = 0L)
```

Arguments

`self`	(Tensor) the input tensor.
`diagonal`	(int, optional) the diagonal to consider

triu(input, diagonal=0, out=NULL) -> Tensor

Returns the upper triangular part of a matrix (2-D tensor) or batch of matrices `input`, the other elements of the result tensor `out` are set to 0.

The upper triangular part of the matrix is defined as the elements on and above the diagonal.

The argument `diagonal` controls which diagonal to consider. If `diagonal` = 0, all elements on and above the main diagonal are retained. A positive value excludes just as many diagonals above the main diagonal, and similarly a negative value includes just as many diagonals below the main diagonal. The main diagonal are the set of indices $\{(i, i)\}$ for $i \in [0, \min\{d_1, d_2\} - 1]$ where d_1, d_2 are the dimensions of the matrix.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(3, 3))
a
torch_triu(a)
torch_triu(a, diagonal=1)
torch_triu(a, diagonal=-1)
b = torch_randn(c(4, 6))
b
torch_triu(b, diagonal=1)
torch_triu(b, diagonal=-1)
}
```

`torch_triu_indices` *Triu_indices*

Description

Triu_indices

Usage

```
torch_triu_indices(
  row,
  col,
  offset = 0,
  dtype = NULL,
  device = NULL,
  layout = NULL
)
```

Arguments

`row`	(`int`) number of rows in the 2-D matrix.
`col`	(`int`) number of columns in the 2-D matrix.
`offset`	(`int`) diagonal offset from the main diagonal. Default: if not provided, 0.
`dtype`	(`torch.dtype`, optional) the desired data type of returned tensor. Default: if `NULL`, `torch_long`.
`device`	(`torch.device`, optional) the desired device of returned tensor. Default: if `NULL`, uses the current device for the default tensor type (see `torch_set_default_tensor_type`). `device` will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
`layout`	(`torch.layout`, optional) currently only support `torch_strided`.

triu_indices(row, col, offset=0, dtype=torch.long, device='cpu', layout=torch.strided) -> Tensor

Returns the indices of the upper triangular part of a `row` by `col` matrix in a 2-by-N Tensor, where the first row contains row coordinates of all indices and the second row contains column coordinates. Indices are ordered based on rows and then columns.

The upper triangular part of the matrix is defined as the elements on and above the diagonal.

The argument `offset` controls which diagonal to consider. If `offset` = 0, all elements on and above the main diagonal are retained. A positive value excludes just as many diagonals above the main diagonal, and similarly a negative value includes just as many diagonals below the main diagonal. The main diagonal are the set of indices $\{(i, i)\}$ for $i \in [0, \min\{d_1, d_2\} - 1]$ where d_1, d_2 are the dimensions of the matrix.

Note

```
When running on CUDA, `row * col` must be less than \eqn{2^{59}} to
prevent overflow during calculation.
```

Examples

```
if (torch_is_installed()) {
## Not run:
a = torch_triu_indices(3, 3)
a
a = torch_triu_indices(4, 3, -1)
a
a = torch_triu_indices(4, 3, 1)
a

## End(Not run)
}
```

torch_true_divide *TRUE_divide*

Description

TRUE_divide

Usage

```
torch_true_divide(self, other)
```

Arguments

self	(Tensor) the dividend
other	(Tensor or Scalar) the divisor

true_divide(dividend, divisor) -> Tensor

Performs "true division" that always computes the division in floating point. Analogous to division in Python 3 and equivalent to torch_div except when both inputs have bool or integer scalar types, in which case they are cast to the default (floating) scalar type before the division.

$$\text{out}_i = \frac{\text{dividend}_i}{\text{divisor}}$$

Examples

```
if (torch_is_installed()) {

dividend = torch_tensor(c(5, 3), dtype=torch_int())
divisor = torch_tensor(c(3, 2), dtype=torch_int())
torch_true_divide(dividend, divisor)
torch_true_divide(dividend, 2)
}
```

torch_trunc *Trunc*

Description

Trunc

Usage

```
torch_trunc(self)
```

Arguments

`self`	(Tensor) the input tensor.

trunc(input, out=NULL) -> Tensor

Returns a new tensor with the truncated integer values of the elements of `input`.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(4))
a
torch_trunc(a)
}
```

---

torch_unbind *Unbind*

Description

Unbind

Usage

```
torch_unbind(self, dim = 1L)
```

Arguments

`self`	(Tensor) the tensor to unbind
`dim`	(int) dimension to remove

unbind(input, dim=0) -> seq

Removes a tensor dimension.

Returns a tuple of all slices along a given dimension, already without it.

Examples

```
if (torch_is_installed()) {

torch_unbind(torch_tensor(matrix(1:9, ncol = 3, byrow=TRUE)))
}
```

torch_unique_consecutive *Unique_consecutive*

Description

Unique_consecutive

Usage

```
torch_unique_consecutive(
  self,
  return_inverse = FALSE,
  return_counts = FALSE,
  dim = NULL
)
```

Arguments

self	(Tensor) the input tensor
return_inverse	(bool) Whether to also return the indices for where elements in the original input ended up in the returned unique list.
return_counts	(bool) Whether to also return the counts for each unique element.
dim	(int) the dimension to apply unique. If NULL, the unique of the flattened input is returned. default: NULL

TEST

Eliminates all but the first element from every consecutive group of equivalent elements.

```
.. note:: This function is different from [`torch_unique`] in the sense that this function
   only eliminates consecutive duplicate values. This semantics is similar to `std::unique`
     in C++.
```

Examples

```
if (torch_is_installed()) {
x = torch_tensor(c(1, 1, 2, 2, 3, 1, 1, 2))
output = torch_unique_consecutive(x)
output
torch_unique_consecutive(x, return_inverse=TRUE)
torch_unique_consecutive(x, return_counts=TRUE)
}
```

torch_unsafe_chunk *Unsafe_chunk*

Description

Unsafe_chunk

Usage

```
torch_unsafe_chunk(self, chunks, dim = 1L)
```

Arguments

self	(Tensor) the tensor to split
chunks	(int) number of chunks to return
dim	(int) dimension along which to split the tensor

unsafe_chunk(input, chunks, dim=0) -> List of Tensors

Works like torch_chunk() but without enforcing the autograd restrictions on inplace modification of the outputs.

Warning

This function is safe to use as long as only the input, or only the outputs are modified inplace after calling this function. It is user's responsibility to ensure that is the case. If both the input and one or more of the outputs are modified inplace, gradients computed by autograd will be silently incorrect.

torch_unsafe_split *Unsafe_split*

Description

Unsafe_split

Usage

```
torch_unsafe_split(self, split_size, dim = 1L)
```

Arguments

self	(Tensor) tensor to split.
split_size	(int) size of a single chunk or list of sizes for each chunk
dim	(int) dimension along which to split the tensor.

unsafe_split(tensor, split_size_or_sections, dim=0) -> List of Tensors

Works like `torch_split()` but without enforcing the autograd restrictions on inplace modification of the outputs.

Warning

This function is safe to use as long as only the input, or only the outputs are modified inplace after calling this function. It is user's responsibility to ensure that is the case. If both the input and one or more of the outputs are modified inplace, gradients computed by autograd will be silently incorrect.

---

torch_unsqueeze *Unsqueeze*

Description

Unsqueeze

Usage

```
torch_unsqueeze(self, dim)
```

Arguments

`self`	(Tensor) the input tensor.
`dim`	(int) the index at which to insert the singleton dimension

unsqueeze(input, dim) -> Tensor

Returns a new tensor with a dimension of size one inserted at the specified position.

The returned tensor shares the same underlying data with this tensor.

A `dim` value within the range `[-input.dim() - 1, input.dim() + 1)` can be used. Negative `dim` will correspond to `unsqueeze` applied at `dim = dim + input.dim() + 1`.

Examples

```
if (torch_is_installed()) {

x = torch_tensor(c(1, 2, 3, 4))
torch_unsqueeze(x, 1)
torch_unsqueeze(x, 2)
}
```

torch_vander *Vander*

Description

Vander

Usage

```
torch_vander(x, N = NULL, increasing = FALSE)
```

Arguments

x	(Tensor) 1-D input tensor.
N	(int, optional) Number of columns in the output. If N is not specified, a square array is returned $(N = len(x))$.
increasing	(bool, optional) Order of the powers of the columns. If TRUE, the powers increase from left to right, if FALSE (the default) they are reversed.

vander(x, N=None, increasing=FALSE) -> Tensor

Generates a Vandermonde matrix.

The columns of the output matrix are elementwise powers of the input vector $x^{(N-1)}, x^{(N-2)}, ..., x^0$. If increasing is TRUE, the order of the columns is reversed $x^0, x^1, ..., x^{(N-1)}$. Such a matrix with a geometric progression in each row is named for Alexandre-Theophile Vandermonde.

Examples

```
if (torch_is_installed()) {

x <- torch_tensor(c(1, 2, 3, 5))
torch_vander(x)
torch_vander(x, N=3)
torch_vander(x, N=3, increasing=TRUE)
}
```

torch_var *Var*

Description

Var

Usage

```
torch_var(self, dim, unbiased = TRUE, keepdim = FALSE)
```

Arguments

self	(Tensor) the input tensor.
dim	(int or tuple of ints) the dimension or dimensions to reduce.
unbiased	(bool) whether to use the unbiased estimation or not
keepdim	(bool) whether the output tensor has dim retained or not.

var(input, unbiased=TRUE) -> Tensor

Returns the variance of all elements in the input tensor.

If unbiased is FALSE, then the variance will be calculated via the biased estimator. Otherwise, Bessel's correction will be used.

var(input, dim, keepdim=False, unbiased=TRUE, out=NULL) -> Tensor

Returns the variance of each row of the input tensor in the given dimension dim.

If keepdim is TRUE, the output tensor is of the same size as input except in the dimension(s) dim where it is of size 1. Otherwise, dim is squeezed (see torch_squeeze), resulting in the output tensor having 1 (or len(dim)) fewer dimension(s).

If unbiased is FALSE, then the variance will be calculated via the biased estimator. Otherwise, Bessel's correction will be used.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(1, 3))
a
torch_var(a)


a = torch_randn(c(4, 4))
a
torch_var(a, 1)
}
```

---

torch_var_mean *Var_mean*

Description

Var_mean

Usage

```
torch_var_mean(self, dim, unbiased = TRUE, keepdim = FALSE)
```

Arguments

self	(Tensor) the input tensor.
dim	(int or tuple of ints) the dimension or dimensions to reduce.
unbiased	(bool) whether to use the unbiased estimation or not
keepdim	(bool) whether the output tensor has dim retained or not.

var_mean(input, unbiased=TRUE) -> (Tensor, Tensor)

Returns the variance and mean of all elements in the input tensor.

If unbiased is FALSE, then the variance will be calculated via the biased estimator. Otherwise, Bessel's correction will be used.

var_mean(input, dim, keepdim=False, unbiased=TRUE) -> (Tensor, Tensor)

Returns the variance and mean of each row of the input tensor in the given dimension dim.

If keepdim is TRUE, the output tensor is of the same size as input except in the dimension(s) dim where it is of size 1. Otherwise, dim is squeezed (see torch_squeeze), resulting in the output tensor having 1 (or len(dim)) fewer dimension(s).

If unbiased is FALSE, then the variance will be calculated via the biased estimator. Otherwise, Bessel's correction will be used.

Examples

```
if (torch_is_installed()) {

a = torch_randn(c(1, 3))
a
torch_var_mean(a)


a = torch_randn(c(4, 4))
a
torch_var_mean(a, 1)
}
```

---

torch_vdot *Vdot*

Description

Vdot

Usage

```
torch_vdot(self, other)
```

Arguments

`self`	(Tensor) first tensor in the dot product. Its conjugate is used if it's complex.
`other`	(Tensor) second tensor in the dot product.

vdot(input, other, *, out=None) -> Tensor

Computes the dot product (inner product) of two tensors. The vdot(a, b) function handles complex numbers differently than dot(a, b). If the first argument is complex, the complex conjugate of the first argument is used for the calculation of the dot product.

Note

This function does not broadcast .

Examples

```
if (torch_is_installed()) {

torch_vdot(torch_tensor(c(2, 3)), torch_tensor(c(2, 1)))
if (FALSE) {
a <- torch_tensor(list(1 +2i, 3 - 1i))
b <- torch_tensor(list(2 +1i, 4 - 0i))
torch_vdot(a, b)
torch_vdot(b, a)
}
}
```

`torch_view_as_complex` *View_as_complex*

Description

View_as_complex

Usage

```
torch_view_as_complex(self)
```

Arguments

`self`	(Tensor) the input tensor.

view_as_complex(input) -> Tensor

Returns a view of `input` as a complex tensor. For an input complex tensor of `size` $m1, m2, \ldots, mi, 2$, this function returns a new complex tensor of `size` $m1, m2, \ldots, mi$ where the last dimension of the input tensor is expected to represent the real and imaginary components of complex numbers.

Warning

torch_view_as_complex is only supported for tensors with `torch_dtype` `torch_float64()` and `torch_float32()`. The input is expected to have the last dimension of `size` 2. In addition, the tensor must have a `stride` of 1 for its last dimension. The strides of all other dimensions must be even numbers.

Examples

```
if (torch_is_installed()) {
if (FALSE) {
x=torch_randn(c(4, 2))
x
torch_view_as_complex(x)
}
}
```

---

torch_view_as_real *View_as_real*

Description

View_as_real

Usage

```
torch_view_as_real(self)
```

Arguments

`self`	(Tensor) the input tensor.

view_as_real(input) -> Tensor

Returns a view of `input` as a real tensor. For an input complex tensor of `size` $m1, m2, \ldots, mi$, this function returns a new real tensor of size $m1, m2, \ldots, mi, 2$, where the last dimension of size 2 represents the real and imaginary components of complex numbers.

Warning

`torch_view_as_real()` is only supported for tensors with `complex dtypes`.

Examples

```
if (torch_is_installed()) {

if (FALSE) {
x <- torch_randn(4, dtype=torch_cfloat())
x
torch_view_as_real(x)
```

```
}
}
```

torch_vstack *Vstack*

Description

Vstack

Usage

```
torch_vstack(tensors)
```

Arguments

tensors	(sequence of Tensors) sequence of tensors to concatenate

vstack(tensors, *, out=None) -> Tensor

Stack tensors in sequence vertically (row wise).

This is equivalent to concatenation along the first axis after all 1-D tensors have been reshaped by `torch_atleast_2d()`.

Examples

```
if (torch_is_installed()) {

a <- torch_tensor(c(1, 2, 3))
b <- torch_tensor(c(4, 5, 6))
torch_vstack(list(a,b))
a <- torch_tensor(rbind(1,2,3))
b <- torch_tensor(rbind(4,5,6))
torch_vstack(list(a,b))
}
```

torch_where *Where*

Description

Where

Usage

```
torch_where(condition, self = NULL, other = NULL)
```

Arguments

condition	(BoolTensor) When TRUE (nonzero), yield x, otherwise yield y
self	(Tensor) values selected at indices where condition is TRUE
other	(Tensor) values selected at indices where condition is FALSE

where(condition, x, y) -> Tensor

Return a tensor of elements selected from either x or y, depending on condition.

The operation is defined as:

$$\text{out}_i = \begin{cases} \text{x}_i & \text{if condition}_i \\ \text{y}_i & \text{otherwise} \end{cases}$$

where(condition) -> tuple of LongTensor

torch_where(condition) is identical to torch_nonzero(condition, as_tuple=TRUE).

Note

The tensors `condition`, `x`, `y` must be broadcastable .

See also torch_nonzero().

Examples

```
if (torch_is_installed()) {

## Not run:
x = torch_randn(c(3, 2))
y = torch_ones(c(3, 2))
x
torch_where(x > 0, x, y)

## End(Not run)



}
```

---

torch_zeros *Zeros*

Description

Zeros

Usage

```
torch_zeros(
  ...,
  names = NULL,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE
)
```

Arguments

`...`	a sequence of integers defining the shape of the output tensor. Can be a variable number of arguments or a collection like a list or tuple.
`names`	optional dimension names
`dtype`	(`torch.dtype`, optional) the desired data type of returned tensor. Default: if `NULL`, uses a global default (see `torch_set_default_tensor_type`).
`layout`	(`torch.layout`, optional) the desired layout of returned Tensor. Default: `torch_strided`.
`device`	(`torch.device`, optional) the desired device of returned tensor. Default: if `NULL`, uses the current device for the default tensor type (see `torch_set_default_tensor_type`). `device` will be the CPU for CPU tensor types and the current CUDA device for CUDA tensor types.
`requires_grad`	(bool, optional) If autograd should record operations on the returned tensor. Default: `FALSE`.

zeros(*size, out=NULL, dtype=NULL, layout=torch.strided, device=NULL, requires_grad=False) -> Tensor

Returns a tensor filled with the scalar value `0`, with the shape defined by the variable argument `size`.

Examples

```
if (torch_is_installed()) {

torch_zeros(c(2, 3))
torch_zeros(c(5))
}
```

---

torch_zeros_like *Zeros_like*

Description

Zeros_like

Usage

```
torch_zeros_like(
  input,
  dtype = NULL,
  layout = NULL,
  device = NULL,
  requires_grad = FALSE,
  memory_format = torch_preserve_format()
)
```

Arguments

input	(Tensor) the size of `input` will determine size of the output tensor.
dtype	(`torch.dtype`, optional) the desired data type of returned Tensor. Default: if `NULL`, defaults to the dtype of `input`.
layout	(`torch.layout`, optional) the desired layout of returned tensor. Default: if `NULL`, defaults to the layout of `input`.
device	(`torch.device`, optional) the desired device of returned tensor. Default: if `NULL`, defaults to the device of `input`.
requires_grad	(bool, optional) If autograd should record operations on the returned tensor. Default: `FALSE`.
memory_format	(`torch.memory_format`, optional) the desired memory format of returned Tensor. Default: `torch_preserve_format`.

zeros_like(input, dtype=NULL, layout=NULL, device=NULL, requires_grad=False, memory_format=torch.preserve_forr -> Tensor

Returns a tensor filled with the scalar value `0`, with the same size as `input`. `torch_zeros_like(input)` is equivalent to `torch_zeros(input.size(), dtype=input.dtype, layout=input.layout, device=input.device)`.

Warning

As of 0.4, this function does not support an `out` keyword. As an alternative, the old `torch_zeros_like(input, out=output)` is equivalent to `torch_zeros(input.size(), out=output)`.

Examples

```
if (torch_is_installed()) {

input = torch_empty(c(2, 3))
torch_zeros_like(input)
}
```

`with_detect_anomaly` *Context-manager that enable anomaly detection for the autograd engine.*

Description

This does two things:

Usage

```
with_detect_anomaly(code)
```

Arguments

`code`	Code that will be executed in the detect anomaly context.

Details

- Running the forward pass with detection enabled will allow the backward pass to print the traceback of the forward operation that created the failing backward function.
- Any backward computation that generate "nan" value will raise an error.

Warning

This mode should be enabled only for debugging as the different tests will slow down your program execution.

Examples

```
if (torch_is_installed()) {
x <- torch_randn(2, requires_grad = TRUE)
y <- torch_randn(1)
b <- (x^y)$sum()
y$add_(1)

try({
  b$backward()

  with_detect_anomaly({
    b$backward()
  })
})
}
```

with_enable_grad *Enable grad*

Description

Context-manager that enables gradient calculation. Enables gradient calculation, if it has been disabled via with_no_grad.

Usage

```
with_enable_grad(code)

local_enable_grad(.env = parent.frame())
```

Arguments

code	code to be executed with gradient recording.
.env	The environment to use for scoping.

Details

This context manager is thread local; it will not affect computation in other threads.

Functions

- `local_enable_grad()`: Locally enable gradient computations.

Examples

```
if (torch_is_installed()) {

x <- torch_tensor(1, requires_grad = TRUE)
with_no_grad({
  with_enable_grad({
    y <- x * 2
  })
})
y$backward()
x$grad
}
```

`with_no_grad` *Temporarily modify gradient recording.*

Description

Temporarily modify gradient recording.

Usage

```
with_no_grad(code)

local_no_grad(.env = parent.frame())
```

Arguments

`code`	code to be executed with no gradient recording.
`.env`	The environment to use for scoping.

Functions

- `local_no_grad()`: Disable autograd until it goes out of scope

Examples

```
if (torch_is_installed()) {
x <- torch_tensor(runif(5), requires_grad = TRUE)
with_no_grad({
  x$sub_(torch_tensor(as.numeric(1:5)))
})
x
x$grad
}
```

Index

∗ **datasets**
jit_ops, 59
∗ **distributions**
distr_bernoulli, 43
distr_chi2, 45
distr_gamma, 46
distr_multivariate_normal, 47
distr_normal, 48
distr_poisson, 49
∗ **linalg**
linalg_cholesky, 65
linalg_cholesky_ex, 66
linalg_det, 69
linalg_eig, 70
linalg_eigh, 71
linalg_eigvals, 73
linalg_eigvalsh, 74
linalg_householder_product, 75
linalg_inv, 76
linalg_inv_ex, 77
linalg_lstsq, 78
linalg_matrix_norm, 80
linalg_matrix_power, 82
linalg_matrix_rank, 83
linalg_multi_dot, 84
linalg_norm, 85
linalg_pinv, 87
linalg_qr, 88
linalg_slogdet, 89
linalg_solve, 90
linalg_solve_triangular, 91
linalg_svd, 92
linalg_svdvals, 94
linalg_tensorinv, 95
linalg_tensorsolve, 96
linalg_vector_norm, 97
∗ **serialization**
load_state_dict, 99
torch_load, 464
torch_save, 543
torch_serialize, 547
∗ **tensor-attributes**
is_torch_device, 55
is_torch_dtype, 55
torch_dtype, 406
torch_finfo, 423
torch_iinfo, 444
torch_qscheme, 521
torch_reduction, 534
torch_set_default_dtype, 547
∗ **tensor-attributtes**
torch_device, 396
∗ **torch_save**
torch_load, 464
torch_save, 543
torch_serialize, 547

as_array, 17
autograd_backward, 20
autograd_function, 21
autograd_grad, 22
autograd_set_grad_mode, 23
AutogradContext, 18, *21*

backends_cudnn_is_available, 23
backends_cudnn_version, 24
backends_mkl_is_available, 24
backends_mkldnn_is_available, 24
backends_mps_is_available, 25
backends_openmp_is_available, 25
broadcast_all, 26
buffer_from_torch_tensor
(torch_tensor_from_buffer), 571

clone_module, 26
Constraint, 27
contrib_sort_vertices, 28
cuda_amp_grad_scaler, 29
cuda_amp_grad_scaler(), *100*

cuda_current_device, 29
cuda_current_device(), *35*
cuda_device_count, 30
cuda_dump_memory_snapshot, 30
cuda_empty_cache, 31
cuda_empty_cache(), *31*
cuda_get_device_capability, 31
cuda_get_rng_state
(torch_get_rng_state), 436
cuda_is_available, 31
cuda_memory_snapshot, 32
cuda_memory_stats, 32
cuda_memory_summary
(cuda_memory_stats), 32
cuda_record_memory_history, 34
cuda_runtime_version, 35
cuda_set_rng_state
(torch_get_rng_state), 436
cuda_synchronize, 35

dataloader, 36
dataloader(), *38, 39*, *326*
dataloader_make_iter, *38*, 38
dataloader_next, 38
dataset, 38
dataset(), *37*, *326, 327*
dataset_subset, 40
distr_bernoulli, 43, *45, 46*, *48, 49*
distr_categorical, 44
distr_chi2, *44*, 45, *46*, *48, 49*
distr_gamma, *44, 45*, 46, *48, 49*
distr_mixture_same_family, 46
distr_multivariate_normal, *44–46*, 47, *49*
distr_normal, *44–46*, *48*, 48, *49*
distr_poisson, *44–46*, *48, 49*, 49
Distribution, 40, *44–46*, *48, 49*

enumerate, 50
enumerate.dataloader, 50

get_install_libs_url, 51

install_torch, 52
install_torch_from_file
(get_install_libs_url), 51
is_dataloader, 53
is_nn_buffer, 53
is_nn_module, 54
is_nn_parameter, 54
is_optimizer, 54
is_torch_device, 55
is_torch_dtype, 55
is_torch_layout, 55
is_torch_memory_format, 56
is_torch_qscheme, 56
is_undefined_tensor, 56
iterable_dataset, 57

jit_compile, 58, *63*
jit_load, 58
jit_ops, 59
jit_save, 60
jit_save(), *59*
jit_save_for_mobile, 60
jit_scalar, 61
jit_serialize, 61, *65*
jit_trace, 62, *64*
jit_trace(), *63*
jit_trace_module, 63
jit_trace_module(), *62, 63*
jit_tuple, 64
jit_unserialize, *61*, 65

linalg_cholesky, 65, *67*, *69*, *71*, *73–78*, *80–82*, *84–86*, *88–92*, *94–98*
linalg_cholesky(), *66, 67*, *72*
linalg_cholesky_ex, *66*, 66, *69*, *71*, *73–78*, *80–82*, *84–86*, *88–92*, *94–98*
linalg_cholesky_ex(), *66*
linalg_cond, 67
linalg_det, *66, 67*, 69, *71*, *73–78*, *80–82*, *84–86*, *88–92*, *94–98*
linalg_eig, *66, 67*, *69*, 70, *73–78*, *80–82*, *84–86*, *88–92*, *94–98*
linalg_eig(), *71, 72*, *74*, *94*
linalg_eigh, *66, 67*, *69*, *71*, 71, *74–78*, *80–82*, *84–86*, *88–92*, *94–98*
linalg_eigh(), *66*, *71, 72*, *75*, *87*, *94*
linalg_eigvals, *66, 67*, *69*, *71*, *73*, 73, *75–78*, *80–82*, *84–86*, *88–92*, *94–98*
linalg_eigvals(), *71*
linalg_eigvalsh, *66, 67*, *69*, *71*, *73, 74*, 74, *76–78*, *80–82*, *84–86*, *88–92*, *94–98*
linalg_eigvalsh(), *72*
linalg_householder_product, *66, 67*, *69*, *71*, *73–75*, 75, *77, 78*, *80–82*, *84–86*, *88–92*, *94–98*

linalg_inv, *66, 67*, *69*, *71*, *73–76*, 76, *78*, *80–82*, *84–86*, *88–92*, *94–98*
linalg_inv(), *68*, *78*, *88*
linalg_inv_ex, *66, 67*, *69*, *71*, *73–77*, 77, *80–82*, *84–86*, *88–92*, *94–98*
linalg_lstsq, *66, 67*, *69*, *71*, *73–78*, 78, *81, 82*, *84–86*, *88–92*, *94–98*
linalg_lstsq(), *87, 88*
linalg_matrix_norm, *66, 67*, *69*, *71*, *73–78*, *80*, 80, *82*, *84–86*, *88–92*, *94–98*
linalg_matrix_power, *66, 67*, *69*, *71*, *73–78*, *80, 81*, 82, *84–86*, *88–92*, *94–98*
linalg_matrix_rank, *66, 67*, *69*, *71*, *73–78*, *80–82*, 83, *85, 86*, *88–92*, *94–98*
linalg_multi_dot, *66, 67*, *69*, *71*, *73–78*, *80–82*, *84*, 84, *86*, *88–92*, *94–98*
linalg_norm, *66, 67*, *69*, *71*, *73–78*, *80–82*, *84, 85*, 85, *88–92*, *94–98*
linalg_norm(), *68*, *98*
linalg_pinv, *66, 67*, *69*, *71*, *73–78*, *80–82*, *84–86*, 87, *89–92*, *94–98*
linalg_pinv(), *77*
linalg_qr, *66, 67*, *69*, *71*, *73–78*, *80–82*, *84–86*, *88*, 88, *90–92*, *94–98*
linalg_qr(), *71*, *73*, *76*, *94*
linalg_slogdet, *66, 67*, *69*, *71*, *73–78*, *80–82*, *84–86*, *88, 89*, 89, *91, 92*, *94–98*
linalg_solve, *66, 67*, *69*, *71*, *73–78*, *80–82*, *84–86*, *88–90*, 90, *92*, *94–98*
linalg_solve(), *77*, *82*
linalg_solve_triangular, *66, 67*, *69*, *71*, *73–78*, *80–82*, *84–86*, *88–91*, 91, *94–98*
linalg_svd, *66, 67*, *69*, *71*, *73–78*, *80–82*, *84–86*, *88–92*, 92, *95–98*
linalg_svd(), *68*, *71*, *73*, *87*, *93*, *95*
linalg_svdvals, *66, 67*, *69*, *71*, *73–78*, *80–82*, *84–86*, *88–92*, *94*, 94, *96–98*
linalg_svdvals(), *93*
linalg_tensorinv, *66, 67*, *69*, *71*, *73–78*, *80–82*, *84–86*, *88–92*, *94, 95*, 95, *97, 98*
linalg_tensorinv(), *97*
linalg_tensorsolve, *66, 67*, *69*, *71*, *73–78*, *80–82*, *84–86*, *88–92*, *94–96*, 96, *98*
linalg_tensorsolve(), *95, 96*
linalg_vector_norm, *66, 67*, *69*, *71*, *73–78*, *80–82*, *84–86*, *88–92*, *94–97*, 97
load_state_dict, 99
local_autocast, 99
local_device, 101
local_enable_grad *(*with_enable_grad*)*, 597
local_no_grad *(*with_no_grad*)*, 598
local_torch_manual_seed *(*torch_manual_seed*)*, 480
lr_cosine_annealing, 102
lr_lambda, 102
lr_multiplicative, 103
lr_one_cycle, 104
lr_reduce_on_plateau, 106
lr_scheduler, 108
lr_step, 108

nn_adaptive_avg_pool1d, 173
nn_adaptive_avg_pool1d(), *330*
nn_adaptive_avg_pool2d, 173
nn_adaptive_avg_pool3d, 174
nn_adaptive_log_softmax_with_loss, 175
nn_adaptive_max_pool1d, 177
nn_adaptive_max_pool2d, 177
nn_adaptive_max_pool3d, 178
nn_aum_loss, 179
nn_avg_pool1d, 180
nn_avg_pool1d(), *355*
nn_avg_pool2d, 181
nn_avg_pool3d, 182
nn_batch_norm1d, 184
nn_batch_norm2d, 185
nn_batch_norm3d, 187
nn_bce_loss, 188
nn_bce_with_logits_loss, 190
nn_bilinear, 191
nn_buffer, 192
nn_buffer(), *261*
nn_celu, 193
nn_contrib_sparsemax, 194
nn_conv1d, 194
nn_conv1d(), *380*
nn_conv2d, 196, *205*, *214, 215*
nn_conv2d(), *381*
nn_conv3d, 199
nn_conv3d(), *382*
nn_conv_transpose1d, 201
nn_conv_transpose1d(), *384*
nn_conv_transpose2d, 203, *205*

nn_conv_transpose2d(), *385*
nn_conv_transpose3d, 206
nn_conv_transpose3d(), *386*
nn_cosine_embedding_loss, 209
nn_cross_entropy_loss, 209
nn_ctc_loss, 211
nn_dropout, 213
nn_dropout2d, *214*, 214
nn_dropout3d, *215*, 215
nn_elu, 216
nn_embedding, 216, *217*
nn_embedding_bag, 218
nn_flatten, 219
nn_fractional_max_pool2d, 220
nn_fractional_max_pool3d, 221
nn_gelu, 222
nn_glu, 223
nn_group_norm, 223
nn_gru, 225
nn_hardshrink, 227
nn_hardsigmoid, 227
nn_hardswish, 228
nn_hardtanh, 229
nn_hinge_embedding_loss, 230
nn_identity, 231
nn_init_calculate_gain, 231
nn_init_constant_, 232
nn_init_dirac_, 232
nn_init_eye_, 233
nn_init_kaiming_normal_, 233
nn_init_kaiming_uniform_, 234
nn_init_normal_, 235
nn_init_ones_, 236
nn_init_orthogonal_, 236
nn_init_sparse_, 237
nn_init_trunc_normal_, 237
nn_init_uniform_, 238
nn_init_xavier_normal_, 239
nn_init_xavier_uniform_, 239
nn_init_zeros_, 240
nn_kl_div_loss, 240
nn_l1_loss, 241
nn_layer_norm, 242
nn_leaky_relu, 244
nn_linear, 245
nn_log_sigmoid, 246
nn_log_softmax, 246
nn_log_softmax(), *209*
nn_lp_pool1d, 247
nn_lp_pool2d, 248
nn_lstm, 250
nn_margin_ranking_loss, 252
nn_max_pool1d, 253
nn_max_pool1d(), *257*
nn_max_pool2d, 254
nn_max_pool2d(), *258*
nn_max_pool3d, 255
nn_max_pool3d(), *260*
nn_max_unpool1d, 257
nn_max_unpool1d(), *177*
nn_max_unpool2d, 258
nn_max_unpool2d(), *178*, *221*
nn_max_unpool3d, 259
nn_max_unpool3d(), *178*, *221*
nn_module, *26*, 260
nn_module(), *62*
nn_module_dict, 262
nn_module_dict(), *263*
nn_module_list, *263*, 263
nn_module_list(), *263*
nn_mse_loss, 264
nn_multi_margin_loss, 269
nn_multihead_attention, 265
nn_multilabel_margin_loss, 267
nn_multilabel_soft_margin_loss, 268
nn_nll_loss, 270
nn_nll_loss(), *241*
nn_pairwise_distance, 271
nn_pairwise_distance(), *171*, *295*
nn_parameter, 272
nn_parameter(), *261*
nn_poisson_nll_loss, 273
nn_prelu, 274
nn_prune_head, 275
nn_relu, 276
nn_relu6, 276
nn_rnn, 277
nn_rrelu, 279
nn_selu, 280
nn_sequential, *219*, 281, *297*
nn_sigmoid, 282
nn_silu, 282
nn_silu(), *165*
nn_smooth_l1_loss, 283
nn_soft_margin_loss, 288
nn_softmax, 284

nn_softmax2d, 285
nn_softmin, 285
nn_softplus, 286
nn_softshrink, 287
nn_softsign, 288
nn_tanh, 289
nn_tanhshrink, 290
nn_threshold, 290
nn_transformer_encoder, 291
nn_transformer_encoder_layer, 292
nn_triplet_margin_loss, 293
nn_triplet_margin_loss(), *296*
nn_triplet_margin_with_distance_loss, 295
nn_triplet_margin_with_distance_loss(), *171*, *294*
nn_unflatten, *220*, 297
nn_upsample, 298
nn_utils_clip_grad_norm_, 299
nn_utils_clip_grad_value_, 299
nn_utils_rnn_pack_padded_sequence, 300
nn_utils_rnn_pack_padded_sequence(), *226*, *251*, *302*
nn_utils_rnn_pack_sequence, 301
nn_utils_rnn_pack_sequence(), *251*, *302*
nn_utils_rnn_pad_packed_sequence, 302
nn_utils_rnn_pad_sequence, 303
nn_utils_weight_norm, 304
nnf_adaptive_avg_pool1d, 109
nnf_adaptive_avg_pool2d, 109
nnf_adaptive_avg_pool3d, 110
nnf_adaptive_max_pool1d, 110
nnf_adaptive_max_pool2d, 111
nnf_adaptive_max_pool3d, 111
nnf_affine_grid, 112
nnf_affine_grid(), *112*, *137*
nnf_alpha_dropout, 112
nnf_area_under_min_fpr_fnr, 113
nnf_avg_pool1d, 113
nnf_avg_pool2d, 114
nnf_avg_pool3d, 115
nnf_batch_norm, 116
nnf_bilinear, 116
nnf_binary_cross_entropy, 117
nnf_binary_cross_entropy_with_logits, 118
nnf_celu, 118
nnf_celu(), *369*
nnf_celu_ *(nnf_celu)*, 118
nnf_contrib_sparsemax, 119
nnf_conv1d, 119
nnf_conv2d, 120
nnf_conv3d, 121
nnf_conv_tbc, 121
nnf_conv_transpose1d, 122
nnf_conv_transpose2d, 123
nnf_conv_transpose3d, 124
nnf_cosine_embedding_loss, 125
nnf_cosine_similarity, 125
nnf_cross_entropy, 126
nnf_ctc_loss, 127
nnf_dropout, 128
nnf_dropout2d, 128
nnf_dropout3d, 129
nnf_elu, 129
nnf_elu_ *(nnf_elu)*, 129
nnf_embedding, 130
nnf_embedding_bag, 131
nnf_fold, 132
nnf_fractional_max_pool2d, 133
nnf_fractional_max_pool3d, 134
nnf_gelu, 135
nnf_glu, 135
nnf_grid_sample, 136
nnf_grid_sample(), *112*
nnf_group_norm, 137
nnf_gumbel_softmax, 138
nnf_hardshrink, 138
nnf_hardsigmoid, 139
nnf_hardswish, 139
nnf_hardtanh, 140
nnf_hardtanh_ *(nnf_hardtanh)*, 140
nnf_hinge_embedding_loss, 140
nnf_instance_norm, 141
nnf_interpolate, 141
nnf_interpolate(), *136*
nnf_kl_div, 143
nnf_l1_loss, 143
nnf_layer_norm, 144
nnf_leaky_relu, 144
nnf_linear, 145
nnf_local_response_norm, 145
nnf_log_softmax, *127*, 146
nnf_logsigmoid, 146
nnf_lp_pool1d, 147
nnf_lp_pool2d, 147

nnf_margin_ranking_loss, 148
nnf_max_pool1d, 148
nnf_max_pool2d, 149
nnf_max_pool3d, 150
nnf_max_unpool1d, 150
nnf_max_unpool2d, 151
nnf_max_unpool3d, 152
nnf_mse_loss, 152
nnf_multi_head_attention_forward, 154
nnf_multi_margin_loss, 156
nnf_multilabel_margin_loss, 153
nnf_multilabel_soft_margin_loss, 153
nnf_nll_loss, 157
nnf_normalize, 158
nnf_one_hot, 158
nnf_pad, 159
nnf_pairwise_distance, 160
nnf_pdist, 160
nnf_pixel_shuffle, 161
nnf_poisson_nll_loss, 161
nnf_prelu, 162
nnf_relu, 162
nnf_relu6, 163
nnf_relu_ *(*nnf_relu*)*, 162
nnf_rrelu, 163
nnf_rrelu_ *(*nnf_rrelu*)*, 163
nnf_selu, 164
nnf_selu_ *(*nnf_selu*)*, 164
nnf_sigmoid, 164
nnf_silu, 165
nnf_smooth_l1_loss, 165
nnf_soft_margin_loss, 169
nnf_softmax, 166, *167*
nnf_softmin, 166
nnf_softplus, 167
nnf_softshrink, 168
nnf_softsign, 168
nnf_tanhshrink, 169
nnf_threshold, 170
nnf_threshold_ *(*nnf_threshold*)*, 170
nnf_triplet_margin_loss, 170
nnf_triplet_margin_with_distance_loss, 171
nnf_unfold, 172

optim_adadelta, 310
optim_adagrad, 312
optim_adam, 313
optim_adamw, 314
optim_asgd, 315
optim_ignite_adagrad, 316
optim_ignite_adam, 317
optim_ignite_adamw, 318
optim_ignite_rmsprop, 319
optim_ignite_sgd, 320
optim_lbfgs, 321
optim_required, 322
optim_rmsprop, 323
optim_rprop, 324
optim_sgd, 325
optimizer, 306
optimizer_ignite, 310
OptimizerIgnite, 308, *316–320*

R6::R6Class(), *39*, *57*, *108*, *261*

sampler, 326
sampler(), *36, 37*
set_autocast *(*local_autocast*)*, 99

tensor_dataset, 327
threads, 327
torch_abs, 328
torch_abs(), *328*
torch_absolute, 328
torch_acos, 329
torch_acos(), *343*
torch_acosh, 329
torch_acosh(), *343*
torch_adaptive_avg_pool1d, 330
torch_add, 331
torch_addbmm, 332
torch_addcdiv, 333
torch_addcmul, 334
torch_addmm, 335
torch_addmv, 336
torch_addr, 337
torch_allclose, 338
torch_amax, 339
torch_amin, 340
torch_angle, 341
torch_arange, 341, *533*
torch_arccos, 343
torch_arccosh, 343
torch_arcsin, 344
torch_arcsinh, 344
torch_arctan, 345
torch_arctanh, 345

torch_argmax, 346
torch_argmax(), *568*
torch_argmin, 347
torch_argsort, 348
torch_argsort(), *568*
torch_as_strided, 350
torch_asin, 348
torch_asin(), *344*
torch_asinh, 349
torch_asinh(), *344*
torch_atan, 351
torch_atan(), *345*
torch_atan2, 351
torch_atanh, 352
torch_atanh(), *345*
torch_atleast_1d, 353
torch_atleast_2d, 354
torch_atleast_2d(), *592*
torch_atleast_3d, 354
torch_atleast_3d(), *405*
torch_avg_pool1d, 355
torch_baddbmm, 356
torch_bartlett_window, 357
torch_bernoulli, 358
torch_bfloat16 *(*torch_dtype*)*, 406
torch_bincount, 359
torch_bitwise_and, 360
torch_bitwise_not, 360
torch_bitwise_or, 361
torch_bitwise_xor, 361
torch_blackman_window, 362
torch_block_diag, 363
torch_bmm, 363
torch_bool *(*torch_dtype*)*, 406
torch_broadcast_tensors, 364
torch_bucketize, 365
torch_can_cast, 366
torch_cartesian_prod, 366
torch_cat, *367*, 367
torch_cdist, 368
torch_cdouble *(*torch_dtype*)*, 406
torch_ceil, 368
torch_celu, 369
torch_celu(), *370*
torch_celu_, 370
torch_cfloat *(*torch_dtype*)*, 406
torch_cfloat128 *(*torch_dtype*)*, 406
torch_cfloat32 *(*torch_dtype*)*, 406
torch_cfloat64 *(*torch_dtype*)*, 406
torch_chain_matmul, 370
torch_chalf *(*torch_dtype*)*, 406
torch_channel_shuffle, 371
torch_channels_last_format *(*torch_memory_format*)*, 489
torch_cholesky, 372
torch_cholesky_inverse, 373
torch_cholesky_solve, 374
torch_chunk, *367*, 375
torch_chunk(), *585*
torch_clamp, 375
torch_clamp(), *377*
torch_clip, 376
torch_clone, 377
torch_combinations, 378
torch_complex, 378
torch_conj, 379
torch_contiguous_format *(*torch_memory_format*)*, 489
torch_conv1d, 380
torch_conv2d, 381
torch_conv3d, 382
torch_conv_tbc, 383
torch_conv_transpose1d, 383
torch_conv_transpose2d, 384
torch_conv_transpose3d, 386
torch_cos, 387
torch_cosh, 388
torch_cosine_similarity, 388
torch_count_nonzero, 389
torch_cross, 390
torch_cummax, 391
torch_cummin, 391
torch_cumprod, 392
torch_cumsum, 393
torch_deg2rad, 394
torch_dequantize, 394
torch_det, 395
torch_device, 396
torch_device(), *570*
torch_diag, 396
torch_diag_embed, 399
torch_diagflat, 397
torch_diagonal, 398
torch_diff, 400
torch_diff(), *400*
torch_digamma, 401

torch_dist, 401
torch_div, 402, *428*, *582*
torch_div(), *333*, *404*
torch_divide, 403
torch_dot, 404
torch_double *(*torch_dtype*)*, 406
torch_dstack, 405
torch_dtype, 406, *570*
torch_eig, 407
torch_einsum, 407
torch_empty, 409
torch_empty_like, 410
torch_empty_strided, 411
torch_eq, 412
torch_equal, 413
torch_erf, 413
torch_erfc, 414
torch_erfinv, 415
torch_exp, 415
torch_exp2, 416
torch_expm1, 417
torch_eye, 417
torch_fft_fft, 418
torch_fft_fft(), *420*, *423*
torch_fft_fftfreq, 419
torch_fft_ifft, 420
torch_fft_irfft, 421
torch_fft_irfft(), *422*
torch_fft_rfft, 422
torch_fft_rfft(), *421*
torch_finfo, 423
torch_finfo(), *83*
torch_fix, 423
torch_flatten, 424
torch_flip, 424
torch_fliplr, 425
torch_flipud, 426
torch_float *(*torch_dtype*)*, 406
torch_float16 *(*torch_dtype*)*, 406
torch_float32 *(*torch_dtype*)*, 406
torch_float64 *(*torch_dtype*)*, 406
torch_floor, 427
torch_floor_divide, 427
torch_floor_divide(), *333*, *403*
torch_fmod, 428
torch_frac, 429
torch_full, 429
torch_full_like, 430
torch_gather, 431
torch_gcd, 432
torch_ge, 433
torch_ge(), *437*
torch_generator, 434
torch_generator(), *507*
torch_geqrf, 434, *510*, *511*
torch_geqrf(), *76*, *511*
torch_ger, 435
torch_get_default_dtype *(*torch_set_default_dtype*)*, 547
torch_get_default_dtype(), *419*
torch_get_num_interop_threads *(*threads*)*, 327
torch_get_num_threads *(*threads*)*, 327
torch_get_rng_state, 436
torch_greater, 436
torch_greater_equal, 437
torch_gt, 437
torch_gt(), *437*
torch_half *(*torch_dtype*)*, 406
torch_hamming_window, 438
torch_hann_window, 439
torch_heaviside, 440
torch_histc, 441
torch_hstack, 442
torch_hypot, 442
torch_i0, 443
torch_i0(), *457*
torch_iinfo, 444
torch_imag, 444
torch_index, 445
torch_index_put, 445
torch_index_put_, 446
torch_index_select, 446
torch_install_path, 447
torch_int *(*torch_dtype*)*, 406
torch_int16 *(*torch_dtype*)*, 406
torch_int32 *(*torch_dtype*)*, 406
torch_int32(), *365*, *545*
torch_int64 *(*torch_dtype*)*, 406
torch_int64(), *365*, *545*
torch_int8 *(*torch_dtype*)*, 406
torch_inverse, 447
torch_is_complex, 454
torch_is_floating_point, 455
torch_is_installed, 455
torch_is_nonzero, 456

torch_isclose, 448
torch_isfinite, 449
torch_isinf, 450
torch_isnan, 450
torch_isneginf, 451
torch_isposinf, 451
torch_isreal, 452
torch_istft, 453
torch_kaiser_window, 456
torch_kron, 458
torch_kthvalue, 458
torch_layout, 459
torch_lcm, 459
torch_le, 460
torch_le(), *462*
torch_lerp, 461
torch_less, 462
torch_less_equal, 462
torch_lgamma, 463
torch_linspace, 463
torch_load, 464, *544*, *547*
torch_load(), *547*
torch_log, 465, *466*
torch_log10, 465
torch_log1p, 466
torch_log2, 467
torch_logaddexp, 468
torch_logaddexp(), *469*
torch_logaddexp2, 468
torch_logcumsumexp, 469
torch_logdet, 470
torch_logical_and, 471
torch_logical_not, 471
torch_logical_or, 472
torch_logical_xor, 473
torch_logit, 473
torch_logspace, 474
torch_logsumexp, 475
torch_logsumexp(), *468*
torch_long *(*torch_dtype*)*, 406
torch_lstsq, 476
torch_lstsq(), *476, 477*
torch_lt, 477
torch_lt(), *462*
torch_lu, 478
torch_lu_solve, 478
torch_lu_unpack, 479
torch_manual_seed, 480
torch_manual_seed(), *436*
torch_masked_select, 481
torch_matmul, *364*, 482, *493*
torch_matrix_exp, 483
torch_matrix_power, 484
torch_matrix_rank, 485
torch_max, 485
torch_maximum, 487
torch_maximum(), *487*
torch_mean, 487
torch_median, 488
torch_memory_format, 489
torch_meshgrid, 490
torch_min, 490
torch_minimum, 492
torch_minimum(), *492*
torch_mm, 493
torch_mm(), *85*
torch_mode, 493
torch_movedim, 494
torch_mul, 495
torch_mul(), *497*
torch_multinomial, 496
torch_multinomial(), *44, 45*
torch_multiply, 497
torch_mv, 498
torch_mvlgamma, 498
torch_nanquantile, 499
torch_nansum, 500
torch_narrow, 501
torch_ne, 502
torch_ne(), *508*
torch_neg, 503
torch_neg(), *503*
torch_negative, 503
torch_nextafter, 504
torch_nonzero, 504
torch_nonzero(), *593*
torch_norm, 505
torch_normal, 506
torch_not_equal, 508
torch_ones, 508
torch_ones_like, 509
torch_orgqr, 510
torch_ormqr, 511
torch_ormqr(), *76*
torch_outer, 511
torch_pdist, 512

torch_per_channel_affine (torch_qscheme), 521
torch_per_channel_symmetric (torch_qscheme), 521
torch_per_tensor_affine (torch_qscheme), 521
torch_per_tensor_symmetric (torch_qscheme), 521
torch_pinverse, 513
torch_pixel_shuffle, 514
torch_poisson, 514
torch_polar, 515
torch_polygamma, 516
torch_pow, 517
torch_preserve_format (torch_memory_format), 489
torch_preserve_format(), *377*
torch_prod, 518
torch_promote_types, 519
torch_qint32 (torch_dtype), 406
torch_qint8 (torch_dtype), 406
torch_qr, *435*, 520
torch_qscheme, 521
torch_quantile, 521
torch_quantile(), *500*
torch_quantize_per_channel, 522
torch_quantize_per_tensor, 523
torch_quint8 (torch_dtype), 406
torch_rad2deg, 524
torch_rand, 524
torch_rand_like, 531
torch_randint, 525
torch_randint_like, 526
torch_randn, 527
torch_randn_like, 529
torch_randperm, 530
torch_range, 532
torch_real, 533
torch_reciprocal, 534
torch_reduction, 534
torch_reduction_mean (torch_reduction), 534
torch_reduction_none (torch_reduction), 534
torch_reduction_sum (torch_reduction), 534
torch_relu, 535
torch_relu(), *535*
torch_relu_, 535
torch_remainder, 536
torch_renorm, 536
torch_repeat_interleave, 537
torch_reshape, 538
torch_result_type, 539
torch_roll, 540
torch_rot90, 540
torch_round, 541
torch_rrelu_, 542
torch_rsqrt, 543
torch_save, *465*, 543, *547*
torch_save(), *547*
torch_scalar_tensor, 544
torch_searchsorted, 545
torch_selu, 546
torch_selu(), *547*
torch_selu_, 546
torch_serialize, *465*, *544*, 547
torch_serialize(), *547*
torch_set_default_dtype, 547
torch_set_num_interop_threads (threads), 327
torch_set_num_threads (threads), 327
torch_set_rng_state (torch_get_rng_state), 436
torch_sgn, 548
torch_short (torch_dtype), 406
torch_sigmoid, 548
torch_sign, *548*, 549
torch_signbit, 550
torch_sin, 550
torch_sinh, 551
torch_slogdet, 552
torch_sort, 553
torch_sparse_coo (torch_layout), 459
torch_sparse_coo_tensor, 553
torch_split, 555
torch_split(), *367*, *586*
torch_sqrt, 556
torch_square, 556
torch_squeeze, *458*, *476*, *486*, *488*, *489*, *491*, *494*, *501*, *518*, *522*, 557, *559*, *560*, *564*, *588*, *589*
torch_squeeze(), *340*
torch_stack, 558
torch_std, 558
torch_std_mean, 559

torch_stft, 560
torch_stft(), *453, 454*, *457*
torch_strided *(*torch_layout*)*, 459
torch_strided(), *420*
torch_sub, 563
torch_sub(), *564*
torch_subtract, 563
torch_sum, 564
torch_svd, 565
torch_t, 566
torch_take, 567
torch_take_along_dim, 568
torch_tan, 569
torch_tanh, 569
torch_tensor, 570
torch_tensor(), *506, 507*
torch_tensor_from_buffer, 571
torch_tensordot, 571
torch_tensordot(), *95*, *97*
torch_threshold_, 572
torch_topk, 573
torch_trace, 574
torch_transpose, 574
torch_trapz, 575
torch_triangular_solve, 576
torch_tril, 577
torch_tril_indices, 578
torch_triu, 579
torch_triu_indices, 580
torch_true_divide, 582
torch_true_divide(), *333*, *403*
torch_trunc, 582
torch_trunc(), *423*
torch_uint8 *(*torch_dtype*)*, 406
torch_unbind, 583
torch_unique_consecutive, 584
torch_unsafe_chunk, 585
torch_unsafe_split, 585
torch_unsqueeze, 586
torch_vander, 587
torch_var, 587
torch_var_mean, 588
torch_vdot, 589
torch_view_as_complex, 590, *591*
torch_view_as_real, 591
torch_view_as_real(), *591*
torch_vstack, 592
torch_where, 592
torch_zeros, 593
torch_zeros_like, 594

unset_autocast *(*local_autocast*)*, 99

with_autocast *(*local_autocast*)*, 99
with_detect_anomaly, 596
with_device *(*local_device*)*, 101
with_enable_grad, 597
with_no_grad, *597*, 598
with_torch_manual_seed
*(*torch_manual_seed*)*, 480